

NAME: MUHAMMAD HAQIEM BIN MOHD FAUZI

STUDENT ID: 52215225398

Questions start

16 of 30 points

✓ Which IAM component contains permissions? *

1/1

☐ IAM User

☐ IAM Group

☒ IAM Policy ✓

☐ IAM Role

✓ Which security principle gives users only the permissions required to perform their tasks? *

*1/1

☒ Principle of Least Privilege ✓

☐ Defense in Depth

☐ Zero Trust

☐ Confidentiality

✓ Which AWS identity has unlimited privileges? *

1/1

☐ IAM User

☐ IAM Group

☒ Root User ✓

☐ IAM Role

✗ Which service model provides virtual machines? *

0/1

☐ PaaS

☐ SaaS

☒ DBaaS ✗

☐ IaaS

Correct answer

☒ IaaS

✗ Which command lists Kubernetes nodes? *

0/1

- ☐ docker ps
- ☐ kubect! get nodes
- ☐ kubect! get buckets
- ☒ aws iam list-users

✗

Correct answer

- ☒ kubect! get nodes

✓ Which deployment model combines private and public cloud? *

1/1

- ☐ Public Cloud
- ☒ Hybrid Cloud
- ☐ Community Cloud
- ☐ Multi-cloud

✓

✗ Which account should never have access keys created for routine use? *

0/1

- ☐ Analyst User
- ☐ IAM Role
- ☐ Root User
- ☒ IAM User

✗

Correct answer

- ☒ Root User

✗ A collection of IAM users is called: *

0/1

- ☒ IAM Policy
- ☐ S3 Bucket
- ☐ IAM Group
- ☐ IAM Role

✗

Correct answer

- ☒ IAM Group

✗ Google Docs is an example of: *

0/1

- ☐ IaaS
- ☒ PaaS
- ☐ Virtual Machine
- ☐ SaaS

Correct answer

- ☒ SaaS

✓ The smallest deployable unit in Kubernetes is: *

1/1

- ☐ Cluster
- ☐ Virtual Machine
- ☐ Node
- ☒ Pod

✗ Which IAM identity is normally used as a temporary identity? *

0/1

- ☒ Root User
- ☐ IAM Role
- ☐ IAM User
- ☐ IAM Group

Correct answer

- ☒ IAM Role

✗ If an access key is compromised, what should be done first? *

0/1

- ☐ Ignore it
- ☐ Restart Docker
- ☒ Delete the IAM user immediately
- ☐ Deactivate or rotate the key

Correct answer

- ☒ Deactivate or rotate the key

✗ Which AWS CLI command verifies the current identity? *

0/1

- ☐ aws login
- ☒ aws iam whoami ✗
- ☐ aws sts get-caller-identity
- ☐ aws identity

Correct answer

- ☒ aws sts get-caller-identity

✓ Which endpoint is commonly used with LocalStack? *

1/1

- ☐ <http://localhost:22>
- ☐ <http://localhost:3389>
- ☐ <http://localhost:80>
- ☒ <http://localhost:4566> ✓

✓ Which tool creates a local Kubernetes cluster? *

1/1

- ☐ LocalStack
- ☒ kind ✓
- ☐ Amazon EC2
- ☐ Docker Desktop

✗ Which deployment model provides the MOST control? *

0/1

- ☒ Community Cloud ✗
- ☐ Private Cloud
- ☐ Hybrid Cloud
- ☐ Public Cloud

Correct answer

- ☒ Private Cloud

✓ LocalStack is used because it: *

1/1

☒ Simulates AWS services locally ✓

☐ Creates AWS accounts

☐ Replaces Docker

☐ Installs Kubernetes

✓ Which service model requires customers to manage the operating system?

*1/1

☐ FaaS

☒ IaaS ✓

☐ PaaS

☐ SaaS

✓ Which characteristic allows cloud resources to automatically grow or shrink?

*1/1

☐ Resource Pooling

☒ Rapid Elasticity ✓

☐ Broad Network Access

☐ On-demand Self-Service

✗ Which ARN component identifies the AWS account that owns the resource?

*0/1

☐ Service

☐ Region

☒ Account ID ✗

☐ Resource ID

Correct answer

☒ Resource ID

✓ A node is: *

1/1

☒ A worker machine ✓

☐ A storage bucket

☐ A database

☐ A Docker image

✓ In the ARN `arn:aws:s3:::my-bucket`, which component represents the AWS service? *1/1

☐ arn

☐ my-bucket

☒ s3 ✓

☐ aws

✓ Which is NOT an essential characteristic of cloud computing? *

1/1

☐ Measured Service

☐ Rapid Elasticity

☐ Resource Pooling

☒ Manual Provisioning ✓

✓ For easier permission management, policies should preferably be attached to: *1/1

☐ Access keys

☒ IAM Groups ✓

☐ The Root User

☐ Individual users

✓ Cloud computing refers to: *

1/1

- ☒ Buying more physical servers ✓
- ☐ Installing software locally
- ☐ Delivering computing resources over the Internet
- ☐ Running applications only on Windows

✓ What does ARN stand for? *

1/1

- ☒ Amazon Resource Name ✓
- ☐ AWS Resource Namespace
- ☐ Amazon Resource Number
- ☐ Amazon Registry Name

✓ A Kubernetes cluster consists of: *

1/1

- ☐ Multiple policies
- ☐ Containers only
- ☐ Access keys
- ☒ Multiple nodes ✓

✓ Access keys are mainly used for: *

1/1

- ☒ Programmatic access ✓
- ☐ Docker login
- ☐ AWS Management Console login
- ☐ Kubernetes dashboard login

✗ Docker is mainly used to: *

0/1

- ☐ Run containers
- ☐ Create AWS accounts
- ☐ Manage IAM
- ☒ Create databases

✗

Correct answer

- ☒ Run containers

✗ Which AWS-managed policy provides full administrative access? *

0/1

- ☒ AmazonS3ReadOnlyAccess
- ☐ AdministratorAccess
- ☐ IAMReadOnlyAccess
- ☐ RootPolicy

✗

Correct answer

- ☒ AdministratorAccess

DONE :)

0 of 0 points

Dont forget to submit your Github Link :)

https://1drv.ms/x/c/7a38c24f0604aa60/IQBG5_ybRu7JT50WvBpQ_rgoAZImon3KdjWW13ULus2yQdY?e=BayPJ8

Thank You :)

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#)

Does this form look suspicious? [Report](#)

Google Forms