```
auyon@Auyons-Air a4 % psql -d ex603_data -P pager=off -e -f q4_1.sql
(15 rows)

SELECT movie_id,
       COUNT(*)                                                AS ratings,
       SUM(CASE WHEN rating_status = 'withdrawn'
                THEN 1 ELSE 0 END)                             AS withdrawn,
       ROUND(100.0 * SUM(CASE WHEN rating_status = 'withdrawn'
                              THEN 1 ELSE 0 END)
                   / COUNT(*), 1)                              AS failure_rate_pct
FROM   ratings
GROUP  BY movie_id
HAVING COUNT(*) >= 10
ORDER  BY failure_rate_pct DESC, movie_id;
 movie_id | ratings | withdrawn | failure_rate_pct
----------+---------+-----------+------------------
       11 |      16 |         5 |             31.3
        9 |      14 |         4 |             28.6
        2 |      16 |         4 |             25.0
        3 |      13 |         3 |             23.1
        6 |      21 |         4 |             19.0
        1 |      11 |         2 |             18.2
        5 |      18 |         3 |             16.7
        7 |      18 |         3 |             16.7
       12 |      17 |         2 |             11.8
       13 |      11 |         1 |              9.1
        8 |      20 |         1 |              5.0
       10 |      19 |         0 |              0.0
(12 rows)
```