Problems Output Debug Console Terminal Ports

```
auyon@Auyons-Air a4 % psql -d ex603_data -P pager=off -e -f q4_2.sql

WITH per_movie AS (
    SELECT movie_id,
           COUNT(*)                                          AS total_ratings,
           SUM(CASE WHEN rating_status = 'withdrawn'
                    THEN 1 ELSE 0 END)                       AS failed_ratings
    FROM   ratings
    GROUP  BY movie_id
)
SELECT COUNT(*)                                              AS high_volume_movies,
       SUM(total_ratings)                                    AS total_ratings,
       SUM(failed_ratings)                                   AS failed_ratings,
       ROUND(100.0 * SUM(failed_ratings)
                   / SUM(total_ratings), 1)                  AS pooled_rate_pct,
       ROUND(AVG(100.0 * failed_ratings / total_ratings), 1) AS mean_rate_pct,
       ROUND(MIN(100.0 * failed_ratings / total_ratings), 1) AS min_rate_pct,
       ROUND(MAX(100.0 * failed_ratings / total_ratings), 1) AS max_rate_pct
FROM   per_movie
WHERE  total_ratings >= 10;
 high_volume_movies | total_ratings | failed_ratings | pooled_rate_pct | mean_rate_pct | min_rate_pct | max_rate_pct
--------------------+---------------+----------------+-----------------+---------------+--------------+--------------
                 12 |           194 |             32 |            16.5 |          17.0 |          0.0 |         31.3
(1 row)

WITH per_movie AS (
    SELECT movie_id,
           COUNT(*)                                          AS total_ratings,
           SUM(CASE WHEN rating_status = 'withdrawn'
                    THEN 1 ELSE 0 END)                       AS failed_ratings
    FROM   ratings
    GROUP  BY movie_id
),
high_volume AS (
    SELECT *
    FROM   per_movie
    WHERE  total_ratings >= 10
),
baseline AS (
    SELECT 100.0 * SUM(failed_ratings) / SUM(total_ratings) AS rate_pct
    FROM   high_volume
)
SELECT h.movie_id,
       h.total_ratings,
       h.failed_ratings,
       ROUND(100.0 * h.failed_ratings / h.total_ratings, 1) AS failure_rate_pct,
       ROUND(b.rate_pct, 1)                                 AS baseline_pct,
       ROUND((100.0 * h.failed_ratings / h.total_ratings)
             / b.rate_pct, 2)                               AS times_baseline,
       CASE
           WHEN 100.0 * h.failed_ratings / h.total_ratings
                >= 1.5 * b.rate_pct                         THEN 'Well above baseline'
           WHEN 100.0 * h.failed_ratings / h.total_ratings
                >  b.rate_pct                               THEN 'Above baseline'
           ELSE                                                  'At or below baseline'
       END                                                  AS assessment
FROM   high_volume h
CROSS  JOIN baseline b
ORDER  BY times_baseline DESC, h.movie_id;
 movie_id | total_ratings | failed_ratings | failure_rate_pct | baseline_pct | times_baseline |      assessment
----------+---------------+----------------+------------------+--------------+----------------+----------------------
       11 |            16 |              5 |             31.3 |         16.5 |           1.89 | Well above baseline
```