```
auyon@Auyons-Air a4 % psql -d ex603_data -e -f q4_1.sql
SELECT COUNT(*)                AS ratings,
       COUNT(score)            AS ratings_with_score,
       SUM(score)              AS total_score,
       ROUND(AVG(score), 2)    AS avg_score,
       MIN(score)              AS min_score,
       MAX(score)              AS max_score,
       COUNT(DISTINCT user_id)  AS distinct_reviewers,
       COUNT(DISTINCT movie_id) AS distinct_movies_rated
FROM   ratings;
 ratings | ratings_with_score | total_score | avg_score | min_score | max_score | distinct_reviewers | distinct_movies_rated
---------+--------------------+-------------+-----------+-----------+-----------+--------------------+-----------------------
     200 |                200 |       569.3 |      2.85 |       0.5 |       5.0 |                 30 |                    13
(1 row)

SELECT rating_status,
       COUNT(*)                      AS ratings,
       MIN(score)                    AS min_score,
       MAX(score)                    AS max_score,
       COUNT(*) FILTER (WHERE score = 0.5) AS scored_exactly_0_5
FROM   ratings
GROUP  BY rating_status
ORDER  BY rating_status;
 rating_status | ratings | min_score | max_score | scored_exactly_0_5
---------------+---------+-----------+-----------+--------------------
 flagged       |      10 |       1.2 |       5.0 |                  0
 published     |     156 |       0.8 |       5.0 |                  0
 withdrawn     |      34 |       0.5 |       0.5 |                 34
(3 rows)

SELECT m.movie_id,
       COUNT(r.rating_id)                                 AS ratings,
       ROUND(AVG(r.score), 2)                             AS avg_score,
       ROUND(AVG(CASE WHEN r.rating_status <> 'withdrawn'
                      THEN r.score END), 2)               AS avg_score_excl_withdrawn
FROM   movies  m
LEFT   JOIN ratings r ON r.movie_id = m.movie_id
GROUP  BY m.movie_id
ORDER  BY ratings DESC, m.movie_id;
 movie_id | ratings | avg_score | avg_score_excl_withdrawn
----------+---------+-----------+--------------------------
        6 |      21 |      2.78 |                     3.32
        8 |      20 |      3.27 |                     3.41
       10 |      19 |      3.31 |                     3.31
        5 |      18 |      3.51 |                     4.11
        7 |      18 |      2.91 |                     3.39
       12 |      17 |      3.00 |                     3.33
        2 |      16 |      2.77 |                     3.53
       11 |      16 |      2.09 |                     2.82
        9 |      14 |      2.46 |                     3.24
        3 |      13 |      2.24 |                     2.76
        1 |      11 |      2.75 |                     3.24
       13 |      11 |      2.82 |                     3.05
        4 |       6 |      2.28 |                     3.18
       14 |       0 |           |
       15 |       0 |           |
(15 rows)

SELECT movie_id,
       COUNT(*)                                           AS ratings,
       SUM(CASE WHEN rating_status = 'withdrawn'
```