



SPECIFICATION SHEET

Orca OM866H-10RF (Gen 2)

Heat Alarm - Wireless Interlink 10 Year



SPECIFICATIONS



Recommended for

Kitchens, Laundries, Garages & Attic areas

The Orca™ Intelligent Wireless Interlink Technology allows multiple units to be wirelessly interlinked to protect the whole household. When one alarm activates, the entire network activates. These alarms are the future of smoke and fire detection. In larger residences, they provide peace of mind knowing that a small fire emerging away from where people are sleeping will still provide an immediate close proximity warning allowing action to be taken before the fire gets out of control.

- Heat sensor – detects dangerous increases in room temperature
- Ideal for kitchens, laundries, garages and attics
- Test button
- Hush feature
- Long-life built-in lithium battery
- Extra loud warning tone
- Low battery warning
- 10 year warranty
- Certified to BS 5446-2:2003
- Complies with NZS 4514:2021 (for Heat alarms)

Connects wirelessly with:

Orca OM866S-10RF Smoke Alarm
Orca OM866C-10RF Alarm Controller

TECHNICAL SPECIFICATIONS

DIMENSIONS	82mm diameter x 33mm depth
SUPPLY VOLTAGE	3v DC
BATTERY	10 year sealed lithium battery
TECHNOLOGY	Heat sensor
ALARM SOUND LEVEL	85db(A) at 3m (minimum)
INSTALLATION POSITIONS	Ceiling or wall
OPERATING TEMPERATURE	+4°C to +38°C
OPERATING HUMIDITY	Up to 90% RH non-condensing
WARRANTY	10 years
WEIGHT	73g
CERTIFIED TO	BS 5446-2:2003
MAXIMUM CONNECTED UNITS	30 units
OPERATING FREQUENCY	868.3MHz
RANGE	30-50 metres

DISCLAIMER The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented here is intended only as a general guide to the use of such products and no liability is accepted by Newfield Group Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information.