

Developing with SailfishOS

a short introduction

Sven Putze, hardcodes.de

December 5, 2013





Contents

1	About	2
2	Download and install	2
2.1	OSX	4
2.2	Windows	12
2.3	Linux	23
2.4	Remove plugins	23
3	Quickstart	24
4	Know your tools	29
4.1	Technology stack	30
4.2	QtCreator integrated development environment (IDE)	30
4.2.1	kits	31
4.2.2	qmake	32
4.2.3	merssh	38
4.2.4	Compilers	40
4.2.5	make	41
4.2.6	rpm	42
4.2.7	Project settings	42
4.2.8	Pimp the clean process	42
4.3	Mer build engine for cross compilation	43
4.4	Scratchbox2	44
4.5	The SailfishOS Emulator	45
4.6	Sailfish Silica	46
4.7	Tools chained up	50
5	Installing additional packages	50
5.1	Emulator	51
5.1.1	zypper	51
5.1.2	Known Logins	52
5.2	Mer SDK Build Engine	52
5.2.1	Directories	53
5.2.2	Known Logins	53
6	Templates for QtCreator	53
7	Physical device	54
7.1	How to connect to SSH over usb connection from PC	54



8 Harbour	54
9 Bug Reports	59
10 Troubleshooting	59
10.1 Mer build engine for cross compilation	59
10.1.1 Management Webpage	59
10.1.2 SSH login	60
10.1.3 Drive(s) not mounted	62
10.1.4 update via command line	65
11 Use your editor of choice	65
12 Community	65
12.1 Jolla	65
12.1.1 SailfishOS	65
12.1.2 Mer	65
12.1.3 Nemo mobile	65
13 Uninstall	65
13.0.4 OSX	66
13.0.5 Windows	69
13.0.6 Linux	69
14 Thanks	69
References	69



1 About

Hi, my name is Sven[hc01] and I am eager to develop for the Jolla smartphone. On my way some questions came up and I tried to answer them as good as I can. After a while I decided to write down what I've learned, so that I had a central place to come back to and maybe others can benefit from this small document, too. The latest and greatest version is to be found on Github[hc02].

This work is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-nc-sa/4.0/deed.en_US.

This goes only for content I have written myself, I don't claim ownership or copyright/left on cited content. Content from other parties remains under its original license.

All mentioned trademarks and trade names are the property of their respective holders, I have not marked them with a TM, [®] or [©] sign. Use some common sense here. Not all information is written by myself, I've tried to quote as responsible as possible and quite intensive if appropriate. Read these notes as a human being, not like a lawyer.

If you find typos, errors or quirks, have suggestions how to make this document better, please drop me a note. Or collaborate. #jolla2gether!

Don't panic if you are not comfortable with writing in L^AT_EX, I am happy to use your Libre/Open Office or even Word documents.

2 Download and install

You will need Virtual Box, because some components of the SailfishOS SDK come as virtual machines. Download for your development machine[vbox01].



The screenshot shows a web browser window with the URL <https://www.virtualbox.org/wiki/Downloads>. The page title is "VirtualBox". On the left, there's a sidebar with links: About, Screenshots, **Downloads**, Documentation, End-user docs, Technical docs, Contribute, and Community. The "Downloads" link is highlighted with a red box. The main content area has a heading "Download VirtualBox" and a sub-section "VirtualBox binaries". It says "Here, you will find links to VirtualBox binaries and its source code." Below this, it says "By downloading, you agree to the terms and conditions of the respective license." There are two bullet points. The first bullet point is about "VirtualBox platform packages" and lists four options, each with a red box around it: "VirtualBox 4.3.2 for Windows hosts" (x86/amd64), "VirtualBox 4.3.2 for OS X hosts" (x86/amd64), "VirtualBox 4.3.2 for Linux hosts" (x86/amd64), and "VirtualBox 4.3.2 for Solaris hosts" (x86/amd64). The second bullet point is about "VirtualBox 4.3.2 Oracle VM VirtualBox Extension Pack" and provides links for "All supported platforms" and specific versions (4.2.20 and 4.1.28) with "here" links.

Figure 1: Download VirtualBox from the virtualbox website.

If you already use VirtualBox, you don't need to load it again, just skip that step. Just make sure that you have the latest updates installed.

To take a dip, head over to the Sailfish Website [sailfishos01] and download the SDK for your operating system.



Figure 2: Download the SDK from the SailfishOS website.

2.1 OSX

Double click on the downloaded disk image for VirtualBox and run the installer application inside. Some file go into system folders and you must be or elevate to an admin account to install successfully.



Figure 3: Downloaded diskimage.

If you use VirtualBox just for the SailfishOS SDK you don't have to care about the VirtualBox application, although you can see which folders are shared inside the preferences.

Double click on the downloaded disk image for the SailfishOS SDK and run the installer app that's inside. The installed files will end in your user directory, you don't need to be an administrator to achieve that.




Figure 4: Install SailfishOS SDK, step 1.




Figure 5: Install SailfishOS SDK, step 2.




Figure 6: Install SailfishOS SDK, step 3. Enter the path to your source code.
There is no folder selector dialog, you must enter it by hand.




Figure 7: Install SailfishOS SDK, step 4.




Figure 8: Install SailfishOS SDK, step 5.



Figure 9: Install SailfishOS SDK, step 6.




Figure 10: Install SailfishOS SDK, step 7.




Figure 11: Unmount SailfishOS SDK disk image, step 8.

With the installation came two hidden directories, you should know about. More about those directories will follow later on.

```
$HOME/.config/SailfishAlpha2  
$HOME/.scratchbox2
```

After you installed the SDK, you should immediately update the components. As of now the progress inside Jolla is at good pace, so it might be that there is some stuff slightly out of date in the installer (see figures 12 and 13).




Figure 12: Inside the SailfishOS folder you find the maintenance application. Run it directly after the installation.




Figure 13: Update components, choose everything that is in store.

With the SDK comes QtCreator¹, a complete IDE for C++ development. This IDE is part of the Qt Framework[qt01] and is simply reused² by Jolla. Personally I use the QtCreator on my machines as well and for better differentiation I made a custom icon for the one in the SailfishOS SDK - feel free to download and use it, too[hc03].

¹Look in in the "bin" folder of the SDK.

²Customized with some little tweaks to suite the SailfishOS development.



Figure 14: Alternative icon for the QtCreator inside the SDK.

2.2 Windows

Double click the `VirtualBox-4.3.4-91027-Win.exe` executable that you have downloaded and follow the installer.




Figure 15: Install VirtualBox, Step 1.



Figure 16: Install VirtualBox, Step 2.




Figure 17: Install VirtualBox, Step 3.




Figure 18: Install VirtualBox, Step 4.




Figure 19: Install VirtualBox, Step 5.




Figure 20: Install VirtualBox, Step 6.



Figure 21: Install VirtualBox, Step 7.



Figure 22: Install VirtualBox, Step 8.




Figure 23: Install VirtualBox, Step 9.



Figure 24: Install VirtualBox, Step 10.



Figure 25: Install VirtualBox, Step 11.

Start the [SailfishOSSDK-Alpha-1310-Qt5-windows-offline.exe](#) executable and install the SDK.




Figure 26: Install SDK, Step 1.




Figure 27: Install SDK, Step 2.




Figure 28: Install SDK, Step 3.




Figure 29: Install SDK, Step 4.




Figure 30: Install SDK, Step 5.




Figure 31: Install VirtualBox, Step 6.




Figure 32: Install VirtualBox, Step 7.




Figure 33: Install VirtualBox, Step 8.




Figure 34: Install VirtualBox, Step 9.

Start the maintenance tool from the start menu and update all components.




Figure 35: SDK and maintenance tool

With the installation come some directories.




Figure 36: Directory after installation.




Figure 37: Directory after installation.

2.3 Linux

Since I have not installed the SDK on Linux yet, I can not provide any information here. Sorry!

Apart from that I have no physical Linux machine that is connected to a display and can be diverted for a test installation. A virtual machine might work but that would result in VMs inside a VM, not very promising.

Volunteers present?

2.4 Remove plugins

If you want to improve the startup time of QtCreator, you can deactivate plugins you don't need or want³. Just don't shoot in your foot here.




Figure 38: About plugins = manage plugins.

³On Windows and Linux the plugins should be found in Extras/Plugins.




Figure 39: Deactivate every plugin you don't need.

3 Quickstart

Start the QtCreator from the fresh installed SDK.

"The SDK comes with a handy SailfishOS application template that gives you a quick way to create your very first Sailfish OS application. Just go to File-> New File or Project in the IDE"[sailfishos2]




Figure 40: First example, step 1.




Figure 41: First example, step 2.




Figure 42: First example, step 3.




Figure 43: First example, step 4.




Figure 44: First example, step 5.




Figure 45: First example, step 1.

Start the SDK from inside the QtCreator.



Figure 46: Starting the SDK.

When the virtual machine with the SDK is running, apply updates if necessary.




Figure 47: Updating the SDK.

Start the Emulator.



Figure 48: Starting the Emulator.

Compile and run your application.



Figure 49: Build and run the application.

Easy as pie, also see figure 70 on page 45. But what happens when and where if you click on those Icons? Look in section *Know your tools*.

A good starting point to look for a more sophisticated starting example is *The missing HelloWorld. Wizard included* by Artem Marchenko[gh01]. You should check that out!

And you should look in the examples folder of the SDK of course.



4 Know your tools

Jolla chose the Qt framework to be part of their technology stack. “Qt is a cross-platform application and UI framework for developers using C++ or QML, a CSS & JavaScript like language. Qt Creator is the supporting Qt IDE. Qt, Qt Quick and the supporting tools are developed as an open source project governed by an inclusive meritocratic model. Qt can be used under open source (LGPL v2.1) or commercial terms.”[qt01]

“Qt - code once, deploy everywhere”, that’s the mantra of the Qt framework. If you have developed for more than one platform in the past, you know that this sounds like heaven. Maintaining different source code and technologies for each and every platform is a tedious task that can eat up all your developer resources. As if software development is not difficult enough if you stay on one platform⁴.

So there were good reasons to choose Qt as framework, no doubt about that. As of now you can develop for Android, iOS, BlackBerry and of course SailfishOS. If you look into the documentation and examples of all these platforms, you will find that those examples assume, that you are developing for this platform only. Quite stupid, if you use the Qt framework. Understandable if you think about the effort that would be necessary to build a documentation that incorporates all other possible platforms. For some time now I was wondering how I should organize my code in such a way, that allows me to develop for more than one target platform at a time. It’s not just compiling for another platform! Each platform has a unique UI that behaves in an own different way, e.g. SailfishOS is gesture based, other ones are touch based. In the long run you will create an UI for each of those targets. Period. Patterns like MVC[wiki01] will come to mind, using separate business logic, yada yada.

To cut a long story short, why am I writing about this stuff, this section is supposed to be about tools? When you prepare a software project for the use for more than one target platform, you will start organizing stuff differently. Maybe you use folders that have the name of the targets to differentiate stuff that’s platform dependent. Maybe you even create a business logic that is really unique and encapsulated in such clever way that it can be reused and does not know anything about the outside world. Such a business logic or model can be driven from tests, command line tools, web or different native UIs. Would be nice to have it in a separate folder or even subproject. If you start to move and/or rename things, your tools will break. Intentionally.

By examining those fractures you can learn a lot about your tools that otherwise work so silently in the background. So go on and break your tools!⁵

⁴In my eyes software development is an art of craftsmanship and can not be done by Mr. Average and thus is a more or less complicated thing to do.

⁵Ok, not so short :-)



Here is what I've learned so far.

4.1 Technology stack



Figure 50: Sailfish architecture, taken from
https://sailfishos.org/images/Sailfish_Architecture.png.

4.2 QtCreator integrated development environment (IDE)

“QtCreator is a cross platform integrated development environment (IDE) tailored to the needs of Qt developers. It has been extended to add support for Sailfish UI application development using Sailfish Silica components. It provides a sophis-

ticated code editor with version control, project and build management system integration.”[sailfishos3].

Reusing an existing open source IDE is a smart move from Jolla. Why should they waste resources on developing something that has already done by others? Or why should they burn up their staff for all those development solutions out there? Be it Visual Studio, Eclipse, Emacs or even Vi. If you really dive in the tools, you can also use those but I doubt that Jolla will provide you with support if something does not work. Working with QtCreator is also quite natural in the Qt universe albeit being a fast IDE. So have a look in the preferences⁶.




Figure 51: Open the QtCreator preferences.

I will not walk through every setting of QtCreator, [qt02] is a better place to start for basic questions. Also I will not use the order of tabs in the preferences, but try to follow the sequence in which those tools touch your source code.

4.2.1 kits

But before we do that, we must talk about *kits*. A kit is kind of an umbrella setting, which combines the information of the following bits and pieces, like qmake, compiler, and device type. This is the information hub that QtCreator uses to pull all information together and initiate its actions.

⁶On Windows and Linux they should be found in Extras/Options.




Figure 52: Preferences, kits tab.

4.2.2 qmake




Figure 53: Preferences, QtVersions tab.


“qmake is a tool that helps simplify the build process for development project across different platforms. qmake automates the generation of Makefiles so that only a few lines of information are needed to create each Makefile. qmake can be used for any software project, whether it is written in Qt or not. qmake generates a Makefile based on the information in a project file. Project files are created by the developer, and are usually simple, but more sophisticated project files can be created for complex projects. qmake contains additional features to support development with Qt, automatically including build rules for moc and uic. qmake can also generate projects for Microsoft Visual studio without requiring the developer to change the project file.”[qt03]

Qt version 5.1.0 for Mer		Details ▾
Name:	Qt 5.1.0 in MerSDK SailfishOS-i486-x86	
ABI:	x86-linux-generic-elf-32bit	
Source:	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr	
mkspec:	linux-g++	
qmake:	/Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK/SailfishOS-i486-x86/qmake	
Version:	5.1.0	
QMAKE_SPEC	linux-g++	
QMAKE_VERSION	3.0	
QMAKE_XSPEC	linux-g++	
QT_HOST_BINS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/bin	
QT_HOST_DATA	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/share/qt5	
QT_HOST_LIBS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib	
QT_HOST_PREFIX	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr	
QT_INSTALL_ARCHDATA	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/share/qt5	
QT_INSTALL_BINS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/bin	
QT_INSTALL_CONFIGURATION	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/etc/xdg	
QT_INSTALL_DATA	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/share/qt5	
QT_INSTALL_DEMOS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/examples	
QT_INSTALL_DOCS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/share/doc/qt5/	
QT_INSTALL_EXAMPLES	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/examples	
QT_INSTALL_HEADERS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/include/qt5	
QT_INSTALL_IMPORTS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/imports	
QT_INSTALL_LIBEXECS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/libexec	
QT_INSTALL_LIBS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib	
QT_INSTALL_PLUGINS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/plugins	
QT_INSTALL_PREFIX	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr	
QT_INSTALL_QML	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/qml	
QT_INSTALL_TESTS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/lib/qt5/tests	
QT_INSTALL_TRANSLATIONS	/Users/sven/SailfishOS/mersdk/targets/SailfishOS-i486-x86/usr/share/qt5/translations	
QT_SYSROOT		
QT_VERSION	5.1.0	

Figure 54: Preferences, QtVersions tab., qmake details

UIC is a tool that creates C++ classes from XML information generated with the UI designer inside QtCreator. This designer is for Qt widgets which should not be used with SailfishOS and is not further explained in this document.

MOC is the Meta-Object Compiler which “reads a C++ header file. If it finds one or more class declarations that contain the `Q_OBJECT` macro, it produces a C++ source file containing the meta-object code for those classes.”[qt04]. If you use qmake to produce your Makefile, you don’t have to worry about it, the rules are created automatically.



```

lastenhuone:~ sven$ cd .config/SailfishAlpha2/mer-sdk-tools/MerSDK/SailfishOS-i486-x86/
lastenhuone:SailfishOS-i486-x86 sven$ ls -lah
total 64
drwxr-xr-x 10 sven staff 340B 20 Nov 14:23 .
drwxr-xr-x  4 sven staff 136B 20 Nov 14:23 ..
-rwxrwx---  1 sven staff 224B 20 Nov 14:23 deploy
-rwxrwx---  1 sven staff 221B 20 Nov 14:23 gcc
-rw-r--r--  1 sven staff 21B 20 Nov 14:23 gcc.dumpmachine
-rwxrwx---  1 sven staff 234B 20 Nov 14:23 gdb
-rwxrwx---  1 sven staff 222B 20 Nov 14:23 make
-rwxrwx---  1 sven staff 223B 20 Nov 14:23 qmake
-rw-r--r--  1 sven staff 1,9K 20 Nov 14:23 qmake.query
-rwxrwx---  1 sven staff 221B 20 Nov 14:23 rpm
lastenhuone:SailfishOS-i486-x86 sven$ ./qmake
Project ERROR: Could not connect to MerSDK Virtual Machine. No private key file given.
lastenhuone:SailfishOS-i486-x86 sven$ 

```

Figure 55: Running qmake from command line.

If you run qmake manually, you will find out that it tries to connect to the *Mer build engine for cross compilation*. The error also appears if the virtual machine is up and running. In the Projects settings you can see how qmake is invoked if started by QtCreator.




Figure 56: Project settings.





Figure 57: Build steps for qmake.



Using those parameters via command line does not work, too.



A terminal window titled "SailfishOS-i486-x86 — bash — 80x24". The command entered is:

```
lastenhuone:SailfishOS-i486-x86 sven$ ./qmake /Users/sven/Documents/QtProjects/BLA/BLA.pro -r -spec linux-g++ CONFIG+=debug CONFIG+=declarative_debug CONFIG+=qm l_debug -after OBJECTS_DIR=obj MOC_DIR=moc UI_DIR=ui RCC_DIR=rcc
```


The output shows an error message:

```
Project ERROR: Could not connect to MerSDK Virtual Machine. No private key file given.
```

lastenhuone:SailfishOS-i486-x86 sven\$

Figure 58: Running qmake from command line with parameters from build steps.

If `qmake` is invoked by the QtCreator it works just fine.



A screenshot of the QtCreator interface showing the "Compile Output" tab. The log output is as follows:

```
11:31:49: Running steps for project BLA...
11:31:49: Starting: "/Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK/SailfishOS-i486-x86/qmake"
/Users/sven/Documents/QtProjects/BLA/BLA.pro -r -spec linux-g++ CONFIG+=debug CONFIG+=declarative_debug CONFIG+=qml_debug -after
OBJECTS_DIR=obj MOC_DIR=moc UI_DIR=ui RCC_DIR=rcc
11:31:51: The process "/Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK/SailfishOS-i486-x86/qmake" exited normally.
11:31:51: Elapsed time: 00:02.
```

The bottom navigation bar shows tabs for Application Output, Compile Output (which is selected), QML/JS Console, and General Messages.

Figure 59: Running qmake from QtCreator (Build menu).

As a result you will find a `Makefile` in your project directory.




Figure 60: Result of running qmake from QtCreator (Build menu).

Here is the snippet about the MOC.

```
##### Sub-libraries

distclean: clean
-$(DEL_FILE) $(TARGET)
-$(DEL_FILE) Makefile

mocclean: compiler_moc_header_clean compiler_moc_source_clean

mocables: compiler_moc_header_make_all compiler_moc_source_make_all

check: first

compiler_rcc_make_all:
compiler_rcc_clean:
compiler_wayland-server-header_make_all:
compiler_wayland-server-header_clean:
```

```
compiler_wayland-client-header_make_all:  
compiler_wayland-client-header_clean:  
compiler_qtwayland-client-header_make_all:  
compiler_qtwayland-client-header_clean:  
compiler_qtwayland-server-header_make_all:  
compiler_qtwayland-server-header_clean:  
compiler_moc_header_make_all: moc/moc_qbusinesslogic.cpp  
compiler_moc_header_clean:  
    -$(DEL_FILE) moc/moc_qbusinesslogic.cpp  
moc/moc_qbusinesslogic.cpp: /usr/include/qt5/QtCore/QObject \  
    /usr/include/qt5/QtCore/qobject.h \  
    /usr/include/qt5/QtCore/qobjectdefs.h \  
    /usr/include/qt5/QtCore/qnamespace.h \  
    /usr/include/qt5/QtCore/qglobal.h \  
    /usr/include/qt5/QtCore/qconfig.h \  
    /usr/include/qt5/QtCore/qfeatures.h \  
    /usr/include/qt5/QtCore/qsystemdetection.h \  
    /usr/include/qt5/QtCore/qcompilerdetection.h \  
    /usr/include/qt5/QtCore/qprocessordetection.h \  
    /usr/include/qt5/QtCore/qglobalstatic.h \  
    /usr/include/qt5/QtCore/qatomic.h \  
    /usr/include/qt5/QtCore/qbasicatomic.h \  
    /usr/include/qt5/QtCore/qatomic_bootstrap.h \  
    /usr/include/qt5/QtCore/qgenericatomic.h \  
    /usr/include/qt5/QtCore/qatomic_msvc.h \  
    /usr/include/qt5/QtCore/qatomic_integrity.h \  
    /usr/include/qt5/QtCore/qoldbasicatomic.h \  
    /usr/include/qt5/QtCore/qatomic_vxworks.h \  
    /usr/include/qt5/QtCore/qatomic_power.h \  
    /usr/include/qt5/QtCore/qatomic_alpha.h \  
    /usr/include/qt5/QtCore/qatomic_armv7.h \  
    /usr/include/qt5/QtCore/qatomic_armv6.h \  
    /usr/include/qt5/QtCore/qatomic_armv5.h \  
    /usr/include/qt5/QtCore/qatomic_bfin.h \  
    /usr/include/qt5/QtCore/qatomic_ia64.h \  
    /usr/include/qt5/QtCore/qatomic_mips.h \  
    /usr/include/qt5/QtCore/qatomic_s390.h \  
    /usr/include/qt5/QtCore/qatomic_sh4a.h \  
    /usr/include/qt5/QtCore/qatomic_sparc.h \  
    /usr/include/qt5/QtCore/qatomic_x86.h \  
    /usr/include/qt5/QtCore/qatomic_cxx11.h \  
    /usr/include/qt5/QtCore/qatomic_gcc.h \  
    /usr/include/qt5/QtCore/qatomic_unix.h \  
    /usr/include/qt5/QtCore/qmutex.h \  
    /usr/include/qt5/QtCore/qlogging.h \  
    /usr/include/qt5/QtCore/qflags.h \  
    /usr/include/qt5/QtCore/qtypeinfo.h \  
    /usr/include/qt5/QtCore/qtypetraits.h \  
    /usr/include/qt5/QtCore/qsysinfo.h \  
    
```

```
/usr/include/qt5/QtCore/qobjectdefs_impl.h \
/usr/include/qt5/QtCore/qstring.h \
/usr/include/qt5/QtCore/qchar.h \
/usr/include/qt5/QtCore/qbytearray.h \
/usr/include/qt5/QtCore/qrefcount.h \
/usr/include/qt5/QtCore/qarraydata.h \
/usr/include/qt5/QtCore/qstringbuilder.h \
/usr/include/qt5/QtCore/qlist.h \
/usr/include/qt5/QtCore/qalgorithms.h \
/usr/include/qt5/QtCore/qiterator.h \
/usr/include/qt5/QtCore/qcoreevent.h \
/usr/include/qt5/QtCore/qscopedspointer.h \
/usr/include/qt5/QtCore/qmetatype.h \
/usr/include/qt5/QtCore/qvarlengtharray.h \
/usr/include/qt5/QtCore/qcontainerfwd.h \
/usr/include/qt5/QtCore/qisenum.h \
/usr/include/qt5/QtCore/qobject_impl.h \
model/qt/qbusinesslogic.h
/usr/lib/qt5/bin/moc $(DEFINES) $(INCPATH) -I/usr/lib/gcc/i486-
meego-linux/4.6.4/../../../../include/c++/4.6.4 -I/usr/lib/gcc/
i486-meego-linux/4.6.4/../../../../include/c++/4.6.4/i486-meego-
linux -I/usr/lib/gcc/i486-meego-linux/4.6.4/../../../../include/c
++/4.6.4/backward -I/usr/lib/gcc/i486-meego-linux/4.6.4/include -I
/usr/local/include -I/usr/include model/qt/qbusinesslogic.h -o moc
/moc_qbusinesslogic.cpp
```

The qmake from the SailfishOS SDK is just a simple bash script, that invokes merssh.

```
#!/bin/bash
exec "/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/...
Resources/merssh" -sdktoolsdir "/Users/sven/.config/SailfishAlpha2
/mer-sdk-tools/MerSDK" -commandtype mb2 -mertarget SailfishOS-i486
-x86 qmake $@oluahuone:SailfishOS-i486-x86
```

So that's the trick: \$@ is replaced with the qmake call parameters, oluahuone is just the name of one of my computers.

4.2.3 merssh

Looking with top showed a process called merssh when qmake was started via QtCreator. Interesting, what's that?



```
○ ○ ○ SailfishOS-i486-x86 — bash — 80x10
lastenhuone:SailfishOS-i486-x86 sven$ find ~ -name merssh
/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/Resources/merssh
lastenhuone:SailfishOS-i486-x86 sven$
```

Figure 61: What is merssh?.

So it is part of the QtCreator that is shipped with the SailfishOS SDK.

```
○ ○ ○ SailfishOS-i486-x86 — bash — 80x11
lastenhuone:SailfishOS-i486-x86 sven$ /Users/sven/SailfishOS/bin/Qt\ Creator.app
/Contents/Resources/merssh
merssh usage:
merssh <options> <command>
  -sdktoolsdir  directory with Qt Creator's target helpers
  -mertarget    the mer target name
  -commandtype ['standard'|'sb2']
All options are mandatory.

lastenhuone:SailfishOS-i486-x86 sven$
```

Figure 62: merssh invoked, what's it?.

The existence of `merssh` need further investigation, I can not tell more at the moment. Probably it corresponds to the settings of the Mer SDK, shown in figure 69 on page 44.

More than that, it calls `sb2` which is short for Scratchbox2, have a look at section Scratchbox2 on page 44, there are more details. For now let's just assume that "Scratchbox 2 is a cross-compilation engine, it can be used to create a highly flexible SDK." [sb2].




Figure 63: Mer plugin, maybe that's the source of merssh?.

I've grepped the command line for the `merssh`

```
$ ps -ef|grep "merssh"
```

And the result is:

```
/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/../Resources
  /merssh -sdktoolsdir /Users/sven/.config/SailfishAlpha2/mer-sdk-
  tools/MerSDK -commandtype mb2 -mertarget SailfishOS-i486-x86 qmake
    /Users/sven/QtProjects/TestSailfishOS/TestSailfishOS.pro -r -spec
      linux-g++ CONFIG+=debug CONFIG+=declarative_debug CONFIG+=
        qml_debug -after OBJECTS_DIR=obj MOC_DIR=moc UI_DIR=ui RCC_DIR=rcc
```

The picture is getting clearer now. QtCreator starts the SDK version of qmake which call `merssh` with all parameters needed to call `qmake` via `mb2` on the virtual machine.

4.2.4 Compilers




Figure 64: Preferences, compiler tab.

The SailfishOS SDK uses GCC as compiler. It is run inside the Mer build engine for cross compilation, see page 43. Stored on your development machine is only



a stub or proxy that wants to connect to the virtual machine and start compiling from there.

```
oluhuone:SailfishOS-i486-x86 sven$ ./gcc
Project ERROR: Could not connect to MerSDK Virtual Machine. No private key file
given.
oluhuone:SailfishOS-i486-x86 sven$
```

Figure 65: Running GCC from command line.

So far I don't know why this piece of software is not installed with the rest of the SDK, `~/.config` is not a directory where I would expect executables. The error message even shows up if the *Mer build engine for cross compilation* is up and running. Again this helper program is invoked via merssh, see page 38.

Looking inside `gcc` from the SDK I also find a bash script:

```
#!/bin/bash
exec "/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/../
Resources/merssh" -sdktoolsdir "/Users/sven/.config/SailfishAlpha2
/mer-sdk-tools/MerSDK" -commandtype sb2 -mertarget SailfishOS-i486
-x86 gcc $@oluhuone:SailfishOS-i486-x86
```

`$@` is replaced with the `gcc` call parameters, `oluhuone` is just the name of my current machine.

4.2.5 make

Again, `make` is just a bash script, `$@` replaced, `oluhuone` my machine:

```
#!/bin/bash
```



```
exec "/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/../Resources/merssh" -sdktoolsdir "/Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK" -commandtype mb2 -mertarget SailfishOS-i486-x86 make $@oluahuone:SailfishOS-i486-x86
```

I've grepped the command line for the merssh while building the application.

```
$ ps -ef|grep "merssh"
```

Resulting in

```
/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/../Resources/merssh -sdktoolsdir /Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK -commandtype mb2 -mertarget SailfishOS-i486-x86 make
```

4.2.6 rpm

Guess what, a bash script:

```
#!/bin/bash
exec "/Users/sven/SailfishOS/bin/Qt Creator.app/Contents/MacOS/../Resources/merssh" -sdktoolsdir "/Users/sven/.config/SailfishAlpha2/mer-sdk-tools/MerSDK" -commandtype mb2 -mertarget SailfishOS-i486-x86 rpm $@oluahuone:SailfishOS-i486-x86
```

4.2.7 Project settings

4.2.8 Pimp the clean process

Every now and then you clean your project. What bugged my for some time using QtCreator⁷ was that it left the Makefile after you cleaned the project. This way qmake is often not run after a make clean. No problem, just hit the button **Add Clean Step ▾** and create an extra step that is executed every time after the cleanup has been done.

⁷That has nothing to do with the SailfishOS SDK, the regular QtCreator does that, too.




Figure 66: Create a custom process step.




Figure 67: Clean step: Remove the Makefile.

Here again for copy and paste:

```
rm
-f ${buildDir}/Makefile
${buildDir}
```

4.3 Mer build engine for cross compilation

“The Mer build engine is a virtual machine (VM) containing the Mer development toolchains and tools. It also includes a SailfishOS target for building and running Sailfish and QML applications. The target is mounted as a shared folder to allow QtCreator to access the compilation target. Additionally, your home directory is shared and mounted in the VM, thus giving access to your source code for compilation. The build engine also supports additional build targets and cross-compilation toolchains. These can be managed from the SDK Control Centre interface within QtCreator which allows toolchains, targets and even individual target packages to be added and removed.”[sailfishos3].



Figure 68: SailfishOS icon.

The VM runs headless⁸, you can not see it running. For you as a developer there is a webpage served by this VM accessible through the SailfishOS icon inside QtCreator. See figure 47 on page 28.

⁸You can change that in Preferences->Mer, uncheck "Headless" and restart the VM or start it from the VirtualBox control center if you need it just once.




Figure 69: Preferences, Mer SDK - virtual machine.

4.4 Scratchbox2

"Scratchbox2 (sbox2 or sb2) is a cross-compilation toolkit designed to make embedded Linux application development easier. It also provides a full set of tools to integrate and cross-compile an entire Linux distribution.

In the Linux world, when building software, many parameters are auto-detected based on the host system (like installed libraries and system configurations), through autotools "./configure" scripts for example. But so, when one wants to build for an embedded target (cross-compilation), most of the detected parameters are incorrect (i.e. host configuration is not the same as the embedded target configuration).

Without Scratchbox2, one has to manually set many parameters and "hack" the "configure" process to be able to generate code for the embedded target.

At the opposite, Scratchbox2 allows one to set up a "virtual" environment that will trick the autotools and executables into thinking that they are directly running on the embedded target with its configuration.

Moreover, Scratchbox2 provides a technology called CPU-transparency that goes further in that area. With CPU-transparency, executables built for the host CPU or for the target CPU could be executed directly on the host with sbox2 handling the task to CPU-emulate if needed to run a program compiled for the target



CPU. So, a build process could mix the usage of program built for different CPU architectures. That is especially useful when a build process requires building the program X to be able to use it to build the program Y (Example: building a Lexer that will be used to generate code for a specific package).”[wiki02]

The Wiki page of the Mer project contains a exhaustive description how to compile a program on platform A for platform B[mer01].

4.5 The SailfishOS Emulator

“The emulator is an x86 VM image containing a stripped down version of the target device software. It emulates most of the functions of the target device running Sailfish operating system, such as gestures, task switching and ambience theming.”[sailfishos3]. At least with the AlphaSDK2 the emulator can not simulate device rotations.





Figure 70: Emulator running the templated SailfishOS Qt Quick Application.


4.6 Sailfish Silica


“Sailfish Silica is a QML module which provides Sailfish UI components for applications. Their look and feel fits with the Sailfish visual style and behavior and enables unique Sailfish UI application features, such as pulley menus and application covers.”[sailfishos3].


QML[qt05] is the Qt Quick Markup Language[qt06] that supersedes widgets for designing user interfaces. It is a declarative “language” that can contain a small subset of Javascript.


Also have a look at some open source examples on Github[sailfishos5]. The emulator comes with a demo application that shows the silica components.











4.7 Tools chained up

Now that we have seen all the tools, bits and pieces, I will try to give an overview how everything works together, when you compile your code in QtCreator for SailfishOS.

TODO put some text and images here. TODO find out, how the packaging happens, Makefile?

5 Installing additional packages

You can use additional libraries for your code, so you don't have to write all functionality for yourself. Some of them are available on the emulator and the physical device later on. Sadly not all library packages that are available for Nemo/Mer are usable here. Have look in section Harbour on ?? for details about allowed packages. That does not mean, that you can not use libraries that are not part of SailfishOS. You can deliver them with your app, linked to the correct



location. Mind the problems⁹ that you inherit by doing so.

5.1 Emulator

You can login from your development machine via terminal and `ssh`, the emulator should be running.

```
$ ssh -p 2223 nemo@localhost
nemo@localhost's password:
# the password is nemo
,---
| SailfishOS 0.98.0.67 (i486,testing)
'---
[nemo@SailfishEmul ~]$
```

As an alternative you can log in the running VM of the emulator. Press CMD+F2¹⁰¹¹ to change to the login screen. User and password are of course the same.

5.1.1 zypper

Additional software and libraries come in RPM packages and the management tool on the emulator is `zypper`. It provides “functions like repository access, dependency solving, package installation”[suse01].

```
[nemo@SailfishEmul ~]$ zypper refresh
```

will update the meta data that is stored from the package repository.

```
[nemo@SailfishEmul ~]$ zypper search
```

will show you all packages that can be installed on the emulator.

⁹Think security updates.

¹⁰On OSX your function keys will probably not work as regular function keys, they provide OSX functionality as printed on them, e.g. volume up/down. Go to System Preferences->Keyboard->Keyboard and check "Use all F1, F2, etc. as standard function keys".

¹¹On Windows and Linux use the CTRL Key instead of CMD.



```
[nemo@SailfishEmul ~]$ zypper search boost
```

will show you all package names that contain boost.

```
[nemo@SailfishEmul ~]$ sudo zypper install boost-filesystem
```

will install the library `boost-filesystem` and all its dependencies on the emulator. *Note:* `boost-filesystem` is not one of the currently available libraries¹².

```
[nemo@SailfishEmul ~]$ sudo zypper remove boost-filesystem
```

will remove the library `boost-filesystem` and all its dependencies from the emulator. Of course you can install additional software on the emulator¹³ that helps you to edit files directly or manage the filesystem better.

Note: you do not need the development packages on the emulator of physical device.

5.1.2 Known Logins

<i>user</i>	<i>password</i>	<i>comment</i>
nemo	nemo	
root		no password needed, just works in the VM for me

5.2 Mer SDK Build Engine



Figure 71: Choose “SailfishOS” from the left pane.

TODO

¹²So why do I use it as an example? Honi soit qui mal y pense.

¹³As long as this software is not part of your app.



5.2.1 Directories

TODO

5.2.2 Known Logins

<i>user</i>	<i>password</i>	<i>comment</i>
nemo	nemo	
root		no password needed, just works in the VM for me

6 Templates for QtCreator

The SailfishOS SDK comes with a template for a new SailfishOS Qt Quick Application project. On OSX those templates are stored inside the QtCreator bundle, you can change those templates there or create new ones.




Figure 72: Template for a new SailfishOS Qt Quick Application.

Just make sure that you don't use the names `obj`, `moc`, `ui` or `rcc` inside your template. These are going to be used to store the compile results and temporaries if you compile a SailfishOS program.



Updates of the SDK may delete changed or new templates, you might want to create a backup in a safe place.

TODO example of a new template, figure out the caveats here!

7 Physical device

Developing with the emulator only will do you no good. You have to experience your program on a real device. Things that might look great on an emulator, may not even work on a real phone. It maybe just you fingers that are hiding the screen. Buttons are too small or too close.

7.1 How to connect to SSH over usb connection from PC

- the usb is either `usb_storage` or `usb_net`
- enable developer mode
- enable SSH (it's openssh, not dropbear)
- set password
- goto usb settings
- change that to developer mode
- reconnect usb cable
- you should see the ip address of the device on the UI
- you should be able to ssh to that address from PC (set an ip address first)

Taken from [ex01].

This section obviously needs a lot more information. Lacking a physical device or an SDK that enables me to interact with it, this has to be done in future.

8 Harbour

our wrote a fantastic app and now you want to bring it to the people. Head over to the Jolla Harbour[jolla02] and submit your app.

There are some things about naming an such to consider when you prepare your app, here is the Sailfish FAQ from the Jolla Harbour as of now = Dec. 2nd



2013. This is of course a moving target, which means there will be more libraries available in future. Even if you don't have an app ready to submit, you should look there once in a while. No need to re-invent the wheel here. If there is missing something, contact Jolla.

Naming

What should I name the application?

You have to use the prefix "harbour-" in front of the application name. Only lower case characters are allowed.

Why do I have to name my Application with a prefix?

The reason for this requirement is so that applications do not clash with other installed packages on the device. It also allows us to verify certain things automatically, e.g. imports of your own QML modules.

What is that '\$NAME' you use here in the FAQ's?

That is your application name including the prefix "harbour-" (e.g. harbour-myawesomeapp).

How can I name the app in the application launch grid? I don't want that long name with prefix to appear there!

In the .desktop file, there is the "Name=" field. The string defined there is shown in the application launcher as the application name. That name does not have to be unique. So there might be more than one application called "HelloWorld!" in the application launcher grid. The package name of the application (\$NAME) does not appear in the UI.

Where must this \$NAME be used?

the executable binary: /usr/bin/\$NAME

the .desktop file: /usr/share/applications/\$NAME.desktop

the icon: /usr/share/icons/hicolor/86x86/apps/\$NAME.png

the folder in /usr/share where you can install other application files: /usr/share/\$NAME

The rpm package name, note that is not necessarily the same as the RPM file name!

The name you get with:

```
rpm -q --queryformat=' %{NAME} \n' -p harbour-awesomeapp-1.0.0.armv7hl.rpm
```

That is what is set in .spec resp. .yaml file under "Name: "

Your own QML imports resp. modules, but with "-" replaced with "." due to QML grammar rules. e.g import harbour.myawesomeapp.

MyQmlModule 1.0 as MyModule

Do I need to put that unique \$NAME into the "Title" field when I upload an app to the Harbour?

No, in the "Title" field you can use a pretty name that will be shown to the user in the store client UI.

RPM-Packaging

In which locations can I install files?

You are allowed to install:

/usr/bin/\$NAME <- the executable binary

/usr/share/applications/\$NAME.desktop <- the desktop file

```
/usr/share/icons/hicolor/86x86/apps/$NAME.png <- the icon file
/usr/share/$NAME/* <- anything else (data files, private shared
    libraries, private QML imports, etc..) goes here
Why are you so restrictive? Why can't I install my libraries, images
    etc in places where I think it makes sense?
We have to ensure that rpms can be installed and do not conflict with
    other rpms. It will also allow us to install store applications
    under a different path (rpm --relocate) in the future.
What does the package name have to be? (.spec/.yaml "Name: foo")
Use "Name: $NAME". See Naming section in this FAQ.

Icons
Which size should the application icon be?
86x86. Older SDK versions contain a template which suggests a size of
    90x90. That is obsolete and will soon be updated with the next
    SDK version.
Where shall the icon be installed?
/usr/share/icons/hicolor/86x86/apps/$NAME.png. Older SDK versions
    contain a template which suggests a size of 90x90 and also a
    different install path. That is obsolete, not supported anymore,
    and will soon be updated with the next SDK version.
What file formats are supported for the icon?
The icon must be a PNG file.
How do I define an icon in the .desktop file, so it shows up in the
    application launcher?
Icon=$NAME

You must not use absolute path names. There was a bug in older SDK
    versions (lipstick < 0.18.6) so the absolute path was necessary
    and the template suggested it. That will soon be updated with the
    next SDK version. The reason to not use absolute path names is: it
    would allow us in the future to install store applications under
    a different path.

.desktop-Files
What do I have to put into the Exec= line?
Exec=$NAME (for Silica applications using C++ and QML) or Exec=
    sailfish-qml $NAME (for QML-only Silica applications without an
        application binary)
What do I have to put into the Icon= line?
Icon=$NAME
What do I have to put into the Name= line?
The name defined there is shown in the application launcher as the
    application name. That name does not have to be unique. So there
    might be more than one application called "HelloWorld!" in the
    application launcher grid.
What do I have to put into the X-Nemo-Application-Type= line and what
    is it good for?
For Silica Qt 5 applications, use "X-Nemo-Application-Type=silica-qt
    5" - this will make sure that the application is launched using
```

the right booster, and will make startup faster.

How can I disable single-instance launching?

In general, you should use single-instance launching (tapping on the application icon will bring the existing window to the foreground). If for some reason your application conflicts with single-instance launching, you can add "X-Nemo-Single-Instance=no" to your .desktop file to disable this behaviour.

QML API

Which QML modules (imports) are allowed?

Currently the following QML modules (imports) are allowed:

QtQuick 2.0

QtQuick 2.1

QtMultimedia 5.0

Sailfish.Silica 1.0

QtQuick.LocalStorage 2.0

QtQuick.XmlListModel 2.0

QtQuick.Particles 2.0

QtQuick.Window 2.0

Why do you not allow more QML modules from Qt/Nemo/Mer or other 3rd party?

Not all modules have a stable API. Before promising compatibility, we must first make sure that we can promise the API is of high quality and will not change (through a review process). We are open for suggestions to provide more APIs.

Can I use QML modules, which I ship together with the application?

Yes, you can do that. But you have to prefix the name of the imports with your \$NAME, but with "--" replaced with "." due to QML grammar rules (e.g. harbour.myapp.myQmlObject, where harbour-myapp = \$NAME). And you have to install them under /usr/share/\$NAME (loadable QML plugins or the QML files) if the type is not built into the application (setContextProperty).

Shared Libraries

Which shared libraries can I link against?

Currently the following shared libraries are allowed:

libsailfishapp.so.1

libmdeclarativecache5.so.0

libQt5Quick.so.5

libQt5Qml.so.5

libQt5Network.so.5

libQt5Gui.so.5

libQt5Core.so.5

libGLESv2.so.2

libpthread.so.0

libstdc++.so.6

libm.so.6

libgcc_s.so.1

libc.so.6

ld-linux-armhf.so.3

libQt5Concurrent.so.5

```
libQt5Multimedia.so.5
libQt5Sql.so.5
libQt5Svg.so.5
libQt5XmlPatterns.so.5
libQt5Xml.so.5
librt.so.1
libz.so.1
libQt5DBus.so.5
```

Why do you allow just such a limited amount of shared libraries?
We can only whitelist libraries that have both a stable API and ABI,
and which we are sure we can provide for the foreseeable future.
For now, the list is quite small, but as Sailfish OS matures, we
expect to add more. We are open for suggestions to allow more
stable shared libraries.

Can I link against shared libraries which I ship with the app
together in the same rpm?

Yes, you can do that. But you have to install the library under /usr/
share/\$NAME/. You have to ensure yourself that the rpath in your
executable is set correct, so the linker finds the library. Future
versions of invoker might set the LD_LIBRARY_PATH to /usr/share/\$
NAME/, but that is not yet in place.

You do not allow OpenGL, what is the alternative?

QtGui in Qt 5 includes a number of classes to replace the OpenGL
classes. In many cases, using the QtGui equivalents will just
involve a renaming (QGL* -> QOpenGL*) and removing the linking
against OpenGL. There are API changes involved in some cases,
but these should not be too difficult.

Startup performance is better without using OpenGL, which is one
reason we are disallowing it. This is due to its dependency on
QtWidgets, which is quite a large library.

Why do you not allow QtWidgets?

QtWidgets is not optimized for (or well tested) on Sailfish OS.
Furthermore, it is generally not going to result in a good user
experience due to using non-touch-optimized controls, and software
rendering (which will be much slower than rendering using OpenGL
ES on Sailfish OS).

I think library XYZ would be useful for others too, I want to make
that library available in the store. Can I submit a library only
rpm?

No, the app store, is as the name says, an application store and not
a shared library store. But if you think an important library is
missing in SailfishOS and you want to see it available in the
platform, then please join the Mer and Nemo project and make the
library available in one of these projects. Then suggest the
library to become a supported one (by making sure it has a stable
API, and is well-maintained and supported).

Runtimes



Can I submit Python applications?
Currently not, there are some enablers missing for that. But we are working on it, to make that happen. You can support us with that effort, please ask in Nemo project how to help with Python.
Can I submit Perl/Ruby/\$MY_FAVOURITE_LANGUAGE applications?
No, and we currently do not plan to support that. But feel free to request it, if there is enough interest, we might allow it in the future.

9 Bug Reports

TODO what's the correct way to report bugs? IMHO IRC and mailing list are just temporary solutions. You can also write to developer-care@jolla.com but right at the moment there is no developer-specific bug tracker.

10 Troubleshooting

10.1 Mer build engine for cross compilation

10.1.1 Management Webpage

For some users (this includes me), the management webpage is not shown, instead there is an empty webpage ("about:blank"). Type "127.0.0.1:8080" as URL and hit <Enter>¹⁴. If it doesn't work at all (even that happened to me), then you can enter "127.0.0.1:8080" in your regular browser.

If you are in doubt that there is anything running at all, you can use telnet or mmap[nm01] to check if someone is listening on the given address and port.

```
$ telnet 127.0.0.1 8080
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.
```

```
nmap -p 8080 -sV localhost

Starting Nmap 6.25 ( http://nmap.org ) at 2013-12-05 18:20 CET
Nmap scan report for localhost (127.0.0.1)
Host is up (0.000071s latency).
PORT      STATE SERVICE VERSION
```

¹⁴the complete URL is <http://127.0.0.1:8080/C/targets/>



```
8080/tcp open  http    WEBrick httpd 1.3.1 (Ruby 1.9.3 (2013-06-05))

Service detection performed. Please report any incorrect results at
http://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 6.49 seconds
```

10.1.2 SSH login

You try to connect via SSH with the VM and get this:

```
$ ssh -p 2222 nemo@localhost
@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@WARNING: REMOTE HOST IDENTIFICATION HAS CHANGED! @
@@@@@@@@@@@@@@@@@@@@@@@@@@@IT IS POSSIBLE THAT SOMEONE IS DOING SOMETHING NASTY!
Someone could be eavesdropping on you right now (man-in-the-middle
attack)!

It is also possible that a host key has just been changed.
The fingerprint for the RSA key sent by the remote host is
75:51:61:e8:3a:80:41:ab:81:36:bc:45:8f:ca:56:76.
Please contact your system administrator.
Add correct host key in /Users/sven/.ssh/known_hosts to get rid of
this message.

Offending RSA key in /Users/sven/.ssh/known_hosts:3
RSA host key for [localhost]:2222 has changed and you have requested
strict checking.

Host key verification failed.
```

Somehow the image of the VM has changed since you last logged in. Remove it from known hosts and re-connect to accept the new host key.

```
$ ssh-keygen -R [localhost]:2222
/Users/sven/.ssh/known_hosts updated.
Original contents retained as /Users/sven/.ssh/known_hosts.old
sylimikro:~ sven$ ssh -p 2222 nemo@localhost
The authenticity of host '[localhost]:2222 ([127.0.0.1]:2222)' can't
be established.
RSA key fingerprint is 75:51:61:e8:3a:80:41:ab:81:36:bc:45:8f:ca
:56:76.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '[localhost]:2222' (RSA) to the list of
known hosts.
```

Check with `mmap[nm01]` if a ssh service is listening at all.

```
# this is an example of a non-working ssh daemon
nmap -p 2222 -sV localhost

Starting Nmap 6.25 ( http://nmap.org ) at 2013-12-05 13:37 CET
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00021s latency).
PORT      STATE SERVICE      VERSION
2222/tcp  open  EtherNet/IP-1?

Service detection performed. Please report any incorrect results at
  http://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 89.49 seconds
```

If you can see that the ssh daemon is not working, you can restart the VM directly from VirtualBox, log into the VM as user `root` from there, check for the daemon and start it.

```
ps -ef | grep sshd
root      533      0 2:05pm tty2      0:00.01 grep sshd
# OK, it is not running - start it
systemctl start sshd.service
# check again
ps -ef | grep sshd
root      534      1 2:06pm tty2      0:00.01 /usr/sbin/sshd -D -f /etc/ssh
  /sshd_config_engine
root      535      1 2:06pm tty2      0:00.01 grep sshd
```

Now you can check from your development machine again.

```
# here the ssh daemon works
nmap -p 2222 -sV localhost

Starting Nmap 6.25 ( http://nmap.org ) at 2013-12-05 14:01 CET
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00013s latency).
PORT      STATE SERVICE VERSION
2222/tcp  open  ssh      OpenSSH 5.6 (protocol 2.0)

Service detection performed. Please report any incorrect results at
  http://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.24 seconds
```

It may even happen that your public key is missing, check with



```
ls ~/.ssh/mer-qt-creator-rsa  
ls: /Users/sven/.ssh/mer-qt-creator-rsa: No such file or directory
```

Right at the moment I am not sure when the key files are delivered. At install time would make sense but here must investigate further. Ok, I have removed them during the last uninstall but shouldn't they come with a new install?

If your SSH connection still does not work, it may be that the drive with the `authorized_keys` file is not mounted.

10.1.3 Drive(s) not mounted

Log into the VM and have a look if the drive with the `authorized_keys` file is mounted.

SailfishSDK login: root
 Last login: Tue Dec 3 17:25:49 on tty2
 [root@SailfishSDK ~]# mount
 /dev/root on / type ext4 (rw,noatime,data=ordered)
 devtmpfs on /dev type devtmpfs (rw,relatime,size=254256k,nr_inodes=63564,mode=755)
 proc on /proc type proc (rw,relatime)
 sysfs on /sys type sysfs (rw,relatime)
 tmpfs on /dev/shm type tmpfs (rw,relatime)
 devpts on /dev/pts type devpts (rw,relatime,gid=5,mode=620)
 tmpfs on /run type tmpfs (rw,nosuid,nodev,mode=755)
 tmpfs on /sys/fs/cgroup type tmpfs (rw,nosuid,nodev,noexec,mode=755)
 cgroup on /sys/fs/cgroup/systemd type cgroup (rw,nosuid,nodev,noexec,relatime,release_agent=/lib/systemd/systemd-cgroups-agent,name=systemd)
 cgroup on /sys/fs/cgroup/cpuset type cgroup (rw,nosuid,nodev,noexec,relatime,cpuset)
 cgroup on /sys/fs/cgroup/cpu_cpuacct type cgroup (rw,nosuid,nodev,noexec,relatime,cpuacct,cpu)
 cgroup on /sys/fs/cgroup/devices type cgroup (rw,nosuid,nodev,noexec,relatime,devices)
 cgroup on /sys/fs/cgroup/freezer type cgroup (rw,nosuid,nodev,noexec,relatime,freezer)
 cgroup on /sys/fs/cgroup/bkl type cgroup (rw,nosuid,nodev,noexec,relatime,bkl)
 cgroup on /sys/fs/cgroup/perf_event type cgroup (rw,nosuid,nodev,noexec,relatime,perf_event)
 systemd-1 on /proc/sys/fs/binfmt_misc type autofs (rw,relatime,fd=19,pgroup=1,timeout=300,minproto=5,maxproto=5,direct)
 debugfs on /sys/kernel/debug type debugfs (rw,relatime)
 mqueue on /dev/mqueue type mqueue (rw,relatime)
 tmpfs on /tmp type tmpfs (rw)
 none on /etc/ssh/authorized_keys type vboxsf (rw,nodev,relatime)
 none on /home/mersdk type vboxsf (rw,nodev,relatime)
 none on /host_targets type vboxsf (rw,nodev,relatime)
 none on /etc/mersdk/share type vboxsf (rw,nodev,relatime)
 none on /media/sf_ssh type vboxsf (rw,nodev,relatime)
 statefs on /run/state type fuse.statefs (rw,nosuid,nodev,relatime,user_id=0,group_id=100,default_permissions,allow_other)
 fusectl on /sys/fs/fuse/connections type fusectl (rw,relatime)
 none on /home/src1 type vboxsf (rw,nodev,relatime)
 none on /etc/ssh/authorized_keys type vboxsf (rw,nodev,relatime)
 [root@SailfishSDK ~]# ls /etc/ssh/authorized_keys
 mersdk root
 [root@SailfishSDK ~]#

Figure 73: Check for authorized_keys.

If the drive exists¹⁵, you can check if the file is accessible.

```
ls -lah /etc/ssh/authorized_keys/mersdk/authorized_keys
ls -lah /etc/ssh/authorized_keys/root/authorized_keys
```

TODo talk about the other drives. TODo maybe caused by missing VBox extension pack

Your VM acts strange and you don't know why? Check if updates for VirtualBox are available. If yes, download and install the latest version and don't forget the extension pack.

¹⁵It seems that the output of mount does not show it right, even if it is mounted and accessible.



Figure 74: Check if VirtualBox update is available.




Figure 75: Update for VirtualBox is available.

I had the situation where everything seems perfect and still it didn't work. For me the last resort was re-installing the VM with the Mer SDK, see section Uninstall on page 65.

TODO check if we can do that via the SDKMaintenanceTool - how to invalidate the VM image?

One one machine the VM was running but slow¹⁶, so every connection attempt timed out. Even control from VirtualBox itself was almost impossible. Until now I found no solution for this.

TODO find out if installing the Guest Additions helps.

¹⁶As in tar pit.



10.1.4 update via command line

TODO

11 Use your editor of choice

Now you are happy with coding for a device with SailfishOS and the SDK, API and all, but for some reason you want to use *your* editor¹⁷ of choice. Because you are used to it, never used something else, it's better, whatever. TODO provide one example of how to build with a foreign editor

12 Community

12.1 Jolla

Jolla homepage: <http://jolla.com>.

Jolla on Twitter: <https://twitter.com/JollaHQ>.

12.1.1 SailfishOS

As a developer you should subscribe to the mailing list at <https://lists.sailfishos.org/cgi-bin/mailman/listinfo-devel>.

Have a look at the Wiki at https://sailfishos.org/wiki/Main_Page.
At freenode: #sailfishos.

12.1.2 Mer

At freenode: #mer. Homepage: <http://merproject.org>.

12.1.3 Nemo mobile

At freenode: #nemomobile. Mer Wiki page about the Nemo project: <https://wiki.merproject.org/wiki/Nemo>.

13 Uninstall

You really want to quit? Stay here, the water is warm! Jokes aside, for whatever reason you might want to uninstall the SDK, here is how it goes.

¹⁷notepadl vi, emacs, eclipse, named it.

13.0.4 OSX



Figure 76: Inside the SailfishOS folder you find the maintenance application. Start it to uninstall the SDK.




Figure 77: Uninstall, step 1.




Figure 78: Uninstall, step 2.




Figure 79: Uninstall, step 3.




Figure 80: Uninstall, step 4.

To make it really clean, remove orphaned files and directories. Of course you can keep those files for later use.

```
# I've seen conflicts with changing ssh keys. Remove to prevent that
# (you may want to install again later on)
rm ~/.ssh/mer-qt-creator-rsa*
# There seem remains of every iteration of the SDK
rm -R ~/.config/SailfishAlpha*
```

If you don't need VirtualBox anymore, mount the diskimage¹⁸ and start the `VirtualBox_Uninstall.tool`, a bash script that removes all components from your system.

¹⁸You still have that, don't you?



Figure 81: Uninstall of VirtualBox.

13.0.5 Windows

- Go to the control panel, choose "programs and features" and uninstall the SailfishOS SDK.
- Uninstall the VirtualBox from the same window if you don't need it anymore.

13.0.6 Linux

Sorry, as for installation: until now I can not provide information here.

14 Thanks

Of course a big thanks goes out to everybody at Jolla. You are #unlike!

References

- [jolla01] Jolla ltd., based in Finland - the inventors of the Jolla smartphone
<http://jolla.com>



- [jolla02] Jolla Harbour - the place for your apps
<https://harbour.jolla.com>
- [sailfishos01] SailfishOS - the operating system driving the Jolla smartphone
<https://sailfishos.org>
- [sailfishos2] Quick introduction into development with the SailfishOS SDK
<https://sailfishos.org/develop.html>
- [sailfishos3] SailfishOS SDK overview
<https://sailfishos.org/develop-overview-article.html>
- [sailfishos4] SailfishOS open source code
<http://releases.sailfishos.org/sdk/>
- [sailfishos5] Unofficial Sailfish OS third party open source apps collection
<https://github.com/sailfishapps>
- [vbox01] VirtualBox, a virtualization platform from Oracle
<https://www.virtualbox.org/wiki/Downloads>
- [hc01] hardcodes, that's my nickname and my website
<http://www.hardcodes.de>
- [hc02] This document on Github
<https://github.com/hardcodes/developwithsailfishos.git>
- [hc03] Alternative Icon for the QtCreator inside of the SailfishOS SDK
<http://blog.hardcodes.de/articles/68/sailfish-os-icon>
- [qt01] The Qt Project.
<https://qt-project.org>
- [qt02] QtCreator.
<https://qt-project.org/doc/qtcreator-2.8/>
- [qt03] qmake manual.
<https://qt-project.org/doc/qt-4.8/qmake-manual.html>
- [qt04] Meta-Object Compiler (MOC)
<https://qt-project.org/doc/qt-4.8/moc.html>



- [qt05] QML
<http://qt-project.org/doc/qt-5.0/qtqml/qtqml-index.html>
- [qt06] QtQuick
<http://qt-project.org/doc/qt-5.0/qtquick/qtquick-index.html>
- [qt07] QtCreator, Adding New Custom Wizards
<http://qt-project.org/doc/qtcreator-2.8/creator-project-wizards.html>
- [wiki01] Wikipedia, Model–view–controller (MVC)
<http://en.wikipedia.org/wiki/Model\T1\textendashview\T1\textendashcontroller>
- [wiki02] Wikipedia, Scratchbox2
<http://en.wikipedia.org/wiki/Scratchbox2>
- [sb2] Scratchbox2 homepage
<https://maemo.gitorious.org/scratchbox2>
- [mer01] Mer Wiki, Platform SDK and SB2
https://wiki.merproject.org/wiki/Platform_SDK_and_SB2
- [ex01] Jolla details on eLinux
<http://elinux.org/Jolla>
- [sdc01] SmartDevCon
<http://smartdevcon.eu>
- [gh01] The missing HelloWorld. Wizard included by Artem Marchenko
<https://github.com/amarchenko/helloworld-pro-sailfish>
- [suse01] openSUSE Portal:Zypper
<http://en.opensuse.org/Portal:Zypper>
- [nm01] Nmap, network security scanner
<http://nmap.org>