




Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)



METRICS Expand view

First Contentful Paint 1.2 s	▲ Largest Contentful Paint 4.2 s
▲ Total Blocking Time 1,110 ms	Cumulative Layout Shift 0
Speed Index 3.0 s	



Show audits relevant to: All [FCP](#) [LCP](#) [TBT](#) [CLS](#)

INSIGHTS

▲ Render-blocking requests — Est savings of 230 ms

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. [FCP](#) [LCP](#) [Unscored](#)

URL	Transfer Size	Duration
localhost 1st Party	18.9 KiB	620 ms
...chunks/0hz1v.k8h9-gw.css (localhost)	2.5 KiB	160 ms
...chunks/0t7hbp5w_cjk.css (localhost)	16.3 KiB	460 ms

▲ Forced reflow

A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations. [Unscored](#)

Top function call	Total reflow time
09cnksaujqigc.js:2	103 ms

Source	Total reflow time
[unattributed]	99 ms
0az4pliqyb7t5.js:1	0 ms
0az4pliqyb7t5.js:1	5 ms
0az4pliqyb7t5.js:1	0 ms
0az4pliqyb7t5.js:1	3 ms
0az4pliqyb7t5.js:1	75 ms
13mnudu6j4hfs.js:1	1 ms
0az4pliqyb7t5.js:1	10 ms
0az4pliqyb7t5.js:1	1 ms
0az4pliqyb7t5.js:1	1 ms
0az4pliqyb7t5.js:1	1 ms
0az4pliqyb7t5.js:1	4 ms
0az4pliqyb7t5.js:1	2 ms
0az4pliqyb7t5.js:1	5 ms
0az4pliqyb7t5.js:1	5 ms
0j700fnrh074k.js:9	2 ms
0j700fnrh074k.js:9	1 ms
0j700fnrh074k.js:9	0 ms
0j700fnrh074k.js:9	0 ms
0az4pliqyb7t5.js:1	1 ms
0az4pliqyb7t5.js:1	3 ms
0j700fnrh074k.js:1	1 ms
0az4pliqyb7t5.js:1	2 ms

▲

Network dependency tree

^

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. (LCP) [Unscored]

Maximum critical path latency: 93 ms

Initial Navigation

http://localhost:3000 - 65 ms, 27.20 KiB

...chunks/0hz1v.k8h9-gw.css (localhost) - 93 ms, 2.54 KiB

...chunks/0t7hbvp5w_cjk.css (localhost) - 93 ms, 16.34 KiB

Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://1wlu6dtl.api.sanity.io/	link
Unused preconnect. Only use `preconnect` for origins that the page is likely to request.	

Origin	Source
https://cdn.sanity.io/	link

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Improve image delivery — Est savings of 43 KiB

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) (FCP) (LCP) (Unscored)

URL	Resource Size	Est Savings
localhost 1st Party	50.4 KiB	42.6 KiB
 Hardik Vatukiya — Full Stack Developer 	50.4 KiB	42.6 KiB
This image file is larger than it needs to be (750x688) for its displayed dimensions (294x270). Use responsive images to reduce the image download size.		42.6 KiB

Legacy JavaScript — Est savings of 14 KiB

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) (FCP) (LCP) (Unscored)

URL	Wasted bytes
localhost 1st Party	13.6 KiB
...chunks/09cnksaujqigc.js (localhost)	13.6 KiB
09cnksaujqigc.js:1 09cnksaujqigc.js:1 09cnksaujqigc.js:1 09cnksaujqigc.js:1 09cnksaujqigc.js:1 09cnksaujqigc.js:1 09cnksaujqigc.js:1	Array.prototype.at Array.prototype.flat Array.prototype.flatMap Object.fromEntries Object.hasOwn String.prototype.trimEnd String.prototype.trimStart

○ Optimize DOM size


A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size.](#) (Unscored)

Statistic	Element	Value
Total elements		981
DOM depth	path	15
Most children	body.min-h-full.flex.flex-col.relative	26

○ LCP breakdown

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. (LCP) (Unscored)

Subpart	Duration
Time to first byte	20 ms
Element render delay	270 ms



Hardik Vatukiya — Full-Stack Developer Hardik Vatukiya
`<h1 class="text-foreground px-8 text-[200px] md:text-[350px] font-hero leading-[0.8] ...">`

○ 3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. (Unscored)

3rd party	Transfer size	Main thread time
mnbndgmknlpdjdnjfmfcdjoegcckoikn	0 KiB	2 ms
chrome-extension://mnbndgmknlpdjdnjfmfcdjoegcckoikn/js/content.js	0 KiB	2 ms
sanity.io	0 KiB	0 ms
...production/4234227...-1920x1080.svg (cdn.sanity.io)	0 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

▲ Reduce JavaScript execution time — 2.8 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) (TBT) (Unscored)

URL	Total CPU Time	Script Evaluation	Script Parse
localhost 1st Party	6,304 ms	2,719 ms	42 ms
...chunks/09cnksaujqigc.js (localhost)	2,833 ms	2,184 ms	17 ms
http://localhost:3000	1,878 ms	31 ms	10 ms
...chunks/0az4pliqyb7t5.js (localhost)	1,447 ms	361 ms	12 ms
...chunks/0cfwitrpb0mv.js (localhost)	146 ms	144 ms	2 ms

URL	Total CPU Time	Script Evaluation	Script Parse
Unattributable	330 ms	11 ms	0 ms
Unattributable	330 ms	11 ms	0 ms

▲ Minimize main-thread work — 6.9 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT Unscored

Category	Time Spent
Script Evaluation	2,852 ms
Style & Layout	1,962 ms
Other	1,521 ms
Rendering	357 ms
Script Parsing & Compilation	124 ms
Parse HTML & CSS	48 ms

▲ Reduce unused JavaScript — Est savings of 93 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript](#) FCP LCP Unscored

URL	Transfer Size	Est Savings
localhost 1st Party	223.9 KiB	92.7 KiB
...chunks/02tru3enbrw6u.js (localhost)	29.7 KiB	24.4 KiB
...chunks/0az4pliqyb7t5.js (localhost)	52.1 KiB	23.8 KiB
...chunks/0j700fnrh074k.js (localhost)	73.0 KiB	23.7 KiB
...chunks/09cnksaujqigc.js (localhost)	69.1 KiB	20.8 KiB

Minify JavaScript — Est savings of 2 KiB

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript](#) FCP LCP Unscored

URL	Transfer Size	Est Savings
chrome-extension://mnbdgmknlpdjdnjfmfcdjoegcckoikn/js/content.js	6.7 KiB	2.3 KiB

○ Avoid long main-thread tasks — 8 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT Unscored

URL	Start Time	Duration
localhost 1st Party		2,124 ms
...chunks/09cnksaujqigc.js (localhost)	5,577 ms	1,060 ms
...chunks/09cnksaujqigc.js (localhost)	5,033 ms	386 ms
http://localhost:3000	930 ms	217 ms
...chunks/09cnksaujqigc.js (localhost)	4,692 ms	114 ms
http://localhost:3000	761 ms	110 ms
...chunks/09cnksaujqigc.js (localhost)	4,561 ms	109 ms
...chunks/0az4pliqyb7t5.js (localhost)	5,453 ms	76 ms
...chunks/09cnksaujqigc.js (localhost)	4,841 ms	52 ms

☐ Avoid non-composited animations — 18 animated elements found ^

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS
Unscored

Element
div.absolute.-bottom-12.-left-12.w-32.h-32.rounded-full.blur-xl.md:blur-3xl.pointer-events-none.transi...
Unsupported CSS Property: visibility
div.absolute.-bottom-12.-left-12.w-32.h-32.rounded-full.blur-xl.md:blur-3xl.pointer-events-none.transi...
Unsupported CSS Property: visibility
div.absolute.-bottom-12.-left-12.w-32.h-32.rounded-full.blur-xl.md:blur-3xl.pointer-events-none.transi...
Unsupported CSS Property: visibility
div.absolute.-bottom-12.-left-12.w-32.h-32.rounded-full.blur-xl.md:blur-3xl.pointer-events-none.transi...
Unsupported CSS Property: visibility
div.js-icon.absolute.top-0.right-0.p-6.md:p-8.text-accent-primary.pointer-events-none.transition-all.du...
Unsupported CSS Property: visibility
div.js-card-content.bg-[color-mix(in_srgb,var(--background),transparent_60%)] backdrop-blur-[20px].b...
Unsupported CSS Property: visibility
span.h-px.w-4.transition-all.duration-300.bg-accent-primary/30
Unsupported CSS Property: visibility
span.w-6.md:w-8.h-px.bg-accent-primary/30.group-hover:w-12.group-hover.bg-accent-secondary.tra...
Unsupported CSS Property: visibility
div.js-icon.absolute.top-0.right-0.p-6.md:p-8.text-accent-primary.pointer-events-none.transition-all.du...
Unsupported CSS Property: visibility
div.js-card-content.bg-[color-mix(in_srgb,var(--background),transparent_60%)] backdrop-blur-[20px].b...
Unsupported CSS Property: visibility
span.w-6.md:w-8.h-px.bg-accent-primary/30.group-hover:w-12.group-hover.bg-accent-secondary.tra...
Unsupported CSS Property: visibility
span.h-px.w-4.transition-all.duration-300.bg-accent-primary/30

Element

Unsupported CSS Property: visibility

div.js-icon.absolute.top-0.right-0.p-6.md:p-8.text-accent-primary.pointer-events-none.transition-all.du...

Unsupported CSS Property: visibility

div.js-card-content.bg-[color-mix(in_srgb,var(--background),transparent_60%)].backdrop-blur-[20px].b...

Unsupported CSS Property: visibility

span.h-px.w-4.transition-all.duration-300.bg-accent-primary/30

Unsupported CSS Property: visibility

span.w-6.md:w-8.h-px.bg-accent-primary/30.group-hover:w-12.group-hover.bg-accent-secondary.tra...

Unsupported CSS Property: visibility

div.js-icon.absolute.top-0.right-0.p-6.md:p-8.text-accent-primary.pointer-events-none.transition-all.du...

Unsupported CSS Property: visibility

div.js-card-content.bg-[color-mix(in_srgb,var(--background),transparent_60%)].backdrop-blur-[20px].b...

Unsupported CSS Property: visibility

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (15) Hide

Use efficient cache lifetimes ^

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#) FCP LCP Unscored

Layout shift culprits ^

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS Unscored

Document request latency ^

Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

- Avoids redirects
- Server responds quickly (observed 14 ms)
- Applies text compression

Duplicated JavaScript ^

Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

Font display ^

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). Unscored

☐ INP breakdown ^

Start investigating [how to improve INP](#) by looking at the longest subpart. Unscored

☐ LCP request discovery ^

[Optimize LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading (Unscored)

Modern HTTP

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#) (FCP) (LCP) (Unscored)

Optimize viewport for mobile

Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile. (Unscored)

meta

Minify CSS

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS](#) (FCP) (LCP) (Unscored)

Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS](#) (FCP) (LCP) (Unscored)

Avoids enormous network payloads — Total size was 626 KiB

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes](#) (Unscored)

URL	Transfer Size
localhost (1st Party)	432.8 KiB
...chunks/0j700fnrh074k.js (localhost)	74.1 KiB
...chunks/09cnksaujqgc.js (localhost)	70.2 KiB
...chunks/0az4pliqyb7t5.js (localhost)	53.2 KiB
/_next/image?url=... (localhost)	51.0 KiB
...media/03bda585a99c6450-s.p.0zzh68k1~whtc.woff2 (localhost)	36.7 KiB
...chunks/02tru3enbrw6u.js (localhost)	30.8 KiB
...media/797e433ab948586e-s.p.09zddjkbdep5a.woff2 (localhost)	30.3 KiB
...media/caa3a2e1cccd8315-s.p.09~u27dqhyhd6.woff2 (localhost)	29.6 KiB
...chunks/12aji617h67maj.js (localhost)	29.6 KiB
http://localhost:3000	27.2 KiB

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks](#) (Unscored)

Image elements have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) (CLS) (Unscored)

Page didn't prevent back/forward cache restoration

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#) (Unscored)



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

NAMES AND LABELS

▲ Buttons do not have an accessible name

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible](#).

Failing Elements

button.w-9.h-9.rounded-full.border.border-border/80.bg-foreground/1.hover:bg-foreground/4.disabl...

button.w-9.h-9.rounded-full.border.border-border/80.bg-foreground/1.hover:bg-foreground/4.disabl...

▲ Links do not have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible](#).

Failing Elements



a.transition-all.duration-300.hover:scale-110.active:scale-95.group

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast](#).

Failing Elements



button.inline-flex.items-center.cursor-pointer.justify-center.font-bold.uppercase.tracking-tighter.transit...

span.relative.z-10.text-accent-primary.font-bold

div.absolute.inset-0.bg-accent-primary/10.border.border-accent-primary/25.rounded-full.shadow-[0_2...

Failing Elements

div.flex.gap-1.5.bg-foreground/2.border.border-border/60.p-1.rounded-full.select-none

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

button.px-3.5.py-1.5.rounded-lg.text-[0.68rem].font-bold.transition-all.duration-300.cursor-pointer.shr...

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

section#faq.relative.z-30.bg-background.text-foreground.px-6.py-10.sm:py-12.border-t.border-border...

span.opacity-60.text-[0.58rem].font-mono

button.px-3.5.py-1.5.rounded-lg.text-[0.68rem].font-bold.transition-all.duration-300.cursor-pointer.shr...

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

section#faq.relative.z-30.bg-background.text-foreground.px-6.py-10.sm:py-12.border-t.border-border....

span.opacity-60.text-[0.58rem].font-mono

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

section#faq.relative.z-30.bg-background.text-foreground.px-6.py-10.sm:py-12.border-t.border-border...

span.opacity-60.text-[0.58rem].font-mono

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

section#faq.relative.z-30.bg-background.text-foreground.px-6.py-10.sm:py-12.border-t.border-border....

span.opacity-60.text-[0.58rem].font-mono

div.faq-hub-header.flex.flex-col.sm:flex-row.items-center.justify-between.gap-6.w-full.mb-6.bg-foregro...

section#faq.relative.z-30.bg-background.text-foreground.px-6.py-10.sm:py-12.border-t.border-border....

These are opportunities to improve the legibility of your content.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)	Hide
Interactive controls are keyboard focusable Custom interactive controls are keyboard focusable and display a focus indicator. Learn how to make custom controls focusable. Unscored	^
Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn how to decorate interactive elements with affordance hints. Unscored	^
The page has a logical tab order Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more about logical tab ordering. Unscored	^
Visual order on the page follows DOM order DOM order matches the visual order, improving navigation for assistive technology. Learn more about DOM and visual ordering. Unscored	^
User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn how to avoid focus traps. Unscored	^
The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn how to direct focus to new content. Unscored	^

HTML5 landmark elements are used to improve navigation	
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more about landmark elements. Unscored	
Offscreen content is hidden from assistive technology	
Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content. Unscored	
Custom controls have associated labels	
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more about custom controls and labels. Unscored	
Custom controls have ARIA roles	
Custom interactive controls have appropriate ARIA roles. Learn how to add roles to custom controls. Unscored	
These items address areas which an automated testing tool cannot cover. Learn more in our guide on conducting an accessibility review.	
PASSED AUDITS (20)	Hide
[aria-*] attributes match their roles	
Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. Learn how to match ARIA attributes to their roles.	
[aria-hidden="true"] is not present on the document <body>	
Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body.	
[role]s have all required [aria-*] attributes	
Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more about roles and required attributes.	
[role] values are valid	
ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles.	
[aria-*] attributes have valid values	
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more about valid values for ARIA attributes.	
[aria-*] attributes are valid and not misspelled	
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more about valid ARIA attributes.	
Image elements have [alt] attributes	
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute.	
Form elements have associated labels	
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more about form element labels.	

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.	^
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag.	
Select elements have associated label elements.	^
Form elements without effective labels can create frustrating experiences for screen reader users. Learn more about the select element.	
ARIA attributes are used as specified for the element's role	^
Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes.	
[aria-hidden="true"] elements do not contain focusable descendents	^
Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements.	
Elements use only permitted ARIA attributes	^
Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles.	
Document has a <title> element	^
The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.	
<html> element has a [lang] attribute	^
If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute.	
<html> element has a valid value for its [lang] attribute	^
Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the lang attribute.	
Touch targets have sufficient size and spacing.	^
Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets.	
Heading elements appear in a sequentially-descending order	^
Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more about heading order.	
Document has a main landmark.	^
One main landmark helps screen reader users navigate a web page. Learn more about landmarks.	
Deprecated ARIA roles were not used	^
Deprecated ARIA roles may not be processed correctly by assistive technology. Learn more about deprecated ARIA roles.	
NOT APPLICABLE (37)	Hide

[accesskey] values are unique	
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more about access keys. Unscored	
button, link, and menuitem elements have accessible names	
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to make command elements more accessible. Unscored	
Elements with role="dialog" or role="alertdialog" have accessible names.	
ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. Learn how to make ARIA dialog elements more accessible. Unscored	
ARIA input fields have accessible names	
When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about input field labels. Unscored	
ARIA meter elements have accessible names	
When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name meter elements. Unscored	
ARIA progressbar elements have accessible names	
When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to label progressbar elements. Unscored	
Elements with an ARIA [role] that require children to contain a specific [role] have all required children.	
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more about roles and required children elements. Unscored	
[role]s are contained by their required parent element	
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element. Unscored	
Elements with the role=text attribute do not have focusable descendents.	
Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute. Unscored	
ARIA toggle fields have accessible names	
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields. Unscored	
ARIA tooltip elements have accessible names	
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name tooltip elements. Unscored	
ARIA treeitem elements have accessible names	
When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling treeitem elements. Unscored	
The page contains a heading, skip link, or landmark region	

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#) (Unscored)

- ☐ `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#) (Unscored)

- ☐ Definition list items are wrapped in `<dl>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#) (Unscored)

- ☐ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#) (Unscored)

- ☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#) (Unscored)

- ☐ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#) (Unscored)

- ☐ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#) (Unscored)

- ☐ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#) (Unscored)

- ☐ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#) (Unscored)

- ☐ Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) (Unscored)

- ☐ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#) (Unscored)

- ☐ List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#) (Unscored)

- ☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) (Unscored)

☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) (Unscored)

☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#) (Unscored)

☐ No element has a `[tabindex]` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute.](#) (Unscored)

☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#) (Unscored)

☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#) (Unscored)

☐ `[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#) (Unscored)

☐ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#) (Unscored)

☐ Tables have different content in the summary attribute and `<caption>`. ^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) (Unscored)

☐ All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) (Unscored)

☐ Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) (Unscored)

☐ Image elements do not have `[alt]` attributes that are redundant text. ^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) (Unscored)

☐ Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) (Unscored)



Best Practices

GENERAL

▲ Uses third-party cookies — 1 cookie found ^

Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions.](#)

Name	URL
sanity.io	
sanitySession	...production/4234227...-1920x1080.svg (cdn.sanity.io)

▲ Issues were logged in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Issue type
Cookie
...production/4234227...-1920x1080.svg (cdn.sanity.io)

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks ^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#) (Unscored)

Description	Directive	Severity
Host allowlists can frequently be bypassed. Consider using CSP nonces or hashes instead, along with "strict-dynamic" if necessary.	script-src	High
"unsafe-inline" allows the execution of unsafe in-page scripts and event handlers. Consider using CSP nonces or hashes to allow scripts individually.	script-src	High

○ Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) (Unscored)

Description	Directive	Severity
No HSTS header found		High

○ Ensure proper origin isolation with COOP ^

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) (Unscored)

Description	Directive	Severity
No COOP header found		High

Mitigate DOM-based XSS with Trusted Types

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types.](#)

Unscored

Description	Severity
No 'Content-Security-Policy' header with Trusted Types directive found	High

PASSED AUDITS (11)

Hide

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS.](#)

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs.](#)

Allows users to paste into input fields

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields.](#)

Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission.](#)

Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications.](#)

Displays images with correct aspect ratio

Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio.](#)

Serves images with appropriate resolution

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images.](#)

Page has the HTML doctype

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration.](#)

Properly defines charset

A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

No browser errors logged to the console ^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

Page has valid source maps ^

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps](#). (Unscored)

NOT APPLICABLE (3) Hide

○ Redirects HTTP traffic to HTTPS ^

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more](#). (Unscored)

○ Mitigate clickjacking with XFO or CSP ^

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking](#). (Unscored)

○ Detected JavaScript libraries ^

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit](#). (Unscored)



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

ADDITIONAL ITEMS TO MANUALLY CHECK (1) Hide

○ Structured data is valid ^

Run the [Structured Data Testing Tool](#) to validate structured data. [Learn more about Structured Data](#). (Unscored)

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (10) Hide

Page isn't blocked from indexing ^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives](#).

Document has a <title> element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles](#).

Document has a meta description ^

Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description.](#)

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes.](#)

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

Links are crawlable



Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)

robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#)

Image elements have [alt] attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

Document has a valid hreflang



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

Document has a valid rel=canonical



Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

■ Captured at Jun 5, 2026, 9:34 AM GMT+5:30

■ Emulated Moto G Power with Lighthouse 13.0.2

■ Single page session

■ Initial page load

■ Slow 4G throttling

■ Using Chromium 148.0.0.0 with devtools