

Classical Synchronization Problem Examples

Bounded-Buffer, Readers-Writers
&
Dining-Philosophers

Classical Problems of Synchronization

- ✓ Bounded-Buffer Problem
- ✓ Readers and Writers Problem
- ✓ Dining-Philosophers Problem

Bounded-Buffer Problem

- There is a buffer of **n slots** and each slot is capable of storing **one unit of data**.
- There are two processes running, Producer and Consumer.
- Producer and Consumer are operating on the buffer.
- The producer tries to **insert** data into an **empty** slot of the buffer.
- The consumer tries to **remove** data from a **filled** slot in the buffer.
- The producer must **not insert** data when the **buffer is full**.
- The consumer must **not remove** data when the **buffer is empty**.
- The producer and Consumer should not insert and remove data simultaneously.

Bounded-Buffer Problem

Three semaphores are used:

1. **Mutex:** a binary semaphore which is used to acquire and release the lock.
2. **Empty:** a counting semaphore whose initial value is the number of slots in the buffer, since, initially all slots are empty.
3. **Full:** a counting semaphore.
 - n buffers, each can hold one item
 - Semaphore mutex initialized to the value 1
 - Semaphore empty initialized to the value n
 - Semaphore full initialized to the value 0

Bounded-Buffer Problem

- The structure of the producer process

```
while (true) {  
    wait(empty) ;  
    wait(mutex) ;  
  
    ...  
    /* add next produced to the buffer */  
    ...  
    signal(mutex) ;  
    signal(full) ;  
}
```

Bounded-Buffer Problem

- The structure of the consumer process

```
while (true) {  
    wait(full) ;  
    wait(mutex) ;  
  
    ...  
    /* remove an item from buffer to next_consumed  
    */  
  
    ...  
    signal(mutex) ;  
    signal(empty) ;  
}
```

Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - **Readers** – only read the data set; they do ***not*** perform any updates
 - **Writers** – can both read and write
- Problem – If a writer and some other (either a reader or a writer) access the data set simultaneously.
- Only one single writer can access the shared data at the same time.
- To ensure that these difficulties do not arise, we require that the writers have exclusive access to the shared data set.

Readers-Writers Problem

- We will make use of two semaphores and an integer variable:
- **mutex** : a semaphore which is used to ensure mutual exclusion when **read_count** is updated i.e. when any reader enters or exit from the critical section.
- **rw_mutex** : a semaphore common to both reader and writer processes.
- **read_count** : an integer variable that keeps track of how many processes are currently reading the data.
- Shared Data
 - Data set
 - Semaphore **mutex** initialized to 1
 - Semaphore **rw_mutex** initialized to 1
 - Integer **read_count** initialized to 0

Readers-Writers Problem

- The structure of a writer process

```
while (true) {  
    wait(rw_mutex) ;  
    ...  
    /* writing is performed */  
    ...  
    signal(rw_mutex) ;  
}
```

Readers-Writers Problem

- The structure of a reader process


```
while (true){
    wait(mutex);
    read_count++;
    if (read_count == 1) /* first reader */
        wait(rw_mutex);
        signal(mutex);

    ...
    /* reading is performed */
    ...

    wait(mutex);
    read_count--;
    if (read_count == 0) /* last reader */
        signal(rw_mutex);
    signal(mutex);
}
```

Dining-Philosophers Problem

- N philosophers' sit at a round table with a bowl of rice in the middle.



- They spend their lives alternating thinking and eating.
- They do not interact with their neighbors.
- Occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - Need both to eat, then release both when done
- In the case of 5 philosophers, the shared data
 - Bowl of rice (data set)
 - Semaphore chopstick [5] initialized to 1

Dining-Philosophers Problem Algorithm


- Semaphore Solution
- The structure of Philosopher *i*:

```
while (true){  
    wait (chopstick[i] );  
    wait (chopStick[ (i + 1) % 5] );  
  
    /* eat for awhile */  
  
    signal (chopstick[i] );  
    signal (chopstick[ (i + 1) % 5] );  
  
    /* think for awhile */  
  
}
```

- What is the problem with this algorithm?

Dining-Philosophers Problem

- Suppose that all five philosophers become hungry simultaneously and each grabs their left chopstick.
- All the elements of chopstick will now be equals to 0.
- When each philosopher tries to grab his right chopstick, he will be delayed forever.



Dining-Philosophers Problem

- Several possible remedies to the deadlock problem are the following:
 - ✓ Allow at most four philosophers to be sitting simultaneously at the table.
 - ✓ Allow a philosopher to pick up his chopsticks only if both chopsticks are available.
 - ✓ Use an asymmetric solution: an odd philosopher picks up first his left chopstick and then his right chopstick whereas an even philosopher picks up his right chopstick and then his left chopstick.