


3D Graphics Programming

T163 - Game Programming




Week 9

Object and App Review
Texturing

Object Review

❖ First, let's do a brief review of objects.



Object Review

❖ Type of Objects:

Regular Objects

Container Objects



Object Review

❖ Regular Objects:


Buffer Objects

Renderbuffer Objects

Query Objects

Texture Objects

Sampler Objects



Object Review


❖ Container Objects:

Framebuffer Objects

Vertex Array Objects

Transform Feedback Objects

Program Pipeline Objects



Object Review


❖ Regular Objects can be bound to different binding points:

GL_ARRAY_BUFFER

GL_TEXTURE_BUFFER

GL_ELEMENT_ARRAY_BUFFER

Etc...



Object Review

- ❖ The binding point decides how the object behaves
 - For buffer objects, for example:

GL_ARRAY_BUFFER -> for Vertex Buffer Objects (VBOs)

GL_TEXTURE_BUFFER -> for Texture Buffer Objects (TBOs)

GL_ELEMENT_ARRAY_BUFFER -> for Index Buffer Objects (IBOs)

Etc...




Object Review

❖ Why a VBO?

OpenGL can't read vertex data in CPU memory.

Vertex data must be sent to the GPU before it can be used in the rendering pipeline.

A VBO is able to take the data stored in the CPU and transmit it to the GPU.



Object Review

❖ Why a VAO?

Let's say that you need to render 12 different characters each with their own data type, offset, etc. All of this information must be prepared before it is rendered. This is a lot of states to set and a lot of error checking that the driver will have to do.

This is where a VAO can help organize all of this information.
A VAO is a container that stores all the states needed for rendering.
It stores the information of vertex-attribute as well as the buffer object.



Object Review

- ❖ So far to describe a single renderable entity we used:

Multiple VBOs

Single IBO

- ❖ Contained in a single VAO



Object Review

❖ So far to describe a single renderable entity we used

❖ Multiple VBOs for:

Vertex Position


Vertex Color



Object Review

- ❖ So far to describe a single renderable entity we used
- ❖ Single IBO for:

Index List



Object Review

VAO

posVBO

0	-0.5	-0.5	0
1	0.5	-0.5	0
2	0.5	0.5	0
3	-0.5	0.5	0

colorVBO

0	1	0	0
1	1	0	0
2	1	0	0
3	1	0	0

IBO

	0	1	2
	0	2	3

Object Review

VAO

posVBO


0	-0.5	-0.5	0
1	0.5	-0.5	0
2	0.5	0.5	0
3	-0.5	0.5	0

colorVBO

0	1	0	0
1	1	0	0
2	1	0	0
3	1	0	0

IBO

Triangle 1	0	1	2
Triangle 2	0	2	3




OpenGL App. Main Components

- 1- Main program
- 2- Vertex Shader
- 3- Fragment Shader



Texturing



What is a Texture?



What is a Texture?

- ❖ Textures are just bytes of data.
- ❖ Each byte represents the color of a texel.




What is a Texture?

If we have a plain, textureless square:



And we want to apply this texture to it:




We need to know how to map them together.



What is a Texture?


The square is made of 4 vertices.

Each vertex should map to a point on the texture.




What is a Texture?

This means that we need a way to divide the texture.




What is a Texture?

UV Mapping!!!





What is a Texture?

OpenGL's system actually uses "ST" from an old Pixar standard (and OpenGL is right-handed)



What is a Texture?

Therefore, each vertex in the square gets a UV coordinate.




What is a Texture?

Clarify texture flipping...



What is a Texture?

Therefore, each vertex in the square gets a UV coordinate.



What is a Texture?

Sounds easy right? So how does it work in code?

VAO

posVBO

0	-0.5	-0.5	0
1	0.5	-0.5	0
2	0.5	0.5	0
3	-0.5	0.5	0

textureVBO

0	0	1
1	1	1
2	1	0
3	0	0


IBO

	0	1	2
	0	2	3



What is a Texture?

Sounds easy right? So how does it work in code?



What is a Texture?

What about the actual image?

VAO

posVBO

0	-0.5	-0.5	0
1	0.5	-0.5	0
2	0.5	0.5	0
3	-0.5	0.5	0

textureVBO

0	0	1
1	1	1
2	1	0
3	0	0

IBO

	0	1	2
	0	2	3

TU 0


boxTO



Applying Textures

Simple OpenGL Image Library

A small and easy-to-use library that loads image files directly into texture objects or creates them for you.



Applying Textures

Textures are applied in the Fragment Shader.

```
#version 410 core

in vec3 myColor;
in vec2 texCoord;
out vec4 frag_colour;

uniform sampler2D texture0;

void main() {
    frag_colour = texture(texture0, texCoord);
}
```



Applying Textures

This means that the Vertex Shader needs to change.

```
#version 410 core
layout(location = 0) in vec3 vertex_position;
layout(location = 1) in vec3 vertex_colour;
layout(location = 2) in vec2 vertex_texture;

out vec3 myColor;
out vec2 texCoord;

uniform highp mat4 MVP;


void main()
{
    myColor = vertex_colour;
    texCoord = vertex_texture;
    gl_Position = MVP * vec4(vertex_position,1.0f);
}
```



Applying Textures

How do we pass the Texture to the GPU?

```
GLint width, height;  
unsigned char* image = SOIL_load_image("/PathToImage/ImageName.png", &width, &height, 0,  
SOIL_LOAD_RGB);
```



Applying Textures

How do we pass the Texture to the GPU?

```
GLuint cube_tex = 0;
glGenTextures(1, &cube_tex);
glActiveTexture(GL_TEXTURE0);
glBindTexture(GL_TEXTURE_2D, cube_tex);
glTexImage2D(GL_TEXTURE_2D, 0, GL_RGB, width, height, 0, GL_RGB, GL_UNSIGNED_BYTE, image);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_NEAREST);
glUniform1i(glGetUniformLocation(program, "texture0"), 0);
```




Applying Textures

How do we pass the Texture to the GPU?

```
glActiveTexture(GL_TEXTURE0);
```

Activates Texture Unit 0





Applying Textures

How do we pass the Texture to the GPU?

```
glBindTexture(GL_TEXTURE_2D, cube_tex);  
glTexImage2D(GL_TEXTURE_2D, 0, GL_RGB, width, height, 0, GL_RGB,  
GL_UNSIGNED_BYTE, image);
```

Binds and transfers Texture
data to boxTO in Unit 0

VAO



Wrapping



GL_REPEAT



GL_MIRRORED_REPEAT




GL_CLAMP_TO_EDGE




GL_CLAMP_TO_BORDER

Filters?



GL_NEAREST



GL_LINEAR

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);  
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);  
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);  
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_NEAREST);
```

Sets the texture properties


```
glUniform1i(glGetUniformLocation(program, "texture0"), 0);
```

Links the texture to the fragment shader

```
#version 410 core

in vec3 myColor;
in vec2 texCoord;
out vec4 frag_colour;

uniform sampler2D texture0;


void main() {
    frag_colour = texture(texture0, texCoord);
}
```

Week 9

Lab Activities

Week 9 Lab

- ❖ For the lab, see Hooman's material (with video)
- ❖ OpenGL examples covered:
 - Textures



Week 9

End