

## B561 Assignment 7

### Relational Programming

1. Consider the relation schema **Graph**(source INTEGER, target INTEGER) representing a directed graph. The graph *Graph* is *connected* if for each pair of nodes  $(s, t)$  in *Graph*, there exists a path in *Graph* from  $s$  to  $t$ .  
An *articulation point* of *Graph* is a node  $n$  in *Graph* such that removing the edges in the graph with source  $n$  as well as removing the edges with target  $n$  results in a graph that is **not** connected. Write a Postgres program that determines the articulation points of *Graph*.
2. Consider the following relational schema. A tuple  $(pid, cpid)$  is in **Parent\_Child** if  $pid$  is a parent of child  $cid$ .

```

Parent_Child
-----
|PId | SId |
-----

```

You can assume that the domain of PId and SId is INTEGER.

Write a Postgres program that computes the pairs  $(id_1, id_2)$  such that  $id_1$  and  $id_2$  belong to the same generation in the **Parent-Child** relation and  $id_1 \neq id_2$ . ( $id_1$  and  $id_2$  belong to the same generation if their distance to the root in the **Parent-Child** relation is the same.)

3. Consider a unary relation  $A(x)$  of integers.  
Using arrays to represent sets, write a program **powerset** in Postgres to compute the powerset of  $A$ .  
For example, if  $A$  is the following relation

A
x
1
2
3

then the output should be the following complex-object relation  
**PowersetA**(subset integer[])

PowersetA subset
{}
{1}
{2}
{3}
{1, 2}
{1, 3}
{2, 3}
{1, 2, 3}

4. In your textbook, you have a description of the  $k$ -means clustering algorithm. Your task is to implement this algorithm. The input data is given in a relation **Points**(Pid,x,y) where Pid is an integer denoting a point and  $x$  and  $y$  are FLOATS given the  $x$  and  $y$  coordinates of that point.

Your algorithm should work for various values of  $k$ .

For more information about  $k$ -means clustering consult

[https://en.wikipedia.org/wiki/K-means\\_clustering](https://en.wikipedia.org/wiki/K-means_clustering).

There, the  $k$ -means algorithm is given for a  $d$ -dimensional space. In this assignment,  $d = 2$ .

5. Implement the HITS authority-hubs algorithm. during class.

The input data is given in a relation **Graph**(source INTEGER, target INTEGER) which represent the graph on which the HITS Algorithm operates. So each node in this graph will receive an authority and a hub score.

For more information about the HITS algorithm consult

[https://en.wikipedia.org/wiki/HITS\\_algorithm](https://en.wikipedia.org/wiki/HITS_algorithm)  
[https://www.youtube.com/watch?v=jr3YGgfDY\\_E](https://www.youtube.com/watch?v=jr3YGgfDY_E)

An important detail of the HITS algorithm concerns the normalization of the authority vector (analogously, the hub vector). This vector needs to be normalized to have norm = 1 after each iteration step. Otherwise, the algorithm will not converge.

Normalization of a vector of numbers can be done as follows: If  $\mathbf{x} = (x_1, \dots, x_n)$  is a vector of real numbers, then its norm  $|\mathbf{x}|$  is given by the formula  $\sqrt{x_1^2 + \dots + x_n^2}$ . Therefore, you can normalize the vector  $(x_1, \dots, x_n)$  by transforming it to the vector  $\frac{\mathbf{x}}{|\mathbf{x}|} = (\frac{x_1}{|\mathbf{x}|} + \dots + \frac{x_n}{|\mathbf{x}|})$ . The norm of this vector will be 1.

6. Suppose you have a weighted undirected graph  $Graph = (V, E)$  stored in a ternary table named **Graph** in your database. A triple  $(n, m, w)$  in **Graph** indicates that  $Graph$  has an edge  $(n, m)$  where  $n$  is the source,  $m$  is the target, and  $w$  is the edge's weight. (In this problem, we will assume that each edge-weight is a positive integer.) Since the graph is undirected, whenever there is an edge  $(n, m, w)$  in the graph, then  $(m, n, w)$  is also in the graph. Below is an example of a graph  $Graph$ .

Graph		
Source	Target	Weight
0	1	2
1	0	2
0	4	10
4	0	10
1	3	3
3	1	3
1	4	7
4	1	7
2	3	4
3	2	4
3	4	5
4	3	5
4	2	6
2	4	6

A *spanning tree*  $T$  of  $Graph$  is a sub-graph of  $Graph$  that is acyclic and such that for each node  $n$  in  $Graph$  there is an edge in  $T$  of the form  $(n, m)$  or  $(m, n)$ . I.e., each node of  $Graph$  is the end point of an edge in  $Graph$ . The weight of a sub-graph of  $Graph$  is the sum of the weights of the edges of that sub-graph. A *minimum spanning tree* of  $Graph$  is a *spanning tree* of  $Graph$  of minimum cost.

Write a Postgres program that determines a minimum spanning tree of a graph  $Graph$ . You can use Prim's Algorithm to determine a spanning tree. Consult

[https://en.wikipedia.org/wiki/Minimum\\_spanning\\_tree](https://en.wikipedia.org/wiki/Minimum_spanning_tree)

and

[https://en.wikipedia.org/wiki/Prim's\\_algorithm](https://en.wikipedia.org/wiki/Prim's_algorithm).

7. Consider the heap data structure. For a description, consult

[https://en.wikipedia.org/wiki/Binary\\_heap](https://en.wikipedia.org/wiki/Binary_heap).

There are many other sites (including video) that discuss how this data structure works.

(a) Implement this data structure. This implies that you need to implement the **insert** and **extract** operations.

You are **not** allowed to use arrays to implement this data structure!

(b) Implement the heap sort algorithm.

You are **not** allowed to use arrays to implement this data structure!

The input format is a list of integers stored in a binary relation  $\text{Data}(\text{index}, \text{value})$ .

For example Data could contain the following data.

Data	
index	value
1	3
2	1
3	2
4	0
5	7

The output of the sort function should be stored in a relation  $\text{SortedData}(\text{index}, \text{value})$ . On the Data relation above, the sort function should return the relation.

SortedData	
index	value
1	0
2	1
3	2
4	3
5	7