Worksheet 6 - creating databases

Jo Hardin

2023-01-16

Your Name:		
Names of people you worked with: _		

- Don't introduce yourself. Name the people in front of you and behind you. Tell your partner what you did this weekend.
- What ideas do you have for working on the class project?

Consider the following fictional tables which exist in a fictional hospital database.¹

$\operatorname{\mathbf{donor}}$			
dName	age	bloodType	
Alice	53	A+	
Peter	34	AB+	
Bob	44	AB-	
~ .			

doctor			
docName	insurance	rate	
Wilhelm	HMO	15,000	
Wilhelm	PPO	20,000	
Heinz	HMO	12,000	
Pferd	PPO	14,000	

	O	
donor	organ	available
Alice	Heart	2014
Bob	Lung	2015
Bob	Bladder	2015
Peter	Foot	2011
Gert	Lung	2014

organ

patient

pName	insurance	age	bloodType
Hilde	HMO	13	A-
Fritz	PPO	87	AB+

takeCare

${f patient}$	organ	\mathbf{doctor}
Hilde	Lung	Wilhelm
Fritz	Heart	Wilhelm

- Variables with black background are the primary keys of a table.
- The variable donor of table organ is a foreign key to table donor.
- The variable patient of table takeCare is a foreign key to table patient.
- The variable doctor of table takeCare stores doctors. However, it is not a foreign key to table doctor, because the primary key of that table also includes insurance information.

 $^{^{1}}$ Example taken from http://cs.iit.edu/~cs425/previous/14fall/

Task:

1. Write a **SQL** statement that creates a new table **assignedTo**, which stores the **donor** and the donor's **organ** assigned to a **patient**. Furthermore, we want to store a treatment **price** for each such record. The combination of donor, organ, and patient uniquely identifies a record. Each record must have a treatment price that is bigger than 0 and smaller than 1,000,000 dollar.

Hint: indicate the primary key(s) as well as the foreign key(s) which link to both the organ table and the patient table.

Write a SQL statement that creates a table worksFor that records which doctor works
for which hospital. For each such relationship between doctors and hospitals we record
a salary for the doctor. A doctor may work for several hospitals (and obviously a
hospital can employ multiple doctors).

Hint: can the table with only the variables doctor, hospital, and salary have any foreign keys?

Solution:

1. Write a **SQL** statement that creates a new table **assignedTo**, which stores the **donor** and the donor's **organ** assigned to a **patient**. Furthermore, we want to store a treatment **price** for each such record. The combination of donor, organ, and patient uniquely identifies a record Each record must have a treatment **price** that is bigger than 0 and smaller than 1,000,000 dollar.

```
CREATE TABLE assignedTo (
    donor VARCHAR (256),
    organ VARCHAR (256),
    patient VARCHAR (256),
    price NUMERIC (8,2) NOT NULL CHECK (price BETWEEN 1 AND 999999),
    PRIMARY KEY (donor, organ, patient),
    FOREIGN KEY (donor, organ) REFERENCES organ(donor, organ),
    FOREIGN KEY (patient) REFERENCES patient(pName)
);
```

2. Write a **SQL** statement that creates a table worksFor that records which doctor works for which hospital. For each such relationship between doctors and hospitals we record a salary for the doctor. A doctor may work for several hospitals (and obviously a hospital can employ multiple doctors).

No foreign keys can be established because none of the variables in worksFor match up with primary keys in any of the other tables.

```
CREATE TABLE worksFor (
doc VARCHAR (256),
hospital VARCHAR (256),
salary NUMERIC (8),
PRIMARY KEY (doc, hospital)
);
```