

GTFS/GTFSRT Web API

V1

Contents

Introduction 3

Sign Up 3

GTFS/GTFSRT Web API Method Calls 4

 1. getToken 4

 2. isValidToken 5

 3. getGTFS 5

 4. getAlerts 6

 5. getTripUpdates..... 6

 6. getVehiclePositions 7

Introduction

NJ Transit's GTFS/GTFSRT allows 3rd parties to access to our real-time data through an API interface.

Below is the swagger endpoint for GTFS and GTFSRT API:

Test: <https://testraildata.njtransit.com/swagger/index.html?urls.primaryName=GTFS>

Production: <https://raildata.njtransit.com/swagger/index.html?urls.primaryName=GTFS>

GTFSRT files are for the real-time data. It's not for scheduled trips that have not left their origin. For schedule data, the developer should be using the [getGTFS](#) to get the zip file.

For any questions with the GTFS data Web API, we can be contacted at ProductionPasscomm@njtransit.com.

NOTE: User access limits are set to allow reasonable daily usage. These limits will not allow further accesses to the web service for the remainder of the day. After midnight these will be reset to zero.

There will be only 10 accesses per day for getToken and isValidToken. Please call these methods once per day.

There will be no limit on GTFSRT data below:

getGTFS, getAlerts, getTripUpdates, getVehiclePositions

Sign Up

To sign up, go to our portal at <https://developer.njtransit.com/registration> and click on "Register". Fill in all the required information and once you register you will receive an e-mail with your Test and Production API credentials.

To get new token:

Please use below endpoint, daily usages limit: 10.

Test: <https://testraildata.njtransit.com/api/GTFSRT/getToken>

Production: <https://raildata.njtransit.com/api/GTFSRT/getToken>

```
curl -X 'POST' \
  'https://testraildata.njtransit.com/api/GTFSRT/getToken' \
  -H 'accept: text/plain' \
  -H 'Content-Type: multipart/form-data' \
  -F 'username=your_username' \
  -F 'password= your_password'
```

GTFS/GTFSRT Method Calls

There are six types of method calls. Please use HttpPost method only, input parameter values in Body Form-Data:

1. getToken

Pass form values, username and password to get new token.

```
curl -X 'POST' \
  'https://testraildata.njtransit.com/api/GTFSRT/getToken' \
  -H 'accept: text/plain' \
  -H 'Content-Type: multipart/form-data' \
  -F 'username=your username' \
  -F 'password=your password'
```

Result #1:

```
{
  "Authenticated": "True",
  "UserToken": "your new token"
}
```

Result #2:

```
{
  "Authenticated": "False",
  "UserToken": ""
}
```

Result #3:

```
{
  "errorMessage": "Daily usage limit:10. Your current daily usage: 11"
}
```

Result #4: (when username/password or account is missing):

Null

2. isValidToken

Pass token to check if it's valid.

```
curl -X 'POST' \
  'https://testraildata.njtransit.com/api/GTFSRT/isValidToken' \
  -H 'accept: text/plain' \
  -H 'Content-Type: multipart/form-data' \
  -F 'token=your token here'
```

Result #1:

```
{
  "validToken": true,
  "userID": "your username"
}
```

Result #2:

```
{
  "validToken": false,
  "userID": null
}
```

Result #3:

```
{
  "errorMessage": "Daily usage limit:10. Your current daily usage: 11"
}
```

Result #4: (when token is empty or not a valid length):

Null

3. getGTFS

This returns Rail GTFS schedule data in ZIP format.

```
curl -X 'POST' \
  'https://testraildata.njtransit.com/api/GTFSRT/getGTFS' \
  -H 'accept: */*' \
  -H 'Content-Type: multipart/form-data' \
  -F 'token=your token here'
```

Result #1:

Zip file will be downloaded.

Result #2:

```
{  
  "errorMessage": "Invalid token."  
}
```

Result #3: (when token is empty or not a valid length):

Null

4. getAlerts

This returns Rail GTFSRT Alerts data in .Proto format.

```
curl -X 'POST' \  
  'https://testraildata.njtransit.com/api/GTFSRT/getAlerts' \  
-H 'accept: */*' \  
-H 'Content-Type: multipart/form-data' \  
-F 'token= your token here'
```

Result #1:

GTFSRT_NJT_Rail_Alerts.proto file will be downloaded.

Result #2:

```
{  
  "errorMessage": "Invalid token."  
}
```

Result #3: (when token is empty or not a valid length):

Null

5. getTripUpdates

This returns Rail GTFSRT Trips data in .Proto format.

```
curl -X 'POST' \  
  'https://testraildata.njtransit.com/api/GTFSRT/getTripUpdates' \  

```

```
-H 'accept: */*' \  
-H 'Content-Type: multipart/form-data' \  
-F 'token=your token here'
```

Result #1:

GTFSRT_NJT_Rail_Trip.proto file will be downloaded.

Result #2:

```
{  
  "errorMessage": "Invalid token."  
}
```

Result #3: (when token is empty or not a valid length):

Null

6. getVehiclePositions

This returns Rail GTFSRT Vehicle Position data in .Proto format.

```
curl -X 'POST' \  
  'https://testraildata.njtransit.com/api/GTFSRT/getVehiclePositions' \  
-H 'accept: */*' \  
-H 'Content-Type: multipart/form-data' \  
-F 'token= your token here'
```

Result #1:

GTFSRT_NJT_Rail_Vehicle.proto file will be downloaded.

Result #2:

```
{  
  "errorMessage": "Invalid token."  
}
```

Result #3: (when token is empty or not a valid length):

Null