NAME: Haresh Kumar N L (192425009)

**COURSE NAME: DATA STRUCTURES FOR MODERN COMPUTING SYSTEMS** 

**COURSE CODE: CSA0302** 

## Experiment 15: INFIX TO PREFIX CONVERSION

```
Code:
#include <stdio.h>
#include <string.h>
#include <ctype.h>
#define SIZE 100
char stack[SIZE];
int top = -1;
void push(char c) {
  stack[++top] = c;
}
char pop() {
  if(top == -1)
    return -1;
  else
    return stack[top--];
}
int precedence(char c) {
  if(c == '^')
    return 3;
  else if(c == '*' | | c == '/')
    return 2;
  else if(c == '+' | | c == '-')
    return 1;
  else
    return -1;
```

```
}
void reverse(char *exp) {
  int i, j;
  char temp;
  for(i = 0, j = strlen(exp) - 1; i < j; i++, j--) {
     temp = exp[i];
     exp[i] = exp[j];
     exp[j] = temp;
  }
}
void infixToPrefix(char *infix, char *prefix) {
  int i, j = 0;
  char ch;
  reverse(infix);
  for(i = 0; infix[i]; i++) {
     ch = infix[i];
     if(ch == '(')
       infix[i] = ')';
     else if(ch == ')')
       infix[i] = '(';
  }
  for(i = 0; infix[i]; i++) {
     ch = infix[i];
     if(isalnum(ch))
       prefix[j++] = ch;
     else if(ch == '(')
       push(ch);
     else if(ch == ')') {
       while(top != -1 && stack[top] != '(')
          prefix[j++] = pop();
        pop();
```

```
} else {
      while(top != -1 && precedence(stack[top]) >= precedence(ch))
        prefix[j++] = pop();
      push(ch);
    }
  }
  while(top != -1)
    prefix[j++] = pop();
  prefix[j] = '\0';
  reverse(prefix);
}
int main() {
  char infix[SIZE], prefix[SIZE];
  printf("Enter infix expression: ");
  scanf("%s", infix);
  infixToPrefix(infix, prefix);
  printf("Prefix expression: %s\n", prefix);
  return 0;
}
Output:
Enter infix expression: (A+B)*(C-D)
Prefix expression: *+AB-CD
=== Code Execution Successful ===
```