

```

a = 5
a
5
a = 5
type(a)
int
a = 5
print(type(a))
<class 'int'>
b = [2,3]
print(type(b))
<class 'list'>
class laptop():
    def config():
        print('i5', 16)
        print('i9', 32)
lap = laptop()
class laptop():
    def config():
        print('i5', 16)
        print('i9', 32)
lap = laptop()
lap.config()
i5 16
i9 32
class laptop():
    def config():
        print('i5', 16)
        print('i9', 32)
lap = laptop()
lap.config()
-----
-----
TypeError                                Traceback (most recent call
last)
/tmp/ipython-input-3832757095.py in <cell line: 0>()
      4     print('i9', 32)
      5 lap = laptop()
----> 6 lap.config()

```

TypeError: laptop.config() takes 0 positional arguments but 1 was given

```
class laptop():
    def config(self):
        print('i5', 16)
        print('i9', 32)
lap = laptop()
lap.config()
```

```
i5 16
i9 32
```

```
class laptop():
    def config(self):
        print('i5', 16)
        print('i9', 32)
lap1 = laptop()
lap2 = laptop()
lap3 = laptop()
lap1.config()
lap2.config()
lap3.config()
```

```
i5 16
i9 32
i5 16
i9 32
i5 16
i9 32
```

```
class computer():
    def config():
        print('i5', '8GB')
```

```
a = 8
print(type(a))
```

```
comp1 = computer()
print(type(comp1))
```

```
<class 'int'>
<class '__main__.computer'>
```

```
__name__
```

```
{"type": "string"}
```

```
class computer():
    def config():
        print('i5', '8GB')
```

```

com1 = computer()

computer.config(com1)
-----
-----
TypeError                                Traceback (most recent call
last)
/tmp/ipython-input-2560848810.py in <cell line: 0>()
      5 com1 = computer()
      6
----> 7 computer.config(com1)

TypeError: computer.config() takes 0 positional arguments but 1 was
given

class computer():
    def config(self):
        print('i5', '8GB')

com1 = computer()

computer.config(com1)

i5 8GB

```

## Special Method

```

class computer():
    def __init__(self):
        print('i7', '16gb')

c1 = computer()

i7 16gb

class computer():
    def __init__(self):
        print('i7', '16gb')

c1 = computer()
c2 = computer()
c3 = computer()

i7 16gb
i7 16gb
i7 16gb

```

```
class computer():
    def config(self):
        print('i7', '16gb')
```

```
c1 = computer()
c2 = computer()
c3 = computer()
```

```
c1.config()
c2.config()
```

```
i7 16gb
i7 16gb
```

```
class computer():
    def __init__(self):
        print('in init')
```

```
com1 = computer()
```

```
in init
```

```
class computer():
```

```
    def __init__(self):
        print('in init')
```

```
    def config(self):
        print('i5', '8gb')
```

```
com1 = computer()
com1.config()
```

```
in init
i5 8gb
```

```
class computer():
    def __init__(self):
        print('in init')
```

```
    def config(self):
        print('i5', '8gb')
```

```
com1 = computer()
```

```
com1.__init__()
com1.config()
```

```
in init
in init
i5 8gb
```

```
class computer:
    def config(self):
        print('i5', '8gb')

    def config2(self):
        print('i7', '32gb')

    def __init__(self):
        print('in init')

com1 = computer()
com2 = computer()
com3 = computer()

com1.config()
com1.config2()

in init
in init
in init
i5 8gb
i7 32gb
```