

Grid Search

Importing Libraries

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

importing the dataset

```
In [3]: dataset = pd.read_csv(r"C:\Users\Lenovo\OneDrive\Desktop\Naresh i Note\sept\12th
X = dataset.iloc[:, [2,3]].values
y = dataset.iloc[:, -1].values
```

Feature Scaling

```
In [4]: from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X = sc.fit_transform(X)
```

Splitting the dataset into the Training set and Test set

```
In [5]: from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_state=0)
```

Training the Kernel SVM model on the Training set

```
In [6]: from sklearn.svm import SVC
classifier = SVC(kernel = 'rbf', random_state=0)
classifier.fit(X_train, y_train)
```

```
Out[6]: SVC
SVC(random_state=0)
```

Predicting the test set results

```
In [7]: y_pred = classifier.predict(X_test)
```

Making the confusion Matrix

```
In [8]: from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
print(cm)
```

```
[[64  4]
 [ 3 29]]
```

Applying K-fold Cross Validation

```
In [9]: from sklearn.model_selection import cross_val_score
accuracies = cross_val_score(estimator=classifier, X = X_train, y = y_train, cv=
print("Accuracies: {:.2f} %".format(accuracies.mean()*100))
print("Standard Deviation: {:.2f} %".format(accuracies.std()*100))
```

Accuracies: 90.00 %

Standard Deviation: 6.83 %

Applying Grid Search to find the best model and the best parameters

```
In [10]: from sklearn.model_selection import GridSearchCV
parameters = [{'C': [1, 10, 100, 1000], 'kernel': ['linear']},
               {'C': [1, 10, 100, 1000], 'kernel': ['rbf'], 'gamma': [0.1, 0.2, 0.3, 0.4, 0.5]}]
grid_search = GridSearchCV(estimator = classifier,
                           param_grid = parameters,
                           scoring = 'accuracy',
                           cv = 10,
                           n_jobs = -1)
grid_search = grid_search.fit(X_train, y_train)
best_accuracy = grid_search.best_score_
best_parameters = grid_search.best_params_
print("Best Accuracy: {:.2f} %".format(best_accuracy*100))
print("Best Parameters:", best_parameters)
```

Best Accuracy: 91.00 %

Best Parameters: {'C': 1, 'gamma': 0.7, 'kernel': 'rbf'}

Visualising the Training set results


```
In [11]: from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).ravel(),
             alpha = 0.75, cmap = ListedColormap(['red', 'green']))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
```

```

for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('Kernel SVM (Training set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

C:\Users\Lenovo\AppData\Local\Temp\ipykernel_18124\2325164593.py:10: UserWarning:
 c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.
 plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],



Visualising the Test set results

```


In [12]: from matplotlib.colors import ListedColormap
X_set, y_set = X_test, y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('Kernel SVM (Test set)')
plt.xlabel('Age')

```

```
plt.ylabel('Estimated Salary')  
plt.legend()  
plt.show()
```

C:\Users\Lenovo\AppData\Local\Temp\ipykernel_18124\493352116.py:10: UserWarning:
c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2D array with a single row if you intend to specify the same RGB or RGBA value for all points.

```
plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
```



In []: