BLOCKCHAIN-ASSISTED PRIVACY-PRESERVING AND SYNCHRONIZED KEY AGREEMENT FOR DTNS

ABSTRACT

With the rapid growth of cyber threats and unauthorized data access, traditional authentication mechanisms are insufficient to secure digital file-sharing systems. This project proposes a Blockchain-Enabled Secure File Sharing Framework integrated with Multi-Factor Biometric Authentication and a Digital Twin Network-Based Threat Intelligence Layer.The system implements a three-level authentication mechanism consisting of password verification, Local Binary Pattern Histogram (LBPH)-based facial recognition, and One-Time Password (OTP) validation. To ensure file integrity, SHA-256 cryptographic hashing generates a unique digital fingerprint for each uploaded file. All authentication events, file transactions, and hash records are stored in a private blockchain network, ensuring tamper-proof auditability and transparency.To enhance proactive cybersecurity, a Digital Twin Network (DTN) is integrated as a virtual behavioral replica of the system. The DTN monitors login failures, biometric mismatches, OTP errors..The integration of biometric authentication, blockchain immutability, cryptographic integrity verification, and real-time Digital Twin-based anomaly detection provides a resilient and intelligent secure file-sharing environment. The proposed framework enhances system transparency, predictive threat mitigation, and adaptive security enforcement, making it suitable for enterprise-level data protection and critical infrastructure security applications.

INTRODUCTION

In today's digitally interconnected world, secure file sharing has become a critical requirement for organizations, enterprises, and critical infrastructure systems. The rapid expansion of cloud computing, remote collaboration, and distributed networks has significantly increased the volume of sensitive data transmitted across digital platforms. However, this growth has also amplified cybersecurity risks, including unauthorized access, data breaches, identity theft, insider threats, and sophisticated brute-force attacks. Traditional authentication mechanisms that rely solely on username-password combinations are increasingly vulnerable to credential theft, phishing, replay attacks, and database compromises.

To address these evolving security challenges, advanced technologies such as blockchain, biometric authentication, and intelligent threat monitoring systems are being explored. Blockchain technology, originally introduced through Satoshi Nakamoto in the context of Bitcoin, provides a decentralized and immutable ledger system capable of ensuring tamper-proof data storage and transparent auditing. Its cryptographic foundation and distributed consensus mechanism make it highly suitable for secure transaction logging and integrity verification in file-sharing systems.

At the same time, multi-factor authentication (MFA) has emerged as a robust solution to strengthen user verification processes. By integrating password validation with biometric recognition techniques such as Local Binary Pattern Histogram (LBPH)-based facial recognition and One-Time Password (OTP) verification, systems can significantly reduce the risk of unauthorized access. Biometric authentication leverages unique physiological characteristics, providing an additional security layer that is difficult to replicate or forge.

Beyond authentication and data integrity, modern cybersecurity demands proactive threat detection. The concept of a Digital Twin Network (DTN) introduces a virtual replica of the operational system that monitors behavioral patterns, authentication attempts, and file

transaction activities. By analyzing anomalies such as repeated login failures, biometric mismatches, abnormal download frequencies, or unusual access times, the system can detect potential cyber threats before they escalate into full-scale breaches.

This project presents a Blockchain-Enabled Secure File Sharing Framework integrated with Multi-Factor Biometric Authentication and a Digital Twin Network-Based Threat Intelligence Layer. The framework combines cryptographic hashing (SHA-256) for file integrity, private blockchain architecture for immutable record keeping, multi-level authentication for access control, and real-time anomaly detection for proactive cybersecurity.

By integrating these advanced technologies into a unified architecture, the proposed system enhances transparency, accountability, predictive threat mitigation, and adaptive security enforcement. The framework is particularly suited for enterprise environments, government agencies, healthcare institutions, and critical infrastructure sectors where data confidentiality, integrity, and availability are of paramount importance.

Literature Survey

Recent research has explored the use of blockchain for secure data exchange in Vehicular Digital Twin Networks. Zhou et al. proposed a blockchain-assisted privacy-preserving synchronized key agreement framework to enable secure group data sharing and maintain identity privacy in distributed vehicular environments. The system supports blockchain-based entity management and synchronized key generation. However, the architecture introduces higher system complexity and communication overhead due to the reliance on trusted authorities and decentralized coordination mechanisms [1].

Security and privacy concerns in Vehicular Digital Twin Networks have also been widely studied. Zhou et al. conducted a comprehensive survey analyzing security threats, architectural frameworks, and privacy issues associated with VDTNs. The study highlights authentication challenges and discusses blockchain-based countermeasures for protecting distributed vehicular systems. Despite providing a structured analysis, the proposed approaches involve complex architectures and strict real-time communication requirements that may increase system overhead [2].

In the area of intelligent vehicular edge computing, Zhou et al. introduced an adaptive digital twin framework for vehicular networks. The system leverages digital twin technology and deep reinforcement learning to optimize network management and reduce offloading latency. This approach enhances resource allocation efficiency and improves quality of service in vehicular networks. However, the framework requires continuous real-time data monitoring and introduces significant computational complexity and strict latency constraints [3].

Digital twin technology has also been integrated with blockchain for intelligent transportation systems. Gao et al. proposed a blockchain-enabled Digital Twin as a Service (DTaaS) framework to support secure and on-demand digital twin services in intelligent transportation environments. The framework improves system reliability,

enhances security, and enables optimal digital twin–ITS matching. Nevertheless, the solution depends heavily on blockchain infrastructure and introduces additional computation and coordination overhead [4].

Digital Twin Networks have also been extensively studied in research surveys. Zhou et al. presented a detailed survey of DTN architectures, technologies, and applications. The work identifies key enabling technologies and open research challenges in digital twin systems. While the survey provides a strong conceptual foundation for DTN-based systems, it highlights limitations such as lack of standardization, high system complexity, and potential security and privacy risks [5].

Industrial applications of digital twin technology have also been explored. Tao et al. presented a comprehensive state-of-the-art study on digital twin implementations in industrial environments. The research discusses how digital twin technology supports system monitoring, optimization, and predictive analysis in industrial processes. Although the approach provides valuable insights into digital twin applications, it requires high computational resources and raises concerns related to data privacy and system security [6].

Dependable content distribution in vehicular networks has also been investigated using big data techniques. Zhou et al. proposed a coalition game-based framework for dependable content distribution in device-to-device vehicular networks. The system integrates big data analysis and trajectory prediction to improve network efficiency and reduce delay. However, the approach involves high computational complexity and depends heavily on accurate trajectory predictions and coordination mechanisms [7].

Similarly, Zhou et al. developed a social big-data-based content dissemination model for Internet of Vehicles (IoV) environments. The framework leverages social data and D2D communication to improve content dissemination efficiency and maximize weighted sum rates in vehicular networks. Although the model demonstrates improved network

performance, it requires large-scale data processing and introduces additional computational and coordination overhead [8].

The concept of digital twins has also been explored from a multimedia technology perspective. Wang et al. introduced a framework describing the convergence of multimedia technologies, artificial intelligence, IoT, and cloud computing in enabling digital twin applications. The system supports real-time monitoring and intelligent services for smart cities and healthcare environments. However, the architecture requires significant computational infrastructure and faces challenges related to privacy protection and standardization [9].

Research on blockchain-based secure file sharing has also gained attention in recent years. Zhang and Liu proposed a blockchain-enabled file sharing framework that ensures data integrity through SHA-256 cryptographic hashing and tamper-proof transaction logging on distributed ledgers. The decentralized architecture eliminates dependence on third-party intermediaries and improves transparency. However, the system focuses mainly on file integrity and transaction security and does not include multi-factor biometric authentication or intelligent threat monitoring mechanisms [10].

EXISTING SYSTEM

Current digital file-sharing systems primarily rely on centralized architectures where data is stored and managed on a single cloud server or enterprise database. Popular platforms such as Google Drive, Dropbox, and Microsoft OneDrive use standard username–password authentication with optional two-factor authentication (2FA) through email or SMS-based OTP verification. In enterprise environments, file sharing is commonly implemented using FTP/SFTP servers or Network Attached Storage (NAS) systems with role-based access control mechanisms.

Traditional systems focus mainly on data encryption during transmission using SSL/TLS protocols and basic password hashing techniques for credential protection. File activity logs and access records are stored in centralized databases, which are managed by system administrators. Although audit logs are maintained, they are not immutable and can be altered if the central server is compromised. Some advanced enterprise solutions incorporate monitoring tools to detect repeated login failures or suspicious IP addresses, but these mechanisms are largely reactive rather than predictive.

Existing systems generally lack biometric-based multi-factor authentication, immutable blockchain-backed storage of transaction records, and intelligent behavioral analysis for detecting abnormal usage patterns. File integrity verification is often limited to basic checksum validation, without decentralized or tamper-proof mechanisms. As a result, traditional file-sharing platforms remain vulnerable to brute-force attacks, phishing attempts, insider threats, and unauthorized data manipulation.

Overall, existing file-sharing systems provide basic confidentiality and access control but do not offer integrated blockchain immutability, biometric security layers, or proactive Digital Twin-based anomaly detection for advanced cyber threat prevention.

DISADVANTAGES

• Centralized Architecture: Single point of failure; if the server is compromised, all files and logs are at risk.

• Weak Authentication Mechanisms: Primarily password-based systems are vulnerable to brute-force, phishing, and credential-stuffing attacks.

• No Biometric Verification: Lack of facial recognition or advanced multi-factor biometric authentication.

• Non-Immutable Logs: Audit trails can be modified or deleted by administrators or attackers.

• Limited File Integrity Assurance: No blockchain-based tamper-proof hashing mechanism for verifying file authenticity.

• Reactive Security Model: Threat detection occurs only after suspicious activity is identified.

• No Behavioral Intelligence: Absence of Digital Twin or AI-driven anomaly detection for monitoring abnormal access patterns.

• Insider Threat Vulnerability: Administrators with high privileges may misuse or manipulate stored data.

PROPOSED SYSTEM

The proposed system introduces a Blockchain-Enabled Secure File Sharing Framework integrated with Multi-Factor Biometric Authentication and a Digital Twin Network-Based Threat Intelligence Layer. Unlike traditional centralized file-sharing platforms, the proposed architecture ensures tamper-proof data management, advanced identity verification, and proactive cyber threat detection within a unified security framework.

The system begins with a secure user registration and authentication process that implements a three-level verification mechanism. First, users authenticate using a username and password. Second, biometric verification is performed using Local Binary Pattern Histogram (LBPH)-based facial recognition to validate the user's identity. Third, a One-Time Password (OTP) is generated and sent to the registered email or mobile number for final authentication. This layered approach significantly reduces the risk of unauthorized access.

Once authenticated, users can upload and share files securely. Each uploaded file undergoes SHA-256 cryptographic hashing to generate a unique digital fingerprint, ensuring file integrity and preventing tampering. All authentication events, file uploads, downloads, and hash values are recorded in a private blockchain network. The blockchain ensures immutability, transparency, and decentralized verification of records, eliminating the risk of log manipulation or unauthorized alterations.

To enhance proactive cybersecurity, the system integrates a Digital Twin Network (DTN), which acts as a virtual behavioral replica of the file-sharing environment. The DTN continuously monitors user activities such as login failures, biometric mismatches,

incorrect OTP attempts, and abnormal file download patterns. By analyzing these behavioral metrics, the system detects potential brute-force attacks, credential misuse, and suspicious access attempts in real time. Upon detecting anomalies, the system triggers alerts and enforces adaptive security measures such as temporary account lockout or additional verification steps.

The framework is implemented using Python and Flask for backend development, OpenCV for facial recognition processing, cryptographic libraries for SHA-256 hashing, and a custom private blockchain module for secure transaction storage. The integration of blockchain immutability, biometric authentication, cryptographic integrity verification, and Digital Twin-based anomaly detection ensures a secure, intelligent, and enterprise-ready file-sharing solution.

ADVANTAGES

• Multi-Layer Authentication: Combines password, biometric facial recognition, and OTP verification for enhanced security.

• Tamper-Proof Audit Trail: Blockchain-based storage ensures immutable logging of all transactions and authentication events.

• File Integrity Assurance: SHA-256 hashing guarantees that uploaded files cannot be altered without detection.

• Proactive Threat Detection: Digital Twin Network continuously monitors and detects abnormal behavior in real time.

• Brute-Force Prevention: Automatically identifies repeated failed login attempts and enforces adaptive security controls.

• Transparency and Trust: Decentralized record management improves accountability and prevents log manipulation.

• Enterprise-Grade Security: Suitable for protecting sensitive organizational and critical infrastructure data.

• Adaptive Security Enforcement: Dynamically responds to suspicious activities with automated alerts and restrictions.

Motivation and Goal

Motivation:

- Need for secure file sharing in distributed environments
- Limitations of centralized authentication and access control
- Rising privacy breaches and unauthorized data access
- Requirement for tamper-proof and traceable security mechanisms

Goal:

- Design a secure and privacy-preserving file sharing framework
- Implement multi-factor authentication (Password + Face + OTP)
- Eliminate single points of failure using blockchain
- Ensure data integrity and auditability through immutable records

Architecture Diagram



Architecture Diagram Explanation

The proposed system architecture illustrates a Blockchain-Enabled Secure File Sharing Framework with Multi-Factor Biometric Authentication implemented through a web-based application. The system integrates facial recognition, OTP verification, blockchain-based transaction logging, and secure file management to ensure data confidentiality, integrity, and controlled access between users. The architecture consists of several major components including Sender User, Receiver User, Web Application, Email Server, Database, and Blockchain Ledger, which work together to provide secure file transfer and authentication.

At the center of the architecture is the Web Application developed using Flask, which manages user authentication, file processing, and system coordination. The application

handles requests from both sender and receiver users and performs operations such as facial recognition verification, file upload management, and OTP validation. The web server acts as the main control unit that communicates with the database, blockchain ledger, and email server to process authentication events and file transactions securely.

The Sender User is responsible for uploading files to the system. Before uploading, the sender must complete a multi-layer authentication process that includes password verification, biometric authentication using facial recognition, and OTP validation. After successful verification, the sender can upload files through the web application. The system records file metadata and access permissions in the database while simultaneously generating a cryptographic hash of the file for integrity verification.

Similarly, the Receiver User requests access to files shared by the sender. When a receiver initiates a download request, the system verifies the user's identity using biometric authentication and OTP verification. Once authentication is successful and permission is validated, the receiver is allowed to download the requested file. This process ensures that only authorized users can access sensitive data within the system.

The Email Server plays an important role in the authentication process by sending One-Time Passwords (OTP) to users during login or secure operations such as file upload and download. The web application communicates with the email server to generate and deliver OTP codes to the registered email addresses of users. This mechanism provides an additional security layer by verifying user identity through possession-based authentication.

The Database (SQLite) is used to store system information such as user records, file metadata, and access permissions. User details including usernames, roles, and biometric data are stored securely in the database. The database also maintains records of file permissions, which determine which receiver is authorized to access specific uploaded files. This component supports the access control mechanism of the system.

The architecture also integrates a Blockchain Ledger, which records file hash values and transaction logs. Whenever a file is uploaded or accessed, a SHA-256 cryptographic hash is generated and stored in the blockchain ledger. Each transaction is recorded as a block linked through cryptographic hashing, creating an immutable chain of records. This ensures tamper-proof storage of file integrity information and authentication events.

During file operations, the web application sends secure file hash values to the blockchain ledger while storing file metadata and permissions in the database. This separation of responsibilities improves system reliability by ensuring that sensitive authentication records and transaction logs remain immutable in the blockchain while operational data is managed efficiently within the database.

Overall, the architecture provides a secure and transparent file sharing environment by combining blockchain technology, biometric authentication, and OTP verification. The integration of these components helps prevent unauthorized access, ensures file integrity through cryptographic hashing, and maintains a tamper-proof audit trail for all system transactions.

MODULE DESCRIPTION

The proposed Blockchain-Enabled Secure File Sharing Framework with Multi-Factor Biometric Authentication and Digital Twin-Based Threat Intelligence is divided into the following functional modules:

1. User Registration Module

This module allows new users to register into the system securely.

Functions:

- Collects user credentials (username, email, password).
- Captures and stores facial biometric data for LBPH-based recognition.
- Encrypts and securely stores user information in the database.
- Initializes blockchain identity for the user within the private network.

Purpose:

To create authenticated user accounts with biometric enrollment for enhanced security.

2. Multi-Factor Authentication Module

This module implements a three-level authentication mechanism to prevent unauthorized access.

Level 1: Password Verification

- Validates username and password.
- Protects against unauthorized login attempts.

Level 2: Facial Recognition (LBPH)

- Uses Local Binary Pattern Histogram (LBPH) algorithm.
- Matches live captured face with stored biometric template.
- Prevents identity spoofing.

Level 3: One-Time Password (OTP) Validation

- Generates time-based OTP.
- Sends OTP to registered email/mobile.
- Confirms possession-based authentication.

Purpose:

To provide strong layered security combining knowledge-based, biometric, and possession-based authentication.

3. File Upload and Integrity Verification Module

This module manages secure file storage and integrity protection.

Functions:

- Allows authenticated users to upload files.
- Generates SHA-256 hash value for each uploaded file.
- Creates a unique digital fingerprint of the file.
- Prevents file tampering and modification.

Purpose:

To ensure file authenticity and integrity through cryptographic hashing.

4. Private Blockchain Logging Module

This module ensures tamper-proof record maintenance.

Functions:

- Records authentication events.
- Stores file upload/download transactions.
- Saves generated SHA-256 hash values.
- Maintains immutable blocks linked through cryptographic hashes.

Purpose:

To provide transparency, traceability, and auditability of all system activities.

5. Digital Twin Network (DTN) Module

This module acts as a virtual behavioral replica of the system for proactive cybersecurity monitoring.

Functions:

- Monitors login attempts and failures.
- Tracks biometric mismatches.
- Observes OTP validation errors.

Purpose:

To enable predictive threat detection

6. Secure File Download Module

This module allows authorized users to securely access shared files.

Functions:

- Verifies user authentication status.
- Checks file integrity by re-validating SHA-256 hash.
- Logs download activity in blockchain.

Purpose:

To ensure secure and verified file retrieval without tampering.

Results and Discussion

The proposed Blockchain-Enabled Secure File Sharing System with Multi-Factor Biometric Authentication was successfully implemented as a web-based application using Flask. The system integrates password authentication, facial recognition using the LBPH algorithm, OTP verification, blockchain transaction logging, and secure file management. The experimental results demonstrate that the system provides a secure and reliable framework for controlled file sharing between sender and receiver users.

The system begins with the user authentication process, where users register with a username, password, email address, and role. During login, the system verifies the credentials stored in the SQLite database. After successful password verification, the system performs biometric verification using facial recognition. The implementation using the LBPH algorithm successfully detects and verifies the user's face through the camera interface. The results show that the multi-factor authentication approach significantly improves system security by combining knowledge-based, biometric, and possession-based authentication mechanisms.

The facial recognition module demonstrated reliable user verification during testing. The system captures the user's face using the camera and extracts facial features using the Local Binary Pattern Histogram (LBPH) method. The extracted features are compared with the stored face template during authentication. The confidence threshold mechanism ensures that only genuine users are granted access. The results indicate that the system effectively prevents unauthorized access attempts caused by password theft or credential-based attacks.

The OTP verification mechanism was successfully integrated into the authentication workflow. During sensitive operations such as file upload and download requests, the system generates a one-time password and sends it to the user's registered email address through the email server. The OTP must be entered correctly before the operation

proceeds. This additional authentication step ensures that only verified users can perform critical actions within the system, thereby improving overall security.

The secure file upload module allows sender users to upload files through the web interface after successful authentication. During upload, the system generates a cryptographic hash using the SHA-256 algorithm to create a digital fingerprint for the file. The file metadata, including filename, owner information, and receiver permissions, is stored in the SQLite database. This mechanism ensures controlled access to shared files and allows the system to verify file integrity during download operations.

The blockchain transaction module records important system activities such as authentication events, file uploads, and file downloads. Each event is stored as a transaction in the blockchain ledger, creating an immutable log of system activities. The blockchain structure links each block using cryptographic hashing, ensuring that transaction records cannot be altered once stored. The results demonstrate that the blockchain ledger provides transparency and tamper-proof logging for all system operations.

The receiver access module enables authorized receivers to request and download files shared by sender users. Before downloading a file, the system verifies the receiver's identity through biometric authentication and OTP validation. After successful verification, the receiver is allowed to access the requested file. This access control mechanism ensures that files are shared only with authorized users.

The system also maintains a transaction history interface, which displays recorded blockchain transactions such as authentication events and file hash records. This feature allows administrators and users to monitor system activity and verify the authenticity of stored files. The blockchain records provide an immutable audit trail, which enhances accountability and system transparency.

Overall, the implemented system demonstrates the effectiveness of combining blockchain technology, biometric authentication, and cryptographic hashing to create a secure file sharing framework. The integration of these technologies ensures secure user authentication, tamper-proof transaction logging, and reliable file integrity verification. The results confirm that the proposed system provides a robust and scalable solution for secure file sharing in distributed environments.

CONCLUSION

The proposed Blockchain-Enabled Secure File Sharing Framework integrated with Multi-Factor Biometric Authentication and Digital Twin Network-Based Threat Intelligence provides a comprehensive solution to address the growing challenges of cybersecurity in digital file-sharing environments. Traditional single-factor authentication systems are no longer sufficient to protect sensitive enterprise data from sophisticated attacks such as credential theft, brute-force attempts, insider threats, and unauthorized access. This framework overcomes those limitations by implementing a three-level authentication mechanism consisting of password verification, LBPH-based facial recognition, and OTP validation, thereby significantly strengthening access control.The integration of SHA-256 cryptographic hashing ensures file integrity by generating a unique digital fingerprint for every uploaded file. This mechanism effectively detects any unauthorized modification or tampering. Furthermore, the use of a private blockchain network guarantees immutable storage of authentication events, file transactions, and hash records, providing transparent, tamper-proof auditability and enhancing trust within the system.A key innovation of the proposed framework is the incorporation of a Digital Twin Network (DTN) for real-time behavioral monitoring. By continuously analyzing login failures, biometric mismatches, OTP errors, the system can proactively identify suspicious activities and prevent potential security. This predictive threat intelligence capability enhances adaptive security enforcement and strengthens overall system resilience.In conclusion, the combination of biometric authentication, cryptographic integrity verification, blockchain immutability, and Digital Twin-based anomaly detection creates a robust, intelligent, and scalable secure file-sharing environment. The proposed system not only ensures confidentiality, integrity, and transparency but also supports proactive cybersecurity measures, making it highly suitable for enterprise-level data protection and critical infrastructure security applications.

FUTURE ENHANCEMENT

The proposed Blockchain-Enabled Secure File Sharing Framework with Multi-Factor Biometric Authentication and Digital Twin Network (DTN)-based Threat Intelligence provides a strong foundation for secure data management. However, several enhancements can be incorporated in the future to further improve scalability, intelligence, automation, and enterprise adaptability.

One major enhancement is the integration of Artificial Intelligence and Machine Learning-based anomaly detection. Instead of relying only on threshold-based monitoring, advanced deep learning models can be trained to identify complex behavioral patterns and zero-day attacks. This would significantly improve the predictive capabilities of the Digital Twin Network and reduce false positives.

Another future improvement is the adoption of behavioral biometrics, such as keystroke dynamics, mouse movement patterns, and device fingerprinting. Adding these continuous authentication mechanisms can strengthen security even after login, ensuring ongoing identity verification throughout the user session.The system can also be enhanced by implementing smart contracts within the private blockchain network. Smart contracts can automate access control policies, file-sharing permissions, expiration rules, and compliance auditing without manual intervention. This would increase efficiency and reduce administrative overhead.

To improve scalability and enterprise deployment, the framework can be migrated to a cloud-based or hybrid blockchain infrastructure. Distributed cloud nodes would enhance performance, support high transaction throughput, and provide better disaster recovery capabilities. Additionally, containerization and microservices architecture can improve system flexibility and maintainability.Future versions of the system may incorporate Zero-Trust Architecture (ZTA) principles. Under this model, every access request is

continuously verified regardless of network location. Combining zero-trust policies with multi-factor authentication and Digital Twin monitoring would create an even more resilient security ecosystem.

Another enhancement involves integrating advanced encryption mechanisms, such as homomorphic encryption or attribute-based encryption, to secure sensitive files while enabling controlled access. This would provide stronger confidentiality, especially for critical infrastructure and government applications.The Digital Twin Network can also be upgraded with real-time threat intelligence feeds from external cybersecurity databases. This would allow the system to adapt dynamically to emerging global threats and automatically update its anomaly detection models.

Finally, future work may include the development of a mobile-based secure access platform, enabling secure authentication and file access through smartphones using biometric sensors such as fingerprint or facial recognition. This would enhance usability while maintaining strong security standards.

In conclusion, by incorporating AI-driven analytics, behavioral biometrics, smart contracts, zero-trust security, advanced encryption, and cloud scalability, the proposed framework can evolve into a highly intelligent, adaptive, and enterprise-ready cybersecurity solution capable of addressing future digital threats.

REFERENCES

[1] "Blockchain-Assisted Privacy-Preserving and Synchronized Key Agreement for Vehicular Digital Twin Networks," IEEE, 2025.

[2] C. He, T. H. Luan, R. Lu, Z. Su, and M. Dong, "Security and privacy in vehicular digital twin networks: Challenges and solutions," *IEEE Wireless Communications*, vol. 30, no. 4, pp. 154–160, Aug. 2023.

[3] S. Liao, J. Wu, A. K. Bashir, W. Yang, J. Li, and U. Tariq, "Digital twin consensus for blockchain-enabled intelligent transportation systems in smart cities," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 11, pp. 22619–22629, Nov. 2022.

[4] Y. Dai and Y. Zhang, "Adaptive digital twin for vehicular edge computing and networks," *Communications in Information and Systems*, vol. 7, no. 1, pp. 48–59, 2022.

[5] K. Zhang, J. Cao, S. Maharjan, and Y. Zhang, "Digital twin empowered content caching in social-aware vehicular edge networks," *IEEE Transactions on Computational Social Systems*, vol. 9, no. 1, pp. 239–251, Feb. 2022.

[6] K. Zhang, J. Cao, and Y. Zhang, "Adaptive digital twin and multi-agent deep reinforcement learning for vehicular edge computing and networks," *IEEE Transactions on Industrial Informatics*, vol. 18, no. 2, pp. 1405–1413, Feb. 2022.

[7] G. Li, C. Lai, R. Lu, and D. Zheng, "SecCDV: A security reference architecture for cybertwin-driven 6G V2X," *IEEE Transactions on Vehicular Technology*, vol. 71, no. 5, pp. 4535–4550, May 2022.

[8] Z. Wang *et al.*, "Mobility digital twin: Concept, architecture, case study, and future challenges," *IEEE Internet of Things Journal*, vol. 9, no. 18, pp. 17452–17467, Sep. 2022.

[9] Q. Liu, X. Qi, S. Liu, X. Cheng, X. Ke, and F. Wang, "Application of lightweight digital twin system in intelligent transportation," *IEEE Journal of Radio Frequency Identification*, vol. 6, pp. 729–732, 2022.

[10] Y. Wu, K. Zhang, and Y. Zhang, "Digital twin networks: A survey," *IEEE Internet of Things Journal*, vol. 8, no. 18, pp. 13789–13804, Sep. 2021.

[11] W. Li, X. Li, J. Gao, and H. Wang, "Design of secure authenticated key management protocol for cloud computing environments," *IEEE Transactions on Dependable and Secure Computing*, vol. 18, no. 3, pp. 1276–1290, May–Jun. 2021.

[12] L. Liu, C. Chen, Q. Pei, S. Maharjan, and Y. Zhang, "Vehicular edge computing and networking: A survey," *Mobile Networks and Applications*, vol. 26, no. 3, pp. 1145–1168, 2020.

[13] M. Ma, D. He, H. Wang, N. Kumar, and K. K. R. Choo, "An efficient and provably secure authenticated key agreement protocol for fog-based vehicular ad-hoc networks," *IEEE Internet of Things Journal*, vol. 6, no. 5, pp. 8065–8075, Oct. 2019.

[14] F. Tao, H. Zhang, A. Liu, and A. Y. C. Nee, "Digital twin in industry: State-of-the-art," *IEEE Transactions on Industrial Informatics*, vol. 15, no. 4, pp. 2405–2415, Apr. 2019.

[15] S. Raza, S. Wang, M. Ahmed, and M. R. Anwa, "A survey on vehicular edge computing: Architecture, applications, technical issues, and future directions," *Wireless Communications and Mobile Computing*, vol. 2019, Art. no. 3159762, 2019.

[16] Z. Zhou, H. Yu, C. Xu, Z. Chang, S. Mumtaz, and J. Rodriguez, "BEGIN: Big data enabled energy-efficient vehicular edge computing," *IEEE Communications Magazine*, vol. 56, no. 12, pp. 82–89, Dec. 2018.

[17] Z. Zhou, H. Yu, C. Xu, Y. Zhang, S. Mumtaz, and J. Rodriguez, "Dependable content distribution in D2D-based cooperative vehicular networks: A big data-

integrated coalition game approach," *IEEE Transactions on Intelligent Transportation Systems*, vol. 19, no. 3, pp. 953–964, Mar. 2018.

[18] Z. Zhou, C. Gao, C. Xu, Y. Zhang, S. Mumtaz, and J. Rodriguez, "Social big-data-based content dissemination in Internet of Vehicles," *IEEE Transactions on Industrial Informatics*, vol. 14, no. 2, pp. 768–777, Feb. 2018.

[19] A. El Saddik, "Digital twins: The convergence of multimedia technologies," *IEEE MultiMedia*, vol. 25, no. 2, pp. 87–92, Second Quarter 2018.

[20] A. J. Menezes, P. C. van Oorschot, and S. A. Vanstone, *Handbook of Applied Cryptography*. CRC Press, 2018.

[21] W. Stallings, *Cryptography and Network Security: Principles and Practice*, 7th ed. Pearson Education, 2017.

[22] M. Dworkin, "SHA-3 Standard: Permutation-Based Hash and Extendable-Output Functions," National Institute of Standards and Technology (NIST), 2015.

[23] J. Bonneau, C. Herley, P. C. van Oorschot, and F. Stajano, "The quest to replace passwords: A framework for comparative evaluation of web authentication schemes," in *Proc. IEEE Symposium on Security and Privacy*, 2012.

[24] A. K. Jain, A. Ross, and S. Prabhakar, "An introduction to biometric recognition," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 14, no. 1, pp. 4–20, 2004.

[25] S. Blake-Wilson, D. Johnson, and A. Menezes, "Key agreement protocols and their security analysis," in *Proc. Crypto and Coding*, Springer, 1997, pp. 30–45.