

e-inter API — integration guide

Audience: teams that will call e-inter from another app (backend, mobile, partner portal, notebook).

Product: Bosch e-inter x BluWheelz electric-fleet console.

Version: 1.1.0

Date: 24 September 2026

Repository: https://github.com/hari8g/e_inter_bluewheelz

This is the HTTP contract. The React dashboard is only one client of these routes. You **do not** need the UI to use the features.

Related product documentation: `FEATURES.md` in the repo root.

1. Overview

Item	Value
Style	REST, JSON
Base path	<code>/api/v1</code>
Auth	Bearer session from <code>POST /auth/login</code>
Ops auth	Header <code>X-Admin-Token</code> (ingest/admin only)
Time format	ISO-8601 strings (<code>2026-09-14T18:22:00.000Z</code>)
Nulls	<code>null</code> means <i>not observed</i> . Do not treat as zero.
CORS	The API reflects the request <code>Origin</code> (browser apps are allowed)

Base URLs

Environment	Origin	Example health URL
Production (this demo)	<code>https://e-inter-bluewheelz.onrender.com</code>	<code>https://e-inter-bluewheelz.onrender.com/api/v1/health</code>
Local	<code>http://127.0.0.1:8787</code>	<code>http://127.0.0.1:8787/api/v1/health</code>
Vercel UI (same-origin proxy)	your <code>*.vercel.app</code> host	<code>https://<app>.vercel.app/api/v1/health</code>

Use the Render (or local) API origin for server-to-server integrations. Do not call `https://e-inter-api.onrender.com` — that host is an older API without login.

Demo fleet IDs

When `Database/` GPS files are loaded (default demo):

Registration	vehicleId	Model	Telemetry
KA01AS1071	<code>v_ka01as1071</code>	Tata Ace	<code>gps_only</code>
KA01AS1094	<code>v_ka01as1094</code>	Zor Grand	<code>gps_only</code>
KA01AS7048	<code>v_ka01as7048</code>	Pro X	<code>gps_only</code>

Device IDs follow `d_<plate lowercase>` (example: `d_ka01as1071`).

2. Quick start (5 minutes)

```
BASE=https://e-inter-bluewheelz.onrender.com/api/v1

# 1. Public health
curl -sS "$BASE/health"

# 2. Login
TOKEN=$(curl -sS -X POST "$BASE/auth/login" \
-H 'Content-Type: application/json' \
-d '{"username":"bluewheelz","password":"bluewheelz"}' \
| python3 -c 'import sys,json; print(json.load(sys.stdin)["token"])')

# 3. Call a feature
curl -sS "$BASE/command-center" -H "Authorization: Bearer $TOKEN"
curl -sS "$BASE/vehicles/v_ka01as1071/gps-metrics" -H "Authorization: Bearer $TOKEN"
```

Default operator credentials (overridable with `DASHBOARD_USERNAME` / `DASHBOARD_PASSWORD`):

- Username: `bluewheelz`
- Password: `bluewheelz`

Token lifetime: **12 hours**.

3. Authentication

3.1 Login

POST `/api/v1/auth/login` — **public**

Request:

```
{ "username": "bluewheelz", "password": "bluewheelz" }
```

Response 200 :

```
{
  "token": "eyJzdWliOiJibHVld2hlZWx6liwiZXhwIjoxNzg5NjlxNDI2NDA1fQ.<hmac>",
  "username": "bluewheelz",
  "displayName": "BluWheelz"
}
```

Errors:

Status	Body	Meaning
400	<code>{ "error": "invalid_body" }</code>	Missing username or password
401	<code>{ "error": "invalid_credentials" }</code>	Wrong username or password

3.2 Using the token

Send on every protected request:

```
Authorization: Bearer <token>
Content-Type: application/json
```

(`Content-Type` is required on POST / PUT / PATCH.)

3.3 Who am I

GET `/api/v1/auth/me` — session required

```
{ "username": "bluewheelz", "displayName": "BluWheelz" }
```

3.4 Errors common to all protected routes

Status	Body	Meaning
401	{ "error": "unauthorized" }	Missing, invalid, or expired token
404	{ "error": "not_found" }	Unknown vehicle or resource
400	{ "error": "..." }	Validation failure (often a Zod flatten object)

3.5 Admin / ops token (separate)

Routes under `/api/v1/ops/*` do **not** use the dashboard Bearer token.

```
X-Admin-Token: <ADMIN_API_TOKEN>
```

If `ADMIN_API_TOKEN` is unset on the server, these routes return `503 { "error": "ops_not_configured" }`.

4. Feature → endpoint map

Use this table to expose a dashboard screen as an API.

Product feature	Method	Path	Notes
Health	GET	<code>/health</code>	Public
Login	POST	<code>/auth/login</code>	Public
Session	GET	<code>/auth/me</code>	
Command centre	GET	<code>/command-center</code>	KPIs + vehicles + policy + optional trips
Trip ledger	GET	<code>/trips</code>	File-demo only; empty in live Kafka mode
One trip	GET	<code>/vehicles/id/trip</code>	
Map / playback	GET	<code>/vehicles/id/gps-history</code>	Point list; UI draws the map
Idle, stops, harsh, geofences	GET	<code>/vehicles/id/gps-metrics</code>	
Daily utilisation	GET	<code>/vehicles/id/daily-distance</code>	
Telemetry workspace	GET	<code>/vehicles/id/can-live</code>	
History sparkline	GET	<code>/vehicles/id/can-history</code>	
Cell pack	GET	<code>/vehicles/id/cells</code>	available: false on this fleet
Battery health	GET	<code>/analytics/battery-health</code>	SOH may be null
Asset lifecycle	GET	<code>/analytics/asset-lifecycle</code>	
Drivers / trip quality	GET	<code>/analytics/driver-classification</code>	Not named drivers
Portfolio FMV	GET	<code>/analytics/portfolio-valuation</code>	INR, heuristic
List / add vehicles	GET, POST	<code>/vehicles</code>	
GPS devices	GET, POST	<code>/devices</code>	
Unpair device	POST	<code>/devices/id/unpair</code>	
Maintenance	GET, POST, PATCH	<code>/maintenance</code> , <code>/maintenance/:id</code>	
Policy	GET, PUT	<code>/policy</code>	Immediate apply
Signal dictionary	GET	<code>/signal-profiles/</code>	
Ingest health	GET	<code>/ops/ingest-health</code>	Admin token
Rollup	POST	<code>/ops/rollup</code>	Admin token; live only
Quarantine	GET	<code>/ops/quarantine</code>	Admin token

Not an API: immobilise (UI button only). Map tiles are OSM in the browser; your app should render `gps-history` itself.

5. Public and fleet routes

5.1 Health — GET /api/v1/health

Public. Use as a liveness probe.

```
{
  "ok": true,
  "product": "e-inter",
  "layer": "api",
  "mode": "demo",
  "database": false
}
```

Field	Meaning
mode	demo (file/seed store) or live (Postgres + Kafka)
database	true only in live mode when Postgres answers SELECT 1

5.2 Command centre — GET /api/v1/command-center

Primary fleet snapshot. Same payload the home screen uses.

Important fields:

Field	Type	Meaning
mode	demo live	Store in use
fleetTotal	number	Vehicle count
reporting	number	Vehicles with a recent fix
noLink	number	Stale / offline
distanceTodayKm	number	Last GPS-day path km (file fleet)
avgSocPercent	number	Average trip-end SOC only where SOC exists
avgSocSampleCount	number	How many vehicles entered that average
estRangePoolKm	number	DTE sum; treat as unused if rangePoolAvailable is false
rangePoolAvailable	boolean	False on the BluWheelz file fleet
energyLedgerKwh	number	Currently 0 (not computed)
reportDistanceKm	number	Workbook km (demo)
dataSource	string	e.g. file path label
policy	object	Current visibility policy
vehicles	array	Full vehicle objects (see §8)
trips	array	Trip ledger (demo)

5.3 Vehicles — GET /api/v1/vehicles

Returns `Vehicle[]`. See §8 for the schema.

5.4 Register vehicle — POST /api/v1/vehicles

```
{
  "registration": "KA01AS9999",
  "displayName": "Pilot Ace",
  "model": "Tata Ace",
  "telemetryMode": "gps_only",
  "allowImmobalise": false,
  "seedLat": 12.9716,
  "seedLng": 77.5946,
  "kwhPack": 21.3,
  "odometerKm": 12000,
  "socPercent": 60,
  "locationLabel": "Bengaluru",
  "oemPlatform": "tata_ace_ev",
  "nominalCapacityAh": null,
  "commissionedOn": "2025-01-15"
}
```

Field	Required	Notes
registration	yes	min 3 chars
displayName	yes	
model	yes	
telemetryMode	yes	gps_only or can_gps
allowImmobalise	yes	UI flag only
seedLat , seedLng	yes	numbers
kwhPack	yes	> 0
odometerKm	yes	≥ 0
socPercent	yes	0–100
locationLabel	yes	
oemPlatform	live mode	mahindra_zeo tata_ace_ev switch_ev eicher_ev

Response: 201 + Vehicle . Live mode without oemPlatform → 400 { "error": "oem_platform_required" }.

6. GPS, trip, and telemetry

:id is the canonical vehicle id (v_ka01as1071).

6.1 GPS history — GET /vehicles/:id/gps-history

Query:

Param	Default	Meaning
max	1500 (API) / 1200 (UI)	Max points after downsample
from	optional	ISO start
to	optional	ISO end

Response:

```
{
  "vehicleId": "v_ka01as1071",
  "registration": "KA01AS1071",
  "from": "2026-09-10T00:00:00.000Z",
  "to": "2026-09-14T18:00:00.000Z",
  "count": 840,
  "points": [
    {
      "t": "2026-09-14T08:01:00.000Z",
      "lat": 12.91,
      "lng": 77.63,
      "speedKph": 22.4,
      "deviceBatteryV": 4.05,
      "auxBatteryV": 13.1,
      "ignition": true
    }
  ]
}
```

Use `points` to draw a polyline, start/end pins, and playback. There is no separate “map API”.

6.2 GPS metrics — [GET /vehicles/:id/gps-metrics](#)

Derived from the GPS trace (and workbook km when present).

Field	Meaning
<code>pathKm</code>	Haversine path length
<code>reportKm</code>	Trip-report km (null if absent)
<code>distanceDeltaKm</code>	Report – path
<code>maxSpeedKph</code>	Peak GPS speed
<code>ignOnPct</code>	Share of samples with ignition on
<code>movingPct</code>	Ignition on and speed ≥ 3 km/h
<code>idleGpsMin</code>	Idle minutes (ign off or speed < 3)
<code>stopCount</code>	Dwells ≥ 5 min within ~ 80 m
<code>stops[]</code>	{ <code>startedAt</code> , <code>endedAt</code> , <code>dwelMin</code> , <code>lat</code> , <code>lng</code> }
<code>harshAccel</code> / <code>harshBrake</code>	Coarse GPS $\Delta v/\Delta t$, threshold 2.5 m/s^2
<code>peakAccelMps2</code> / <code>peakBrakeMps2</code>	Peak magnitudes
<code>medianGapSec</code>	Median sample gap
<code>coveragePct</code>	Time coverage estimate
<code>firstFixAt</code> / <code>lastFixAt</code>	Trace bounds
<code>pointCount</code>	Raw / kept points
<code>deviceBatteryV</code> / <code>auxBatteryV</code>	Last values
<code>deviceMinV</code> ... <code>auxMaxV</code>	Spans
<code>lowDeviceV</code>	Device < 3.9 V seen
<code>lowAuxV</code>	Aux < 12.2 V seen
<code>geofences</code>	Names of depot disks that were hit

Harsh events are **not** CAN harsh channels. Sampling on these files is ~ 30 s.

6.3 Daily distance — [GET /vehicles/:id/daily-distance](#)

```
{
  "vehicleId": "v_ka01as1071",
  "items": [
    { "day": "2026-09-14", "km": 42.1, "ignOnPct": 61, "maxSpeedKph": 48, "harshTotal": 3 }
  ]
}
```

6.4 Trips — GET /trips

```
{
  "updatedAt": "2026-09-24T14:00:00.000Z",
  "items": [ { "vehicleId": "v_ka01as1071", "registration": "KA01AS1071", "distanceKm": 38.2 } ]
}
```

File demo: one row per ingested workbook trip, plus `gpsDistanceKm` and `distanceDeltaKm` .

Live Kafka mode: `items` is `[]` .

6.5 Trip detail — GET /vehicles/:id/trip

One `TripLedgerRow` . 404 if none.

6.6 Canonical live — GET /vehicles/:id/can-live

Signal grid used by Telemetry.

```
{
  "vehicleId": "v_ka01as1071",
  "registration": "KA01AS1071",
  "capturedAt": "2026-09-14T18:00:00.000Z",
  "freshnessSeconds": null,
  "signals": [
    {
      "id": "gps.speed_kph",
      "label": "GPS speed",
      "unit": "km/h",
      "domain": "gps",
      "domainLabel": "GPS trace",
      "value": 0,
      "quality": "measured"
    }
  ],
  "position": { "lat": 12.91, "lng": 77.63, "gpsSpeedKph": 0, "joinGapSeconds": null },
  "observability": {
    "oemPlatform": "tata_ace_ev",
    "signalProfileId": "file_gps",
    "availableSignals": [ "gps.speed_kph", "trip.distance_km" ],
    "pendingSignals": [],
    "unavailableSignals": [ "batt.cell_voltage_v" ],
    "lastFrameAt": null,
    "coverage24hPct": 0
  },
  "trip": { "distanceKm": 38.2, "endSocPct": 64 }
}
```

On this fleet, CAN domains are listed as unavailable. Do not invent cell voltages from `signals` .

6.7 History — GET /vehicles/:id/can-history

Query: `signal` (required in live), optional `from` , `to` .

Demo mode (file fleet): `signal` defaults to `gps.speed_kph` . Supported picks: `gps.speed_kph` , `veh.speed_kph` , `gps.device_battery_v` , `gps.aux_battery_v` , `gps.ignition` (0/1).

Live mode: `signal` must be one of:

`batt.soc_pct` , `veh.odometer_km` , `veh.speed_kph` , `batt.dte_km` , `batt.pack_voltage_v` , `batt.pack_current_a` , `batt.pack_power_kw` , `batt.cell_delta_mv` , `batt.cell_temp_max_c` , `batt.cell_v_max` , `batt.cell_v_min` , `drv.accel_pedal_pct` .

Response:

```
{
  "signal": "gps.speed_kph",
  "unit": "km/h",
  "from": "...",
  "to": "...",
  "points": [ { "t": "...", "v": 22.4 } ]
}
```

6.8 Cells — GET /vehicles/:id/cells

On the BluWheelz file fleet:

```
{
  "vehicleId": "v_ka01as1094",
  "available": false,
  "reason": "Cell voltages are not in the GPS or trip files.",
  "cellVoltagesV": [],
  "cellTempsC": []
}
```

When `available` is `false`, **do not** plot empty arrays as a pack.

7. Analytics routes

All return JSON. Wrap lists as shown.

7.1 Battery — GET /analytics/battery-health

```
{ "updatedAt": "...", "items": [ /* BatteryHealthPoint */ ] }
```

On file fleet, `sohPercent` is `null` and `sohMethod` is `unavailable`. Trip energy / 12 V fields may still be filled. History/forecast arrays can be empty — that is honest, not a bug.

7.2 Lifecycle — GET /analytics/asset-lifecycle

```
{ "updatedAt": "...", "items": [ /* AssetLifecycleStage */ ] }
```

`heuristics.thermalStressIndex` may be `null`. Prefer `operatorSummary` / `operatorFindings` / `operatorActions` for operator copy.

7.3 Drivers (trip quality) — GET /analytics/driver-classification

```
{ "updatedAt": "...", "items": [ /* DriverClassification */ ] }
```

`driverId` is a vehicle-scoped id. `eventSource` is `derived_speed` on this fleet. There is no driver identity table.

7.4 Portfolio — GET /analytics/portfolio-valuation

```
{
  "updatedAt": "...",
  "currency": "INR",
  "disclaimer": "...",
  "assumedLeaseMonths": 36,
  "enterprise": {
    "vehicleCount": 3,
    "totalIndicativeListInr": 0,
    "totalFairMarketValueInr": 0,
    "totalResidualValueInr": 0,
    "avgSohPercent": null,
    "portfolioRiskShare": 0
  },
  "items": []
}
```

Heuristic INR model. When SOH is unobservable, valuation confidence is lowered. Not an invoice or certified appraisal.

8. Core schemas

Types match `backend/src/types/domain.ts`. Only fields you will always see are listed as required; others may be omitted.

8.1 Vehicle

Field	Type	Notes
id	string	Canonical id
registration	string	Plate
displayName	string	
model	string	Tata Ace / Zor Grand / Pro X
telemetryMode	gps_only can_gps	File fleet is gps_only
allowImmobilise	boolean	UI only
kwhPack	number	Declared pack size
odometerKm	number	From trip end odo when known
socPercent	number	0 when SOC was never in the file (Zor Grand)
status	active charging idle offline	Stale files → often offline
locationLabel	string	
position	{ lat, lng, lastFixAt }	Last GPS fix
deviceId	string null	
gps	object omitted	Last speed, ignition, batteries
trip	object omitted	Workbook bookends
track	{ lat, lng }[]	Optional short track
gpsMetrics	lite object	pathKm, stopCount, tripScore, ...
can	omitted on file fleet	Never invent
sohMethod	unavailable on file fleet	

KA01AS1094: trip.startSocPct / endSocPct are null . Do not average SOC across the fleet without checking avgSocSampleCount or per-vehicle nulls.

8.2 TripLedgerRow

Field	Type
vehicleId , registration , model , operator	string
startAt , endAt	string null
distanceKm , durationMin , avgSpeedKph	number null
startSocPct , endSocPct	number null
startOdoKm , endOdoKm	number null
energyUsed , efficiency , idleMin , acIdleMin	number null
score , chargingMin , startDteKm , endDteKm	number null
startLat , startLng , endLat , endLng	number null
fuelType	string null
gpsDistanceKm	number null
distanceDeltaKm	number null

8.3 FleetPolicy

Field	Type	Range / default role
showMap	boolean	
showSocStrip	boolean	
showImmobalise	boolean	
highlightLowSoc	boolean	
showAssetStrip	boolean	
showTripLedger	boolean	
highlightStaleGps	boolean	
geofenceBreachAlerts	boolean	
highlightGpsReportMismatch	boolean	
gpsUplinkTargetSeconds	number	10–600
stalePositionMinutes	number	1–240
lowSocAlertPercent	number	5–80
deviceBatteryAlertVolts	number	2–6

PUT /policy accepts a **partial** object; omitted keys stay unchanged. Response is the full policy.

8.4 GpsDevice

```
{
  "id": "d_ka01as1071",
  "serial": "BLU-GPS-KA01AS1071",
  "firmware": "file-1",
  "type": "GPS",
  "lastSeenAt": "...",
  "pairedVehicleId": "v_ka01as1071",
  "pointCount": 7315,
  "firstFixAt": "...",
  "lastDeviceBatteryV": 4.05,
  "lastAuxBatteryV": 13.1
}
```

POST /devices body: { "serial": "optional-string" } → 201 .

POST /devices/:id/unpair → updated device or 404 .

8.5 Maintenanceltem

```
{
  "id": "m1",
  "vehicleId": "v_ka01as1071",
  "workType": "odometer_audit",
  "title": "GPS path vs trip report km",
  "dueDate": "2026-09-20",
  "odometerAtDueKm": 18400,
  "vendor": null,
  "notes": "Path and report differ by more than 40 km.",
  "status": "open",
  "createdAt": "..."
}
```

Create (POST /maintenance): vehicleId , workType , title , dueDate , notes ; optional odometerAtDueKm , vendor .

Patch (PATCH /maintenance/:id): { "status": "open" | "in_progress" | "done" } .

9. Policy, devices, profiles, ops

9.1 Policy

- GET /api/v1/policy → FleetPolicy
- PUT /api/v1/policy → partial update, returns full policy

9.2 Signal profiles — GET /api/v1/signal-profiles/

Returns OEM profiles, capability matrix, feasibility, observability sets, canonical dictionary, and `fileCanonicalMap` (workbook/CSV column → signal id). Use this to decide which analytics a platform can honestly support.

9.3 Ops (admin token)

Method	Path	Demo behaviour
GET	/ops/ingest-health	{ mode: "demo", metrics, vehicles: [] }
POST	/ops/rollup	503 { "error": "demo_mode" }
GET	/ops/quarantine	[]

10. Honesty contract (required for integrators)

1. **null is data.** Do not coerce SOC, SOH, DTE, or cell arrays to zero.
2. **No CAN cells on this demo fleet.** If `cells.available === false`, show the `reason`.
3. **No invented SOH %.** `sohMethod === "unavailable"` means do not draw a fade curve from empty history.
4. **Zor Grand (KA01AS1094) has no trip SOC.** Exclude it from SOC averages unless you document the gap.
5. **GPS files end ~14 Sep 2026.** `offline` / `stale` is expected.
6. **Harsh counts are GPS-derived,** not CAN.
7. **Portfolio INR values are a model,** not a valuation certificate.
8. **Immobilise is not remotely executed.**

11. Language examples

11.1 JavaScript / TypeScript (browser or Node 18+)

```
const BASE = "https://e-inter-bluewheelz.onrender.com/api/v1";

async function login(username: string, password: string) {
  const res = await fetch(`${BASE}/auth/login`, {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ username, password }),
  });
  if (!res.ok) throw new Error(await res.text());
  return res.json() as Promise<{ token: string }>;
}

async function api<T>(token: string, path: string, init: RequestInit = {}): Promise<T> {
  const res = await fetch(`${BASE}${path}`, {
    ...init,
    headers: {
      Authorization: `Bearer ${token}`,
      ...(init.body ? { "Content-Type": "application/json" } : {}),
      ...(init.headers ?? {}),
    },
  });
  if (!res.ok) throw new Error(`${res.status} ${await res.text()}`);
  return res.json() as Promise<T>;
}

const { token } = await login("bluewheelz", "bluewheelz");
const fleet = await api(token, "/command-center");
const metrics = await api(token, "/vehicles/v_ka01as1071/gps-metrics");
```

11.2 Python

```

import os
import requests

BASE = os.environ.get("EINTER_API", "https://e-inter-bluewheelz.onrender.com/api/v1")

def login(user="bluewheelz", password="bluewheelz"):
    r = requests.post(f"{BASE}/auth/login", json={"username": user, "password": password}, timeout=30)
    r.raise_for_status()
    return r.json()["token"]

def get(token, path):
    r = requests.get(f"{BASE}{path}", headers={"Authorization": f"Bearer {token}"}, timeout=60)
    r.raise_for_status()
    return r.json()

token = login()
print(get(token, "/health") if False else get(token, "/command-center")["fleetTotal"])
print(get(token, "/vehicles/v_ka01as1071/gps-metrics")["pathKm"])

```

11.3 Recommended integration flow

1. GET /health — confirm product === "e-inter" .
2. POST /auth/login — store token; refresh by logging in again after 12 h.
3. GET /vehicles — cache ids.
4. Fan-out per vehicle: /gps-metrics , /gps-history , /trip , /can-live as needed.
5. Pull /analytics/* on a slower cadence (they are derived, not live frames).
6. Treat null and available: false as first-class states in your UI.

12. Errors and limits

Situation	What you see
No token	401 { "error": "unauthorized" }
Bad login	401 { "error": "invalid_credentials" }
Unknown vehicle	404 { "error": "not_found" }
Bad body	400 + Zod flatten or invalid_body
Live register without OEM	400 { "error": "oem_platform_required" }
Live history unsupported signal	400 { "error": "unsupported_signal", "supported": [...] }
Ops without config	503 { "error": "ops_not_configured" }
Rollup in demo	503 { "error": "demo_mode" }
Render free tier sleep	First request after idle can take 30–60 s

There is no published rate limit. Do not poll GPS history faster than every 10–15 s; the file fleet does not change in real time.

Demo store is **in memory** on the API process. A Render restart reloads files from disk; it does not persist vehicles you POST unless you run live Postgres.

13. Security notes for a partner app

- Prefer **server-side** calls if you cannot ship the operator password to a public client.
- Rotate DASHBOARD_PASSWORD and AUTH_SECRET before any external share.
- Set ADMIN_API_TOKEN if you expose /ops/* .
- CORS currently reflects any origin. For a locked partner list, change the API (today ALLOWED_ORIGINS is not enforced).
- The session token is an HMAC over { sub, exp } . Treat it like a password.

14. Local run (for integration tests)

```
# Terminal 1
cd backend && npm install && npm run dev
# listens on http://127.0.0.1:8787

curl -sS http://127.0.0.1:8787/api/v1/health
```

Needs Node 20+. `Database/` must be present for the three BluWheelz vehicles.

15. Document set

File	Use
docs/e-inter-api.md	This specification (source)
docs/e-inter-api.pdf	Printable / email share
FEATURES.md	Operator-facing product features
README.md	Clone, run, deploy

Bosch e-inter · BluWheelz · API 1.1.0