Search Page SEO Migration

Colive website rebuild (Next.js, repository `website-react`, branch `Dev`) · Work date: 31 Oct 2026 · Author: hariColive

1. Summary

The SEO content from the legacy .NET WebForms search page (`search.aspx.cs`, used by pages such as `https://www.colive.com/pg-in-bangalore/`) has been ported to the Next.js search pages. Every city, locality and `/search?loc=` page now outputs:

- Meta title, meta description and meta keywords
- Canonical link and hreflang alternate links
- A location-specific H1
- The overview copy (with "Read more") and FAQs (with "View more") below the property results
- All JSON-LD schemas from the legacy file (FAQPage, WebSite, Organization, LocalBusiness, Product, BreadcrumbList, @graph schemas, etc.)

Locations without their own copy fall back to the generic copy with the place name filled in, exactly as the legacy site did.

> Status at time of writing: verified against the local dev server; TypeScript and ESLint pass. Changes are not yet committed.

2. Content ported

The legacy file (about 30,000 lines of C# `switch` statements) was evaluated by a one-off script and converted into one JSON file per location. Counts below are from the generated files (100 files including `default.json`).

Content	Legacy C# function	Locations	Where it appears now
Meta title	DivMetaTitle	80	<title>
H1	DivMetaTitle (h1Title)	79	Search hero heading
Meta description	DivMetaContent	99	<meta name="description">
Overview copy	DivFaqContent	54	Section below results
FAQs	DivFaqContent / DivCommonFAQ	56	Section below results
JSON-LD schemas	JsonFormat, DivSchemaContent, DivPLSchemaContent, BreadcrumbSchemaContent, OrganizationSchemaContent	55	<script type="application/ld+json">
Hreflang links	HrefLangTagsContent	28	<link rel="alternate" hreflang>
Meta keywords	Page_Load (pattern)	All	Generated from the location name
Canonical	Page_Load (request URL)	All	Generated from the page path

Locations with their own overview/FAQ copy: aecs-layout, bagmane-tech-park, banaswadi, bangalore, bannerghatta-road, bellandur, bommanahalli, bommasandra, brookfield, btm-layout, chennai, couple-friendly, ejipura, electronic-city, hbr-layout, hebbal, hennur-road, hinjewadi, hoodi, hope-farm, hsr-layout, hyderabad, indiranagar, itpl, jaya-nagar, kadubeesanahalli, koramangala, kr-puram, kudlu-gate, kundalahalli, lal-bagh, madiwala, mahadevapura, manyata-tech-park, marathahalli, men-bangalore, mg-road, murugeshpalya, nagawara, navi-mumbai, pimpri-chinchwad, pune, sarjapur, shantiniketan, silk-board, tathawade, thanisandra, thippasandra, ultra-luxury, varthur, wakad, whitefield, wilson-garden, wipro, women-bangalore.

3. Files changed

File	Change
`src/content/search-seo/*.json`	New. 100 SEO content files, one per location key, plus `default.json` (generic copy).
`src/content/search-seo/index.ts`	New. Map of location key to lazy JSON import.
`src/lib/searchSeo.ts`	New. Loads a location's copy, falls back to default, fills in `$strCity$`, builds Next.js metadata (title, description, keywords, canonical, hreflang).
`src/lib/searchLocation.ts`	Added `seoKey` and `canonical` to `SearchLocation`.
`src/components/search/SearchSeoContent.tsx`	New. Renders JSON-LD scripts, overview and FAQs below the results.
`src/components/search/SeoOverview.tsx`	New (client). Overview with "Read more" / "Read less".
`src/components/search/SeoFaqs.tsx`	New (client). FAQ accordion using <details>, with "View more" / "View less".
`src/components/search/richText.ts`	New. Tailwind styles for the HTML copy (headings, lists, tables, links).
`src/components/search/SearchHero.tsx`	H1 now comes from the SEO copy; "Find a 6-Star Home" is a small label above it.
`src/components/search/SearchPage.tsx`	Adds the SEO section; old inline `searchMetadata` removed.
`src/app/[...slug]/page.tsx`, `src/app/search/page.tsx`	Use the new `searchMetadata(location)`.
`src/app/layout.tsx`	Added `metadataBase: https://www.colive.com` so canonical links are absolute.

4. How it works

4.1 Request flow

1. The route (`[...slug]` or `/search`) resolves the URL into a `SearchLocation` (`locationFromPath` / `locationFromQuery`).
2. `generateMetadata` calls `searchMetadata(location)`, which loads the SEO copy and returns title, description, keywords, canonical and hreflang.

3. The page renders `SearchHero` (H1), the results, then `SearchSeoContent` (JSON-LD, overview, FAQs).

4.2 Which content file is used (location key)

The same rule as the legacy site: take the last path segment and remove `pg-in-`.

URL	Location key	File
/pg-in-bangalore	bangalore	bangalore.json
/men-pg-in-bangalore	men-bangalore	men-bangalore.json
/women-pg-in-bangalore	women-bangalore	women-bangalore.json
/bangalore/pg-in-whitefield	whitefield	whitefield.json
/bangalore/central/pg-in-koramangala	koramangala	koramangala.json
Any URL containing btm-layout	btm-layout	btm-layout.json
/search?loc=Electronic City, Bangalore	electronic-city	electronic-city.json
Location with no file (e.g. /bangalore/pg-in-xyz)	xyz	default.json

Each field falls back independently: if a location file has a title but no FAQs, the FAQs come from `default.json`.

4.3 Place-name placeholder

Any text containing `$strCity$` has it replaced with the location label at render time: "Bangalore" for a city page, "Koramangala, Bangalore" for a locality page, or the `loc` value for `/search`. On `/search` the value comes from the URL, so it is HTML-escaped before it is inserted into HTML or JSON-LD (tested with a script-injection URL).

4.4 Keywords and canonical

- City page keywords: "pg in Bangalore, PG for Boys Bangalore, PG for Couples Bangalore, …"
- Locality keywords: "pg in Whitefield, PG for Boys in Whitefield, PG for Couples in Whitefield, …"
- Canonical: the lower-case page path, e.g. `https://www.colive.com/bangalore/pg-in-whitefield`. For /search it is `/search?loc=…` (filter parameters are left out).

5. Content file format

Every field is optional; missing fields use `default.json`. HTML fields are trusted content and are rendered as-is. The // comments below are explanations only; JSON files cannot contain comments.

```
{
  "title": "Best 120+ Coliving PGs in Bangalore for Professionals, Boys & Girls",
  "description": "PGs in Bangalore: Find premium furnished PGs ...",
  "h1": "Best PGs In Bangalore - PG Rooms/Stays In Bangalore",
  "overview": {
    "intro": "<h2>Overview</h2><p>...</p>",      // always visible
    "more": "<p>...</p>"                         // behind "Read more"
  },
  "faqs": [
    {
      "heading": "FAQ's on PG in Bangalore",
      "initiallyVisible": 5,                        // rest behind "View more"
      "items": [ { "question": "...", "answer": "<p>...</p>" } ]
    }
  ],
  "jsonLd": [ { "@context": "https://schema.org", "@graph": [ ... ] } ],
  "hreflang": [ { "hreflang": "en-in", "href": "https://www.colive.com/pg-in-bangalore/" } ]
}
```

6. How-to

6.1 Edit SEO copy for a location

1. Open `src/content/search-seo/<key>.json` (key from section 4.2).
2. Edit the field. Use `$strCity$` where the place name should appear.
3. For JSON-LD, check the result with Google's Rich Results Test or validator.schema.org.

6.2 Add copy for a new location

1. Create `src/content/search-seo/<key>.json` with only the fields you need.
2. Add a line to `src/content/search-seo/index.ts`, e.g. `"new-key": () => import("./new-key.json"),`
3. Open the page locally and check the title, H1, FAQs and JSON-LD in the page source.

6.3 Change the generic copy

Edit `src/content/search-seo/default.json`. This affects every location without its own value for that field.

7. Corrections made to the legacy content

Issue in legacy file	Pages	Action
Placeholder schema entries ([[PROPERTY 1 NAME...]], [[ADD PROPERTY URL]], colive_ppm_XXXX, [CONFIRM: ...])	silk-board, manyata-tech-park, btm-layout, wakad, tathawade, kr-puram	Removed the placeholder entries/fields
Malformed hreflang tags (missing quote, "www colive.com")	men-bangalore, women-bangalore, navi-mumbai and others	Repaired
Schema type "Website"	men-bangalore, women-bangalore	Changed to "WebSite"
Hreflang filed under "chinchwad", so it never showed	pimpri-chinchwad	Now shown on that page

Mismatched FAQ heading tags hid most FAQs	kr-puram, navi-mumbai	Fixed; now 7 and 5 questions
H1 tags inside the content (multiple H1s)	6 pages incl. marathahalli, whitefield	Changed to H2; hero owns the only H1
Title typos ("PGr" + line break; trailing space)	btm-layout, chennai	Fixed
Hreflang URLs ending in "/" (redirected by this site)	All with hreflang	Trailing slash removed at render time
Bootstrap classes, ids, inline attributes in HTML	All	Stripped; styled with Tailwind instead

8. Verification (31 Oct 2026, local dev server)

Page	Hreflang	JSON-LD	FAQs	Result
/pg-in-bangalore	22	1	15	Pass
/bangalore/pg-in-whitefield	21	1	20	Pass
/men-pg-in-bangalore	24	1	14	Pass
/pune/pg-in-tathawade	9	6	25	Pass
/bangalore/central/pg-in-domlur (generic FAQs)	0	1	8	Pass
/bangalore/pg-in-btm-layout	21	1	30	Pass
/search?loc=Electronic City, Bangalore	21	1	18	Pass
/search?loc=<script-injection test>	–	–	–	Pass (escaped)

On every page checked: all JSON-LD parses as valid JSON, no `$strCity$` placeholder is left in the output, and there is exactly one H1.

9. Open items

Item	Detail	Recommendation
Trailing slash	Legacy URLs end in "/" (e.g. /pg-in-bangalore/); this site redirects them to the version without the slash. Canonical and hreflang use the no-slash form.	Decide before go-live. To keep legacy URLs identical, set `trailingSlash: true` in next.config.ts and restore slashes in canonical/hreflang.
Hreflang usage	Legacy tags mark 20+ different pages as en-in alternates of each other. Hreflang is meant for translations of the same page; Google will likely ignore or flag these.	Remove the hreflang lists (ported as-is for now).
Trending-category pages	Copy for couple-friendly and ultra-luxury is ported, but /trending-categories/... has no route yet (404). Legacy hard-coded titles for other trending categories are not ported.	Port when the trending-categories route is built.

Duplicate schemas	Tathawade outputs 6 JSON-LD blocks, including Organization and LocalBusiness twice (same as legacy).	Review and merge into one @graph.
Commit	All changes are uncommitted on Dev.	Review and commit.

10. Notes

- The legacy-to-JSON conversion script was a one-off tool and is not kept in the repository. The JSON files in `src/content/search-seo` are now the single source of truth; edit them directly.
- Collapsed overview text and FAQ answers remain in the page HTML, so search engines can still index them.
- JSON-LD is rendered with "<" escaped, following the Next.js JSON-LD guide (`node_modules/next/dist/docs/01-app/02-guides/json-ld.md`).