

學號：B06502149 系級：資工二 姓名：張琦琛

1. 請比較你本次作業的架構，參數量、結果和原 HW3 作業架構、參數量、結果做比較。(1%)

HW3 Model 架構


Layer (type)	Output Shape	Param #
conv2d_9 (Conv2D)	(None, 48, 48, 64)	1664
leaky_re_lu_9 (LeakyReLU)	(None, 48, 48, 64)	0
batch_normalization_13 (Batch Normalization)	(None, 48, 48, 64)	256
max_pooling2d_9 (MaxPooling2D)	(None, 24, 24, 64)	0
dropout_13 (Dropout)	(None, 24, 24, 64)	0
conv2d_10 (Conv2D)	(None, 24, 24, 128)	73856
leaky_re_lu_10 (LeakyReLU)	(None, 24, 24, 128)	0
batch_normalization_14 (Batch Normalization)	(None, 24, 24, 128)	512
max_pooling2d_10 (MaxPooling2D)	(None, 12, 12, 128)	0
dropout_14 (Dropout)	(None, 12, 12, 128)	0
conv2d_11 (Conv2D)	(None, 12, 12, 512)	590336
leaky_re_lu_11 (LeakyReLU)	(None, 12, 12, 512)	0
batch_normalization_15 (Batch Normalization)	(None, 12, 12, 512)	2048
max_pooling2d_11 (MaxPooling2D)	(None, 6, 6, 512)	0
dropout_15 (Dropout)	(None, 6, 6, 512)	0
conv2d_12 (Conv2D)	(None, 6, 6, 512)	2359808
leaky_re_lu_12 (LeakyReLU)	(None, 6, 6, 512)	0
batch_normalization_16 (Batch Normalization)	(None, 6, 6, 512)	2048
max_pooling2d_12 (MaxPooling2D)	(None, 3, 3, 512)	0
dropout_16 (Dropout)	(None, 3, 3, 512)	0
flatten_3 (Flatten)	(None, 4608)	0
dense_7 (Dense)	(None, 512)	2359808
batch_normalization_17 (Batch Normalization)	(None, 512)	2048
dropout_17 (Dropout)	(None, 512)	0
dense_8 (Dense)	(None, 512)	262656
batch_normalization_18 (Batch Normalization)	(None, 512)	2048
dropout_18 (Dropout)	(None, 512)	0
dense_9 (Dense)	(None, 7)	3591
Total params: 5,660,679		
Trainable params: 5,656,199		

HW8 Model 架構


Layer (type)	Output Shape	Param #
input_1 (InputLayer)	(None, 48, 48, 1)	0
initial_conv (Conv2D)	(None, 24, 24, 16)	144
initial_bn (BatchNormalizati	(None, 24, 24, 16)	64
initial_act (Activation)	(None, 24, 24, 16)	0
block0_dw (DepthwiseConv2D)	(None, 24, 24, 16)	144
block0_bn1 (BatchNormalizati	(None, 24, 24, 16)	64
block0_act1 (Activation)	(None, 24, 24, 16)	0
block0_pw (Conv2D)	(None, 24, 24, 16)	256
block0_bn2 (BatchNormalizati	(None, 24, 24, 16)	64
block0_act2 (Activation)	(None, 24, 24, 16)	0
block1_dw (DepthwiseConv2D)	(None, 24, 24, 16)	144
block1_bn1 (BatchNormalizati	(None, 24, 24, 16)	64
block1_act1 (Activation)	(None, 24, 24, 16)	0
block1_pw (Conv2D)	(None, 24, 24, 32)	512
block1_bn2 (BatchNormalizati	(None, 24, 24, 32)	128
block1_act2 (Activation)	(None, 24, 24, 32)	0
block2_dw (DepthwiseConv2D)	(None, 24, 24, 32)	288
block2_bn1 (BatchNormalizati	(None, 24, 24, 32)	128
block2_act1 (Activation)	(None, 24, 24, 32)	0
block2_pw (Conv2D)	(None, 24, 24, 64)	2048
block2_bn2 (BatchNormalizati	(None, 24, 24, 64)	256
block2_act2 (Activation)	(None, 24, 24, 64)	0
block3_dw (DepthwiseConv2D)	(None, 12, 12, 64)	576
block3_bn1 (BatchNormalizati	(None, 12, 12, 64)	256
block3_act1 (Activation)	(None, 12, 12, 64)	0
block3_pw (Conv2D)	(None, 12, 12, 128)	8192
block3_bn2 (BatchNormalizati	(None, 12, 12, 128)	512
block3_act2 (Activation)	(None, 12, 12, 128)	0
block4_dw (DepthwiseConv2D)	(None, 12, 12, 128)	1152
block4_bn1 (BatchNormalizati	(None, 12, 12, 128)	512
block4_act1 (Activation)	(None, 12, 12, 128)	0
block4_pw (Conv2D)	(None, 12, 12, 128)	16384
block4_bn2 (BatchNormalizati	(None, 12, 12, 128)	512
block4_act2 (Activation)	(None, 12, 12, 128)	0
block5_dw (DepthwiseConv2D)	(None, 12, 12, 128)	1152
block5_bn1 (BatchNormalizati	(None, 12, 12, 128)	512
block5_act1 (Activation)	(None, 12, 12, 128)	0
block5_pw (Conv2D)	(None, 12, 12, 256)	32768
block5_bn2 (BatchNormalizati	(None, 12, 12, 256)	1024
block5_act2 (Activation)	(None, 12, 12, 256)	0
global_avg (GlobalAveragePoo	(None, 256)	0
softmax (Dense)	(None, 7)	1799
Total params: 69,655		
Trainable params: 67,607		
Non-trainable params: 2,048		

在 HW3 的 CNN 模型中我使用了 4 層 Convolution layer, 在每一組都用了 LeakyReLU, BatchNormalization, Dropout, Filter 數量是越來越多個, 為了避免 OverFitting, 我的 Dropout rate 也有慢慢增加, 分別是 0.25、0.3、0.35、0.35。最後再將圖壓平, 進入 2 層的 Fully-connected-network, Dropout rate 設為 0.5, 再利用 softmax 當作 Activation function, 產生 7 種分類, 總參數量為 5660679。而在 HW8 我參考 Mobilenet 的模型架構, 一開始先用 16 個 filter 作一般的 convolution, 之後慢慢增加 filter 數量作 Depthwise convolution, 而每個 Depthwise convolution 後面都接一個 Pointwise convolution, 總共 6 組。最後一層 filter 數量最多, 共 256 個, 總參數量為 69655。而我同樣也是用 softmax 當作 Activation function、Adam 當作 optimizer、categorical_crossentropy 計算 loss。我認為兩者最不一樣的地方在於 Mobilenet 用 Depthwise 加 Pointwise convolution 減少參數量, 而且為了避免超過大小限制, 我每層的 filter 數量相較於 HW3 的 CNN, 每層少了將近 2-3 倍。HW3 在 Kaggle 的分數為 0.70075, HW8 為 0.63109。

- 請使用 MobileNet 的架構, 畫出參數量-acc 的散布圖 (橫軸為參數量, 縱軸為 accuracy, 且至少 3 個點, 參數量選擇時儘量不要離的太近, 結果選擇只要大致收斂, 不用 train 到最好沒關係。) (1%)



3. 請使用一般 **CNN** 的架構，畫出參數量-**acc** 的散布圖（橫軸為參數量，縱軸為 **accuracy**，且至少 **3** 個點，參數量選擇時儘量不要離的太近，結果選擇只要大致收斂，不用 **train** 到最好沒關係。） (1%)



4. 請你比較題 **2** 和題 **3** 的結果，並請針對當參數量相當少的時候，如果兩者參數量相當，兩者的差異，以及你認為為什麼會造成這個原因。 (2%)

從題 2 和題 3 的結果可以發現，HW3 的 CNN 模型看似有較好的準確率，雖然兩者最佳準確率的差距為 0.06353，但是兩者的參數量差距約為 560 萬，以 560 萬的代價換來的準確率似乎不算高。雖然兩張圖是不同的模型，但是從散佈圖的趨勢可以發現當參數量超過某個大小，準確率不升反降，必須不斷嘗試才能找出最好的模型架構。當兩者參數量皆約為 15 萬時，一般 CNN 模型的分數為 0.60406，Mobilenet 架構的模型為 0.61939;當參數量再下降到約 7 萬時，差距又更加明顯，一般 CNN 模型的分數為 0.56422，Mobilenet 架構的模型為 0.63109，並且我發現在 train 一般 CNN 時有 underfitting 的情況。我認為儘管兩者參數量相當，但對於普通 CNN 模型，filter 數量不能設太大且 model 深度較受限制，但對於 Mobilenet 這種是作 separable convolution 而言，可以增加多一點 layer 及 filter 數量，整體架構是高瘦型，而普通 CNN 大致是矮胖型，我在查詢網路上的資料後也發現高瘦型的 model 通常有較好的表現，因此我認為主要差異是模型的深度，導致 underfitting，若模型不夠深，就如線性函數無法準確的擬合一個以高次多項式函數產生的資料一樣。