

Back To Practice

Q1

Save

LRU Page Replacement Algorithm

Write a C program to implement the LRU Page Replacement Algorithm. The program should accept a reference string and the number of frames. For each page request, identify whether it results in a Hit or a Fault. If a Fault occurs and the frames are full, replace the page that was accessed least recently. Display the frame status at each step and calculate the total number of Page Faults and Hits

Input Format

1. The first line of input contains an integer representing the number of pages in the reference string.
2. The second line contains the page reference string as a sequence of integers.
3. The third line contains an integer representing the number of available frames.

Output Format

The output displays the total number of Page Faults and the total number of Page Hits after processing the entire reference string using the LRU page replacement algorithm.

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, frames;
5
6     printf("Enter number of pages in reference string: \n");
7     scanf("%d", &n);
8
9     int pages[n];
10    printf("Enter the reference string: \n");
11    for (int i = 0; i < n; i++)
12        scanf("%d", &pages[i]);
13
14    printf("Enter number of frames: \n");
15    scanf("%d", &frames);
16
17    int frame[frames], recent[frames], faults = 0, hits = 0, count = 0;
18    for (int i = 0; i < frames; i++) { frame[i] = -1; recent[i] = 0; }
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Success

Input :

Expected Output :

[Back To Practice](#)[Save](#)

Completed

LRU Page Replacement Algorithm

Write a C program to implement the LRU Page Replacement Algorithm. The program should accept a reference string and the number of frames. For each page request, identify whether it results in a Hit or a Fault. If a Fault occurs and the frames are full, replace the page that was accessed least recently. Display the frame status at each step and calculate the total number of Page Faults and Hits.

Input Format

- The first line of input contains an integer representing the number of pages in the reference string.
- The second line contains the page reference string as a sequence of integers.
- The third line contains an integer representing the number of available frames.

Output Format

The output displays the total number of Page Faults and the total number of Page Hits after processing the entire reference string using the LRU page replacement algorithm.

Select Language : C (GCC 9.2.0)

```
20 for (int i = 0; i < n; i++) {
21     int found = -1;
22
23     // Check if page already in frame (Hit)
24     for (int j = 0; j < frames; j++)
25         if (frame[j] == pages[i]) { found = j; break; }
26
27     if (found != -1) {
28         hits++;
29         recent[found] = ++count;
30     } else {
31         faults++;
32         int pos = 0;
33
34         // Find empty frame first
35         int empty = -1;
36         for (int j = 0; j < frames; j++)
37             if (frame[j] == -1) { empty = j; break; }
```

Test Cases 2

Run Sample CasesRun All Cases

Custom Test Case

Custom Test

Input:

Expected Output:

Success

Back To Practice

Save

LRU Page Replacement Algorithm

Write a C program to implement the LRU Page Replacement Algorithm. The program should accept a reference string and the number of frames. For each page request, identify whether it results in a Hit or a Fault. If a Fault occurs and the frames are full, replace the page that was accessed least recently. Display the frame status at each step and calculate the total number of Page Faults and Hits.

Input Format

1. The first line of input contains an integer representing the number of pages in the reference string.
2. The second line contains the page reference string as a sequence of integers.
3. The third line contains an integer representing the number of available frames.

Output Format

The output displays the total number of Page Faults and the total number of Page Hits after processing the entire reference string using the LRU page replacement algorithm.

Select Language : C (GCC 9.2.0)

```

40 pos = empty;
41 } else {
42     // Find LRU page (least recently used)
43     int lru = recent[0];
44     pos = 0;
45     for (int j = 1; j < frames; j++)
46         if (recent[j] < lru) { lru = recent[j]; pos = j; }
47 }
48
49 frame[pos] = pages[i];
50 recent[pos] = ++count;
51 }
52 }
53
54 printf("\nTotal Page Faults: %d\n", faults);
55 printf("Total Page Hits: %d\n", hits);
56
57 return 0;
58 }

```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Success

Input:

Expected Output: