Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:5

Sequence[]={1,3,4,1,2,2,2,2,3}

the subsequence is {1,2,2,2,2,3}

Output:6

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n], dp[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
        dp[i] = 1;
    }

    for (int i = 1; i < n; i++) {
        for (int j = 0; j < i; j++) {
            if (a[i] >= a[j] && dp[i] < 1 + dp[j])
                dp[i] = dp[j] + 1;
        }
    }

    int max = dp[0];

    for (int i = 1; i < n; i++) {
        if (dp[i] > max)
            max = dp[i];
    }

    printf("%d", max);

    return 0;
}
```

	Input	Expected	Got	
✔	9 1 3 4 1 2 2 2 2 3	6	6	✔
✔	7 1 2 3 4 5 6 7	7	7	✔

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgcaab

s1	a	a	g	t	a	b
s2	g	a	t	a	a	y	b

The length is 4

Solving it using Dynamic Programming

For example:

Input	Result
aab aab	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <string.h>

int main() {
    char a[100], b[100];
    scanf("%s", a);
    scanf("%s", b);

    int m = strlen(a);
    int n = strlen(b);
    int dp[m + 1][n + 1];

    for (int i = 0; i <= m; i++)
        dp[i][0] = 0;

    for (int j = 0; j <= n; j++)
        dp[0][j] = 0;

    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (a[i - 1] == b[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
                dp[i][j] = dp[i - 1][j] > dp[i][j - 1] ? dp[i - 1][j] : dp[i][j - 1];
        }
    }

    printf("%d", dp[m][n]);

    return 0;
}
```

	Input	Expected	Got	
✔	aab aab	2	2	✔
✔	rmit rmit	4	4	✔

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0) that the position of the top left White rook. He is been given a task to reach the bottom right black rock position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input:

3

1 2 3

2 3 4

8 7 1

Output:

15

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value=1+2+8+7+1=15

Input Format:

First Line consists the integer n .

The next n lines consists the n*n chessboard values

Output Format:

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```
#include<stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n][n];

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &a[i][j]);

    for (int i = 1; i < n; i++)
        a[i][0] += a[i - 1][0];

    for (int j = 1; j < n; j++)
        a[0][j] += a[0][j - 1];

    for (int i = 1; i < n; i++)
        for (int j = 1; j < n; j++)
            a[i][j] += (a[i - 1][j] > a[i][j - 1]) ? a[i - 1][j] : a[i][j - 1];

    printf("%d", a[n - 1][n - 1]);

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 2 3 4 8 7 1	15	15	✔
✔	4 1 1 1 1 1 1 1 1 1 1 1 1	12	12	✔
✔	5 1 2 3 4 5 1 5 7 8 9 2 3 7 9 8 1 6 8 9 9	36	36	✔

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*

Output:8

Explanation: *There are 8 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format:

First Line contains the number n.

Output Format:

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input:

6

Sample Output:

8

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long dp[n + 1];

    dp[0] = 1;

    for (int i = 1; i <= n; i++) {
        dp[i] = dp[i - 1];

        if (i >= 3)
            dp[i] = dp[i] + dp[i - 3];
    }

    printf("%lld", dp[n]);

    return 0;
}
```

	Input	Expected	Got	
✔	6	8	8	✔
✔	25	98721	98721	✔
✔	100	24382819596721629	24382819596721629	✔