Status	Finished
Started	Saturday, 10 October 2026, 5:52 PM
Completed	Saturday, 10 October 2026, 5:57 PM
Duration	4 mins 56 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. (58,47,36,25)

b. (3,14,25)

c. (36, 25, 14) ✓

d. Error

Question **2**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

a. <class 'str'> ✓

b. <class 'int'>

c. str

d. <class 'tuple'>

Question **3**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

a. (11,3)(11,3)(11,3)

b. [11,11,11,3,3,3]

c. (11,3,11,11,3,11,11,11,3)

d. (11, 3, 11, 3, 11, 3) ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '30', '8']

b. ['30', '8', '3', '2']

c. ['2', '3', '8', '30']

d. ['8', '30', '3', '2'] ✓

Question **5**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

- a. 5
- b. 2
- c. Error ✓
- d. 1

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

- a. {4} ✓
- b. {2}
- c. {1,3,4}
- d. {1,3,2}

Question **8**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t1 = (55, 44, 33, 22, 11)

x = [t1[i] for i in range(0, len(t1), 2)]

print(x)

- a. [55, 33, 11] ✓
- b. [(55,33,11)]
- c. ([55,33,11])
- d. (55,33,11)

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True ✓
True

b. True
False

c. False
False

d. False
True

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,0,9}

b. It will throw an error as there are two 0 while creating the set.

c. {9}

d. {0,9} ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

- a. iii
- b. ii
- c. All of the above
- d. i,ii ✓

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

- a. Error
- b. {'rec', True, ('cse', 'ece')}
- c. {'rec', 1, ('cse', 'ece')} ✓
- d. {'rec', 1, ('cse', 'ece'),True}

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. (1,2,3,4,5,6) ✓
- b. (1,2,3,3,2,1)
- c. (1,2,3)(4,5,6)
- d. Error

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (10, 20, 30, 40) (40, 50, 60, 70, 80)

b. (30, 40, 50) (10, 20, 30, 40)

c. (30, 40, 50)(40, 50, 60, 70, 80)

d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **15**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. No, No

b. Yes, Yes

c. "==" is not supported for set in Python

d. Yes, No ✓