

## LEGEND:

2

ယ

	CT2		$\bigcirc$	Vs	တ		M		SYMBOL
ICP DATA CABINET 12U WALL MOUNT	DUAL INPUT MODULE FOR INTERFACE TO GAS DETECTION SYSTEM	INTERFACE TO GAS DETECTION SYSTEM	HEAT DETECTOR	CEILING RECESSED VOICE EVACUATION SPEAKER	SMOKE DETECTOR	W/P SOCKET IN FLOOR BOX	TANENT METER	400 A TPN ISOLATING SWITCH	DESCRIPTION

175.00 K.W	TOTAL LOAD	
3.00 K.W 8.500 K.W	MUA-G-0079B	
2.20 K.W	KEF-G-0079B	
1.10 K.W	AHU-G-0079B.K	ν.
2.20 K.W	AHU-G-0079B	)
166.50 K.W	LIGHT, POWER & EQUIPMENT	
LOAD IN K.W	DESCRIPTION	S.NO

- GENERAL NOTES:
  01.25mmØ CONDUIT TO BE LAID FROM EACH F&B UNIT
  ELECTRICAL PANEL LOCATION TO KEF LOCATION ON ROOF
  FOR ELECTRICAL SUPPLY TO KEF.
- 02. 25mmØ CONDUIT WITH DRAW WIRE TO BE LAID FROM THE TENANT DB LOCATION TO BACK BOX PROVIDED IN OUT SIDE SEATING AREA FOR TENANT USE. BACKBOX PROVIDED IS FOR FUTURE SOCKET BY TENANT.

## NOTES:

- ISOLATOR WILL BE LOCATED AT HIGH LEVEL ABOVE FALSE CEILING
- IDF SYSTEMS AS PER DESIGN DRAWINGS

ELEC	TRADE	USAGE.	UNIT NO.	RESTAURANT ELEC.PLAN
1.50 @ A1	SCALE	RESTAURANT	G-116	ANT ELEC
DEC 2020	DATE	ANT	3,	).PLAN

DRAWN BY CHECKED BY APPROVED BY
M.RAMADAN

05 OF 09

