


FAN COIL UNITS SCHEDULE:										
F	CU NO.	RETAIL NO.	MODEL	SUPPLY AIR (CFM)	FRESH AIR (L/S)	COOLING LOATOTAL	AD (BTU/Hr) SENSIBLE	ELEC. HEATER (KW)	CHILLED WATER FLOW (L/S)	MOTOR (WATT)
	F102	M1-44	42DC-12	1145	80	23243	18801	2.5	0.29	149.2

NOTE:-

- 1. ALL FCUS ARE SLECTED AT MEDIUM SPEED.
- 2. CHILLED WATER FLOW AND RETURN
- TEMPERATURES = $7.2 \, ^{\circ}\text{C}$ AND $12.8 \, ^{\circ}\text{C}$.
- 3. EXTERNAL STATIC PRESSURE IS 40PA.



<u>NOTE</u>

- * THIS DRAWING IS ACCURATE AS AT THE DATE SHOWN ON THE DRAWING.
- * THIS DRAWING IS SUBJECT TO CHANGE AS PLANNING, DEVELOPMENT AND CONSTRUCTION CONTINUES THROUGH UNTIL OPENING OF THE SHOPPING CENTRE.
- * IT IS THE RESPONSIBILITY OF THE RECIPIENT OF THIS DRAWING TO UPDATE THEMSELVES WITH ANY SUBSEQUENT REVIEWS, UPDATES, ADDITIONS, DELETIONS AND/OR SUBSTITUTIONS.
- * TAMDEEN SHOPPING CENTRE DEVELOPMENT CO. (OR ANY OF IT'S AFFILIATED COMPANIES) DOES NOT ACCEPT ANY LIABILITY OF ANY FORM FOR THE RECIPIENT'S USE AND/OR INTERPRETATION OF THIS DRAWING.
- * REFER TO 360° -KWUAIT INVESTOR FITOUT & DESIGN GUIDELINES

<u>HVAC NOTES</u>:

- FAN COIL UNITS SHALL BE SUPPLIED AND INSTALLED BY LAND LORD AND PAID FOR BY TENANT.
- 2. DUCT WORK DISTRIBUTION FROM FCU TO DIFFUSER SHALL BE THE TENANTS RESPONSIBILITY.
- 3. ALL DIMENSION ARE IN MM UNLESS OTHERWISE SPECIFIED.

 4. ALL FLOW RATES ARE IN LITERS PER SECOND LINESS SHOW
- 4. ALL FLOW RATES ARE IN LITERS PER SECOND UNLESS SHOWN OTHERWISE.
- 5. ALL DUCT SIZES ARE CLEAR INSIDE DUCT DIMENSION.

<u>LEGEND & ABBREVIATIONS</u>:

<u> </u>	- ABBITETIFITIONS	•
FCU		FAN COIL UNIT
AHU		AIR HANDLING UNIT
FAD		FRESH AIR DUCT
SAD		SUPPLY AIR DUCT
RAD		RETURN AIR DUCT
EAD		EXHAUST AIR DUCT
TE		TOILET EXHAUST
SACD		SUPPLY AIR CEILING DIFFUSER
RACD		RETURN AIR CEILING DIFFUSER
FFL		FINISH FLOOR LEVEL
BDD		BACK DRAFT DAMPER
SD		SMOKE DAMPER
FD		FIRE DAMPER
BOD		BOTTOM OF DUCT
CL		CENTER LINE LEVEL
H/L		HIGH LEVEL
L/L		LOW LEVEL
T/A		TO ABOVE
T/B		TO BELOW
F/A		FROM ABOVE
F/B		FROM BELOW
ΑĎ	AD.	ACCESS DOOR
VCD	<u> </u>	VOLUME CONTROL DAMPER
Т	ന്	THERMOSTAT (WALL MOUNTED)
CD		CONDENSATE DRAIN PIPE
CHWS		CHILLED WATER SUPPLY PIPE
CHWR		CHILLED WATER RETURN PIPE
CV	₹AP	COMMISSION SET
l IV	\bowtie	ISOLATE VALVE
FD		FLOOR DRIAN
1		

PRO

360° MALL SOUTH SURRA, KUWAIT



OWNER:



HVACITECT

RTKL International Ltd.
1717 Pacific Avenue
Dallas, Texas 75201-4688
214 871 8877
www.rtkl.com
RTKL International Ltd. 2005

CONSULTANT:

CONSULTANT CONSULTANT CONSULTANT ENGINEERS, HVACITECTS & PLANNERS

TEL:2420508/518 - 2429932/1 - 2402373/2473, FAX:2436511
P. O. Box 6249 HAWALLY, CODE NO:32037 - Kuwait
E-mail ohac@ncc.moc.kw

IN CONTRACTOR:



DRAWING TITLE:

HVAC PLAN

TIVAOT EAN								
RETAIL	NO.	M1-44						
DATE	SCALE	DRAWN BY	CHECKED BY	APPROVED BY				
28-02-08	1:50 @ A1							
TRADE	ACTC.REV.	DRAWING No.	OF	REV.				
HVAC	09	AC-05	05	00				