

10/10/25

EXERCISE-16

PROCEDURES AND FUNCTIONS

PROCEDURES

DEFINITION

A procedure or function is a logically grouped set of SQL and PL/SQL statements that perform a specific task. They are essentially sub-programs. Procedures and functions are made up of,

- Declarative part
- Executable part
- Optional exception handling part

These procedures and functions do not show the errors.

KEYWORDS AND THEIR PURPOSES

REPLACE: It recreates the procedure if it already exists.

PROCEDURE: It is the name of the procedure to be created.

ARGUMENT: It is the name of the argument to the procedure. Paranthesis can be omitted if no arguments are present.

IN: Specifies that a value for the argument must be specified when calling the procedure ie. used to pass values to a sub-program. This is the default parameter.

OUT: Specifies that the procedure passes a value for this argument back to it's calling environment after execution ie. used to return values to a caller of the sub-program.

INOUT: Specifies that a value for the argument must be specified when calling the procedure and that procedure passes a value for this argument back to it's calling environment after execution.

RETURN: It is the datatype of the function's return value because every function must return a value, this clause is required.

PROCEDURES – SYNTAX

```
create or replace procedure <procedure name> (argument {in,out,inout} datatype ) {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

FUNCTIONS – SYNTAX

```
create or replace function <function name> (argument in datatype,.....) return datatype {is,as}
variable declaration;
```

constant declaration;
 begin
 PL/SQL subprogram body;
 exception
 exception PL/SQL block;
 end;

CREATING THE TABLE 'ITITEMS' AND DISPLAYING THE CONTENTS

SQL> create table ititems(itemid number(3), actualprice number(5), ordid number(4), prodid number(4));
 Table created.

SQL> insert into ititems values(101, 2000, 500, 201);
 1 row created.

SQL> insert into ititems values(102, 3000, 1600, 202);
 1 row created.

SQL> insert into ititems values(103, 4000, 600, 202);
 1 row created.

SQL> select * from ititems;

ITEMID	ACTUALPRICE	ORDID	PRODID
101	2000	500	201
102	3000	1600	202
103	4000	600	202

PROGRAM FOR GENERAL PROCEDURE - SELECTED RECORD'S PRICE IS INCREMENTED BY 500 , EXECUTING THE PROCEDURE CREATED AND DISPLAYING THE UPDATED TABLE

```
SQL> create procedure itsum(identity number, total number) is price number;
2 null_price exception;
3 begin
4 select actualprice into price from ititems where itemid=identity;
5 if price is null then
6 raise null_price;
7 else
8 update ititems set actualprice=actualprice+total where itemid=identity;
9 end if;
10 exception
11 when null_price then
12 dbms_output.put_line('price is null');
13 end;
14 /
```

Procedure created.

SQL> exec itsum(101, 500);
 PL/SQL procedure successfully completed.

SQL> select * from ititems;

ITEMID	ACTUALPRICE	ORDID	PRODID
--------	-------------	-------	--------

101	2500	500	201
102	3000	1600	202
103	4000	600	202

PROCEDURE FOR 'IN' PARAMETER – CREATION, EXECUTION

SQL> set serveroutput on;

```
SQL> create procedure yyy (a IN number) is price number;
2 begin
3 select actualprice into price from ititems where itemid=a;
4 dbms_output.put_line('Actual price is ' || price);
5 if price is null then
6 dbms_output.put_line('price is null');
7 end if;
8 end;
9 /
```

Procedure created.

SQL> exec yyy(103);

Actual price is 4000

PL/SQL procedure successfully completed.

PROCEDURE FOR 'OUT' PARAMETER – CREATION, EXECUTION

SQL> set serveroutput on;

```
SQL> create procedure zzz (a in number, b out number) is identity number;
2 begin
3 select ordid into identity from ititems where itemid=a;
4 if identity<1000 then
5 b:=100;
6 end if;
7 end;
8 /
```

Procedure created.

SQL> declare

```
2 a number;
3 b number;
4 begin
5 zzz(101,b);
6 dbms_output.put_line('The value of b is ' || b);
7 end;
8 /
```

The value of b is 100

PL/SQL procedure successfully completed.

PROCEDURE FOR 'INOUT' PARAMETER – CREATION, EXECUTION

SQL> create procedure itit (a in out number) is

```
2 begin
3 a:=a+1;
```

```
4 end;
5 /
Procedure created
```

```
SQL> declare
2 a number:=7;
3 begin
4 itit(a);
5 dbms_output.put_line('The updated value is '||a);
6 end;
7 /
```

The updated value is 8

PL/SQL procedure successfully completed.

CREATE THE TABLE 'ITTRAIN' TO BE USED FOR FUNCTIONS

```
SQL>create table ittrain ( tno number(10), tfare number(10));
Table created.
```

```
SQL>insert into ittrain values (1001, 550);
1 row created.
```

```
SQL>insert into ittrain values (1002, 600);
1 row created.
```

```
SQL>select * from ittrain;
   TNO   TFARE
-----
```

1001	550
1002	600

PROGRAM FOR FUNCTION AND IT'S EXECUTION

```
SQL> create function aaa (trainnumber number) return number is
2 trainfunction ittrain.tfare % type;
3 begin
4 select tfare into trainfunction from ittrain where tno=trainnumber;
5 return(trainfunction);
6 end;
7 /
```

Function created.

```
SQL> set serveroutput on;
```

```
SQL> declare
2 total number;
3 begin
4 total:=aaa (1001);
5 dbms_output.put_line('Train fare is Rs. '||total);
6 end;
7 /
```

Train fare is Rs.550

PL/SQL procedure successfully completed.

Program 1

FACTORIAL OF A NUMBER USING FUNCTION

```
SET SERVEROUTPUT ON;  
CREATE OR REPLACE FUNCTION factorial (n NUMBER)  
RETURN NUMBER  
IS  
    fact NUMBER := 1;  
BEGIN  
    FOR i IN 1..n LOOP  
        fact := fact * i;  
    END LOOP;  
    RETURN fact;  
END;
```

⌋

```
DECLARE  
    num NUMBER := 5;  
    result NUMBER;  
BEGIN  
    result := factorial (num);  
    DBMS_OUTPUT.PUT_LINE ('factorial of ' || num || ' is ' ||  
                             result);  
END;
```

⌋


Program 2

Write a PL/SQL program using Procedures IN, INOUT, OUT parameters to retrieve the corresponding book information in library

```

SET SERVEROUTPUT ON;
CREATE OR REPLACE PROCEDURE get-book-info
(P-book-id IN NUMBER, P-book-name OUT
VARCHAR2, P-author OUT VARCHAR, P-price IN OUT
NUMBER) IS
BEGIN
    SELECT book-name, author, price INTO P-book-name,
P-author, P-price FROM library WHERE book-id = P-book-id;
    DBMS_OUTPUT.PUT_LINE ('Book Name: ' || P-book-name);
    DBMS_OUTPUT.PUT_LINE ('Author: ' || P-author);
    DBMS_OUTPUT.PUT_LINE ('Price: ' || P-price);
EXCEPTION
    WHEN NO-DATA-FOUND THEN
        V-book-name VARCHAR2(50);
        V-author VARCHAR2(50);
        V-price NUMBER := 0;

```

Evaluation Procedure	Marks awarded
PL/SQL Procedure(5)	5
Program/Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	

```

BEGIN
    get-book-info (101, V-book-name, V-author, V-price);
    DBMS_OUTPUT.PUT_LINE ('Book info Retrieved
    Successfully');
END;

```