

Experiment 9

Nmap Timing and Performance Commands

Aim

To perform IDS evasion and timing scans using Nmap.

Theory

Timing options control the speed and stealthiness of Nmap scans.

Commands

i) Polite IDS Evasion

`nmap -T2 192.168.1.10`

Description:

Slows down scanning to reduce the chance of detection.

ii) Normal Scan

`nmap -T3 192.168.1.10`

Description:

Default balanced scanning speed.

Procedure

1. Identify target IP address.
2. Execute Nmap timing commands.
3. Observe scan duration and results.
4. Compare scan speeds.

Result

Successfully executed Nmap timing and performance scans in Kali Linux.

Session Actions Edit View Help

(harikamytheyi@kali)-[~]

\$ nmap -T2 127.0.0.1

Starting Nmap 7.99 (<https://nmap.org>) at 2026-10-08 10:34 -0400

(harikamytheyi@kali)-[~]

\$ nmap 127.0.0.1

Starting Nmap 7.99 (<https://nmap.org>) at 2026-10-08 10:40 -0400

Nmap scan report for localhost (127.0.0.1)

Host is up (0.0000040s latency).

All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.

Not shown: 1000 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.08 seconds

(harikamytheyi@kali)-[~]

\$ nmap -T3 127.0.0.1

Starting Nmap 7.99 (<https://nmap.org>) at 2026-10-08 10:41 -0400

Nmap scan report for localhost (127.0.0.1)

Host is up (0.0000020s latency).

All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.

Not shown: 1000 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.04 seconds

(harikamytheyi@kali)-[~]

\$ nmap -T3 127.0.0.1

Starting Nmap 7.99 (<https://nmap.org>) at 2026-10-08 10:41 -0400

Nmap scan report for localhost (127.0.0.1)

Host is up (0.0000020s latency).

All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.

Not shown: 1000 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.04 seconds

(harikamytheyi@kali)-[~]

\$