Playwright Cheat Sheet

@aman_views

→ 1. Setup Flow

browserType.launch()	:	starts the browser
browser.newContext()	:	creates isolated test session
context.newPage()	:	opens a new tab/page



→ 2. Navigation Methods

page.goto(url)	:	open a website URL
page.reload()	:	refresh current page
page.goBack()	:	go to previous page
page.goForward()	:	go to next page
page.url()	:	get current URL
page.title()	:	get page title

→ 3. Page & Viewport

page.setViewportSize()	:	set browser page size
page.bringToFront()	:	focus the current tab
page.close()	:	closes current page
context.close()	:	closes the context
browser.close()	:	closes full browser

→ 4. Example Flow

```
const browser = await chromium.launch();          // launch browser
const context = await browser.newContext();       // create context
const page = await context.newPage();             // open new page
await page.goto('https://example.com');           // navigate to URL
console.log(await page.title());                  // get page title
console.log(page.url());                          // get current URL
await page.close();                               // close page
await context.close();                            // close context
await browser.close();                            // close browser
```

Playwright Cheat Sheet

@aman_views

→ 1. Locators

```
page.locator('selector')                : generic locator by selector
page.getByText('Login')                 : find element by visible text
page.getByRole('button',{name:'Save'})  : semantic locator
page.getByLabel('Email')                : find input by label
page.getByPlaceholder('Search')         : locate by placeholder
page.getByTestId('submit-btn')          : locate by test id
```

→ 2. Narrowing Results

```
locator.first()                         : first matched element
locator.last()                          : last matched element
locator.nth(1)                          : element by index
locator.filter({ hasText: 'Admin' })    : filter matching elements
locator.locator('.child')               : find child inside locator
```

Parent Locator ⟶ Child Locator

→ 3. Common Actions

```
locator.click()                 : click element
locator.fill('Aman')            : clear and type text
locator.type('Hello')           : type text character by character
locator.press('Enter')          : press keyboard key
locator.hover()                 : move mouse over element
locator.dblclick()              : double click element
locator.check() / uncheck()     : handle checkbox
locator.selectOption('IN')      : choose dropdown option
```

→ 4. Quick Example

```
await page.goto('https://example.com');
await page.getByLabel('Email').fill('aman@example.com');
await page.getByLabel('Password').fill('mypassword');
await page.getByRole('button', { name:'Login' }).click();
await expect(page.getByText('Welcome')).toBeVisible();
await page.locator('.item').first().click();
```

Playwright Cheat Sheet

@aman_views

→ 1. Element Assertions

```
expect(locator).toBeVisible()     : verify element is visible
expect(locator).toBeHidden()      : verify element is hidden
expect(locator).toBeEnabled()     : verify element is enabled
expect(locator).toBeDisabled()    : verify element is disabled
expect(locator).toBeChecked()     : verify checkbox/radio is checked
expect(locator).toHaveCount(3)    : verify number of matched elements
```

→ 2. Text & Value Assertions

```
expect(locator).toHaveText('Success')          :  exact text match
expect(locator).toContainText('Success')       :  partial text match
expect(locator).toHaveValue('aman@test.com')   :  verify input value
expect(locator).toHaveAttribute('type', 'email') :  verify attribute value
expect(locator).toHaveClass(/active/)          :  verify CSS class
```

→ 3. Page Assertions

```
expect(page).toHaveURL(/dashboard/)      : verify current page URL
expect(page).toHaveTitle(/Home/)         : verify page title
expect(locator).toHaveCSS('display', 'block'): verify CSS property
```

Exact Match	Partial Match
expect(locator).toHaveText('Success') (matches exact text)	expect(locator).toContainText('Success') (matches partial text)

→ 4. Quick Example

```
await page.goto('https://example.com');
await expect(page).toHaveURL(/dashboard/);
const button = page.locator('button');
await expect(button).toBeVisible();
const message = page.locator('.message');
await expect(message).toContainText('Success');
const input = page.locator('#email');
await expect(input).toHaveValue('aman@test.com');
```

Playwright Cheat Sheet

@aman_views

→ 1. Wait Methods

```
page.waitForLoadState('load')                : wait for full page load
page.waitForLoadState('domcontentloaded')    : wait for DOM ready
page.waitForLoadState('networkidle')         : wait for network to settle
locator.waitFor()                            : wait for locator state
page.waitForURL('**/dashboard')              : wait until URL changes
page.waitForResponse('**/api/users')         : wait for API response
page.waitForRequest('**/login')              : wait for request to be sent
```

→ 2. Tabs & Popups

```
context.newPage()            : open a new tab/page
page.waitForEvent('popup')   : capture popup window
context.pages()              : list all open pages
popup.bringToFront()         : focus popup page
```



→ 3. Frames

```
page.frame({ name: 'frameName' })  : access frame by name
page.frameLocator('#my-frame')     : work inside iframe
frameLocator.locator('button')     : find element inside frame
```



→ 4. Quick Example

```
// Handle a popup
const [popup] = await Promise.all([
      page.waitForEvent('popup'),              // capture popup
      page.click('a[target="_blank"]')         // click link to open popup
]);
await popup.bringToFront();                    // focus popup page

// Work with an iframe
const frame = page.frameLocator('#my-frame');
await frame.locator('button').click();         // click button inside frame
```

Playwright Cheat Sheet

@aman_views

→ 1. Screenshots & Files

`page.screenshot({ path: 'page.png', fullPage: true })`	:	capture full page screenshot
`locator.screenshot({ path: 'btn.png' })`	:	capture element screenshot
`locator.setInputFiles('resume.pdf')`	:	upload file
`page.waitForEvent('download')`	:	capture file download

→ 2. Network Mocking

`page.route('**/api/**', route => route.fulfill(...))`	:	mock API response
`route.continue()`	:	continue original request
`route.abort()`	:	block request
`page.on('response', res => ...)`	:	inspect responses



→ 3. Storage & Browser Execution

`context.storageState({ path: 'auth.json' })`	:	save login state
`browser.newContext({ storageState: 'auth.json' })`	:	reuse saved session
`page.evaluate(() => localStorage.clear())`	:	run code in browser
`page.keyboard.press('Control+A')`	:	keyboard action
`page.mouse.move(100, 200)`	:	mouse action

→ 4. Dialogs & Debug

`page.on('dialog', d => d.accept())`	:	handle alert/prompt
`page.pause()`	:	open Playwright inspector
`locator.dragTo(target)`	:	drag and drop element

→ 5. Quick Example

```
const context = await browser.newContext({ storageState: 'auth.json' });
await page.route('**/api/**', route => route.fulfill({ status: 200, body: 'OK' }));
page.on('dialog', d => d.accept());
await page.goto('https://example.com');
await page.screenshot({ path: 'final.png', fullPage: true });
await context.storageState({ path: 'auth.json' });
await context.close();
```