

Terminal

VPC1 * VPC2 * L2-SW-1 * CORE * L2-SW-2 * VPC3 * VPC4 * ROUTER *

84 bytes from 20.0.0.10 icmp_seq=5 ttl=63 time=2.672 ms

VPC1> ping 20.0.0.10 -t

84 bytes from 20.0.0.10 icmp_seq=1 ttl=63 time=2.843 ms

84 bytes from 20.0.0.10 icmp_seq=2 ttl=63 time=2.152 ms

84 bytes from 20.0.0.10 icmp_seq=3 ttl=63 time=2.496 ms

84 bytes from 20.0.0.10 icmp_seq=4 ttl=63 time=2.307 ms

84 bytes from 20.0.0.10 icmp_seq=5 ttl=63 time=2.615 ms

84 bytes from 20.0.0.10 icmp_seq=6 ttl=63 time=2.745 ms

^C

VPC1> ping 30.0.0.10

30.0.0.10 icmp_seq=1 timeout

30.0.0.10 icmp_seq=2 timeout

30.0.0.10 icmp_seq=3 timeout

30.0.0.10 icmp_seq=4 timeout

30.0.0.10 icmp_seq=5 timeout

VPC1> ping 30.0.0.10

84 bytes from 30.0.0.10 icmp_seq=1 ttl=62 time=5.502 ms

84 bytes from 30.0.0.10 icmp_seq=2 ttl=62 time=4.380 ms

84 bytes from 30.0.0.10 icmp_seq=3 ttl=62 time=3.482 ms

84 bytes from 30.0.0.10 icmp_seq=4 ttl=62 time=3.732 ms

84 bytes from 30.0.0.10 icmp_seq=5 ttl=62 time=3.283 ms

VPC1> █

Terminal

VPC1 * VPC2 * L2-SW-1 * CORE * L2-SW-2 * VPC3 * VPC4 * ROUTER *

```
40.0.0.10 icmp_seq=4 timeout
40.0.0.10 icmp_seq=5 timeout
```

```
VPC2> ping 1.0.0.2
```

```
1.0.0.2 icmp_seq=1 timeout
1.0.0.2 icmp_seq=2 timeout
1.0.0.2 icmp_seq=3 timeout
1.0.0.2 icmp_seq=4 timeout
1.0.0.2 icmp_seq=5 timeout
```

```
VPC2> ping 1.0.0.1
```

```
64 bytes from 1.0.0.1 icmp_seq=1 ttl=255 time=1.661 ms
64 bytes from 1.0.0.1 icmp_seq=2 ttl=255 time=1.440 ms
64 bytes from 1.0.0.1 icmp_seq=3 ttl=255 time=1.582 ms
64 bytes from 1.0.0.1 icmp_seq=4 ttl=255 time=1.214 ms
64 bytes from 1.0.0.1 icmp_seq=5 ttl=255 time=1.435 ms
```

```
VPC2> ping 40.0.0.10
```

```
64 bytes from 40.0.0.10 icmp_seq=1 ttl=62 time=5.586 ms
64 bytes from 40.0.0.10 icmp_seq=2 ttl=62 time=3.771 ms
64 bytes from 40.0.0.10 icmp_seq=3 ttl=62 time=4.515 ms
64 bytes from 40.0.0.10 icmp_seq=4 ttl=62 time=3.396 ms
64 bytes from 40.0.0.10 icmp_seq=5 ttl=62 time=3.138 ms
```

```
VPC2> █
```

```
Terminal
VPC1 x VPC2 x L2-SW-1 x CORE x L2-SW-2 x VPC3 x VPC4 x ROUTER x
L2-SW-1#conf t
Enter configuration commands, one per line. End with CNTL/Z.
L2-SW-1(config)#int e0/0
L2-SW-1(config-if)#ssw
L2-SW-1(config-if)#s
L2-SW-1(config-if)#swi
L2-SW-1(config-if)#switchport ac
L2-SW-1(config-if)#switchport access vlan 10
% Access VLAN does not exist. Creating vlan 10
L2-SW-1(config-if)#exit
L2-SW-1(config)#int e0/1
L2-SW-1(config-if)#switchport access vlan 20
% Access VLAN does not exist. Creating vlan 20
L2-SW-1(config-if)#exit
L2-SW-1(config)#int e0/2
L2-SW-1(config-if)#sw
L2-SW-1(config-if)#switchport tr
L2-SW-1(config-if)#switchport trunk en
L2-SW-1(config-if)#switchport trunk encapsulation do
L2-SW-1(config-if)#switchport trunk encapsulation dot1q
L2-SW-1(config-if)#swi
L2-SW-1(config-if)#switchport mo
L2-SW-1(config-if)#switchport mode tr
L2-SW-1(config-if)#switchport mode trunk
L2-SW-1(config-if)#exit
L2-SW-1(config)#
*Sep 18 02:33:46.383: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
L2-SW-1(config)#
```

```

terminal
VPC1 x VPC2 x L2-SW-1 x CORE x L2-SW-2 x VPC3 x VPC4 x ROUTER x
*Sep 18 02:51:27.569: %SYS-5-CONFIG_I: Configured from console by console
CORE#sh ip rout
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        a - application route
        + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

1.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       1.0.0.0/8 is directly connected, Ethernet0/1
L       1.0.0.1/32 is directly connected, Ethernet0/1
10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Vlan10
L       10.0.0.1/32 is directly connected, Vlan10
20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Vlan20
L       20.0.0.1/32 is directly connected, Vlan20
S       30.0.0.0/8 [1/0] via 1.0.0.2
S       40.0.0.0/8 [1/0] via 1.0.0.2
CORE#
CORE#
CORE#

```

Terminal

VPC1 * VPC2 * L2-SW-1 * CORE * L2-SW-2 * VPC3 * VPC4 * ROUTER *

```
L2-SW-2(config-if)#switchport trunk encapsulation do
L2-SW-2(config-if)#switchport trunk encapsulation dot1q
L2-SW-2(config-if)#sw
L2-SW-2(config-if)#switchport mo
L2-SW-2(config-if)#switchport mode tr
L2-SW-2(config-if)#switchport mode trunk
L2-SW-2(config-if)#ex
L2-SW-2(config)#
*Sep 18 02:40:10.880: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
L2-SW-2(config)#sh ip route
```

% Invalid input detected at '^' marker.

```
L2-SW-2(config)#do sh
L2-SW-2(config)#do show ip route
```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

```
L2-SW-2(config)#
```

terminal

VPC1 × VPC2 × L2-SW-1 × CORE × L2-SW-2 × VPC3 × VPC4 × ROUTER ×

Press '?' to get help.

Executing the startup file

VPC3>

VPC3> ip 30.0.0.10/8 30.0.0.1

Checking for duplicate address...

VPC3 : 30.0.0.10 255.0.0.0 gateway 30.0.0.1

VPC3> ping 40.0.0.10

40.0.0.10 icmp_seq=1 timeout

*30.0.0.1 icmp_seq=2 ttl=255 time=1.560 ms (ICMP type:3, code:1, Destination host unreachable)

*30.0.0.1 icmp_seq=3 ttl=255 time=1.743 ms (ICMP type:3, code:1, Destination host unreachable)

*30.0.0.1 icmp_seq=4 ttl=255 time=1.701 ms (ICMP type:3, code:1, Destination host unreachable)

*30.0.0.1 icmp_seq=5 ttl=255 time=1.614 ms (ICMP type:3, code:1, Destination host unreachable)

VPC3> ping 40.0.0.10

84 bytes from 40.0.0.10 icmp_seq=1 ttl=63 time=4.081 ms

84 bytes from 40.0.0.10 icmp_seq=2 ttl=63 time=2.169 ms

84 bytes from 40.0.0.10 icmp_seq=3 ttl=63 time=3.264 ms

84 bytes from 40.0.0.10 icmp_seq=4 ttl=63 time=2.782 ms

84 bytes from 40.0.0.10 icmp_seq=5 ttl=63 time=2.362 ms

VPC3> █

```
terminal
VPC1 x VPC2 x L2-SW-1 x CORE x L2-SW-2 x VPC3 x VPC4 x ROUTER x
VPCS is free software, distributed under the terms of the "BSD" licence.
Source code and license can be found at vpcs.sf.net.
For more information, please visit wiki.freecode.com.cn.
Modified version for EVE-NG.

Press '?' to get help.

Executing the startup file

VPC4>
VPC4> ip 40.0.0.10/8 40.0.0.1
Checking for duplicate address...
VPC4 : 40.0.0.10 255.0.0.0 gateway 40.0.0.1

VPC4> ping 30.0.0.10

host (40.0.0.1) not reachable

VPC4> ping 30.0.0.10

84 bytes from 30.0.0.10 icmp_seq=1 ttl=63 time=3.030 ms
84 bytes from 30.0.0.10 icmp_seq=2 ttl=63 time=2.909 ms
84 bytes from 30.0.0.10 icmp_seq=3 ttl=63 time=2.606 ms
84 bytes from 30.0.0.10 icmp_seq=4 ttl=63 time=2.250 ms
84 bytes from 30.0.0.10 icmp_seq=5 ttl=63 time=2.133 ms

VPC4> █
```

terminal

VPC1 x VPC2 x L2-SW-1 x CORE x L2-SW-2 x VPC3 x VPC4 x ROUTER x

ROUTER(config-if)#ex

ROUTER(config)#ip route 0.0.0.0 0.0.0.0 1.0.0.1

ROUTER(config)#ex

% Ambiguous command: "ex"

ROUTER(config)#do sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP

D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2

ia - IS-IS inter area, * - candidate default, U - per-user static route

o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP

a - application route

+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is 1.0.0.1 to network 0.0.0.0

S* 0.0.0.0/0 [1/0] via 1.0.0.1

1.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 1.0.0.0/8 is directly connected, Ethernet0/1

L 1.0.0.2/32 is directly connected, Ethernet0/1

S 10.0.0.0/8 [1/0] via 1.0.0.1

S 20.0.0.0/8 [1/0] via 1.0.0.1

30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 30.0.0.0/8 is directly connected, Ethernet0/0.1

L 30.0.0.1/32 is directly connected, Ethernet0/0.1

40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

--More--