

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

```
R3#wr
Building configuration...
[OK]
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#ip dhcp pool production
R3(dhcp-config)#network 212.25.0.0 255.255.255.0
R3(dhcp-config)#default-route 212.25.0.1
R3(dhcp-config)#dns-server 8.8.8.8
R3(dhcp-config)#lease 1 2 3
R3(dhcp-config)#ip dhcp excluded 212.25.0.1 212.25.0.100
R3(config)#exit
R3#
*Sep 11 05:30:42.718: %SYS-5-CONFIG_I: Configured from console by console
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#ip dhcp pool mgmt
R3(dhcp-config)#network 129.23.0.0 255.255.0.0
R3(dhcp-config)#default-rou
R3(dhcp-config)#default-route 129.23.0.1
R3(dhcp-config)#dns-server 8.8.8.8
R3(dhcp-config)#lease 1 2 3
R3(dhcp-config)#ex
R3(config)#ip dhcp excluded 129.23.0.1 129.23.0.100
R3(config)#exit
R3#
*Sep 11 05:32:46.439: %SYS-5-CONFIG_I: Configured from console by console
R3#wr
Building configuration...
[OK]
R3#
```

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

```
R2(config-if)#ex
R2(config)#int e0/2
R2(config-if)#ip add 222.215.0.1 255.255.255.0
R2(config-if)#no sh
R2(config-if)#ex
R2(config)#int e0/0
R2(config-if)#no ip add 172.50.0.2 255.0.0.0
R2(config-if)#ip add 172.50.0.2 255.255.0.0
R2(config-if)#no sh
R2(config-if)#ex
R2(config)#int e0/3
R2(config-if)#ip add 62.0.0.1 255.0.0.0
R2(config-if)#no sh
R2(config-if)#ex
R2(config)#ip route 29.0.0.1 255.0.0.0
+Sep 11 05:15:21.400: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R2(config)#ip route 29.0.0.0 255.0.0.0 12.0.0.1
%Invalid next hop address (it's this router)
R2(config)#ip route 29.0.0.0 255.0.0.0 12.0.0.2
R2(config)#ip route 1.0.0.0 255.0.0.0 172.50.0.1
R2(config)#ip ro
R2(config)#ip route 212.25.0.0 255.255.255.0 62.0.0.2
R2(config)#ip route 129.23.0.0 255.255.0.0 222.215.0.2
R2(config)#exit
R2#
+Sep 11 05:17:33.595: %SYS-5-CONFIG_I: Configured from console by console
R2#wr
Building configuration...
[OK]
R2#
```

```
Terminal
R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *
R1#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#int e0/1
R1(config-if)#ip add 1.0.0.1 255.0.0.0
R1(config-if)#no sh
R1(config-if)#ex
R1(config)#int e0/0
R1(config-if)#ip add 172.50.0.1 255.255.0.0
R1(config-if)#no sh
R1(config-if)#ex
R1(config)#ip rou
R1(config)#ip route 0.0.0.0 0.0.0.0 172.50.0.2
R1(config)#exit
R1#w
*Sep 11 05:19:06.044: %SYS-5-CONFIG_I: Configured from console by console
R1#wr
Building configuration...
[OK]
R1#
*Sep 11 05:22:41.039: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R1#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#int e0/1
R1(config-if)#ip helper-add
R1(config-if)#ip helper-address 12.0.0.2
R1(config-if)#ex
R1(config)#exit
R1#
*Sep 11 05:34:09.728: %SYS-5-CONFIG_I: Configured from console by console
R1#
```

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

```
R5(config-if)#no sh
R5(config-if)#ex
R5(config)#int e0/1
R5(config-if)#ip add 212.25.0.1 255.255.255.0
R5(config-if)#no sh
R5(config-if)#ex
R5(config)#ip rout
R5(config)#ip route 0.0.0.0 0.0.0.0 62.0.0.1
R5(config)#exit
R5#w
*Sep 11 05:20:56.319: %SYS-5-CONFIG_I: Configured from console by console
R5#wr
Building configuration...
[OK]
R5#
*Sep 11 05:22:20.706: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R5#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R5(config)#int e0/1
R5(config-if)#ip he
R5(config-if)#ip helper-
R5(config-if)#ip helper-address 12.0.0.2
R5(config-if)#ex
R5(config)#exit
R5#
*Sep 11 05:35:50.746: %SYS-5-CONFIG_I: Configured from console by console
R5#wr
Building configuration...
[OK]
R5#
```

```
Terminal
R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *
R4(config)#int e0/0
R4(config-if)#ip add 222.215.0.2 255.255.255.0
R4(config-if)#no sh
R4(config-if)#ex
R4(config)#int e0/1
R4(config-if)#ip add 129.23.0.1 255.255.0.0
R4(config-if)#no sh
R4(config-if)#ex
R4(config)#ip ro
R4(config)#ip route 0.0.0.0 0.0.0.0 222.215.0.1
R4(config)#exit
R4#
*Sep 11 05:22:57.832: %SYS-5-CONFIG_I: Configured from console by console
R4#wr
Building configuration...
[OK]
R4#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R4(config)#int e0/1
R4(config-if)#ip h
R4(config-if)#ip help-
R4(config-if)#ip helper-
R4(config-if)#ip helper-address 12.0.0.2
R4(config-if)#ex
R4(config)#exit
R4#e
*Sep 11 05:36:37.035: %SYS-5-CONFIG_I: Configured from console by console
R4#wr
Building configuration...
[OK]
R4#
```


Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

```
C:\WINDOWS\system32\cmd.exe
(C) Copyright 1985-2001 Microsoft Corp.
C:\Documents and Settings\user>ncpa.cpl
C:\Documents and Settings\user>ipconfig
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 1.0.0.101
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 1.0.0.1

C:\Documents and Settings\user>ping 212.25.0.1
Pinging 212.25.0.1 with 32 bytes of data:
Reply from 212.25.0.1: bytes=32 time=2ms TTL=253
Reply from 212.25.0.1: bytes=32 time=1ms TTL=253
Reply from 212.25.0.1: bytes=32 time=1ms TTL=253
Reply from 212.25.0.1: bytes=32 time=1ms TTL=253

Ping statistics for 212.25.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms
C:\Documents and Settings\user>_
```

Local Area Connection
LAN or High-Speed Internet



Start | C:\WINDOWS\system32\cmd.exe | Network Connections | 5:10 AM

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection:

```
Connection-specific DNS Suffix . : 
IP Address . . . . . : 129.23.0.101
Subnet Mask . . . . . : 255.255.0.0
Default Gateway . . . . . : 129.23.0.1
```

C:\Documents and Settings\user>ping 29.0.0.1

Pinging 29.0.0.1 with 32 bytes of data:

```
Reply from 29.0.0.1: bytes=32 time=1ms TTL=253
Reply from 29.0.0.1: bytes=32 time=1ms TTL=253
Reply from 29.0.0.1: bytes=32 time=2ms TTL=253
Reply from 29.0.0.1: bytes=32 time=2ms TTL=253
```

Ping statistics for 29.0.0.1:

```
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 2ms, Average = 1ms
```

C:\Documents and Settings\user>

C:\RO
ASDM-1...

Old Java ASDM



PuTTY



ifpd32

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 212.25.0.101
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 212.25.0.1

C:\Documents and Settings\user>ping 129.23.0.1

Pinging 129.23.0.1 with 32 bytes of data:

Reply from 129.23.0.1: bytes=32 time=4ms TTL=253
Reply from 129.23.0.1: bytes=32 time=1ms TTL=253
Reply from 129.23.0.1: bytes=32 time=2ms TTL=253
Reply from 129.23.0.1: bytes=32 time=1ms TTL=253

Ping statistics for 129.23.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 4ms, Average = 2ms

C:\Documents and Settings\user>_
```

1hpdc

Start C:\WINDOWS\system...

6:03 AM

Terminal

R3 * R2 * R1 * R5 * R4 * Win-1 * Win-3 * Win-4 * Win-2 *

