

Emotional Analysis using Hugging Face Ecosystem

Set Environment

In this notebook, we have to install following additional libraries (compared to previous notebooks) from Huggingface to enhance our workflow: **transformers**, **datasets**, **evaluate**, and **accelearte**. In addition, we are also installing **wandb**.

- The transformers library provides **Trainer** class that we will use to manage Training process.
- The **datasets** library simplifies the process of accessing and manipulating a wide array of datasets.
- The **evaluate** library offers a suite of standardized metrics and methods for robust and consistent model evaluation.
- We will not use **accelerate** library directly. However , we need to install it as transformer librray usses it in the background.
- Finally **wandb** library provide tools for efficient experiment tracking.

```

In [1]: import sys
# If in Colab, then import the drive module from google.colab
if 'google.colab' in str(get_ipython()):
    from google.colab import drive
    # Mount the Google Drive to access files stored there
    drive.mount('/content/drive')

    # !pip install torchtext -qq
    # # Install the torchinfo library quietly
    !pip install torchinfo -qq
    # # !pip install torchtext --upgrade -qq
    !pip install torchmetrics -qq
    # !pip install torchinfo -qq
    !pip install fast_ml -qq
    !pip install joblib -qq
    # !pip install sklearn -qq
    # !pip install pandas -qq
    # !pip install numpy -qq
    !pip install scikit-multilearn -qq
    !pip install transformers evaluate wandb accelerate -U -qq
    !pip install pytorch-ignite -qq -U

    basepath = '/content/drive/MyDrive/Colab_Notebooks/BUAN_6342_Applied
_Natural_Language_Processing'
    sys.path.append('/content/drive/MyDrive/Colab_Notebooks/BUAN_6342_Ap
plied_Natural_Language_Processing/0_Custom_files')
else:
    basepath = '/Users/harikrishnadev/Library/CloudStorage/GoogleDrive-h
arikrish0607@gmail.com/My Drive/Colab_Notebooks/BUAN_6342_Applied_Natu
ral_Language_Processing/'
    sys.path.append('/Users/harikrishnadev/Library/CloudStorage/GoogleDr
ive-harikrish0607@gmail.com/My Drive/Colab_Notebooks/BUAN_6342_Applied
_Natural_Language_Processing/0_Custom_files')

```

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).

```

In [2]: # Importing PyTorch library for tensor computations and neural network
modules
import torch
import torch.nn as nn

# For working with textual data vocabularies and for displaying model
summaries
from torchtext.vocab import vocab

# General-purpose Python libraries for random number generation and nu
merical operations
import random
import numpy as np

# Utilities for efficient serialization/deserialization of Python obje
cts and for element tallying
import joblib
from collections import Counter

# For creating lightweight attribute classes and for partial function
application
from functools import partial

# For filesystem path handling, generating and displaying confusion ma
trices, and date-time manipulations
from pathlib import Path
from sklearn.metrics import confusion_matrix
from datetime import datetime

# For plotting and visualization
import matplotlib.pyplot as plt
import seaborn as sns
# %matplotlib inline

### NEW #####
# imports from Huggingface ecosystem
from transformers.modeling_outputs import SequenceClassifierOutput
from transformers import PreTrainedModel, PretrainedConfig
from transformers import TrainingArguments, Trainer
from datasets import Dataset, load_dataset
import evaluate

# wandb library
import wandb

import os

```

Specify Project Folders

```
In [3]: # base_folder = Path(basepath)
# data_folder = base_folder/'datasets/aclImdb'
# model_folder = base_folder/'models/nlp_spring_2024/imdb/nn'
# custom_functions = base_folder/'custom-functions'

# Set the base folder path using the Path class for better path handling
base_folder = Path(basepath)

# Define the data folder path by appending the relative path to the base folder
# This is where the data files will be stored
data_folder = base_folder / '0_Data_Folder'

# Define the model folder path for saving trained models
# This path points to a specific folder designated for NLP models related to the IMDB dataset
model_folder = data_folder

custom_functions = base_folder / '0_Custom_files'
```

```
In [4]: model_folder.mkdir(exist_ok=True, parents = True)
```

```
In [5]: model_folder
```

```
Out[5]: PosixPath('/content/drive/MyDrive/Colab_Notebooks/BUAN_6342_Applied_Natural_Language_Processing/0_Data_Folder')
```

Loading data

```
In [6]: if 'google.colab' in str(get_ipython()):
!chmod 600 /content/drive/MyDrive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle/kaggle.json
!ls -la /content/drive/MyDrive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle
else:
!chmod 600 '/Users/harikrishnadev/Library/CloudStorage/GoogleDrive-harikrish0607@gmail.com/My Drive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle/kaggle.json'
!ls -la '/Users/harikrishnadev/Library/CloudStorage/GoogleDrive-harikrish0607@gmail.com/My Drive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle'
```

```
total 1
-rw----- 1 root root 70 Nov 27 02:27 kaggle.json
```

```
In [7]: if 'google.colab' in str(get_ipython()):
        os.environ['KAGGLE_CONFIG_DIR']='/content/drive/MyDrive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle'
    else:
        os.environ['KAGGLE_CONFIG_DIR']='/Users/harikrishnadev/Library/CloudStorage/GoogleDrive-harikrish0607@gmail.com/My Drive/Colab_Notebooks/BUAN_6382_Applied_DeepLearning/Data/.kaggle'
```

```
In [8]: ! kaggle competitions download -c emotion-detection-spring2014

Downloading emotion-detection-spring2014.zip to /content
 0% 0.00/609k [00:00<?, ?B/s]
100% 609k/609k [00:00<00:00, 36.4MB/s]
```

```
In [9]: ! unzip emotion-detection-spring2014.zip

Archive:  emotion-detection-spring2014.zip
  inflating: sample_submission.csv
  inflating: test.csv
  inflating: train.csv
```

```
In [10]: import pandas as pd
train_dataset = pd.read_csv('train.csv', usecols=lambda column: column != 'ID')
```

```
In [11]: type(train_dataset)
```

```
Out[11]: pandas.core.frame.DataFrame
def __init__(data=None, index: Axes | None=None, columns: Axes | None=None, dtype: Dtype | None=None, copy: bool | None=None) -> None
Two-dimensional, size-mutable, potentially heterogeneous tabular data.

Data structure also contains labeled axes (rows and columns).
Arithmetic operations align on both row and column labels. Can be
thought of as a dict-like container for Series objects. The primary
```

```
In [12]: train_dataset.columns
```

```
Out[12]: Index(['Tweet', 'anger', 'anticipation', 'disgust', 'fear', 'joy', 'love',
               'optimism', 'pessimism', 'sadness', 'surprise', 'trust'],
              dtype='object')
```

```
In [13]: label_columns = ['anger', 'anticipation', 'disgust', 'fear', 'joy', 'love', 'optimism', 'pessimism', 'sadness', 'surprise', 'trust']
```

```
In [14]: len(label_columns)
```

```
Out[14]: 11
```

```
In [15]: trainset = Dataset.from_dict({
        'texts': train_dataset['Tweet'],
        'labels': train_dataset[label_columns].values.tolist(), # Exclude
        'Tweet' column
    })
```

```
In [16]: trainset.features
```

```
Out[16]: {'texts': Value(dtype='string', id=None),
        'labels': Sequence(feature=Value(dtype='int64', id=None), length=-1,
        id=None)}
```

```
In [17]: trainset.features['labels']
```

```
Out[17]: Sequence(feature=Value(dtype='int64', id=None), length=-1, id=None)
```

```
In [18]: trainset[1]
```

```
Out[18]: {'texts': 'Whatever you decide to do make sure it makes you #happy.',
        'labels': [0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0]}
```

```
In [19]: import pandas as pd
        pd.DataFrame(train_dataset['Tweet']).head()
```

```
Out[19]:
```

	Tweet
0	"Worry is a down payment on a problem you may ...
1	Whatever you decide to do make sure it makes y...
2	@Max_Kellerman it also helps that the majorit...
3	Accept the challenges so that you can literall...
4	My roommate: it's okay that we can't spell bec...

Create Custom Model and Model Config Class

```
In [20]: class CustomConfig(PretrainedConfig):
        def __init__(self, vocab_size=0, embedding_dim=256, hidden_dim1=51
        2, hidden_dim2=256, num_labels=11, **kwargs):
            super().__init__()
            self.vocab_size = vocab_size
            self.embedding_dim = embedding_dim
            self.hidden_dim1 = hidden_dim1
            self.hidden_dim2 = hidden_dim2
            self.num_labels = num_labels
```

```
In [21]: class CustomLSTM(PreTrainedModel):
          config_class = CustomConfig

          def __init__(self, config):
              super().__init__(config)

              self.embedding_bag = nn.EmbeddingBag(config.vocab_size, config.embedding_dim)
              self.lstm = nn.LSTM(config.embedding_dim, config.hidden_dim1, batch_first=True)
              self.layers = nn.Sequential(
                  nn.Linear(config.hidden_dim1, config.hidden_dim2),
                  nn.BatchNorm1d(num_features=config.hidden_dim2),
                  nn.ReLU(),
                  nn.Dropout(p=0.5),
                  nn.Linear(config.hidden_dim2, config.num_labels) # 11 out
              )

          def forward(self, input_ids, offsets, labels=None):
              embed_out = self.embedding_bag(input_ids, offsets)
              # print('embed shape', embed_out.shape)
              lstm_out, _ = self.lstm(embed_out.unsqueeze(0))
              lstm_out = lstm_out.squeeze(0)
              logits = self.layers(lstm_out)
              # print('logit shape', logits.shape)
              # print('labels', labels.shape)
              # print('labels', type(labels))

              loss = None
              if labels is not None:
                  loss_fct = nn.BCEWithLogitsLoss()
                  loss = loss_fct(logits, labels)

              return SequenceClassifierOutput(
                  loss=loss,
                  logits=logits
              )
```

Train Model

Collate Function

```
In [22]: def get_vocab(dataset, min_freq=1):
          """
          Generate a vocabulary from a dataset.

          Args:
              dataset (Dataset): A Hugging Face Dataset object. The dataset
              should have a key 'texts' that contains the text data.
```

```

        min_freq (int): The minimum frequency for a token to be included in
                           the vocabulary.

    Returns:
        torchtext.vocab.Vocab: Vocabulary object containing tokens from the
                                dataset that meet or exceed the specified
                                minimum frequency. It also includes a special
                                '<unk>' token for unknown words.
    """
    # Initialize a counter object to hold token frequencies
    counter = Counter()

    # Update the counter with tokens from each text in the dataset
    # Iterating through texts in the dataset
    for text in dataset['Tweet']: ##### Change from previous function #####
        counter.update(str(text).split())

    # Create a vocabulary using the counter object
    # Tokens that appear fewer times than `min_freq` are excluded
    my_vocab = vocab(counter, min_freq=min_freq)

    # Insert a '<unk>' token at index 0 to represent unknown words
    my_vocab.insert_token('<unk>', 0)

    # Set the default index to 0
    # This ensures that any unknown word will be mapped to '<unk>'
    my_vocab.set_default_index(0)

    return my_vocab

```

```
In [23]: tweet_vocab = get_vocab(train_dataset, min_freq=2)
         tweet_vocab
```

```
Out[23]: Vocab()
```

```
In [24]: tweet_vocab['Accept']
```

```
Out[24]: 45
```

```
In [25]: # Creating a function that will be used to get the indices of words from vocab
         def tokenizer(text, vocab):
             """Converts text to a list of indices using a vocabulary dictionary"""
             return [vocab[token] for token in str(text).split()]

```


In [26]: `def collate_batch(batch, my_vocab):`

```
    """
    Prepares a batch of data by transforming texts into indices based
    on a vocabulary and
    converting labels into a tensor.

    Args:
        batch (list of dict): A batch of data where each element is a
            dictionary with keys
                'labels' and 'texts'. 'labels' are the s
            entiment labels, and
                'texts' are the corresponding texts.
        my_vocab (torchtext.vocab.Vocab): A vocabulary object that map
            s tokens to indices.

    Returns:
        dict: A dictionary with three keys:
            - 'input_ids': a tensor containing concatenated indices
            of the texts.
            - 'offsets': a tensor representing the starting index of
            each text in 'input_ids'.
            - 'labels': a tensor of the labels for each text in the
            batch.

    The function transforms each text into a list of indices based on
    the provided vocabulary.
    It also converts the labels into a tensor. The 'offsets' are compu
    ted to keep track of the
    start of each text within the 'input_ids' tensor, which is a flatt
    ened representation of all text indices.
    """

    # Get labels and texts from batch dict samples
    labels = [sample['labels'] for sample in batch]
    # print(labels)
    texts = [sample['texts'] for sample in batch]

    # Convert the list of labels into a tensor of dtype int32
    labels = torch.tensor(labels, dtype=torch.float32)
    # print(labels)
    # print(labels.shape)

    # Convert the list of texts into a list of lists; each inner list
    contains the vocabulary indices for a text
    list_of_list_of_indices = [tokenizer(text, my_vocab) for text in t
    exts]

    # Concatenate all text indices into a single tensor
    input_ids = torch.cat([torch.tensor(i, dtype=torch.int64) for i in
    list_of_list_of_indices])

    # Compute the offsets for each text in the concatenated tensor
    offsets = [0] + [len(i) for i in list_of_list_of_indices]
    offsets = torch.tensor(offsets[:-1]).cumsum(dim=0)

    return {
        'input_ids': input_ids,
```

```
        'offsets': offsets,  
        'labels': labels  
    }
```

```
In [27]: tweet_vocab = get_vocab(train_dataset, min_freq=2)  
collate_fn = partial(collate_batch, my_vocab=tweet_vocab)
```

Instantiate Model

We will now specify the model using (1) model config class - CustomConfig and (2) model class - CustomLSTM created earlier.

```
In [28]: my_config = CustomConfig(vocab_size=len(tweet_vocab))
```

```
In [29]: my_config
```

```
Out[29]: CustomConfig {  
  "embedding_dim": 256,  
  "hidden_dim1": 512,  
  "hidden_dim2": 256,  
  "id2label": {  
    "0": "LABEL_0",  
    "1": "LABEL_1",  
    "2": "LABEL_2",  
    "3": "LABEL_3",  
    "4": "LABEL_4",  
    "5": "LABEL_5",  
    "6": "LABEL_6",  
    "7": "LABEL_7",  
    "8": "LABEL_8",  
    "9": "LABEL_9",  
    "10": "LABEL_10"  
  },  
  "label2id": {  
    "LABEL_0": 0,  
    "LABEL_1": 1,  
    "LABEL_10": 10,  
    "LABEL_2": 2,  
    "LABEL_3": 3,  
    "LABEL_4": 4,  
    "LABEL_5": 5,  
    "LABEL_6": 6,  
    "LABEL_7": 7,  
    "LABEL_8": 8,  
    "LABEL_9": 9  
  },  
  "transformers_version": "4.39.3",  
  "vocab_size": 10344  
}
```

```
In [30]: my_config.id2label = {
        0: 'anger',
        1: 'anticipation',
        2: 'disgust',
        3: 'fear',
        4: 'joy',
        5: 'love',
        6: 'optimism',
        7: 'pessimism',
        8: 'sadness',
        9: 'surprise',
        10: 'trust'
    }
```

```
In [31]: # Generating id_to_label by reversing the key-value pairs in label_to_id
my_config.label2id = {v: k for k, v in my_config.id2label .items() }
```

```
In [32]: my_config
```

```
Out[32]: CustomConfig {
  "embedding_dim": 256,
  "hidden_dim1": 512,
  "hidden_dim2": 256,
  "id2label": {
    "0": "anger",
    "1": "anticipation",
    "2": "disgust",
    "3": "fear",
    "4": "joy",
    "5": "love",
    "6": "optimism",
    "7": "pessimism",
    "8": "sadness",
    "9": "surprise",
    "10": "trust"
  },
  "label2id": {
    "anger": 0,
    "anticipation": 1,
    "disgust": 2,
    "fear": 3,
    "joy": 4,
    "love": 5,
    "optimism": 6,
    "pessimism": 7,
    "sadness": 8,
    "surprise": 9,
    "trust": 10
  },
  "transformers_version": "4.39.3",
  "vocab_size": 10344
}
```

```
In [34]: model = CustomLSTM(config=my_config)
```

```
In [35]: model
```

```
Out[35]: CustomLSTM(  
  (embedding_bag): EmbeddingBag(10344, 256, mode='mean')  
  (lstm): LSTM(256, 512, batch_first=True)  
  (layers): Sequential(  
    (0): Linear(in_features=512, out_features=256, bias=True)  
    (1): BatchNorm1d(256, eps=1e-05, momentum=0.1, affine=True, track_  
running_stats=True)  
    (2): ReLU()  
    (3): Dropout(p=0.5, inplace=False)  
    (4): Linear(in_features=256, out_features=11, bias=True)  
  )  
)
```

Compute_metrics function

```
In [36]: from datasets import load_metric  
def compute_metrics(eval_pred):  
    combined_metrics = evaluate.combine([evaluate.load("accuracy"), eval  
uate.load("f1", average = "macro")])  
    logits, labels = eval_pred  
    predictions = (logits>0.5).astype(int).reshape(-1)  
    evaluations = combined_metrics.compute(predictions=predictions, refe  
rences=labels.astype(int).reshape(-1))  
    return evaluations
```

Training Arguments

```
In [37]: # Configure training parameters
training_args = TrainingArguments(

    # Training-specific configurations
    num_train_epochs=20,
    per_device_train_batch_size=128, # Number of samples per training
    batch
    per_device_eval_batch_size=128, # Number of samples per validation
    batch
    weight_decay=0.1, # weight decay (L2 regularization)
    learning_rate=0.001, # learning rate
    optim='adamw_torch', # optimizer
    remove_unused_columns=False, # flag to retain unused columns

    # Checkpoint saving and model evaluation settings
    output_dir=str(model_folder), # Directory to save model checkpoint
    ts
    evaluation_strategy='steps', # Evaluate model at specified step i
    ntervals
    eval_steps=50, # Perform evaluation every 50 training steps
    save_strategy="steps", # Save model checkpoint at specified step
    intervals
    save_steps=50, # Save a model checkpoint every 50 training steps
    load_best_model_at_end=True, # Reload the best model at the end o
    f training
    save_total_limit=2, # Retain only the best and the most recent mo
    del checkpoints
    # Use 'accuracy' as the metric to determine the best model
    metric_for_best_model="accuracy",
    greater_is_better=True, # A model is 'better' if its accuracy is
    higher

    # Experiment logging configurations
    logging_strategy='steps',
    logging_steps=50,
    report_to='wandb', # Log metrics and results to Weights & Biases
    platform
    run_name='tweet_hf_trainer', # Experiment name for Weights & Bias
    es
)
```

Initialize Trainer

```
In [64]: trainset[0]
```

```
Out[64]: {'texts': "'Worry is a down payment on a problem you may never have'.  
\\xa0Joyce Meyer. #motivation #leadership #worry",  
'labels': [0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1]}
```

```
In [39]: # Split train dataset into train and validation sets
# train_size = int(0.8 * len(train_dataset))
# valid_size = len(train_dataset) - train_size
train_set = trainset.train_test_split(test_size=0.2)
```

```
In [63]: train_set
```

```
Out[63]: DatasetDict({
  train: Dataset({
    features: ['texts', 'labels'],
    num_rows: 6179
  })
  test: Dataset({
    features: ['texts', 'labels'],
    num_rows: 1545
  })
})
```

```
In [41]: [sample['labels'] for sample in train_set['train']][:5]
```

```
Out[41]: [[0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 1, 1, 1, 0, 0, 1, 0],
 [0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0],
 [1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0]]
```

```
In [42]: [sample['texts'] for sample in train_set['train']][:5]
```

```
Out[42]: ['petrify me in the fossil type of way',
 'I WANNA GET UP AND DANCE!!!! (but everyone is in bed) this sucks! Ev
 everyone wake up!! 🤔 #hyper #happy #letsdance #dirtydancinginthemoonlig
 ht👉',
 '@PatBlanchfield so you mean "like Uber but for despair for someone o
 ther than the driver"',
 '@ImJim_YoureNot cyber bully',
 '@DailyMailCeleb @KTHopkins Katie I love how you describe yourself as
 'normal'. Really you're anything but! #neverchange"]
```

```
In [43]: label_mt = train_set['train']['labels']
# label_mt
```

```
In [44]: type(label_mt)
```

```
Out[44]: list
```

```
In [45]: trainer = Trainer(
    model=model,
    args=training_args,
    train_dataset=train_set['train'],
    eval_dataset = train_set['test'],
    data_collator=collate_fn,
    compute_metrics=compute_metrics,
)
```

```
/usr/local/lib/python3.10/dist-packages/accelerate/accelerator.py:436:
FutureWarning: Passing the following arguments to `Accelerator` is dep
recated and will be removed in version 1.0 of Accelerate: dict_keys
(['dispatch_batches', 'split_batches', 'even_batches', 'use_seedable_s
ampler']). Please pass an `accelerate.DataLoaderConfiguration` instea
d:
dataloader_config = DataLoaderConfiguration(dispatch_batches=None, spl
it_batches=False, even_batches=True, use_seedable_sampler=True)
warnings.warn(
```

Setup WandB

```
In [46]: if 'google.colab' in str(get_ipython()):
    from google.colab import userdata
    wandb.login(key=userdata.get('wandb'))
else:
    !wandb login
```

wandb: W&B API key is configured. Use `wandb login --relogin` to force relogin

wandb: **WARNING** If you're specifying your api key in code, ensure this code is not shared publicly.

wandb: **WARNING** Consider setting the WANDB_API_KEY environment variable, or running `wandb login` from the command line.

wandb: Appending key for api.wandb.ai to your netrc file: /root/.netrc

```
In [47]: # specify the project name where the experiment will be logged
%env WANDB_PROJECT = nlp_course_spring_2024-emotion-analysis-hf-traine
r-lstm
```

env: WANDB_PROJECT=nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm

Training and Validation

```
In [48]: trainer.train()
```


Changes to your `wandb` environment variables will be ignored because your `wandb` session has already started. For more information on how to modify your settings with `wandb.init()` arguments, please refer to [the W&B docs \(https://wandb.me/wandb-init\)](https://wandb.me/wandb-init).

wandb: Currently logged in as: **harikrish0607 (harikrishnad)**. Use **`wandb login --relogin`** to force relogin

Tracking run with wandb version 0.16.6

Run data is saved locally in `/content/wandb/run-20240405_231255-z5y5es7b`

Syncing run **tweet hf trainer** (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm/runs/z5y5es7b) to [Weights & Biases](https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm) (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm) (docs (<https://wandb.me/run>))

View project at https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm)

View run at https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm/runs/z5y5es7b (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm/runs/z5y5es7b)

Step	Training Loss	Validation Loss	Accuracy	F1
50	0.519900	0.492763	0.784819	0.007598
100	0.456100	0.460963	0.788879	0.083759
150	0.425300	0.446586	0.798235	0.195637
200	0.397300	0.434848	0.804648	0.267108
250	0.369600	0.429968	0.811297	0.324415
300	0.346300	0.437914	0.815063	0.387926
350	0.328700	0.435834	0.818241	0.403783
400	0.310600	0.437066	0.820124	0.427421
450	0.291400	0.443022	0.819006	0.452084
500	0.280600	0.448930	0.822830	0.454034
550	0.266700	0.446900	0.823831	0.467639
600	0.259400	0.465008	0.822713	0.466631
650	0.246000	0.458587	0.825007	0.476408
700	0.241200	0.462138	0.823360	0.479542
750	0.232900	0.472338	0.823183	0.481628
800	0.224600	0.474630	0.824007	0.481539
850	0.215800	0.475016	0.823595	0.484703
900	0.215800	0.481325	0.823654	0.488305
950	0.212600	0.480865	0.823477	0.486301

Removed shared tensor {'lstm.bias_ih_l0', 'lstm.bias_hh_l0', 'lstm.weight_hh_l0'} while saving. This should be OK, but check by verifying that you don't receive any warning while reloading
There were missing keys in the checkpoint model loaded: ['lstm.weight_hh_l0', 'lstm.bias_ih_l0', 'lstm.bias_hh_l0'].

Out[48]: TrainOutput(global_step=980, training_loss=0.3044367989715265, metrics={'train_runtime': 142.9704, 'train_samples_per_second': 864.374, 'train_steps_per_second': 6.855, 'total_flos': 51918688180800.0, 'train_loss': 0.3044367989715265, 'epoch': 20.0})

```
In [49]: trainer.evaluate()
```

[13/13 00:03]

```
Out[49]: {'eval_loss': 0.45691511034965515,
          'eval_accuracy': 0.8245954692556634,
          'eval_f1': 0.4736005650715169,
          'eval_runtime': 6.4902,
          'eval_samples_per_second': 238.051,
          'eval_steps_per_second': 2.003,
          'epoch': 20.0}
```

```
In [50]: test_dataset = pd.read_csv('test.csv', usecols=lambda column: column != 'ID')
```

```
In [67]: testset = Dataset.from_dict({
          'texts': test_dataset['Tweet'].to_list(),
          'labels': [[0] * 11] * len(test_dataset), # Exclude 'Tweet' column
        })
```

```
In [68]: testset[0]
```

```
Out[68]: {'texts': '@Adnan__786__ @AsYouNotWish Dont worry Indian army is on its ways to dispatch all Terrorists to Hell',
          'labels': [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]}
```

```
In [69]: valid_output = trainer.predict(testset)
```

```
In [70]: valid_output._fields
```

```
Out[70]: ('predictions', 'label_ids', 'metrics')
```

```
In [71]: valid_preds = np.argmax(valid_output.predictions, axis=-1)
          valid_labels = np.array(valid_output.label_ids)
```


Get best checkpoint

```
In [75]: # After training, let us check the best checkpoint
          # We need this for Inference
          best_model_checkpoint_step = trainer.state.best_model_checkpoint.split(
            '-')[0]
          print(f"The best model was saved at step {best_model_checkpoint_step}.")
```

The best model was saved at step 650.

```
In [76]: wandb.finish()
```

Run history:



Run summary:

eval/accuracy	0.8246
eval/f1	0.4736
eval/loss	0.45692
eval/runtime	6.4902
eval/samples_per_second	238.051
eval/steps_per_second	2.003
total_flos	51918688180800.0
train/epoch	20.0
train/global_step	980
train/grad_norm	0.22986
train/learning_rate	3e-05
train/loss	0.2126
train_loss	0.30444
train_runtime	142.9704
train_samples_per_second	864.374
train_steps_per_second	6.855

View run **tweet_hf_trainer** at: https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm/runs/z5y5es7b (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm/runs/z5y5es7b)

View project at: https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm (https://wandb.ai/harikrishnad/nlp_course_spring_2024-emotion-analysis-hf-trainer-lstm)

Synced 5 W&B file(s), 0 media file(s), 0 artifact file(s) and 0 other file(s)

Find logs at: `./wandb/run-20240405_231255-z5y5es7b/logs`

Performance on Test Set

```
In [77]: # Define the path to the best model checkpoint
# 'model_checkpoint' variable is constructed using the model folder path and the checkpoint step
# This step is identified as having the best model performance during training
model_checkpoint = model_folder/f'checkpoint-{best_model_checkpoint_step}'
```

```
In [78]: # Instantiate the CustomMLP model with predefined configurations
# 'my_config' is an instance of the CustomConfig class, containing specific model settings like
# vocabulary size, embedding dimensions, etc.
model = CustomLSTM(my_config)
```

```
In [79]: model
```

```
Out[79]: CustomLSTM(
  (embedding_bag): EmbeddingBag(10344, 256, mode='mean')
  (lstm): LSTM(256, 512, batch_first=True)
  (layers): Sequential(
    (0): Linear(in_features=512, out_features=256, bias=True)
    (1): BatchNorm1d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (2): ReLU()
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=256, out_features=11, bias=True)
  )
)
```

```
In [80]: # Load the pre-trained weights into the CustomMLP model from the speci
         # fied checkpoint
         # 'model_checkpoint' refers to the path where the model's best-perform
         # ing state is saved
         # This step ensures the model is initialized with weights from its mos
         # t effective training state
         model = model.from_pretrained(model_checkpoint, config = my_config)
```

Some weights of CustomLSTM were not initialized from the model checkpoint at /content/drive/MyDrive/Colab_Notebooks/BUAN_6342_Applied_Natural_Language_Processing/0_Data_Folder/checkpoint-650 and are newly initialized: ['lstm.bias_hh_l0', 'lstm.bias_ih_l0', 'lstm.weight_hh_l0'] You should probably TRAIN this model on a down-stream task to be able to use it for predictions and inference.

```
In [81]: model
```

```
Out[81]: CustomLSTM(
  (embedding_bag): EmbeddingBag(10344, 256, mode='mean')
  (lstm): LSTM(256, 512, batch_first=True)
  (layers): Sequential(
    (0): Linear(in_features=512, out_features=256, bias=True)
    (1): BatchNorm1d(256, eps=1e-05, momentum=0.1, affine=True, track_
running_stats=True)
    (2): ReLU()
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=256, out_features=11, bias=True)
  )
)
```

```
In [82]: # Create a partial function 'collate_fn' using 'collate_batch' with 'm
         # y_vocab' set to 'imdb_vocab'
         # This function will be used by the Trainer to process batches of data
         # during evaluation
         collate_fn = partial(collate_batch, my_vocab=tweet_vocab)

         # Configure training arguments for model evaluation
         # 'output_dir' specifies where to save the results
         # 'per_device_eval_batch_size' sets the batch size for evaluation, adj
         # usted based on available GPU memory
         # 'do_train = False' and 'do_eval=True' indicate that training is not
         # performed, but evaluation is
         # 'remove_unused_columns=False' ensures that all columns in the datase
         # t are retained during evaluation
         # 'report_to=[]' disables logging to external services like Weights &
         # Biases

         training_args = TrainingArguments(
             output_dir="./results",
             per_device_eval_batch_size=16,
             do_train=False,
             do_eval=True,
             remove_unused_columns=False,
             report_to=[]
         )
```

```
In [83]: # Initialize the Trainer with the specified model and training arguments
# 'model' is the CustomMLP model loaded with pre-trained weights
# 'training_args' contains the configurations for evaluation, including batch sizes and output directory
# 'eval_dataset' is set to 'testset', which is the dataset used for evaluating the model
# 'data_collator' is assigned 'collate_fn', the function for processing batches of data
# 'compute_metrics' is a function that calculates evaluation metrics like accuracy and F1 score

trainer = Trainer(
    model=model,
    args=training_args,
    eval_dataset=testset,
    data_collator=collate_fn,
    compute_metrics=compute_metrics,
)
```

```
/usr/local/lib/python3.10/dist-packages/accelerate/accelerator.py:436:
FutureWarning: Passing the following arguments to `Accelerator` is deprecated and will be removed in version 1.0 of Accelerate: dict_keys(['dispatch_batches', 'split_batches', 'even_batches', 'use_seedable_sampler']). Please pass an `accelerate.DataLoaderConfiguration` instead:
dataloader_config = DataLoaderConfiguration(dispatch_batches=None, split_batches=False, even_batches=True, use_seedable_sampler=True)
warnings.warn(
```

```
In [84]: trainer.evaluate()
```

[204/204 00:58]

```
Out[84]: {'eval_loss': 1.4013041257858276,
          'eval_accuracy': 0.8668582108287539,
          'eval_f1': 0.0,
          'eval_runtime': 60.4449,
          'eval_samples_per_second': 53.917,
          'eval_steps_per_second': 3.375}
```

```
In [85]: test_predictions = trainer.predict(testset)
```

```
In [86]: test_predictions._fields
```

```
Out[86]: ('predictions', 'label_ids', 'metrics')
```



```
In [87]: test_predictions.metrics
```

```
Out[87]: {'test_loss': 1.4013041257858276,  
          'test_accuracy': 0.8668582108287539,  
          'test_f1': 0.0,  
          'test_runtime': 63.6613,  
          'test_samples_per_second': 51.193,  
          'test_steps_per_second': 3.204}
```

```
In [92]: test_predictions.label_ids
```

```
Out[92]: array([[0., 0., 0., ..., 0., 0., 0.],  
               [0., 0., 0., ..., 0., 0., 0.],  
               [0., 0., 0., ..., 0., 0., 0.],  
               ...,  
               [0., 0., 0., ..., 0., 0., 0.],  
               [0., 0., 0., ..., 0., 0., 0.],  
               [0., 0., 0., ..., 0., 0., 0.]], dtype=float32)
```

```
In [91]: test_preds = np.argmax(test_predictions.predictions, axis=1)  
test_labels = np.array(test_predictions.label_ids)
```

Model Inference

Model inference is the stage in the machine learning process where a trained model is used to make predictions on new, unseen data. Unlike the training or evaluation phases, labels are not required at this stage, as the primary goal is to apply the model's learned patterns and knowledge to generate predictions.

```
In [93]: testset
```

```
Out[93]: Dataset({  
          features: ['texts', 'labels'],  
          num_rows: 3259  
        })
```

```
In [94]: sample_X = testset['texts']
```

Step 1. Preprocessing

```
In [95]: device = 'cpu'
# Convert the list of texts into a list of lists; each inner list contains the vocabulary indices for a text
list_of_list_of_indices = [tokenizer(text, tweet_vocab) for text in sample_X]

# Compute the offsets for each text in the concatenated tensor
offsets = [0] + [len(i) for i in list_of_list_of_indices]
offsets = torch.tensor(offsets[:-1]).cumsum(dim=0)

# Concatenate all text indices into a single tensor
indices = torch.cat([torch.tensor(i, dtype=torch.int64) for i in list_of_list_of_indices])
```

Step 2: Get Predictions

```
In [96]: # move model to appropriate device
model.to(device)

# put model in evaluation mode
model.eval()

# get outputs (logits) from model
outputs = model(indices, offsets)
outputs
```

```
Out[96]: SequenceClassifierOutput(loss=None, logits=tensor([[ -0.1290, -12.7504, -10.1923, ..., -33.7357, -22.6788, -27.0854],
[ 2.9891, -19.6176, -9.1088, ..., -37.8043, -30.5580, -36.7081],
[ 1.8495, -20.7513, -12.8665, ..., -43.2483, -32.6759, -38.2814],
...,
[ -2.6846, -24.7797, -18.1971, ..., -45.8147, -39.0044, -44.8310],
[ -3.8930, -25.0800, -18.7555, ..., -43.6822, -37.4418, -42.2962],
[ -2.5615, -25.2132, -17.8407, ..., -45.1339, -37.5399, -44.5249]]), grad_fn=<AddmmBackward0>), hidden_states=None, attentions=None)
```

```
In [97]: outputs.logits
```

```
Out[97]: tensor([[ -0.1290, -12.7504, -10.1923, ..., -33.7357, -22.6788, -27.0
854],
          [  2.9891, -19.6176,  -9.1088, ..., -37.8043, -30.5580, -36.7
081],
          [  1.8495, -20.7513, -12.8665, ..., -43.2483, -32.6759, -38.2
814],
          ...,
          [ -2.6846, -24.7797, -18.1971, ..., -45.8147, -39.0044, -44.8
310],
          [ -3.8930, -25.0800, -18.7555, ..., -43.6822, -37.4418, -42.2
962],
          [ -2.5615, -25.2132, -17.8407, ..., -45.1339, -37.5399, -44.5
249]],
          grad_fn=<AddmmBackward0>)
```

Step 3: Post Processing

```
In [106]: predictions = outputs.logits >= 0
           predictions = predictions.numpy()
           original_labels = {column for id, column in enumerate(label_columns)}
```

```
In [107]: original_labels
```

```
Out[107]: {'anger',
            'anticipation',
            'disgust',
            'fear',
            'joy',
            'love',
            'optimism',
            'pessimism',
            'sadness',
            'surprise',
            'trust'}
```

```
In [111]: predictions
```

```
Out[111]: array([[False, False, False, ..., False, False, False],
                  [ True, False, False, ..., False, False, False],
                  [ True, False, False, ..., False, False, False],
                  ...,
                  [False, False, False, ..., False, False, False],
                  [False, False, False, ..., False, False, False],
                  [False, False, False, ..., False, False, False]])
```

```
In [109]: mapped_labels = []
           for prediction_row in predictions:
               mapped_row = [label for label, pred in zip(original_labels, prediction_row) if pred]
               mapped_labels.append(mapped_row)
```

```
In [115]: mapped_labels[:5]
```

```
Out[115]: [['anger'],
            ['anticipation', 'anger'],
            ['anticipation', 'anger'],
            ['anticipation', 'anger'],
            ['anticipation', 'anger']]
```

```
In [113]: submission = pd.read_csv('/content/sample_submission.csv')
```

```
In [116]: submission.head()
```

Out [116]:

[illegible]

```
In [121]: submission.columns
```

```
Out[121]: Index(['ID', 'anger', 'anticipation', 'disgust', 'fear', 'joy', 'love',
                'optimism', 'pessimism', 'sadness', 'surprise', 'trust'],
                dtype='object')
```

```
In [118]: predictions_num = predictions.astype(int)
```

```
In [119]: predictions_num[:5]
```

```
Out[119]: array([[0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0],
                  [1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0],
                  [1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0],
                  [1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0],
                  [1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0]])
```

```
In [120]: pd.DataFrame(predictions_num, columns=label_columns)
```

Out[120]:

	anger	anticipation	disgust	fear	joy	love	optimism	pessimism	sadness	surprise	trust
0	0	0	0	0	1	0	0	0	0	0	0
1	1	0	0	0	1	0	0	0	0	0	0
2	1	0	0	0	1	0	0	0	0	0	0
3	1	0	0	0	1	0	0	0	0	0	0
4	1	0	0	0	1	0	0	0	0	0	0
...
3254	0	0	0	0	1	0	0	0	0	0	0
3255	0	0	0	0	1	0	0	0	0	0	0
3256	0	0	0	0	1	0	0	0	0	0	0
3257	0	0	0	0	1	0	0	0	0	0	0
3258	0	0	0	0	1	0	0	0	0	0	0

3259 rows × 11 columns

```
In [122]: submission[['anger', 'anticipation', 'disgust', 'fear', 'joy', 'love',  
                    'optimism', 'pessimism', 'sadness', 'surprise', 'trust']]  
          = predictions_num
```

```
In [123]: submission.head()
```

Out[123]:

	ID	anger	anticipation	disgust	fear	joy	love	optimism	pessimism	sadness	surprise
0	2018-01559	0	0	0	0	1	0	0	0	0	0
1	2018-03739	1	0	0	0	1	0	0	0	0	0
2	2018-00385	1	0	0	0	1	0	0	0	0	0
3	2018-03001	1	0	0	0	1	0	0	0	0	0
4	2018-01988	1	0	0	0	1	0	0	0	0	0

```
In [127]: submission.to_csv(model_folder/'lstm.csv', index = False)
```

```
In [128]: from kaggle import api
          comp = 'emotion-detection-spring2014'
          api.competition_submit(model_folder/'lstm.csv', 'lstm apr6', comp)
```

Warning: Looks like you're using an outdated API Version, please consider updating (server 1.6.7 / client 1.5.16)

100%|██████████| 105k/105k [00:00<00:00, 124kB/s]

Out[128]: Successfully submitted to Emotion Detection Spring2024