

GEOGUARD: PREDICTIVE LANDSLIDE EARLY WARNING SYSTEM

A Geotechnically-Coupled Multiphysics Modeling, Real-Time Kinematic Telemetry & Machine Learning Framework

Project Abstract & Technical Brief | MATLAB & Simulink Implementation | Verified Release v2.0

Core Domain: Engineering Geology	Physics Model: Bishop Slip + Infiltration	AI Model: Decision Tree (99.96% Acc.)	Test Status: 6/6 Automated Tests Passed
----------------------------------	---	---------------------------------------	---

EXECUTIVE ABSTRACT — Rainfall-induced shallow landslides and translational slope failures cause catastrophic loss of life and devastation to civil infrastructure in mountainous regions. Traditional landslide early warning systems (LEWS) rely almost exclusively on empirical rainfall intensity–duration (I–D) thresholds, which frequently generate false alarms and cannot account for site-specific antecedent moisture, transient pore-water pressure spikes, or progressive soil deformation. This project introduces **GeoGuard LEWS v2.0**, an authoritative, computationally-efficient, and physically-consistent landslide early warning platform developed in MATLAB and Simulink. The system couples 1D mass-conserving hydrological infiltration, limit equilibrium slope stability (Bishop's circular shear arc), progressive plastic shear kinematics, and a calibrated machine learning decision tree classifier. An automated forward-looking predictive engine projects slope stability 10 minutes ahead using low-pass filtered rate-of-change dynamics ($dFoS/dt$), deriving dynamic Time-to-Failure (TTF). A dual-threshold Schmitt Trigger state machine enforces alert hysteresis, eliminating chatter across Safe (0), Advisory (1), and Evacuate (2) warning tiers. Validated across 12,000 synthesized storm trajectories, GeoGuard achieves 100% mass conservation, robust duration scaling (discriminating 12-minute from 12-hour storms), and 99.96% holdout classification accuracy. A high-fidelity graphical command console provides real-time hillside cross-section deformation and multi-channel telemetry for civil protection decision-makers.

Keywords: Landslide Early Warning Systems (LEWS), Geotechnical Slope Stability, Factor of Safety (FoS), Infiltration Hydrology, Pore-Water Pressure, Tertiary Creep, Decision Tree Classification, Simulink, MATLAB.

1. MULTIPHYSICS GEOTECHNICAL & HYDROLOGICAL ARCHITECTURE

GeoGuard addresses the fundamental limitation of empirical LEWS by establishing a strict causal multiphysics chain: **Precipitation** → **Soil Infiltration & Drainage** → **Pore-Water Pressure Generation** → **Effective Stress Reduction** → **Limit Equilibrium FoS Degradation** → **Tertiary Kinematic Creep & Plastic Strain** → **Multi-Tier Emergency Alerting**. All physics equations are consolidated in a centralized, authoritative single-source-of-truth engine (`Lews_physics.m`), eliminating parameter discrepancies across simulation, training, and deployment scripts.

A. Hydrological Infiltration & Mass Conservation:

Net volumetric soil moisture evolution follows mass balance:

- Infiltration: $\Delta\theta_{infil} = (I_{rain} \cdot \Delta t_{phys} \cdot 0.85) / (z \cdot 1000)$
 - Deep Drainage: $\Delta\theta_{drain} = (k_{drain} \cdot \max(0, \theta - \theta_{field}) \cdot \Delta t_{phys}) / z$
 - Moisture Update: $\theta_{t+1} = \min(\theta_{sat}, \max(0.12, \theta_t + \Delta\theta_{infil} - \Delta\theta_{drain}))$
- where calibrated drainage conductivity $k_{drain} = 2.5 \times 10^{-5} \text{ s}^{-1}$, $z = 1.5 \text{ m}$ (regolith mantle depth), $\theta_{field} = 0.18$, and $\theta_{sat} = 0.50$. Physical time Δt_{phys} is decoupled from dashboard animation ticks, ensuring mass-conserving infiltration across any storm duration.

B. Pore Pressure & Limit Equilibrium FoS:

Positive pore-water pressure (u) develops upon exceeding critical field moisture ($\theta_{crit} = 0.34$):

- $u = \gamma_w \cdot z \cdot \cos^2(\beta) \cdot [(\theta - \theta_{crit}) / (\theta_{sat} - \theta_{crit})] \cdot 1.8 \text{ kPa}$
- Under Bishop limit equilibrium, stability is governed by:
- Normal Stress: $\sigma = \gamma_s \cdot z \cdot (\cos \beta - k_h \sin \beta) \cos \beta$
 - Effective Resisting Shear: $\tau_f = c' + \max(\sigma - u, 0.05) \cdot \tan(\phi)$
 - Driving Gravitational Shear: $\tau_d = \gamma_s \cdot z \cdot (\sin \beta + k_h \cos \beta) \cos \beta$
 - Factor of Safety: $FoS = \tau_f / \tau_d$
- where nominal parameters ($\beta=35^\circ$, $c'=12 \text{ kPa}$, $\phi=30^\circ$, $\gamma_s=18 \text{ kN/m}^3$) yield exact baseline $FoS_0 = 1.7705$.

2. PROGRESSIVE KINEMATICS, TERTIARY CREEP & SEISMIC COUPLING

Tertiary Creep Acceleration: Ground surface deformation kinematics are formulated through an empirical inverse-velocity creep model: $\omega_{tilt} = 0.08 / (FoS - 0.98)^{1.6} + 0.12 \cdot tremor$ (deg/h). As FoS approaches unity, tilt velocity accelerates asymptotically, reproducing the tertiary creep phase documented in catastrophic slope failures.

Seismic Tremor Coupling: Ground shaking is integrated via pseudostatic seismic acceleration coefficient $k_h = 0.015 \cdot tremor$, which simultaneously reduces normal confinement stress and amplifies downslope inertial driving forces.

Irreversible Plastic Shear Strain: When FoS drops below 1.05, plastic slip offset accumulates irreversibly: $\delta_{slip}(t+\Delta t) = \delta_{slip}(t) + 0.03$. Crucially, post-storm drying stabilizes the slope (increasing FoS) without unphysical 'soil healing' or backward displacement, correctly reflecting geological plastic strain.

3. PREDICTIVE FORECASTER & SCHMITT TRIGGER DECISION ENGINE

Advance Disaster Forecasting: To provide actionable emergency lead time, GeoGuard employs a forward-looking linear extrapolator: $FoS_{pred} = FoS + (dFoS/dt \cdot 600 \text{ s})$, projecting slope stability 10 minutes into the future. The derivative $dFoS/dt$ is conditioned through a low-pass filter ($\alpha = \min(0.3, 0.05 + 0.1 \Delta t_{phys})$) to prevent sensor noise from generating false alarm spikes. Estimated Time-to-Failure is computed via $TTF = (FoS - 1.05) / |dFoS/dt|$ and reports nominal stability (**Safe / NaN**) rather than artificial constants.

Schmitt Trigger Hysteresis: Traditional thresholding suffers from rapid alarm chatter during intermittent rainfall. GeoGuard enforces dual-threshold hysteresis: escalating to **Stage 2 (Evacuate)** when $FoS \leq 1.05$ or $\omega_{tilt} \geq 2.2^\circ/\text{h}$, requiring substantial recovery past $FoS > 1.15$ and $\omega_{tilt} < 1.8^\circ/\text{h}$ before stepping down to Advisory. Similarly, clearing **Stage 1 (Advisory)** back to Safe requires $FoS > 1.48$, rain $< 20 \text{ mm/h}$, and moisture $< 23\%$.

4. MACHINE LEARNING MULTI-CLASS DECISION SUPPORT

A multi-class Decision Tree classifier (`landslide_model.mat`) is seamlessly coupled to the real-time simulation engine. Trained across **12,000 causally-synthesized storm trajectories** spanning varied rainfall intensities (0–120 mm/h), durations (0.2–12 h), slope angles (20°–50°), and antecedent moisture conditions (15%–55%), the model evaluates live feature vectors $\mathbf{X} = [\text{FoS}, \text{Moisture}(\%), \text{RainRate}(\text{mm/h}), \text{TiltRate}(\text{deg/h})]$ at every simulation step. On an independent holdout test partition of 2,400 samples, the model achieved an exceptional **99.96% overall accuracy**, with 100% sensitivity for critical evacuation conditions (50/50 critical events correctly identified, zero false negatives), providing resilient algorithmic redundancy alongside the deterministic geomechanical solver.

5. AUTOMATED TEST SUITE & EMPIRICAL VERIFICATION

Test Case	Target Parameter / Equation	Benchmark Condition	Simulated Output	Status
Test 1: Baseline FoS	Limit equilibrium equation equivalence	$\beta=35^\circ$, $c'=12 \text{ kPa}$, $\phi=30^\circ$, $u=0$	$FoS = 1.7705$ (exact match)	PASSED
Test 2: Mass Balance	Cumulative rainfall physical integration	75 mm/h storm $\times$ 3.0 hr = 225.0 mm	CumRain = 225.0 mm (100% mass)	PASSED

Test 3: Storm Duration	Hydrological time-scale decoupling	12-minute vs. 12-hour duration	FoS: 1.770 (Safe) vs. 0.982 (Fail)	PASSED
Test 4: ML Inference	Classifier integration & live score vector	Nominal vs. saturated failure input	Class: 0 (Safe) vs. 2 (Evacuate)	PASSED
Test 5: Alert Hysteresis	Schmitt trigger state de-escalation	FoS = 1.10 → remains Evacuate (2)	Prevents alarm chatter / reset	PASSED
Test 6: Derivative Filter	Step-0 initial derivative & TTF sanity	t = 0 baseline condition	dFoS/dt = 0, FoS _{pred} = 1.77, TTF = NaN	PASSED

6. TELEMETRY TIMESERIES & SENSOR RESPONSE VALIDATION




Figure 1: Two-hour continuous LEWS telemetry simulation. (Top-Left) Rainfall rate and mass accumulation; (Top-Right) Soil moisture and pore-water pressure generation above 34% critical threshold; (Bottom-Left) Factor of Safety degradation and 10-minute predictive lookahead; (Bottom-Right) Surface tilt rate velocity and Schmitt trigger emergency alert escalation (Safe → Advisory → Evacuate).

7. COMMAND CONSOLE CAPABILITIES & DISASTER MANAGEMENT IMPACT

Interactive Command Console (`predictive_dashboard.m`): GeoGuard features an interactive command dashboard designed for geotechnical engineers and disaster relief commanders. The visual canvas renders a realistic hillside cross-section with multi-stratum geology (jointed bedrock foundation, Bishop circular shear arc, colluvium soil mantle, phreatic water table, alpine mountain chalet settlement, evergreen forest, monitoring station, and tension scarp cracking). Dynamic weather animation visually portrays storm severity, while a heads-up display (HUD) card delivers instant status telemetry.

Operational Significance: By bridging empirical rainfall monitoring with geotechnical limit equilibrium and machine learning inference, GeoGuard delivers reliable advance warning (10–30 minute window), eliminates false alarms through hysteresis filtering, and provides an open-source, verifiable engineering foundation for regional landslide early warning deployments.