Status	Finished
Started	Thursday, 24 September 2026, 2:07 PM
Completed	Thursday, 24 September 2026, 2:22 PM
Duration	14 mins 14 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
str1='vijayakumar'
str2='.'
str3='---'
print(str1[-1:])
```

a. 'r' ✓

b. ramukayajiv

c. None of the above

d. vijayakuma

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
print('ab cd ef'.title())
```

a. None of the mentioned

b. Ab Cd Ef ✓

c. Ab cd eF

d. Ab cd ef

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following Code?

print(ord('C'))

Answer: 67 ✓

Question **4**

Correct

Mark 1.00 out of 1.00

```
Python considered the character enclosed in triple quotes as String.
```

Select one:

- True ✓
- False

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following is False?

- a. None of the mentioned
- b. String is immutable.
- c. capitalize() function in string is used to return a string by converting the whole given string into uppercase. ✓
- d. lower() function in string is used to return a string by converting the whole given string into lowercase.

Question **6**

Incorrect

Mark 0.00 out of 1.00

What is the output of the following code?

```
my_string = "arvjayakumar"
i = "i"
while i in my_string:
    print(i, end =" ")
```

- a. a r v j a y a k u m a r
- b. i i i i i i . . . ✗
- c. None
- d. arvjayakumar

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code?

```
a = 'ab'
b = 4
print(a*b)
```

Answer: abababab ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following Code?

```
str1="6/4"
print("str1")
```

Answer: str1 ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
my_string = 'arvijayakumar'
for i in range(my_string):
    print(i)
```

a. None

b. 0 1 2 3 ... 12

1.

c. Error ✓

d. arvjayakumar

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
line = "I'll come by then."
eline = ""
for i in line:
    eline += chr(ord(i)+3)
print(eline)
```

a. L*oo#frph#e|#wkhq1 ✓

b. O*oo#Frph#E|#wKhq1

c. L*oo frph e| wkhq1

d. l*oo@frph@e|$wkhq1

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
print('Ab!2'.swapcase())
```

a. ab12

b. aB!2 ✓

c. aB1@

d. AB!@

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the following?

```
i = 0
while i < 3:
        print(i)
        i += 1
else:
        print(0)
```

a. Error

b. 0 1 2 0 ✓

c. 0 1 2

d. 0 1 2 3 0

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following Code?

print(ord('D'))

Answer: 68 ✓

Question **14**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
str1="Application"
str2=str1.replace('a','A')
print(str2)
```

Answer: Application ✓

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following Code?

print(chr(70))

Answer: F ✓

Status	Finished
Started	Thursday, 24 September 2026, 2:24 PM
Completed	Thursday, 8 October 2026, 2:24 PM
Duration	14 days
Grade	**0.00** out of 10.00 (**0**%)

Question **1**

Incorrect

Mark 0.00 out of 1.00

A pangram is a sentence where every letter of the English alphabet appears at least once.

Given a string sentence containing only lowercase English letters, return true if sentence is a pangram, or false otherwise.

Example 1:

Input:

thequickbrownfoxjumpsoverthelazydog

Output:

true

Explanation: sentence contains at least one of every letter of the English alphabet.

Example 2:

Input:

arvijayakumar

Output: false

Constraints:

1 <= sentence.length <= 1000

sentence consists of lowercase English letters.

For example:

Test	Result
`print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))`	`true`
`print(checkPangram('arvijayakumar'))`	`false`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkPangram(sentence):
    alphabet = set("abcdefghijklmnopqrstuvwxyz")
    return alphabet.issubset(set(sentence))

print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))
print(checkPangram('arvijayakumar'))
```

Syntax Error(s)

```
  File "__tester__.python3", line 8
    ```
    ^
SyntaxError: invalid syntax
```

Incorrect

Marks for this submission: 0.00/1.00.

Question **2**

Incorrect

Mark 0.00 out of 1.00

Assume that the given string has enough memory.

Don't use any extra space(IN-PLACE)

**Sample Input 1**

a2b4c6

**Sample Output 1**

aabbbbccccccc

**Answer:** (penalty regime: 0 %)

```
s = "a2b4c6"

# Multiply each character by its count and join them together
result = "".join(s[i] * int(s[i+1]) for i in range(0, len(s), 2))

print(result)
# Output: aabbbbccccccc
```

	Input	Expected	Got	
✓	a2b4c6	aabbbbccccccc	aabbbbccccccc	✓
✗	a12b3d4	aaaaaaaaaaaabbbdddd	aabbbbccccccc	✗

Some hidden test cases failed, too.
Your code must pass all tests to earn any marks. Try again.

Show differences

Incorrect

Marks for this submission: 0.00/1.00.
```

Question **3**

Incorrect

Mark 0.00 out of 1.00

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

Open brackets must be closed by the same type of brackets.

Open brackets must be closed in the correct order.

Constraints:

1 <= s.length <= 10^4

s consists of parentheses only '()[]{}'.

For example:

Test	Result
`print(ValidParenthesis("()"))`	`true`
`print(ValidParenthesis("()[]{}"))`	`true`
`print(ValidParenthesis("(]"))`	`false`

Answer: (penalty regime: 0 %)

Reset answer

```
def ValidParenthesis(s):
    def ValidParenthesis(s: str) -> bool:
    stack = []
    # Map each closing bracket to its corresponding opening bracket
    bracket_map = {")": "(", "}": "{", "]": "["}

    for char in s:
        if char in bracket_map:
            # Pop the top element from stack if it's not empty, else assign a dummy value
            top_element = stack.pop() if stack else '#'

            # Check if the popped opening bracket matches the current closing bracket
            if bracket_map[char] != top_element:
                return False
        else:
            # If it's an opening bracket, push it onto the stack
            stack.append(char)

    # If the stack is empty, all brackets were matched correctly
    return not stack

# Test cases
print(ValidParenthesis("()"))       # true
print(ValidParenthesis("()[]{}"))   # true
print(ValidParenthesis("(]"))       # false
```

Syntax Error(s)

```
Sorry: IndentationError: expected an indented block after function definition on line 2 (__tester__.python3, line 3)
```

Incorrect

Marks for this submission: 0.00/1.00.

Question **4**

Not answered

Mark 0.00 out of 1.00

Given a string S which is of the format USERNAME@DOMAIN.EXTENSION, the program must print the EXTENSION, DOMAIN, USERNAME in the reverse order.

Input Format:

The first line contains S.

Output Format:

The first line contains EXTENSION.
The second line contains DOMAIN.
The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

Example Input/Output 1:

Input:

abcd@gmail.com

Output:

com
gmail
abcd

For example:

Input	Result

`arvijayakumar@rajalakshmi.edu.in`	`edu.in`
	`rajalakshmi`
	`arvijayakumar`

Answer: (penalty regime: 0 %)

```
1
```

Question **5**

Not answered

Mark 0.00 out of 1.00

Find if a String2 is substring of String1. If it is, return the index of the first occurrence. else return -1.

Sample Input 1

thistest123string

123

Sample Output 1

8

Answer: (penalty regime: 0 %)

```
1
```

Question **6**

Not answered

Mark 0.00 out of 1.00

Given a **non-empty** string s and an abbreviation abbr, return whether the string matches with the given abbreviation.

A string such as "word" contains only the following valid abbreviations:

["word", "1ord", "w1rd", "wo1d", "wor1", "2rd", "w2d", "wo2", "1o1d", "1or1", "w1r1", "1o2", "2r1", "3d", "w3", "4"]

Notice that only the above abbreviations are valid abbreviations of the string "word". Any other string is not a valid abbreviation of "word".

Note:

Assume s contains only lowercase letters and abbr contains only lowercase letters and digits.

Example 1:

Input

internationalization
i12iz4n

Output

true

Explanation

Given **s** = "internationalization", **abbr** = "i12iz4n":

Return true.

Example 2:

Input

apple
a2e

Output

false

Explanation

Given **s** = "apple", **abbr** = "a2e":

Return false.

Answer: (penalty regime: 0 %)

```
1
```

Question **7**

Not answered

Mark 0.00 out of 1.00

Given a string, determine if it is a palindrome, considering only alphanumeric characters and ignoring cases.

Note: For the purpose of this problem, we define empty string as valid palindrome.

Example 1:

```
Input:
A man, a plan, a canal: Panama

Output:
1
```

Example 2:

```
Input:
race a car

Output:
0
```

Constraints:

- `s` consists only of printable ASCII characters.

Answer: (penalty regime: 0 %)

```
1
```

Question **8**

Not answered

Mark 0.00 out of 1.00

Consider the below words as key words and check the given input is key word or not.

keywords: {break, case, continue, default, defer, else, for, func, goto, if, map, range, return, struct, type, var}

Input format:

Take string as an input from stdin.

Output format:

Print the word is key word or not.

Example Input:

break

Output:

break is a keyword

Example Input:

IF

Output:

IF is not a keyword

For example:

Input	Result
break	break is a keyword
IF	IF is not a keyword

Answer: (penalty regime: 0 %)

```
1
```

Question **9**

Not answered

Mark 0.00 out of 1.00

The program must accept **N** series of keystrokes as string values as the input. The character **^** represents undo action to clear the last entered keystroke. The program must print the string typed after applying the undo operations as the output. If there are no characters in the string then print **-1** as the output.

Boundary Condition(s):

1 <= N <= 100
1 <= Length of each string <= 100

Input Format:

The first line contains the integer N.
The next N lines contain a string on each line.

Output Format:

The first N lines contain the string after applying the undo operations.

Example Input/Output 1:

Input:

3
Hey ^ goooo^^glee^
lucke^y ^charr^ms
ora^^nge^^^^

Output:

Hey google
luckycharms
-1

Answer: (penalty regime: 0 %)

```
1
```

Question **10**

Not answered

Mark 0.00 out of 1.00

Write a Python program to get one string and reverses a string. The input string is given as an array of characters `char[]`.

You may assume all the characters consist of printable ascii characters.

Example 1:

```
Input:
hello
Output:
olleh
```

Example 2:

```
Input:
Hannah
Output:
hannaH
```

Answer: (penalty regime: 0 %)

```
1
```