Status	Finished
Started	Thursday, 8 October 2026, 11:37 AM
Completed	Thursday, 8 October 2026, 11:48 AM
Duration	10 mins 22 secs
Grade	**10.00** out of 15.00 (**66.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Write the output of : print(min(tuple("computer")))

a. u
b. o
c. c ✓
d. t

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following are advantages of using function in program?

a. All of the mentioned ✓
b. It increases reusability.
c. It makes debugging easier.
d. It increases readability of program.

Question **3**

Incorrect

Mark 0.00 out of 1.00

Which of the following is not the type of function argument?

a. default argument
b. Keyword argument
c. Required argument ✗
d. initial argument

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is not the scope of variable?

a. None of the mentioned
b. Global
c. Outside ✓
d. Local

Question **5**

Incorrect

Mark 0.00 out of 1.00

Write the output of : print(max([1, 2, 3, 4], [4, 5, 6], [7]))

a. [1, 2, 3, 4] ✗
b. [4, 5, 6]
c. 7
d. [7]

Question **6**

Incorrect

Mark 0.00 out of 1.00

Which one of the following is the correct way of calling a function?

a. function_name()
b. call function_name() ✗
c. function function_name()
d. ret function_name()

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def fun1(num):
    return num + 25
fun1(5)
print(num)
```

- a. NameError ✓
- b. num
- c. 5
- d. 25

Question **8**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def sayHello():
    print('Hello World!')
sayHello()
sayHello()
```

- a. Hello
  Hello
- b. 'Hello World!'
  'Hello World!'
- c. Hello World! ✓
  Hello World!
- d. None of the mentioned

Question **9**

Correct

Mark 1.00 out of 1.00

Fill in the line of the following Python code for calculating the factorial of a number?

```
def factorial🤔 :
    if (n==1 or n==0):
       return 1
    else:
        return ——
num = 5;
print("number : ",num)
print("Factorial : ",factorial(num))
```

a. (n * factorial(n - 1)) ✓

b. fact(n)*fact(n-1)

c. n*(n-1)

d. (n-1)*(n-2)

Question **10**

Correct

Mark 1.00 out of 1.00

Which keyword is used for defining a function?

a. Fun

b. Define

c. def ✓

d. Function

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following function definition header is wrong?

a. def mul(p1, n1, m1):

b. def div(p1=4, p2, p3): ✓

c. def scan(p1, p2 = 4, p3 = 5):

d. def sum(n1, n2, n = 3):

Question **12**

Incorrect

Mark 0.00 out of 1.00

cal(n1) : What is n1?

- a. Keyword
- b. Parameter ✗
- c. Argument
- d. None of the mentioned

Question **13**

Incorrect

Mark 0.00 out of 1.00

Which of the following items are present in the function header?

- a. B. parameter list ✗
- b. Both A and B
- c. return value
- d. A. function name

Question **14**

Correct

Mark 1.00 out of 1.00

The _____ statement returns the values from the function to the calling function.

- a. return ✓
- b. give
- c. send
- d. take

Question **15**

Correct

Mark 1.00 out of 1.00

Which keyword is used to begin the definition of a function?

- a. def ✓
- b. Def
- c. DEF
- d. Define

Status	Finished
Started	Thursday, 15 October 2026, 2:04 PM
Completed	Tuesday, 27 October 2026, 12:36 PM
Duration	11 days 22 hours
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1
2
3 def coinChange(n):
4     return n // 4 + n % 4
5
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for p in (2, 3, 5):
        while n % p == 0:
            n //= p

    return "ugly" if n == 1 else "not ugly"

```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(n):
    s = str(n)
    pairs = {'0': '0', '1': '1', '6': '9', '8': '8', '9': '6'}

    for i in range(len(s)):
        if s[i] not in pairs or pairs[s[i]] != s[len(s) - 1 - i]:
            return False

    return True

```

	Test	Expected	Got	
✓	`print(Strobogrammatic(69))`	`True`	`True`	✓
✓	`print(Strobogrammatic(88))`	`True`	`True`	✓
✓	`print(Strobogrammatic(962))`	`False`	`False`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
`print(Summation(8))`	`9872`

Answer: (penalty regime: 0 %)

Reset answer

```
def Summation(a):
    a = str(a)
    return int(a) + int(a * 2) + int(a * 3) + int(a * 4)
```

	Test	Expected	Got	
✓	`print(Summation(8))`	`9872`	`9872`	✓
✓	`print(Summation(10))`	`10203040`	`10203040`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
`print(christmasDiscount(578))`	12

Answer: (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(orderValue):
    return sum(int(digit) for digit in str(orderValue) if digit in '2357')
```

	Test	Expected	Got	
✓	`print(christmasDiscount(578))`	12	12	✓
✓	`print(christmasDiscount(57))`	12	12	✓
✓	`print(christmasDiscount(222))`	6	6	✓
✓	`print(christmasDiscount(77777))`	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.