

REACT-17

```
$ npx create-react-app fetchuserapp  
$ cd fetchuserapp
```

Output:

```
Creating a new React app in C:\Users\Student\fetchuserapp.  
  
Installing packages. This might take a couple of minutes.  
Installing react, react-dom, and react-scripts...  
  
Success! Created fetchuserapp at C:\Users\Student\fetchuserapp  
Inside that directory, you can run several commands:  
  
  npm start  
    Starts the development server.  
  
Happy hacking!
```

(src/Getuser.js):

```
import React, { Component } from 'react';  
  
class Getuser extends Component {  
  constructor(props) {  
    super(props);  
    this.state = {  
      user: null,  
      loading: true  
    };  
  }  
  
  componentDidMount() {  
    fetch('https://api.randomuser.me/')  
      .then(response => response.json())  
      .then(data => {  
        this.setState({  
          user: data.results[0],  
          loading: false  
        });  
      })  
      .catch(error => console.log(error));  
  }  
  
  render() {  
    const { user, loading } = this.state;  
  
    if (loading) {  
      return <h2>Loading user...</h2>;  
    }  
  
    return (  
      <div className="getuser">  
        <h2>  
          {user.name.title} {user.name.first}  
        </h2>  
        <img src={user.picture.large} alt={user.name.first} />  
      </div>  
    );  
  }  
}
```

```
    </div>
  );
}
}

export default Getuser;
```

(src/App.js):

```
import React from 'react';
import './App.css';
import Getuser from './Getuser';

function App() {
  return (
    <div className="App">
      <h1>Fetch User App</h1>
      <Getuser />
    </div>
  );
}

export default App;
```

```
$ npm start
```

Output:

```
Compiled successfully!

You can now view fetchuserapp in the browser.

   Local:            http://localhost:3000
  On Your Network:  http://192.168.1.5:3000

Note that the development build is not optimized.
To create a production build, use npm run build.
```

Output

