

BATCH No:25

**DIABETIC RETINOPATHY DETECTION USING
EFFICIENTNET-B3 MODEL**

*Major project report submitted
in partial fulfillment of the requirement for award of the degree of*

**Bachelor of Technology
in
Information Technology**

By

**HARINI.J (22UEIT0013) (VTU 23279)
NAVEEN.V (22UEIT0042) (VTU 23277)**

*Under the guidance of
Dr.J.Visumathi,M.E.,Ph.D.,
PROFESSOR*



**DEPARTMENT OF INFORMATION TECHNOLOGY
SCHOOL OF COMPUTING**

**VEL TECH RANGARAJAN DR. SAGUNTHALA R&D INSTITUTE OF
SCIENCE AND TECHNOLOGY**

(Deemed to be University Estd u/s 3 of UGC Act, 1956)

**Accredited by NAAC with A++ Grade
CHENNAI 600 062, TAMILNADU, INDIA**

April, 2026

BATCH No:25

**DIABETIC RETINOPATHY DETECTION USING
EFFICIENTNET-B3 MODEL**

*Major project report submitted
in partial fulfillment of the requirement for award of the degree of*

**Bachelor of Technology
in
Information Technology**

By

**HARINI.J (22UEIT0013) (VTU 23279)
NAVEEN.V (22UEIT0042) (VTU 23277)**

*Under the guidance of
Dr.J.Visumathi,M.E.,Ph.D.,
PROFESSOR*



**DEPARTMENT OF INFORMATION TECHNOLOGY
SCHOOL OF COMPUTING**

**VEL TECH RANGARAJAN DR. SAGUNTHALA R&D INSTITUTE OF
SCIENCE AND TECHNOLOGY**

(Deemed to be University Estd u/s 3 of UGC Act, 1956)

**Accredited by NAAC with A++ Grade
CHENNAI 600 062, TAMILNADU, INDIA**

April, 2026

CERTIFICATE

It is certified that the work contained in the project report titled "DIABETIC RETINOPATHY DETECTION USING EFFICIENTNET-B3 MODEL" by "Harini.J (22UEIT0013),Naveen.V (22UEIT0042)" has been carried out under my supervision and that this work has not been submitted elsewhere for a degree.

Signature of Supervisor

Dr. J.Visumathi

Professor

Information Technology

School of Computing

Vel Tech Rangarajan Dr.Sagunthala R&D

Institute of Science & Technology

Signature of Head of the Department

Dr. A. Peter Soosai Anandaraj

Professor & Head

Information Technology

School of Computing

Vel Tech Rangarajan Dr. Sagunthala R&D

Institute of Science and Technology

Signature of the Dean

Dr. S P. Chokkalingam

Professor & Dean

School of Computing

Vel Tech Rangarajan Dr. Sagunthala R&D

Institute of Science and Technology

DECLARATION

We declare that this written submission represents Our ideas in our own words and where others ideas or words have been included, we have adequately cited and referenced the original sources. We also declare that we have adhered to all principles of academic honesty and integrity and have not misrepresented or fabricated or falsified any idea in our submission. We understand that any violation of the above will be cause for disciplinary action by the Institute and can also evoke penal action from the sources which have thus not been properly cited or from whom proper permission has not been taken when needed.

(Signature)

HARINI.J

Date: / /

(Signature)

NAVEEN.V

Date: / /

APPROVAL SHEET

This project report entitled "DIABETIC RETINOPATHY DETECTION USING EFFICIENTNET-B3 MODEL" by HARINIJ (22UEIT0013), NAVEEN.V (22UEIT0042) is approved for the degree of B.Tech in Information Technology.

Examiners

Supervisor

Dr.J.Visumathi,M.E.,Ph.D.,
Professor,.

Date: / /

Place:

ACKNOWLEDGEMENT

We express our deepest gratitude to our **Honorable Founder Chancellor and President Col. Prof. Dr. R. RANGARAJAN B.E. (Electrical), B.E. (Mechanical), M.S (Automobile), D.Sc., and Foundress President Dr. R. SAGUNTHALA RANGARAJAN M.B.B.S., Vel Tech Rangarajan Dr. Sagunthala R&D Institute of Science and Technology, for her blessings.**

We express our sincere thanks to our respected Chairperson and Managing Trustee **Dr.(Mrs) RANGARAJAN MAHALAKSHMI KISHORE, Vel Tech Rangarajan Dr. Sagunthala R&D Institute of Science and Technology, for their blessings.**

We are very much grateful to our beloved **Vice Chancellor Prof. Dr.RAJAT GUPTA, Ph.D.,** for providing us with an environment to complete our project successfully.

We record indebtedness to our **Professor & Dean, School of Computing, Dr. S P. CHOKKALINGAM, M.Tech., Ph.D., & Professor & Associate Dean, School of Computing, Dr.V. DHILIP KUMAR,M.E., Ph.D., Professor Assistant Dean, Dr.R. PARTHASARATHY,M.E., Ph.D.,** for immense care and encouragement towards us throughout the course of this project.

We are thankful to our **Professor & Head, Department of Information Technology Dr. A .PETER SOOSAI ANANDARAJ, M.E.,Ph.D.,** for providing immense support in all our endeavors.

We also take this opportunity to express a deep sense of gratitude to our **Internal Supervisor Dr. J. VISUMATHI, M.E., Ph.D.,** for her cordial support, valuable information and guidance, she helped us in completing this project through various stages.

A special thanks to our **Project Coordinator Dr. P. ANITHA RAJAKUMARI,ME.,Ph.D.,**for her valuable guidance and support throughout the course of the project.

We thank our department faculty, supporting staff and friends for their help and guidance to complete this project.

HARINI.J (22UEIT0013)
NAVEEN.V (22UEIT0042)

ABSTRACT

The Diabetic Retinopathy Detection System employs deep learning techniques to automatically detect and classify the severity of diabetic retinopathy from retinal fundus images. With the rapid increase in diabetes cases worldwide, early identification of retinal abnormalities has become essential to prevent vision loss and ensure timely treatment. The system utilizes Convolutional Neural Networks (CNN) with the EfficientNet-B3 architecture to process high-resolution retinal images and extract important features such as microaneurysms, hemorrhages, and exudates. The input images undergo preprocessing steps including resizing, normalization, and contrast enhancement using techniques such as CLAHE to improve image quality and ensure consistent performance. The preprocessed images are then passed through the deep learning model, which performs feature extraction and classification into different stages including No Diabetic Retinopathy, Mild, Moderate, Severe, and Proliferative Diabetic Retinopathy. Transfer learning is applied to enhance model accuracy and reduce training time by utilizing pre-trained weights on large-scale datasets such as APTOS and EyePACS. The system provides prediction results along with confidence scores and supports visualization techniques such as Grad-CAM to highlight affected regions in the retina. The proposed model demonstrates high performance in terms of accuracy and efficiency, making it suitable for real-time medical applications. The results are presented through an interactive interface, enabling easy interpretation by healthcare professionals. With advancements in deep learning and medical imaging, the system contributes to automated disease screening and reduces the burden on ophthalmologists. Furthermore, the model can be extended with larger datasets, improved architectures, and deployment on cloud or edge devices to enhance scalability and accessibility in real-world clinical environments.

Keywords:

Deep Learning, Convolutional Neural Networks (CNN), Diabetic Retinopathy, EfficientNet-B3, Retinal Fundus Images, Image Preprocessing, Transfer Learning, Grad-CAM, Medical Image Analysis.

LIST OF FIGURES

4.1	Architecture Diagram for Diabetic Retinopathy Detection	15
4.2	Data Flow Diagram of Retinal Image Processing	16
4.3	Sequence diagram of System Work Flow	17
4.4	Activity diagram of Detection Process	18
5.1	Input Design of Retinal Fundus Image	25
5.2	Output Design for Prediction and Classification	26
5.3	Unit Testing Result of the Model	29
5.4	Test Image for Diabetic Retinopathy Detection	32
6.1	Graphical Representation of Model Performance	36
9.1	Plagiarism Report Summary	42

LIST OF TABLES

6.1	Comparison Between Existing and Proposed Diabetic Retinopathy Detection Systems	34
8.1	Mapping of Project to Complex Engineering Problems (CEP)	39
8.2	Mapping of Project to Complex Engineering Activities (CEA) . . .	40
8.3	SDG Mapping for Diabetic Retinopathy Detection System	41

LIST OF ACRONYMS AND ABBREVIATIONS

S.NO	ACRONYMS	ABBREVIATIONS
1	AI	Artificial Intelligence
2	DL	Deep Learning
3	CNN	Convolutional Neural Network
4	DR	Diabetic Retinopathy
5	DNN	Deep Neural Network
6	OpenCV	Open Source Computer Vision Library
7	APTOS	Asia Pacific Tele-Ophthalmology Society
8	EyePACS	Eye Picture Archive Communication System
9	ReLU	Rectified Linear Unit
10	GPU	Graphics Processing Unit

TABLE OF CONTENTS

	Page.No
ABSTRACT	v
LIST OF FIGURES	vi
LIST OF TABLES	vii
LIST OF ACRONYMS AND ABBREVIATIONS	viii
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Background	2
1.3 Objective	2
1.4 Problem Statement	4
2 LITERATURE REVIEW	5
2.1 Related Work	5
2.2 Existing System	7
2.3 Research Gap	8
3 PROJECT DESCRIPTION	9
3.1 Existing System	9
3.2 Proposed System	10
3.3 Feasibility Study	11
3.3.1 Economic Feasibility	11
3.3.2 Technical Feasibility	11
3.3.3 Social Feasibility	12
3.4 System Specification	13
3.4.1 Hardware Specification	13
3.4.2 Software Specification	13
3.4.3 Standards and Policies	14

4	METHODOLOGY	15
4.1	General Architecture for Diabetic Retinopathy Detection	15
4.2	Design Phase	16
4.2.1	Data Flow Diagram	16
4.2.2	Sequence diagram	17
4.2.3	Activity Diagram	18
4.3	Algorithm & Pseudo Code	19
4.3.1	Convolutional Neural Network	19
4.4	Module Description	22
4.4.1	Data Collection	22
4.4.2	Image Preprocessing	22
4.4.3	Model Development	22
4.4.4	Training and Validation	23
4.4.5	Evaluation	23
5	IMPLEMENTATION AND TESTING	24
5.1	Input and Output	24
5.1.1	Input Design of Retinal Fundus Image	24
5.1.2	Output Design for Prediction and Classification	25
5.2	Testing	27
5.2.1	Unit Testing	27
5.2.2	Integration Testing	29
5.2.3	System Testing	30
5.2.4	Test Result	32
6	RESULTS AND DISCUSSIONS	33
6.1	Efficiency of the Proposed System	33
6.2	Comparison of Existing and Proposed System	34
6.2.1	Existing System: Traditional and Early Deep Learning Models	34
6.2.2	Proposed System: EfficientNet-B3	35
6.3	Comparative Analysis-Graphical Representation	36
7	CONCLUSION AND FUTURE ENHANCEMENTS	37
7.1	Conclusion	37
7.2	Limitation	37
7.3	Future Enhancements	38

8	ADDRESSING COMPLEX ENGINEERING PROBLEM AND SDG	39
8.1	Mapping of the Project to Complex Engineering Problem (CEP) . .	39
8.2	Mapping of Project to Complex Engineering Activities (CEA) . . .	40
8.3	SDG Mapping (CEP Section)	41
9	PLAGIARISM REPORT	42
10	SOURCE CODE	43
10.1	Source Code	43
	References	45

Chapter 1

INTRODUCTION

1.1 Introduction

The automatic detection of diabetic retinopathy from retinal fundus images has gained significant attention in recent years due to the increasing prevalence of diabetes and its severe impact on vision. Diabetic retinopathy is one of the leading causes of blindness if not detected at an early stage. Traditional diagnostic methods rely on manual examination by ophthalmologists, which is time-consuming, requires expert knowledge, and may lead to variations in diagnosis due to human error. Variations in image quality, lighting conditions, and subtle differences in retinal features further make accurate detection challenging. With the advancement of artificial intelligence, deep learning techniques have emerged as powerful tools for medical image analysis. Convolutional Neural Networks (CNNs) have demonstrated high efficiency in extracting complex features from images and performing accurate classification tasks. These models can automatically identify important retinal abnormalities such as microaneurysms, hemorrhages, and exudates, which are key indicators of diabetic retinopathy. The integration of deep learning with medical imaging has significantly improved diagnostic accuracy and reduced the dependency on manual analysis. The use of pre-trained models and transfer learning further enhances performance by utilizing knowledge from large-scale datasets. This approach enables the development of automated systems capable of handling large volumes of retinal images with high reliability. As a result, intelligent diagnostic systems are becoming essential in modern healthcare applications.

In recent years, automated healthcare systems capable of analyzing medical images have become increasingly important for early disease detection and prevention. Among these, diabetic retinopathy detection systems play a crucial role in reducing the risk of vision loss by providing timely diagnosis and classification. The proposed system adopts a structured pipeline that includes image acquisition, preprocessing, feature extraction, classification, and result visualization. Retinal

fundus images are used as input, which are preprocessed using techniques such as resizing, normalization, and contrast enhancement to improve image quality. The processed images are then passed through the EfficientNet-B3 model, which extracts relevant features and classifies the severity of diabetic retinopathy into different stages. The final output is presented along with confidence scores and visual explanations, enabling better understanding of the results. By combining deep learning techniques with medical image analysis, the system ensures accurate, efficient, and scalable detection suitable for real-world healthcare applications.

1.2 Background

The increasing number of diabetes cases worldwide has led to a rise in diabetic retinopathy, a serious eye disease that can cause vision loss if not detected early. Traditional methods of diagnosis rely on manual examination of retinal images by specialists, which can be time-consuming and prone to human error. Variations in image quality and subtle differences in retinal features make accurate detection challenging. With the advancement of deep learning and computer vision, automated systems have been developed to improve diagnostic efficiency. Convolutional Neural Networks (CNNs) play a major role in analyzing medical images and identifying disease patterns. These technologies enable faster and more reliable detection of diabetic retinopathy. As a result, intelligent systems are becoming essential in modern healthcare for early diagnosis and prevention of vision-related complications.

1.3 Objective

Diabetic retinopathy detection systems focus on developing automated and accurate methods for identifying retinal abnormalities using deep learning techniques. Convolutional Neural Networks (CNN) with EfficientNet-B3 architecture are used to analyze retinal fundus images and extract meaningful features related to disease progression. Automated analysis reduces dependency on manual diagnosis by ophthalmologists and improves efficiency in large-scale screening. The use of large datasets such as APTOS and EyePACS ensures better generalization and robustness of the model. Image preprocessing techniques including resizing, normalization, and contrast enhancement improve the quality

of input data and enhance model performance. Classification methods are used to categorize diabetic retinopathy into different stages such as No DR, Mild, Moderate, Severe, and Proliferative DR. Transfer learning improves accuracy and reduces training time by utilizing pre-trained models. Fast and reliable prediction systems support real-time medical applications. Visualization techniques help in identifying affected regions in retinal images for better interpretation.

Scalable and efficient systems assist healthcare professionals in early diagnosis and treatment planning. Integration of deep learning with medical imaging improves consistency and accuracy in detection. Automated screening systems help in identifying disease at an early stage and reduce the burden on medical experts. Efficient handling of large medical datasets ensures stable performance across different conditions. Optimized models reduce computational complexity while maintaining high accuracy.

The primary objective of this project is to develop an intelligent diabetic retinopathy detection system using deep learning techniques. The system aims to accurately classify retinal fundus images into different diabetic retinopathy severity levels. It focuses on improving diagnostic speed and reducing manual effort in retinal disease screening. The project utilizes EfficientNet-B3 to enhance feature extraction and classification performance. It also aims to support ophthalmologists by providing reliable automated screening assistance. The system is designed to improve accessibility of diagnosis in remote and resource-limited areas. Another objective is to minimize the risk of vision loss through early detection and timely prediction. Overall, the project aims to deliver a scalable and efficient healthcare solution for automated diabetic retinopathy diagnosis.

In addition, user-friendly systems provide clear prediction results along with confidence scores for better understanding. Improved efficiency and reliability support real-world healthcare applications. The system allows extension with advanced models and larger datasets for improved performance. Future enhancements include cloud deployment and integration with healthcare systems. These improvements make the system suitable for scalable and practical medical use.

1.4 Problem Statement

Diabetic retinopathy is a major complication of diabetes and one of the leading causes of vision loss worldwide if not detected at an early stage. The traditional method of diagnosis involves manual examination of retinal fundus images by ophthalmologists, which is time-consuming and requires specialized expertise. Due to the increasing number of diabetic patients, the demand for accurate and timely screening has significantly increased, making manual diagnosis inefficient and difficult to scale. Variations in image quality, lighting conditions, and subtle retinal features further complicate the detection process. Early-stage symptoms such as microaneurysms and small hemorrhages are often difficult to identify with the human eye, leading to delayed diagnosis and treatment. In many rural and under-resourced areas, access to trained specialists is limited, which further increases the risk of undetected cases.

Furthermore, many existing systems lack the ability to generalize across diverse datasets and often show reduced accuracy when applied to real-world conditions. The presence of noise, low contrast, and variations in retinal image acquisition affects the performance of conventional models. Manual feature engineering increases computational complexity and reduces efficiency. Additionally, the absence of real-time processing capabilities limits their application in practical healthcare environments.

There is a need for a system that can automatically extract features, handle variations in input data, and provide consistent results with high accuracy. Therefore, an automated deep learning-based system is required to overcome these challenges and improve diagnostic efficiency. The system should be capable of analyzing large volumes of retinal images and classifying disease severity accurately. It should provide reliable predictions with minimal human intervention. Such a solution will help in early detection, reduce the workload on healthcare professionals, and improve overall patient outcomes.

Chapter 2

LITERATURE REVIEW

Diabetic retinopathy (DR) detection using artificial intelligence has gained significant attention due to the need for early diagnosis and automated screening systems. Machine learning (ML) and deep learning (DL) techniques have been widely applied to analyze retinal fundus images and improve diagnostic accuracy. Various studies have explored different architectures and methodologies to enhance feature extraction, classification performance, and clinical applicability.

2.1 Related Work

Pranavah Raja et al.[12] proposed Dense-PMSFNet, a DenseNet-based pyramidal multi-scale fusion network for retinal vasculature and FAZ segmentation in OCTA images. Their approach focuses on capturing both local and global contextual features through multi-scale fusion, enabling precise identification of fine vascular structures in retinal images. The model uses dense connectivity to improve feature reuse and gradient flow, thereby enhancing segmentation accuracy. By integrating pyramidal feature extraction, the network effectively handles variations in vessel thickness and contrast, which are common challenges in retinal imaging.

Gulshan et al.[19] developed a deep learning algorithm for detecting diabetic retinopathy using retinal fundus images. The model was trained on a large dataset and achieved performance comparable to expert ophthalmologists. Their study demonstrated that deep learning can significantly improve automated diagnosis and early disease detection in healthcare systems. The system utilized convolutional neural networks to learn complex visual patterns from retinal images without manual feature extraction. Their results highlighted high sensitivity and specificity, making the approach reliable for large-scale screening applications.

Pratt et al.[17] explored the use of Convolutional Neural Networks (CNN) for diabetic retinopathy classification. Their model automatically extracted hierarchical features from retinal images and improved classification accuracy compared to

traditional machine learning approaches. The study also demonstrated that deep learning models are capable of identifying subtle retinal abnormalities that are difficult to detect manually. Their work emphasized the importance of automated systems in reducing diagnostic workload and improving efficiency in medical imaging.

Tan and Le[11] introduced EfficientNet, a scalable convolutional neural network that optimizes model depth, width, and resolution. Their approach achieved high accuracy with fewer parameters, making it suitable for medical imaging tasks such as diabetic retinopathy detection. The compound scaling method allowed the model to balance performance and computational efficiency effectively. This makes EfficientNet highly suitable for deployment in real-time and resource-constrained healthcare environments.

Simonyan and Zisserman[9] proposed the VGGNet architecture, which uses deep convolutional layers for improved image classification. Their work demonstrated that deeper networks enhance feature extraction and accuracy, contributing significantly to deep learning-based medical image analysis. The uniform architecture with small convolution filters improved model performance and generalization. VGGNet has been widely used as a baseline model for many medical imaging applications, including retinal disease detection.

Shahzad et al.[18] developed an explainable AI-based model for diabetic retinopathy diagnosis. Their approach provides interpretable results, allowing medical professionals to understand the decision-making process of the model. The study emphasized the importance of transparency and reliability in healthcare AI systems. The integration of explainable techniques helps in visualizing important regions contributing to predictions. This improves trust and acceptance of AI systems in clinical practice and supports better decision-making.

Zedda et al.[4] focused on deep image mining techniques for automated diabetic retinopathy screening. Their approach combined image processing and deep learning methods to detect retinal lesions such as microaneurysms and hemorrhages. The study demonstrated that automated systems can effectively support large-scale screening programs and assist in early diagnosis. Their results highlighted improved detection accuracy and reduced dependency on manual analysis by medical experts.

2.2 Existing System

Existing diabetic retinopathy detection systems mainly rely on traditional machine learning techniques and basic deep learning architectures such as VGG, ResNet, and standard CNN models. These systems often depend on handcrafted feature extraction or limited automatic feature learning, which restricts their ability to capture complex retinal patterns. Many models are trained on small or imbalanced datasets, resulting in poor generalization and biased classification results. Variations in retinal image quality, including noise, low contrast, and uneven illumination, further degrade performance. Additionally, distinguishing between similar severity levels such as mild and moderate DR remains a significant challenge due to subtle visual differences. Most traditional approaches are not robust enough to handle large-scale clinical data effectively. These limitations reduce the overall reliability of automated detection systems. Moreover, inconsistent dataset quality further impacts model performance across different environments.

Another major limitation of existing systems is their high computational complexity and lack of efficiency. Many deep learning models require large computational resources and long training times, making them unsuitable for real-time or resource-constrained environments. Furthermore, these systems often lack effective preprocessing and data augmentation techniques, which are essential for improving model performance and robustness. The absence of optimization strategies also leads to overfitting, reducing accuracy on unseen data. In many cases, models are not designed to handle diverse datasets, limiting their applicability in real-world healthcare scenarios.

In addition, most existing diabetic retinopathy detection systems function as black-box models without providing clear explanations for their predictions. This lack of interpretability reduces trust among medical professionals and limits clinical adoption. Many systems are not integrated into real-time healthcare workflows, making deployment difficult in hospitals and diagnostic centers. Moreover, limited use of transfer learning restricts their ability to leverage pre-trained knowledge for improved accuracy. These challenges highlight the need for a more efficient, scalable, and reliable automated detection system.

2.3 Research Gap

Despite significant advancements in deep learning for diabetic retinopathy detection, several research gaps still remain. Many existing models struggle to handle class imbalance in datasets, which leads to biased predictions and reduced performance for minority classes. Variations in retinal image quality, such as noise and lighting conditions, also affect model accuracy. Additionally, most systems face difficulty in accurately distinguishing between intermediate stages like mild and moderate DR, where visual differences are minimal. These limitations reduce the reliability of automated diagnostic systems. There is also a need for improved feature extraction techniques to capture fine retinal details more effectively.

Another important research gap is the lack of models that effectively balance high accuracy with computational efficiency. Many advanced deep learning architectures achieve good performance but require high computational power, making them unsuitable for real-time deployment in resource-limited environments. There is also limited use of optimized architectures that can provide faster inference while maintaining accuracy. Furthermore, insufficient use of transfer learning techniques prevents models from fully utilizing pre-trained knowledge, reducing their effectiveness on medical datasets. Efficient model design is essential for practical healthcare applications.

Moreover, most existing systems lack interpretability and real-world applicability. The absence of explainable AI techniques makes it difficult for clinicians to understand and trust model predictions. There is also limited integration of these systems into clinical workflows, which restricts their practical use in healthcare settings. Therefore, there is a need for a robust and efficient deep learning model that improves classification accuracy, reduces computational cost, enhances interpretability, and supports real-time deployment in clinical environments. Future systems should also focus on scalability and adaptability to different datasets and healthcare conditions.

Chapter 3

PROJECT DESCRIPTION

3.1 Existing System

The existing diabetic retinopathy detection systems primarily rely on traditional diagnostic methods and basic machine learning techniques for identifying retinal abnormalities. In conventional approaches, ophthalmologists manually examine retinal fundus images to detect features such as microaneurysms, hemorrhages, and exudates, which indicate the presence and severity of the disease. This process is time-consuming, requires expert knowledge, and may lead to variations in diagnosis due to human error. Some automated systems use machine learning algorithms such as Support Vector Machines (SVM), K-Nearest Neighbors (KNN), and Decision Trees for classification. These methods depend heavily on manual feature extraction techniques, which limit their ability to capture complex patterns in retinal images. Variations in image quality, illumination, and noise further affect the performance of these systems. Early-stage detection is particularly challenging due to subtle retinal changes. The increasing number of diabetic patients makes manual screening inefficient and difficult to scale. These systems also require continuous monitoring and expert validation. As a result, traditional approaches are not sufficient for large-scale automated screening. These limitations highlight the need for improved diagnostic systems.

Existing systems also face challenges in handling large-scale datasets and adapting to real-world conditions. Traditional methods struggle to generalize across diverse datasets and often show reduced accuracy when applied to different environments. The presence of noise, low contrast, and variations in image acquisition further reduces performance. Manual feature engineering increases computational complexity and requires domain expertise. Many systems lack real-time processing capabilities, which limits their practical application in healthcare settings. These drawbacks emphasize the need for a robust and automated system that can improve accuracy and efficiency.

3.2 Proposed System

The proposed diabetic retinopathy detection system utilizes advanced deep learning techniques to improve the accuracy and efficiency of retinal image analysis. Convolutional Neural Networks (CNN) with the EfficientNet-B3 architecture are used to automatically extract relevant features from retinal fundus images without the need for manual feature engineering. The system is trained using large-scale datasets such as APTOS and EyePACS, which enables it to handle variations in image quality, illumination, and retinal patterns effectively. Image preprocessing techniques such as resizing, normalization, and contrast enhancement using CLAHE are applied to improve the quality of input images and ensure consistent performance. The structured workflow includes image acquisition, preprocessing, feature extraction, and classification. The deep learning model identifies important retinal abnormalities such as microaneurysms, hemorrhages, and exudates. These features are essential for determining the severity of diabetic retinopathy. The system is designed to process large volumes of medical images efficiently. Automated feature extraction improves accuracy and reduces human intervention. The model ensures better generalization across different datasets. This approach enhances overall diagnostic performance in medical image analysis.

The classification module categorizes retinal images into different stages such as No DR, Mild, Moderate, Severe, and Proliferative DR. The system provides prediction results along with confidence scores for better interpretation. Visualization techniques such as Grad-CAM are used to highlight affected regions in the retina. The system supports fast and reliable predictions suitable for real-time healthcare applications. Improved scalability allows deployment in hospitals, clinics, and remote healthcare systems. The automated process reduces workload on medical professionals and improves screening efficiency. The system ensures consistent and accurate results across different conditions. It can be extended with advanced deep learning models for improved performance. Integration with healthcare systems enhances practical usability. This makes the proposed system a reliable and efficient solution for diabetic retinopathy detection.

3.3 Feasibility Study

3.3.1 Economic Feasibility

The proposed diabetic retinopathy detection system is economically feasible as it utilizes open-source tools and technologies for development and implementation. The use of Python, TensorFlow, Keras, and OpenCV reduces the overall software cost significantly. Pre-trained deep learning models minimize the need for extensive training, which helps in reducing computational expenses. The system can be executed on standard computing devices without requiring high-end hardware, making it cost-effective for hospitals and diagnostic centers. The availability of public datasets such as APTOS and EyePACS eliminates the need for costly data collection. Maintenance costs are also low due to the use of widely supported frameworks and libraries. The system reduces the workload of medical professionals by automating the screening process. This leads to better utilization of resources and improves operational efficiency. The scalability of the system ensures that it can be deployed in multiple locations without additional cost. It also supports integration with existing healthcare infrastructure, reducing implementation expenses. The use of efficient algorithms ensures reduced processing time and energy consumption. Overall, the system provides a cost-effective solution for large-scale diabetic retinopathy screening. This makes it suitable for real-world healthcare applications.

3.3.2 Technical Feasibility

The system is technically feasible as it is based on well-established deep learning and computer vision techniques. EfficientNet-B3 provides high accuracy and optimized performance for medical image classification tasks. The system utilizes preprocessing techniques to enhance image quality and improve model performance. It supports implementation using widely available tools such as Python and deep learning frameworks. The availability of large datasets enables effective training and validation of the model. The system can be deployed on standard platforms such as Windows and Linux environments. With GPU support, faster processing and real-time performance can be achieved.

The architecture of the system ensures efficient handling of large-scale image data and supports automated feature extraction. The model is capable of generalizing across different datasets and conditions, improving reliability. Integration with visualization techniques enhances interpretability of results. The system design allows easy modification and extension with advanced models. It supports scalable deployment in real-world healthcare environments. Efficient memory and resource management ensures stable system performance. The use of optimized algorithms reduces computational complexity. Overall, the system meets all technical requirements for practical implementation.

3.3.3 Social Feasibility

The proposed diabetic retinopathy detection system is socially feasible as it provides significant benefits in improving healthcare services and early disease detection. The system helps in identifying diabetic retinopathy at an early stage, which reduces the risk of vision loss and improves patient outcomes. It enhances accessibility to diagnostic services, especially in rural and underdeveloped areas where medical experts are not readily available. Automated screening reduces the dependency on ophthalmologists and allows faster diagnosis for a large number of patients. The system supports healthcare professionals by providing accurate and consistent results, minimizing human error in diagnosis. It also promotes the use of artificial intelligence in the medical field, contributing to technological advancement in healthcare. The system can be used in hospitals, clinics, and remote healthcare centers, making it widely applicable. By reducing the time required for diagnosis, it improves the efficiency of healthcare services. The system also helps in raising awareness about the importance of regular eye screening among diabetic patients. Proper handling of medical data ensures privacy and ethical usage of patient information. The system can be integrated into existing healthcare infrastructure without major changes. It supports large-scale screening programs and improves overall healthcare management. The use of advanced technology ensures better reliability and trust among users. Overall, the system contributes to improved quality of life and better healthcare accessibility.

3.4 System Specification

3.4.1 Hardware Specification

- Processor: Intel Core i5 (10th Gen or higher) / AMD Ryzen 5 or equivalent
- RAM: Minimum 8GB (Recommended 16GB for better performance)
- GPU: NVIDIA GPU with CUDA support (Optional but recommended for deep learning acceleration)
- Storage: Minimum 256GB SSD (Recommended 512GB SSD for faster processing)
- Display: Standard monitor with minimum resolution of 1366×768
- Input Device: Keyboard and Mouse
- Operating System: Windows 10/11 or Linux (Ubuntu 20.04 or higher)
- Power Supply: Standard power adapter for laptops or 500W+ SMPS for desktops
- Internet Connectivity: Required for dataset download, updates, and model integration

3.4.2 Software Specification

- Programming Language: Python 3.7 or higher
- Deep Learning Framework: TensorFlow / Keras
- Computer Vision Library: OpenCV
- Image Processing Libraries: NumPy, PIL (Python Imaging Library)
- Data Handling Libraries: Pandas, Matplotlib
- Development Environment: Jupyter Notebook / Google Colab / VS Code
- Operating System: Windows / Linux / macOS
- Dataset: APTOS 2019, EyePACS retinal fundus image datasets
- Model Architecture: EfficientNet-B3
- Dependency Management: pip / conda

3.4.3 Standards and Policies

Data Privacy

All retinal fundus images used in this system are anonymized to ensure that no patient-identifiable information such as names, IDs, or personal records is included. The datasets utilized, including APTOS 2019 and EyePACS, are publicly available and already comply with ethical data-sharing standards.

Data privacy is maintained throughout the system by securely storing and processing images without exposing sensitive information. Access to the data is restricted, and proper data handling procedures are followed to prevent unauthorized use. The system adheres to standard data protection practices to ensure confidentiality, integrity, and security of medical data. These measures are essential in healthcare applications to maintain trust and comply with ethical guidelines.

Standard Used: ISO/IEC 27001

Model Reproducibility

The proposed deep learning model ensures reproducibility by maintaining consistency across different training runs. Random seeds (seed = 42) are fixed for libraries such as NumPy, TensorFlow, and Python to ensure that results remain consistent. This helps in achieving stable performance and reliable evaluation metrics.

Additionally, the entire codebase is managed using version control systems such as GitHub, allowing tracking of changes and maintaining transparency in model development. The use of fixed hyperparameters, structured data preprocessing steps, and documented training procedures further enhances reproducibility.

Environment configurations, including library versions and dependencies, are also maintained using tools such as pip or conda to ensure that the model can be replicated on different systems without inconsistencies. These practices make the system reliable and suitable for real-world medical applications.

Standard Used: ISO/IEC 27001

Chapter 4

METHODOLOGY

4.1 General Architecture for Diabetic Retinopathy Detection




Figure 4.1: Architecture Diagram for Diabetic Retinopathy Detection

The architecture diagram of the Diabetic Retinopathy Detection System shown in Figure 4.1 illustrates the overall workflow of the system. The process begins with retinal image collection from datasets such as APTOS and EyePACS. The images are preprocessed using resizing, normalization, noise reduction, and data augmentation techniques. The processed images are passed to the feature extraction module using EfficientNet-B3 with transfer learning. Important retinal features such as microaneurysms, hemorrhages, and exudates are extracted. These features are used in the classification stage with Softmax activation to determine severity levels. The system generates the final output indicating the predicted stage of diabetic retinopathy.

4.2 Design Phase

4.2.1 Data Flow Diagram




Figure 4.2: Data Flow Diagram of Retinal Image Processing

The Data Flow Diagram of the Diabetic Retinal Image Processing System shown in Figure 4.2 represents the flow of data from input to output. The process begins with image input collected from datasets such as APTOS and EyePACS. The input images are passed to the module where resizing, normalization, and enhancement are performed. The processed images are then forwarded to the feature extraction stage using Efficient Net-B3. Important retinal features are extracted and passed to the classification module. The classification stage uses Softmax activation to categorize images into different levels. The system generates the final output indicates the predicted stage of diabetic retinopathy. The overall flow ensures efficient and accurate processing of retinal images.

4.2.2 Sequence diagram




Figure 4.3: Sequence diagram of System Work Flow

The Sequence diagram of System Work Flow shown in Figure 4.3 represents the interaction between different system components in a sequential manner. The process begins with the user uploading retinal fundus images into the system. The system receives the input and sends it to the preprocessing module for resizing, normalization, and enhancement. The preprocessed images are then passed to the feature extraction module using EfficientNet-B3. Important retinal features such as microaneurysms, hemorrhages, and exudates are extracted. These features are forwarded to the classification module for analysis. The classification stage determines the severity level of diabetic retinopathy. The system processes the data and generates prediction results. The output is then sent to the result display module. The user can view the predicted results along with relevant information. The interaction between components ensures proper data flow and processing. This sequence improves system efficiency and accuracy.

4.2.3 Activity Diagram




Figure 4.4: Activity diagram of Detection Process

The Activity Diagram of Detection Process System shown in Figure 4.4 represents the flow of activities involved in the system from input to output. The process starts with the user uploading retinal fundus images into the system. The system receives the images and begins the preprocessing stage. In this stage, operations such as resizing, normalization, noise reduction, and enhancement are performed. The processed images are then forwarded to the feature extraction module. EfficientNet-B3 is used to extract important retinal features required for analysis. The extracted features are passed to the classification stage. The classification module categorizes the images into different diabetic retinopathy severity levels. Based on the classification, the system generates prediction results. The results are processed and prepared for display. The output is then shown to the user along with relevant details. The user can view and analyze the results for further action. The flow continues smoothly between each stage of the system. Decision points ensure proper classification and processing of images. The activity flow ensures accurate and efficient detection of diabetic retinopathy.

4.3 Algorithm & Pseudo Code

4.3.1 Convolutional Neural Network

Step 1: Model Initialization and Setup

- Load the pre-trained EfficientNet-B3 model, which is optimized for high accuracy and computational efficiency in image classification tasks.
- Import required libraries such as TensorFlow, Keras, OpenCV, NumPy, Pandas, and Matplotlib for model development and visualization.
- Define the input image size (300×300 pixels) to ensure compatibility with the EfficientNet-B3 architecture.
- Initialize preprocessing parameters including normalization, scaling, and image standardization.
- Load retinal fundus image datasets from APTOS 2019 and EyePACS sources.
- Perform data augmentation techniques such as rotation, flipping, zooming, and brightness adjustment to increase dataset diversity.
- Split the dataset into training (70%), validation (15%), and testing (15%) sets for proper evaluation.
- Configure hyperparameters such as learning rate, batch size, and number of epochs for model training.

Step 2: Image Preprocessing

- Load the retinal fundus image as input to the system.
- Resize the image to 300×300 pixels to maintain uniformity.
- Normalize pixel intensity values to a fixed range (0 to 1) to improve convergence during training.
- Apply Contrast Limited Adaptive Histogram Equalization (CLAHE) to enhance important retinal features.
- Perform noise reduction techniques such as Gaussian filtering to remove unwanted distortions.
- Apply image centering and cropping to focus on the region of interest.

Step 3: Feature Extraction

- Pass the preprocessed image through the EfficientNet-B3 convolutional layers.
- Automatically extract deep hierarchical features from the retinal images.
- Detect key patterns such as microaneurysms, hemorrhages, and exudates.
- Generate feature maps that represent spatial and semantic information.
- Apply global average pooling to reduce dimensionality and retain essential features.

Step 4: Classification

- Feed the extracted features into fully connected layers for classification.
- Apply Softmax activation function for multi-class prediction.
- Classify the image into diabetic retinopathy stages: No DR, Mild, Moderate, Severe, and Proliferative DR.
- Compute class probabilities and select the highest probability as the final prediction.

Step 5: Display Results

- Generate prediction output based on the classification results.
- Display the predicted diabetic retinopathy stage clearly to the user.
- Show confidence scores (probability values) for each class.
- Visualize affected retinal regions using Grad-CAM for better interpretability.
- Provide graphical outputs such as probability charts for better understanding.

Step 6: System Control and Optimization

- Allow users to upload and analyze multiple retinal images efficiently.
- Handle exceptions and errors during preprocessing and classification stages.
- Ensure continuous system operation even if individual predictions fail.
- Optimize performance using GPU acceleration to reduce computation time.
- Monitor system performance and improve efficiency using batch processing techniques.

BEGIN

Step 1: Initialize System

```
Load EfficientNet-B3 pre-trained model
Import required libraries (TensorFlow, Keras, OpenCV, NumPy)
Set input image size (300 x 300)
Initialize hyperparameters (learning rate, batch size)
Set random seed for reproducibility
```

Step 2: Load Dataset

```
Load retinal fundus images from APTOS and EyePACS
Split dataset into training, validation, and testing sets
Apply data augmentation (rotation, flipping, zooming)
```

Step 3: Input Image

```
Read retinal fundus image
Validate image format and size
Store image for processing
```

Step 4: Preprocessing

- Resize image to 300 x 300
- Normalize pixel values (0 to 1)
- Apply CLAHE for contrast enhancement
- Apply Gaussian filtering for noise removal
- Crop and center region of interest

Step 5: Feature Extraction

- Pass image through EfficientNet-B3 convolution layers
- Extract deep features from retinal image
- Generate feature maps
- Apply global average pooling

Step 6: Classification

- Pass features to fully connected layers
- Apply Softmax activation function
- Compute class probabilities
- Classify image into DR stages:
 - No DR, Mild, Moderate, Severe, Proliferative DR

Step 7: Output Generation

- Display predicted class label
- Show confidence score (probability)
- Highlight affected regions using Grad-CAM
- Store prediction results

Step 8: Performance Check

- Evaluate model using accuracy, precision, recall, F1-score
- Generate confusion matrix

Step 9: Repeat

- If more images available:
 - Go to Step 3
- Else:
 - Stop

END

4.4 Module Description

4.4.1 Data Collection

The data collection module is responsible for gathering retinal fundus images required for training and testing the system. The images are obtained from publicly available datasets such as APTOS 2019 and EyePACS. These datasets contain labeled images representing different stages of diabetic retinopathy. In total, approximately 30,000 retinal images are collected and used in this project. The collected data includes variations in image quality, lighting conditions, and disease severity, which helps improve model generalization. The images are organized and stored in a structured format for efficient processing. Proper data collection ensures balanced representation of all classes and improves the overall performance of the system. The collected dataset also includes both normal and abnormal retinal images, which helps the model learn different retinal patterns effectively. Proper labeling and categorization of the dataset improve classification accuracy and reduce prediction errors during testing.

4.4.2 Image Preprocessing

The image preprocessing module prepares the retinal images for analysis by enhancing quality and ensuring uniformity. Each image is resized to a fixed dimension (300×300 pixels) to match the model input requirements. Pixel values are normalized to improve model performance and stability. Contrast enhancement techniques such as CLAHE are applied to highlight important retinal features. Noise reduction methods are used to remove unwanted distortions. Data augmentation techniques such as rotation, flipping, and scaling are applied to increase dataset diversity. These steps ensure that the images are standardized and suitable for deep learning. Preprocessing also improves the visibility of retinal lesions and enhances important image features required for accurate classification. The preprocessing stage reduces unwanted variations between images and improves overall model robustness.

$$I' = \frac{I - \mu}{255} \quad (4.1)$$

4.4.3 Model Development

The model development module focuses on building the deep learning model for diabetic retinopathy detection. EfficientNet-B3 architecture is used due to its high accuracy and efficiency in image classification tasks. Transfer learning is applied by using pre-trained weights and fine-tuning the model on retinal datasets. The convolutional layers extract important features such as microaneurysms, hemorrhages, and exudates. The model is designed to automatically learn complex patterns from input images without manual feature extraction. This module forms the core of the system. Dropout layers and batch normalization techniques are incorporated to improve training stability and reduce overfitting. The final classification layer uses Softmax activation to classify retinal images into different diabetic retinopathy severity levels. The developed model achieves better performance with reduced computational complexity, making it suitable for real-time medical image analysis applications. The architecture efficiently balances model depth, width, and image resolution to improve feature learning capability. Fine-tuning of hyperparameters is performed to enhance classification accuracy and optimize overall model performance. The system automatically

identifies retinal abnormalities by learning discriminative visual patterns from fundus images. Feature maps generated by convolutional layers help in detecting important retinal lesion regions effectively. The developed model supports automated screening and assists ophthalmologists in early diabetic retinopathy diagnosis.

4.4.4 Training and Validation

The training and validation module is responsible for training the model using labeled datasets and evaluating its performance during training. The dataset is split into training, validation, and testing sets in the ratio of 70%, 15%, and 15% respectively to ensure proper evaluation. The model learns patterns from training data and is validated using validation data to avoid overfitting. Optimization techniques such as Adam optimizer and categorical cross-entropy loss function are used. The training process is carried out over multiple epochs to improve model learning and convergence. Data augmentation techniques such as rotation, flipping, zooming, and scaling are applied to enhance dataset diversity and improve generalization capability. Early stopping and model checkpointing are implemented to monitor validation loss and prevent overfitting. Batch normalization and dropout layers are also used to stabilize training and improve model performance. The learning rate is adjusted dynamically to achieve better convergence and accuracy. This module ensures that the model is trained efficiently and produces reliable results. The model performance is continuously monitored during each epoch to track improvements in accuracy and loss values. Training logs and validation metrics are stored for further analysis and comparison. Proper validation techniques help in improving model reliability and ensure better prediction performance on unseen retinal images.

4.4.5 Evaluation

The evaluation module assesses the performance of the trained model using various metrics. The model is tested using unseen data to measure its accuracy and reliability. Performance metrics such as accuracy, precision, recall, and F1-score are calculated. Confusion matrix analysis is also used to evaluate classification performance and understand misclassification patterns. The evaluation results help in identifying strengths and limitations of the model for further improvement. Comparative analysis with existing models is performed to validate the effectiveness of the proposed system. Visualization techniques such as performance graphs, loss curves, and ROC curves are used to better interpret the model results. The system also evaluates prediction confidence levels to ensure reliability in medical diagnosis. This comprehensive evaluation ensures the robustness and effectiveness of the diabetic retinopathy detection system. The evaluation process also helps in detecting classification errors and improving model optimization strategies. Different retinal image samples are tested to verify the consistency and stability of the model predictions. The obtained results demonstrate that the proposed system achieves reliable diabetic retinopathy classification with improved diagnostic accuracy.

Chapter 5

IMPLEMENTATION AND TESTING

5.1 Input and Output

5.1.1 Input Design of Retinal Fundus Image

The input design of the Diabetic Retinopathy Detection System plays a crucial role in ensuring accurate and reliable predictions. The system accepts retinal fundus images as the primary input, which can be obtained from publicly available datasets such as APTOS 2019 and EyePACS or uploaded by the user from local storage. The system supports multiple image formats including JPEG, PNG, and BMP, allowing flexibility in data input. Once an image is provided, the system initiates preprocessing steps to standardize the input and improve the quality of analysis. The images are resized to a fixed dimension of 224×224 pixels to match the input requirements of the EfficientNet-B3 deep learning model. Pixel values are normalized to ensure consistency across different images and to reduce the impact of varying lighting conditions. In addition, image enhancement techniques such as contrast adjustment and noise reduction are applied to improve the visibility of important retinal features. After preprocessing, the system focuses on isolating relevant regions within the retinal image that are essential for disease detection. The enhanced images are then passed to the feature extraction module, where deep learning techniques identify critical features such as microaneurysms, hemorrhages, and exudates. These features are significant indicators of diabetic retinopathy and are used for classification. The system is designed to handle variations in image quality, resolution, and illumination, ensuring robust performance across different datasets. Validation checks are also performed to detect and handle invalid inputs such as blurred images or incomplete retinal scans. If an image does not meet the required quality standards, the system prompts the user to provide a better-quality image. Furthermore, the input design ensures efficient data handling and smooth integration with the deep learning pipeline. The system is capable of processing multiple images sequentially, making it suitable for large-scale screening applications. Proper preprocessing and input validation significantly improve the performance and accuracy of the model. By ensuring that only high-quality and standardized images are used, the system enhances the reliability and consistency of diabetic retinopathy detection, making it suitable for real-world healthcare applications.




Figure 5.1: Input Design of Retinal Fundus Image

The input design result shown in Figure 5.1 illustrates the process of selecting and loading retinal fundus images into the system. The interface allows users to browse and choose images from the dataset for further processing. It ensures that the input images are properly visualized before undergoing preprocessing steps. The system verifies image quality and compatibility with the model requirements. This design improves user interaction and ensures smooth data flow into the diabetic retinopathy detection pipeline.

5.1.2 Output Design for Prediction and Classification

The output design of the Diabetic Retinopathy Detection System is structured to provide accurate, clear, and user-friendly presentation of the prediction results. After processing the input retinal fundus image through various stages such as preprocessing, feature extraction, and classification, the system generates the final output indicating the severity level of diabetic retinopathy. The output is displayed in a well-organized format to ensure easy interpretation by users, including healthcare professionals. The primary components of the output design include predicted class labels, confidence scores, and visual representations of affected regions. The system classifies retinal images into categories such as No DR, Mild, Moderate, Severe, and Proliferative DR, and displays the predicted class prominently. The prediction results are accompanied by probability scores, which indicate the confidence level of the model for each classification. For instance, the output may display results such as “Moderate DR (Confidence: 99), helping users understand the reliability of the prediction. To enhance interpretability, the system incorporates visualization techniques such as Grad-CAM, which highlights the important regions in the retinal image that contribute to the prediction.

The system also supports multiple output formats for flexibility and usability. The prediction results can be displayed directly on the screen or stored in structured formats such as CSV or JSON for further analysis and record-keeping. In addition, the system can be integrated with external healthcare applications, where outputs can be shared through APIs for seamless communication. The design ensures that the results are clearly presented across different platforms including desktop and web-based interfaces. Furthermore, the output design includes mechanisms to handle uncertainty and improve decision-making. In cases where the confidence score is low, the system can indicate uncertainty and suggest further medical examination. The system is also capable of processing multiple images sequentially and displaying results for each input efficiently. Overall, the output design focuses on delivering accurate, interpretable, and accessible results, making the system suitable for real-world clinical and screening applications.




Figure 5.2: Output Design for Prediction and Classification

The output design for Prediction and Classification System is shown in Figure 5.2 after processing the retinal fundus image. The system displays the segmented retinal regions and analyzed output in an organized interface for easy interpretation. It provides detected abnormality information along with prediction values to support diagnosis. This output design improves usability and helps users understand the prediction results effectively.

5.2 Testing

Testing is an important phase in the development of the Diabetic Retinopathy Detection System, ensuring that each module functions correctly, integrates smoothly, and performs accurately on retinal images. The system undergoes various levels of testing to validate its efficiency, reliability, and accuracy. Testing helps in identifying errors, improving system performance, and ensuring that the model meets the required objectives. Different types of testing such as unit testing, integration testing, and system testing are carried out to evaluate the overall functionality of the system.

5.2.1 Unit Testing

Unit testing is performed to verify the functionality of individual modules of the Diabetic Retinopathy Detection System before integration. The goal is to ensure that each component produces the correct output for a given input. The main modules tested in unit testing include image preprocessing, feature extraction using EfficientNet-B3, and classification of diabetic retinopathy stages. For the preprocessing module, testing ensures that input retinal images are correctly resized, normalized, and enhanced. For the feature extraction module, the model is tested to confirm that meaningful features such as microaneurysms, hemorrhages, and exudates are properly identified. In the classification module, test cases include images from different severity levels such as No DR, Mild, Moderate, Severe, and Proliferative DR. The expected result is that the model accurately classifies the input image into the correct category. Unit testing helps in detecting errors early and ensures the reliability of each individual component before system integration.

Input

```
1 import cv2
2 import numpy as np
3 from tensorflow.keras.models import load_model
4
5 # Load trained model
6 model = load_model("efficientnet_b3_dr_model.h5")
7
8 # Class labels
9 classes = ["No DR", "Mild", "Moderate", "Severe", "Proliferative DR"]
10
11 # Function to preprocess image
12 def preprocess_image(img_path):
13     image = cv2.imread(img_path)
14
15     assert image is not None, "Error: Image not loaded properly"
16
17     # Resize to 224x224
18     image = cv2.resize(image, (224, 224))
19
20     # Normalize
21     image = image / 255.0
22
```



```

23     # Expand dimensions
24     image = np.expand_dims(image, axis=0)
25
26     return image
27
28 # Load test image
29 img_path = "test_image.jpg"
30 image = preprocess_image(img_path)
31
32 print("Image loaded and preprocessed successfully for Unit Test")
33
34 # Prediction
35 pred = model.predict(image)
36
37 assert pred is not None, "Error: Model prediction failed"
38
39 predicted_class = classes[np.argmax(pred)]
40 confidence = np.max(pred)
41
42 print("Unit Test Passed")
43 print(f"Predicted Class: {predicted_class}")
44 print(f"Confidence: {confidence:.2f}")

```

Test Result




Figure 5.3: Unit Testing Result of the Model

The unit testing result shown in Figure 5.3 demonstrates the successful validation of individual modules in the Diabetic Retinopathy Detection System. The output screen confirms that the input image is correctly processed and passed through the model. Each module, including preprocessing, feature extraction, and classification, is tested independently to ensure proper functionality. The results indicate that the model is able to generate predictions without errors. The displayed output verifies that the system correctly identifies the class of the retinal image. Confidence values further indicate the reliability of the prediction results. The successful execution of unit testing ensures that each component works accurately before integration. This improves the overall reliability and stability of the system.

5.2.2 Integration Testing

Integration testing evaluates how well the individual modules of the Diabetic Retinopathy Detection System interact with each other when combined. The preprocessing, feature extraction, and classification modules must work together seamlessly to ensure smooth data flow. The preprocessing module prepares retinal images by resizing and normalizing them before passing them to the EfficientNet-B3 model. The feature extraction module processes the images and extracts meaningful features, which are then forwarded to the classification module. Integration testing verifies that there is no data loss or mismatch between modules. Test cases include processing multiple retinal images with varying quality and resolution. The expected result is that the system processes images correctly through all stages and produces accurate predictions without errors or interruptions.

Input

```
1 import cv2
2 import numpy as np
3 from tensorflow.keras.models import load_model
4
5 model = load_model("efficientnet_b3_dr_model.h5")
6
7 classes = ["No DR", "Mild", "Moderate", "Severe", "Proliferative DR"]
8
9 def full_pipeline(img_path):
10     # Preprocessing
11     image = cv2.imread(img_path)
12     assert image is not None, "Image loading failed"
13
14     image = cv2.resize(image, (224, 224))
15     image = image / 255.0
16     image = np.expand_dims(image, axis=0)
17
18     # Prediction
19     pred = model.predict(image)
20     assert pred is not None, "Prediction failed"
21
22     label = classes[np.argmax(pred)]
23
24     return label
25
26 # Test integration
27 result = full_pipeline("test_image.jpg")
28
29 print("Integration Test Passed")
30 print("Prediction:", result)
```

5.2.3 System Testing

System testing is performed to evaluate the complete functionality of the Diabetic Retinopathy Detection System in real-world conditions. In this stage, the fully integrated system is tested using different retinal fundus images to ensure accurate and reliable predictions. The system is validated for handling input images, processing them through preprocessing, feature extraction, and classification modules, and generating correct outputs. Test cases include images with varying quality, resolution, and disease severity levels. Performance metrics such as accuracy, precision, recall, and F1-score are used to evaluate system performance. The expected result is that the system consistently produces accurate predictions and operates smoothly in real-time applications.

Input

```
1 import cv2
2 import numpy as np
3 from tensorflow.keras.models import load_model
4 import os
5
6 # Load model
7 model = load_model("efficientnet_b3_dr_model.h5")
8
9 classes = ["No DR", "Mild", "Moderate", "Severe", "Proliferative DR"]
10
11 # Folder containing test images
12 test_folder = "test_images/"
13
14 def test_system(folder_path):
15     for file in os.listdir(folder_path):
16         if file.endswith(".jpg") or file.endswith(".png"):
17             img_path = os.path.join(folder_path, file)
18
19             image = cv2.imread(img_path)
20             if image is None:
21                 print(f"Skipping {file} (invalid image)")
22                 continue
23
24             # Preprocessing
25             image = cv2.resize(image, (224, 224))
26             image = image / 255.0
27             image = np.expand_dims(image, axis=0)
28
29             # Prediction
30             pred = model.predict(image)
31             label = classes[np.argmax(pred)]
32             confidence = np.max(pred)
33
34             print(f"Image: {file}")
35             print(f"Prediction: {label}, Confidence: {confidence:.2f}")
36             print("-" * 40)
37
38 # Run system test
39 test_system(test_folder)
40
41 print("System Testing Completed Successfully")
```

5.2.4 Test Result




Figure 5.4: Test Image for Diabetic Retinopathy Detection

The test result of the Diabetic Retinopathy Detection System is shown in Figure 5.4 , which demonstrates the model's ability to process retinal images and generate accurate predictions. The system successfully loads and preprocesses the input image before passing it to the EfficientNet-B3 model for classification. The output displays the detected retinal features and highlights the affected regions clearly. The model effectively identifies different stages of diabetic retinopathy based on learned patterns. The prediction results include the classified category along with confidence levels, ensuring reliability. The system performs efficiently even with variations in image quality and illumination. Overall, the results confirm that the proposed model provides accurate and consistent predictions for diabetic retinopathy detection.

Chapter 6

RESULTS AND DISCUSSIONS

6.1 Efficiency of the Proposed System

The proposed system demonstrates significant improvements in the detection and classification of diabetic retinopathy using deep learning techniques. By utilizing the EfficientNet-B3 architecture, the model effectively extracts complex retinal features such as microaneurysms, hemorrhages, and exudates from fundus images. Unlike traditional diagnostic approaches that rely heavily on manual analysis, the system automates the entire process, reducing human effort and minimizing diagnostic errors. The preprocessing stage, including image resizing, normalization, and data augmentation, ensures that input images are standardized and robust against variations in lighting and noise. This enhances the consistency of predictions across different datasets such as APTOS and EyePACS. Furthermore, transfer learning helps in improving model performance by leveraging pre-trained knowledge, enabling faster convergence and better generalization. As a result, the system achieves high classification accuracy across multiple severity levels of diabetic retinopathy, demonstrating its effectiveness in real-world applications.

In addition to accuracy, the proposed system exhibits strong computational efficiency and scalability. The integration of TensorFlow and OpenCV enables faster processing and real-time inference capabilities, making the system suitable for practical deployment in healthcare environments. GPU acceleration further reduces processing time, allowing the system to handle large volumes of retinal images efficiently without significant delay. Performance evaluation using metrics such as accuracy, precision, recall, and F1-score confirms the reliability of the model. The confusion matrix analysis indicates that the system can accurately distinguish between different stages of diabetic retinopathy with minimal misclassification. Moreover, the model shows strong generalization when tested on unseen data, ensuring consistent performance. Overall, the proposed system provides a fast, reliable, and scalable solution for automated diabetic retinopathy detection, supporting early diagnosis and assisting medical professionals in improving patient care outcomes.

The proposed system also improves the accessibility of diabetic retinopathy screening by reducing dependency on specialized medical experts for initial diagnosis. The automated framework can assist healthcare professionals in conducting large-scale retinal screening programs more efficiently and accurately. Early identification of retinal abnormalities helps in timely treatment and reduces the risk of severe vision loss among diabetic patients. The system can also be further enhanced by integrating explainable AI techniques, cloud-based deployment, and mobile healthcare support for remote diagnosis and real-time monitoring applications.

6.2 Comparison of Existing and Proposed System

Table 6.1: Comparison Between Existing and Proposed Diabetic Retinopathy Detection Systems

Feature	Existing System	Proposed System
Algorithm Used	Uses traditional deep learning techniques such as SVM, Random Forest, and basic CNN models.	Uses advanced deep learning model EfficientNet-B3 with transfer learning.
Feature Extraction	Requires manual feature extraction and domain knowledge for identifying retinal features.	Automatically extracts features like microaneurysms, hemorrhages, and exudates using CNN.
Handling Image Variations	Struggles with variations in lighting, noise, and image quality.	Handles variations effectively using preprocessing and data augmentation techniques.
Real-Time Processing	Limited real-time capability due to slower processing and manual intervention.	Supports faster inference and near real-time processing using optimized deep learning frameworks.
Accuracy	Moderate accuracy due to limited feature representation and simpler models.	High accuracy achieved using EfficientNet and large-scale datasets like APTOS and EyePACS.
Adaptability to New Data	Requires retraining from scratch with new datasets.	Uses transfer learning, enabling easy adaptation to new datasets with minimal retraining.
Computational Efficiency	Higher computational cost due to manual processing and inefficient models.	Optimized performance using GPU acceleration and efficient model architecture.
Application Areas	Limited to controlled clinical environments and small datasets.	Suitable for large-scale screening, real-world clinical applications, and telemedicine systems.

6.2.1 Existing System: Traditional and Early Deep Learning Models

The existing systems for DR detection and retinal image analysis rely on conventional image processing techniques and early deep learning models. Traditional methods such as thresholding, filtering, and handcrafted feature extraction are commonly used to identify retinal structures like blood vessels and lesions. However, these approaches depend heavily on manual calibration and predefined rules, making them less effective in handling complex retinal patterns and variations in OCTA images. According to the base paper, traditional segmentation techniques often fail due to

noise, artifacts, and device variability present in retinal images. These methods struggle to accurately differentiate between arteries, veins, and capillaries, especially when the structures are overlapping or unclear. Additionally, blurry boundaries of important regions such as the Foveal Avascular Zone (FAZ) further reduce segmentation accuracy. The lack of robust preprocessing techniques further affects the reliability of retinal image analysis. Variations in illumination and contrast also reduce the effectiveness of traditional segmentation approaches.

Even with the introduction of basic deep learning models like U-Net and standard CNN architectures, several limitations persist. These models face challenges in capturing multi-scale features and maintaining fine vascular details. They often suffer from poor generalization, high data dependency, and overfitting issues when trained on limited datasets. Moreover, existing models lack robustness in handling variations in image quality and fail to provide consistent performance across different datasets. Many existing systems also require high computational resources, limiting their real-time clinical applicability. In addition, the absence of efficient feature optimization techniques reduces overall classification performance. Due to these limitations, existing systems are not fully reliable for accurate and early detection of diabetic retinopathy. Hence, there is a need for more advanced deep learning architectures that can effectively extract multi-scale features, improve segmentation accuracy, and handle complex retinal structures in real-world clinical scenarios.

6.2.2 Proposed System: EfficientNet-B3

The proposed system uses a deep learning approach based on EfficientNet-B3 for detecting diabetic retinopathy from retinal fundus images. EfficientNet-B3 is an advanced Convolutional Neural Network (CNN) that provides high accuracy with optimized computational efficiency. It uses compound scaling to balance depth, width, and resolution, improving overall performance compared to traditional models. The architecture efficiently extracts both local and global retinal features required for accurate diabetic retinopathy classification. Transfer learning is also applied to improve learning efficiency and reduce training time.

In this system, input images are first preprocessed through resizing, normalization, and enhancement to improve quality. The processed images are then passed to the EfficientNet-B3 model, which automatically extracts important retinal features such as microaneurysms, hemorrhages, and exudates. These features are essential for identifying different stages of diabetic retinopathy. Overall, the proposed system offers higher accuracy, better generalization, and faster processing compared to traditional methods. It is suitable for real-time medical applications and helps in early detection of diabetic retinopathy, supporting doctors in effective diagnosis and treatment. The proposed framework also reduces manual effort and improves the consistency of retinal image analysis. Experimental results demonstrate that the system achieves reliable performance across different retinal image datasets.

6.3 Comparative Analysis-Graphical Representation




Figure 6.1: Graphical Representation of Model Performance

The comparative analysis shown in Figure 6.1 presents a graphical representation of the performance of the existing system and the proposed system. The chart clearly illustrates improvements in key metrics such as accuracy, precision, recall, and F1-score. The proposed system achieves higher accuracy due to the use of the EfficientNet-B3 deep learning model. It also demonstrates better precision and recall, indicating more reliable and consistent predictions. The F1-score highlights the balance between precision and recall, showing overall improved model performance. Additionally, the proposed system shows significant improvement in adaptability compared to the existing system. The speed of processing is also enhanced, making it suitable for real-time applications. The comparison table further supports that EfficientNet-B3 outperforms other models like InceptionV3 and CNN-based approaches. Overall, the figure confirms that the proposed system provides better efficiency, accuracy, and robustness for diabetic retinopathy detection.

Chapter 7

CONCLUSION AND FUTURE ENHANCEMENTS

7.1 Conclusion

The proposed Diabetic Retinopathy Detection System presents an effective and reliable approach for the automated diagnosis of diabetic retinopathy using deep learning techniques. In this project, the EfficientNet-B3 model is employed due to its ability to achieve high accuracy with optimized computational efficiency. The system processes retinal fundus images through multiple stages including preprocessing, feature extraction, and classification. Preprocessing techniques such as resizing, normalization, and image enhancement ensure that the input data is standardized and suitable for model training and inference. The deep learning model automatically extracts critical retinal features such as microaneurysms, hemorrhages, and exudates, which are key indicators of diabetic retinopathy.

The use of transfer learning significantly improves the model's performance by leveraging pre-trained weights, reducing the need for large datasets and long training time. The system is capable of classifying images into different severity levels such as No DR, Mild, Moderate, Severe, and Proliferative DR with high precision. Evaluation metrics such as accuracy, precision, recall, and F1-score demonstrate that the proposed system performs better than traditional machine learning approaches. Early detection of diabetic retinopathy is crucial in preventing vision loss and improving patient outcomes. By automating the screening process, the system reduces the workload on ophthalmologists and enables faster diagnosis, especially in regions with limited medical resources. Furthermore, the system is scalable and can be integrated into clinical workflows or deployed as a standalone application. In conclusion, the proposed system provides a cost-effective, accurate, and efficient solution for diabetic retinopathy detection. It demonstrates the potential of deep learning in medical image analysis and highlights how artificial intelligence can be used to improve healthcare services. The system not only enhances diagnostic accuracy but also contributes to early intervention and better treatment planning.

7.2 Limitation

The proposed system achieves improved accuracy in diabetic retinopathy detection, certain limitations still exist. The performance of the model highly depends on the quality and diversity of the training dataset. Poor-quality retinal images with excessive noise, blur, or low illumination may affect prediction accuracy. The system also requires high computational resources and GPU support

for efficient training and real-time inference. In some cases, misclassification may occur between similar severity stages such as Mild and Moderate diabetic retinopathy. The model performance can decrease when tested on unseen datasets with different image distributions. Additionally, the system currently focuses only on retinal fundus images and does not incorporate other clinical data for diagnosis. Further improvements are required to enhance interpretability, scalability, and robustness in real-world healthcare environments. The current system also requires continuous model updates to maintain performance with newly collected datasets. Limited availability of balanced medical datasets can affect the learning capability of the model. Future research can focus on integrating explainable AI techniques and lightweight architectures for improved clinical usability.

7.3 Future Enhancements

The proposed system can be further improved by incorporating larger and more diverse datasets to enhance model robustness and generalization. Training the model on a wide range of retinal images collected from different sources will help in achieving consistent performance across various real-world conditions. This will also reduce bias and improve the reliability of predictions. Advanced deep learning architectures can be explored to further improve system performance. Models such as higher versions of EfficientNet or transformer-based approaches like Vision Transformers can be used to achieve better accuracy and feature representation. These models have shown promising results in image classification tasks and can enhance the detection capability of diabetic retinopathy.

The integration of Explainable Artificial Intelligence (XAI) techniques can also be considered as an important enhancement. By providing visual explanations such as heatmaps, the system can highlight the regions of the retinal image that contribute to the prediction. This will help medical professionals better understand and trust the system's decisions. Models such as higher versions of EfficientNet or transformer-based approaches like Vision Transformers can be used to achieve better accuracy and feature representation. In addition, the system can be developed into a real-time or mobile-based application to improve accessibility, especially in rural and remote areas. Deploying the model on cloud platforms or mobile devices will enable large-scale screening and early diagnosis. Integration with hospital management systems can further streamline the workflow. Future work can also focus on extending the system to detect other retinal diseases such as glaucoma and cataract. By incorporating multi-disease detection capabilities, the system can become a comprehensive diagnostic tool. Performance optimization techniques like model compression and GPU acceleration can be used to improve speed and reduce computational cost. Overall, these enhancements aim to improve accuracy, scalability, usability, and real-world applicability of the system, making it more effective for medical diagnosis and healthcare support.

Chapter 8

ADDRESSING COMPLEX ENGINEERING PROBLEM AND SDG

8.1 Mapping of the Project to Complex Engineering Problem (CEP)

Table 8.1: Mapping of Project to Complex Engineering Problems (CEP)

Level	Attribute	Characteristics	Targeted WKs	Justification
WP1	Depth of Knowledge	Cannot be resolved without in-depth engineering knowledge at levels K3, K4, K5, K6 or K8.	WK3, WK4, WK5, WK6, WK8	Requires strong knowledge of deep learning, CNNs, and medical image processing for accurate DR detection.
WP2	Range of Conflicting Requirements	Involves wide-ranging and conflicting technical and non-technical issues.	WK4, WK5, WK6, WK8	Balances model accuracy, computational cost, and handling of large retinal datasets.
WP3	Depth of Analysis Required	No obvious solution and requires originality in analysis.	WK3, WK4, WK5, WK8	Requires analysis of complex retinal patterns and optimization of EfficientNet-B3.
WP4	Familiarity of Issues	Involves infrequently encountered or novel problems.	WK4, WK8	Deals with medical image classification and challenges like class imbalance.
WP5	Extent of Applicable Codes	Problems not fully covered by standard engineering practices.	WK6, WK8	Requires custom model design and validation for retinal image analysis.
WP6	Stakeholder Involvement	Involves multiple stakeholders with different requirements.	WK5, WK6, WK7	Involves doctors, patients, and developers for reliable diagnosis and usability.
WP7	Interdependence	High-level problem requiring system integration approach.	WK3, WK5, WK6	Integrates preprocessing, feature extraction, classification, and evaluation modules.

Mapping of Diabetic Retinopathy Detection System to Complex Engineering Problems (CEP)

8.2 Mapping of Project to Complex Engineering Activities (CEA)

Table 8.2: Mapping of Project to Complex Engineering Activities (CEA)

EA No.	Attribute	Characteristics	Justification based on the Project
EA1	Range of Resources	Involves diverse resources and technologies	The project utilizes large-scale datasets such as APTOS and EyePACS, deep learning frameworks like TensorFlow/Keras, and computational resources for training EfficientNet-B3.
EA2	Level of Interactions	Optimization of complex interactions	The system manages interactions between image preprocessing, feature extraction, model training, and classification to ensure accurate diabetic retinopathy detection.
EA3	Innovation	Creative and research-based solutions	The use of EfficientNet-B3 with transfer learning for retinal image classification demonstrates an innovative and efficient approach in medical image analysis.
EA4	Consequences to Society and Environment	Significant societal impact	The system helps in early detection of diabetic retinopathy, reducing vision loss and supporting healthcare professionals in timely diagnosis.
EA5	Familiarity	Extends beyond prior experience	The project applies advanced deep learning techniques and medical imaging concepts beyond conventional approaches, addressing real-world healthcare challenges.

8.3 SDG Mapping (CEP Section)

Table 8.3: SDG Mapping for Diabetic Retinopathy Detection System

SDG No.	SDG Title	Relevance to the Project
SDG 3	Good Health and Well-being	Enables early and accurate detection of diabetic retinopathy, improving patient outcomes and reducing vision loss. Supports access to quality healthcare services and assists doctors through AI-based diagnosis.
SDG 4	Quality Education	Supports learning in medical imaging and deep learning by providing a practical system for research, training, and interdisciplinary education in healthcare and AI.
SDG 9	Industry, Innovation and Infrastructure	Introduces advanced deep learning techniques using EfficientNet-B3 and transfer learning, promoting innovation in AI-driven healthcare systems and digital medical infrastructure.
SDG 10	Reduced Inequalities	Provides accessible diagnostic support for rural and underserved areas where expert ophthalmologists may not be available, reducing healthcare inequality.
SDG 17	Partnerships for the Goals	Encourages collaboration between healthcare professionals, researchers, and institutions, supporting data sharing and development of AI-based healthcare solutions.

Chapter 9

PLAGIARISM REPORT




Figure 9.1: Plagiarism Report Summary

Chapter 10

SOURCE CODE

10.1 Source Code

```
1
2 # Import required libraries
3 import numpy as np
4 import cv2
5 import os
6 from tensorflow.keras.models import load_model
7 from tensorflow.keras.preprocessing.image import img_to_array
8
9 # =====
10 # Model Loading Section
11 # =====
12
13 # Path to trained model
14 MODEL_PATH = "efficientnet_b3_dr_model.h5"
15
16 # Load the trained deep learning model
17 model = load_model(MODEL_PATH)
18
19 # Define class labels for DR stages
20 CLASS_LABELS = ['No DR', 'Mild', 'Moderate', 'Severe', 'Proliferative DR']
21
22 # Define input image size
23 IMG_SIZE = 224
24
25 # =====
26 # Image Preprocessing Function
27 # =====
28
29 def preprocess_image(image):
30     """
31     Resize, normalize and prepare image for prediction
32     """
33     # Resize image to required input size
34     image = cv2.resize(image, (IMG_SIZE, IMG_SIZE))
35
36     # Normalize pixel values (0 to 1)
37     image = image / 255.0
38
39     # Convert to array format
40     image = img_to_array(image)
41
42     # Expand dimensions for model input
43     image = np.expand_dims(image, axis=0)
44
45     return image
```



```

46
47 # =====
48 # Prediction Function
49 # =====
50
51 def predict_dr(image):
52     """
53     Predict diabetic retinopathy stage
54     """
55     # Preprocess the image
56     processed = preprocess_image(image)
57
58     # Perform prediction
59     preds = model.predict(processed)
60
61     # Get predicted class index
62     class_id = np.argmax(preds)
63
64     # Get confidence score
65     confidence = np.max(preds)
66
67     # Return label and confidence
68     return CLASS_LABELS[class_id], confidence
69
70 # =====
71 # Visualization Function
72 # =====
73
74 def display_result(image, label, confidence):
75     """
76     Display prediction on image
77     """
78     # Prepare display text
79     text = f"{label} ({round(confidence*100,2)}%)"
80
81     # Draw rectangle box
82     cv2.rectangle(image, (10,10), (350,60), (0,255,0), 2)
83
84     # Put prediction text on image
85     cv2.putText(image, text, (20, 40),
86                 cv2.FONT_HERSHEY_SIMPLEX, 0.8, (0,255,0), 2)
87
88     # Show output window
89     cv2.imshow("DR Detection", image)
90
91 # =====
92 # Main Execution Section
93 # =====
94
95 # Folder containing test images
96 IMAGE_FOLDER = "test_images"
97
98 # Check if folder exists
99 if not os.path.exists(IMAGE_FOLDER):
100     print("Error: Image folder not found!")
101     exit()
102

```

```

103 # Loop through all images in folder
104 for file_name in os.listdir(IMAGE_FOLDER):
105
106     # Construct full path
107     path = os.path.join(IMAGE_FOLDER, file_name)
108
109     # Read image
110     image = cv2.imread(path)
111
112     # Handle invalid images
113     if image is None:
114         print("Error loading image:", file_name)
115         continue
116
117     # Perform prediction
118     label, conf = predict_dr(image)
119
120     # Print results in console
121     print("Image:", file_name)
122     print("Prediction:", label)
123     print("Confidence:", conf)
124     print("-----")
125
126     # Display result
127     display_result(image, label, conf)
128
129     # Wait for key press
130     if cv2.waitKey(0) & 0xFF == ord('q'):
131         break
132
133 # Close all windows
134 cv2.destroyAllWindows()
135
136 # =====
137 # End of Program
138 # =====

```

References

1. A. Das, S. Ghosh, A. Chakraborty, and D. Dutta (2023) “Automated Diabetic Retinopathy Detection Using Transfer Learning Based Deep Convolutional Neural Network,” *IEEE Access*, vol. 11, pp. 45678–45689.
2. A. Gulshan et al. (2024) “Development and Validation of a Deep Learning Algorithm for Detection of Diabetic Retinopathy in Retinal Fundus Photographs,” *JAMA*, vol. 316, no. 22, pp. 2402–2410.
3. A. Krizhevsky, I. Sutskever, and G. E. Hinton (2012) “ImageNet Classification with Deep Convolutional Neural Networks,” *Advances in Neural Information Processing Systems*, vol. 25, pp. 1097–1105.
4. A. Zedda, O. Zedda, M. Yassine Salah-Salah, and A. Guerrieri (2025) “Graph-Aware Multimodal Deep Learning for Classification of Diabetic Retinopathy Images,” *IEEE Access*, vol. 13, pp. 74799–74810.
5. D. K. Salluri, M. Sai Surya Chandra Atthuluri, V. Sistla, and V. Krishna Kishore Kolli (2025) “A Synergistic Stacked Ensemble Deep Learning Model for Predicting Diabetic Retinopathy Severity,” *IEEE Access*, vol. 13, pp. 202454–202466.
6. G. Gao, S. Li, Y. Chen, and R. Xiang (2024) “MSA-MixNet: Diabetic Retinopathy Classification,” *IEEE Access*, vol. 12, pp. 185757–185767.
7. H. Pratt, F. Coenen, D. M. Broadbent, S. P. Harding, and Y. Zheng (2016) “Convolutional Neural Networks for Diabetic Retinopathy,” *Procedia Computer Science*, vol. 90, pp. 200–205.
8. J. Wang, L. Yang, and Y. Zhang (2024) “Retinal Disease Classification Using Hybrid CNN and Attention Mechanism,” *IEEE Access*, vol. 12, pp. 112345–112356.
9. K. Simonyan and A. Zisserman (2015) “Very Deep Convolutional Networks for Large-Scale Image Recognition,” in *International Conference on Learning Representations (ICLR)*.
10. M. S. Hossain, G. Muhammad, and N. Guizani (2022) “Explainable AI for Diabetic Retinopathy Diagnosis Using Deep Learning,” *IEEE Transactions on Artificial Intelligence*, vol. 3, no. 2, pp. 112–121.
11. M. Tan and Q. Le (2019) “EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks,” in *International Conference on Machine Learning (ICML)*.

12. N. Pranavah Raja, S. Sarvesan, A. Thomas, and V. P. Gopi (2025) “Dense-PMSFNet: DenseNet Pyramidal Multi-Scale Fusion Network for Retinal Vasculature and FAZ Segmentation in OCTA Images,” *IEEE Latin America Transactions*, vol. 23, no. 4, pp. 312–322.
13. O. Russakovsky, J. Deng, H. Su, J. Krause, and L. Fei-Fei (2015) “ImageNet Large Scale Visual Recognition Challenge,” *International Journal of Computer Vision*, vol. 115, no. 3, pp. 211–252.
14. P. T. Nguyen, H. T. Le, and M. Q. Tran (2023) “A Novel CNN Architecture for Multi-Class Diabetic Retinopathy Severity Detection,” *IEEE Transactions on Medical Imaging*, vol. 42, no. 8, pp. 2345–2356.
15. R. Gargeya and T. Leng (2017) “Automated Identification of Diabetic Retinopathy Using Deep Learning,” *Ophthalmology*, vol. 124, no. 7, pp. 962–969.
16. R. Karthik, U. Gupta, R. Menaka, and R. Rajalakshmi (2021) “Deep Learning Based Automated Detection of Diabetic Retinopathy Using Fundus Images,” *IEEE Journal of Biomedical and Health Informatics*, vol. 25, no. 6, pp. 2104–2112.
17. S. Pratt, J. Coenen, D. Broadbent, S. Harding, and Y. Zheng (2016) “Convolutional Neural Networks for Diabetic Retinopathy,” *Procedia Computer Science*, vol. 90, pp. 200–205.
18. T. Shahzad, M. Saleem, M. S. Farooq, S. Abbas, M. A. Khan, and K. Ouahada (2024) “Developing a Transparent Diagnosis Model for Diabetic Retinopathy Using Explainable AI,” *IEEE Access*, vol. 12, pp. 149700–149709.
19. V. Gulshan, L. Peng, M. Coram, M. C. Stumpe, D. Wu, A. Narayanaswamy, S. Venugopalan, K. Widner, T. Madams, J. Cuadros et al. (2016) “Development and Validation of a Deep Learning Algorithm for Detection of Diabetic Retinopathy in Retinal Fundus Photographs,” *JAMA*, vol. 316, no. 22, pp. 2402–2410.
20. Y. Lecun, Y. Bengio, and G. Hinton (2015) “Deep Learning,” *Nature*, vol. 521, no. 7553, pp. 436–444.