DG INTERNS HUB CYBER SECURITY INTERNSHIP

Week 2 Report



Network Traffic Analysis, Nmap and Windows Logging

PROGRAMME	DG Interns Hub Cyber Security Internship
WEEK	Week 2
TOPICS	Packet analysis with Wireshark, Nmap scanning, Windows event logging, PowerShell hunting
PREPARED BY	**Harini**
REPORT DATE	30 October 2026

Contents

1. Introduction 3

2. Summary of the work 3

3. Lab environment 3

4. Task 1: Capturing traffic 4

5. Task 2: Nmap scans 5

6. Task 3: Windows events 8

7. Task 4: PowerShell hunting 11

8. Task 5: Cheat sheets 12

9. TryHackMe rooms 13

10. Wireshark sample capture analyses 13

11. Theory notes 13

12. Problems I faced and how I solved them 14

13. Safety and privacy 14

14. What I learned 15

15. Conclusion 15

Appendix: Submission contents 15

1. Introduction

This report describes the work I completed in Week 2 of the DG Interns Hub Cyber Security Internship. The topic of the week was network traffic analysis, Nmap scanning and Windows event logging. The goal was to learn how to read packets and Windows event logs, so that the endpoint and IDS work in Week 3 makes sense.

The report covers the four hands-on tasks (traffic capture, Nmap scans, Windows events and PowerShell hunting), the two cheat sheets, the six TryHackMe rooms, the three Wireshark sample capture analyses and the theory notes. It also lists the problems I met and how I solved each one.

All tests were run only on my own lab machines, and I used free tools only.

2. Summary of the work

Part	What I did	Result	Evidence
Theory notes	Answered the eight theory questions of the task in eight separate notes.	Completed	Notes folder
TryHackMe	Completed six rooms on Nmap and Windows.	All six at 100%	Writeups 01 to 06
Task 1: Capture traffic	Installed Apache on Ubuntu and recorded ping, curl and DNS traffic from Kali.	Completed	kali-capture.pcap, 6 screenshots
Task 2: Nmap	Ran -sn, -sS, -sV, -O and -A against the Ubuntu VM and the Windows laptop, with -oN and -oX output.	Completed	9 text files, 9 XML files, syn-scan.pcap, 10 screenshots
Task 3: Windows events	Generated and located events 4625, 4624, 4720, 4732, 7045 and 1102.	Completed	6 screenshots
Task 4: PowerShell hunting	Exported all 4625 events to CSV and counted failures per account.	Completed	CSV file, 1 screenshot
Task 5: Cheat sheets	Made a 20-entry Wireshark filter sheet and a 15-entry Windows Event ID sheet.	Completed	2 PDF files
Wireshark sample captures	Analysed http_with_jpegs, telnet-cooked and dns.cap.	Completed	Writeups 07 to 09

3. Lab environment

The lab runs on VirtualBox on my Windows 11 laptop. The machines are connected by a Host-only network, 192.168.56.0/24. I did not have a Windows virtual machine, so my real Windows laptop acted as the Windows target.

Machine	Role	Address
Windows 11 laptop	Runs VirtualBox, Wireshark and PowerShell. Windows target for Nmap and for the event log tasks.	192.168.56.1
Kali Linux VM (kali-lab)	Scanning and testing machine, command line only.	192.168.56.101
Ubuntu Server VM (ubuntu-lab)	Target machine, running the Apache web server.	192.168.56.102

Tools used (all free): VirtualBox, Kali Linux, Ubuntu Server, Apache 2.4.66, Nmap 7.991, tcpdump, Wireshark 4.6.9, Windows PowerShell, Windows Event Viewer and Google Drive for desktop.

4. Task 1: Capturing traffic

4.1 Preparing the web server

I installed Apache on the Ubuntu VM and confirmed that the service was running (Figure 1). From Kali, I sent a request with `curl -I http://192.168.56.102` and received HTTP/1.1 200 OK from Apache/2.4.66 (Ubuntu) (Figure 2). This showed that the web server was reachable before I started recording.

```
Created symlink '/etc/systemd/system/multi-user.target.wants/apache-htcacheclean.service' → '/usr/lib/systemd/system/apa
che-htcacheclean.service'.
Processing triggers for ufw (0.36.2-9build1)…
Processing triggers for man-db (2.13.1-1build1)…
Processing triggers for libc-bin (2.43-2ubuntu2.4)…
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ubuntu-lab:~$ systemctl is-active apache2
active
ubuntu@ubuntu-lab:~$
```

Figure 1. Apache is active on the Ubuntu VM.

```
┌──(kali㉿kali-lab)-[~]
└─$ curl -I http://192.168.56.102
HTTP/1.1 200 OK
Date: Tue, 27 Oct 2026 06:42:16 GMT
Server: Apache/2.4.66 (Ubuntu)
Last-Modified: Tue, 27 Oct 2026 06:31:28 GMT
ETag: "29b0-65ecc98acf5b4"
Accept-Ranges: bytes
Content-Length: 10672
Vary: Accept-Encoding
Content-Type: text/html
```

Figure 2. A curl check from Kali returns 200 OK from Apache.

4.2 Recording the traffic

Wireshark on my Windows laptop could not see the traffic between the two virtual machines. So I recorded on the Ubuntu VM with tcpdump (interface enp0s8, filter `host 192.168.56.101`), and copied the file to my laptop with scp. While recording, I ran ping, curl and nslookup from Kali against Ubuntu. I then opened kali-capture.pcap in Wireshark. The capture has 32 packets and lasts about 56 seconds.

4.3 What the capture shows

Evidence	Packets	What I saw
ICMP echo	1 to 8	Four echo requests from Kali to Ubuntu, each answered by an echo reply.
TCP handshake	13 to 15	SYN, SYN-ACK and ACK between Kali and port 80 of Ubuntu.
HTTP GET	16, 18, 19	The request GET / HTTP/1.1, then the reply 200 OK with text/html.
TCP closing	22 to 24	A FIN-ACK from each side and a final ACK.
DNS query	27, 29, 31	Three queries for the A record of example.com. Each was answered by ICMP Destination unreachable (Port unreachable).
ARP	6 packets	Kali and Ubuntu asked each other for their hardware addresses.




Figure 3. Filter tcp.port == 80: handshake (13 to 15), GET (16), 200 OK (18, 19) and closing (22 to 24).




Figure 4. Filter http.request: the HTTP GET request in packet 16.




Figure 5. Filter dns: three DNS queries, each followed by an ICMP Port unreachable message.




Figure 6. Filter icmp: four ping request and reply pairs, and the three Port unreachable messages.

Why the DNS query has no answer. I sent the DNS queries to the Ubuntu VM, but it does not run a DNS server. Nothing listens on UDP port 53, so Ubuntu replied with ICMP Port unreachable. I kept this result as it is, because the DNS query is clearly visible and the reply shows that the port is closed.

5. Task 2: Nmap scans

I ran five scan types from Kali with Nmap 7.991: ping scan (-sn), SYN scan (-sS), service version detection (-sV), OS detection (-O) and aggressive mode (-A). The Ubuntu VM and the Windows laptop were the targets. Every scan saved its output with -oN (text) and -oX (XML).

5.1 Scan results

Scan	Target	Result	Time
-sn	192.168.56.0/24	3 hosts up: 192.168.56.1, 192.168.56.102 and 192.168.56.101.	6.99 s
-sS	Ubuntu VM	Port 22 (ssh) and port 80 (http) open. 998 ports closed (reset).	3.27 s
-sV	Ubuntu VM	OpenSSH 10.2p1 Ubuntu 2ubuntu3.8 on port 22. Apache httpd 2.4.66 (Ubuntu) on port 80.	9.90 s
-O	Ubuntu VM	No exact OS matches for the host. Network distance 1 hop.	14.82 s
-A	Ubuntu VM	Same services. Page title: Apache2 Ubuntu Default Page: It works. No exact OS match. Traceroute: 1 hop.	22.00 s
-sS	Windows laptop	All 1000 scanned ports filtered (no response).	23.94 s
-sV	Windows laptop	All 1000 ports filtered. No service information.	24.21 s
-O	Windows laptop	All ports filtered. Too many fingerprints match this host.	24.88 s
-A	Windows laptop	All ports filtered. Too many fingerprints match this host. Traceroute: 1 hop.	30.41 s

The text output files are named sn-scan, ss-scan, sv-scan, o-scan and a-scan for the Ubuntu VM, and win-ss-scan, win-sv-scan, win-o-scan and win-a-scan for the Windows laptop. Each exists as a .txt file and as an .xml file.

```
# Nmap 7.991 scan initiated Tue Oct 27 10:01:05 2026 as: /usr/lib/nmap/nmap -sn -oN sn-scan.txt -oX sn-scan.xml 192.168.56.0/24
Nmap scan report for 192.168.56.1
Host is up (0.00061s latency).
Nmap scan report for 192.168.56.102
Host is up (0.00070s latency).
Nmap scan report for 192.168.56.101
Host is up.
# Nmap done at Tue Oct 27 10:01:12 2026 -- 256 IP addresses (3 hosts up) scanned in 6.99 seconds

┌──(kali㉿kali-lab)-[~/week2]
└─$
```

Figure 7. Ping scan of the Host-only network: 3 hosts up.

```
# Nmap 7.991 scan initiated Tue Oct 27 10:06:38 2026 as: /usr/lib/nmap/nmap -sS -oN ss-scan.txt -oX ss-scan.xml 192.168.56.102
Nmap scan report for 192.168.56.102
Host is up (0.00073s latency).
Not shown: 998 closed tcp ports (reset)
PORT   STATE SERVICE
22/tcp open  ssh
80/tcp open  http

# Nmap done at Tue Oct 27 10:06:42 2026 -- 1 IP address (1 host up) scanned in 3.27 seconds

┌──(kali㉿kali-lab)-[~/week2]
└─$
```

Figure 8. SYN scan of the Ubuntu VM: ports 22 and 80 open.

```
# Nmap 7.991 scan initiated Tue Oct 27 10:17:01 2026 as: /usr/lib/nmap/nmap -sV -oN sv-scan.txt -oX sv-scan.xml 192.168.56.102
Nmap scan report for 192.168.56.102
Host is up (0.00069s latency).
Not shown: 998 closed tcp ports (reset)
PORT   STATE SERVICE VERSION
22/tcp open  ssh     OpenSSH 10.2p1 Ubuntu 2ubuntu3.8 (Ubuntu Linux; protocol 2.0)
80/tcp open  http    Apache httpd 2.4.66 ((Ubuntu))
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
# Nmap done at Tue Oct 27 10:17:11 2026 -- 1 IP address (1 host up) scanned in 9.90 seconds

┌──(kali㉿kali-lab)-[~/week2]
└─$
```

Figure 9. Version detection on the Ubuntu VM: OpenSSH 10.2p1 and Apache 2.4.66.

```
# Nmap 7.991 scan initiated Tue Oct 27 10:19:47 2026 as: /usr/lib/nmap/nmap -O -oN o-scan.txt -oX o-scan.xml 192.168.56.102
Nmap scan report for 192.168.56.102
Host is up (0.0012s latency).
Not shown: 998 closed tcp ports (reset)
PORT   STATE SERVICE
22/tcp open  ssh
80/tcp open  http
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/ ).
TCP/IP fingerprint:

Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
# Nmap done at Tue Oct 27 10:20:02 2026 -- 1 IP address (1 host up) scanned in 14.82 seconds

┌──(kali㉿kali-lab)-[~/week2]
└─$
```

Figure 10. OS detection on the Ubuntu VM: no exact OS match.



Figure 11. Aggressive scan of the Ubuntu VM: services, page title and traceroute.




Figure 12. SYN scan of the Windows laptop: all 1000 ports filtered.




Figure 13. OS detection on the Windows laptop: too many fingerprints match.

The other two Windows screenshots (-sV and -A) show the same filtered result and are kept in the Findings folder.

5.2 What the Windows result means

Nmap found no open ports on the Windows laptop. All 1000 ports were filtered, which means there was no reply to any probe. The Windows firewall dropped the packets, so Nmap could not learn anything about services, and the OS scan could not narrow down the system. I report this result as it is. It shows a firewall doing its job, and it is a good contrast with the Ubuntu VM, where closed ports answered with a reset and open ports answered with a SYN-ACK.

5.3 The SYN scan on the wire

I recorded the -sS scan of the Ubuntu VM in syn-scan.pcap and opened it in Wireshark with the filter `tcp.flags.syn==1 && tcp.flags.ack==0`. The capture shows the pattern of a port scan:

- 1000 SYN packets from 192.168.56.101 to 192.168.56.102, each to a different port.
- All of them sent in about half a second (0.52 s), from the same source port, 58943, with no ACK flag.
- The Ubuntu VM answered with 998 RST packets for the closed ports and 2 SYN-ACK packets, from ports 22 and 80. This matches Nmap's result of 998 closed and 2 open ports.




Figure 14. Filter tcp.flags.syn==1 && tcp.flags.ack==0 shows the burst of SYN packets to many ports.

This pattern is what a detection tool such as Snort can find in Week 3: many SYN packets from one source to many different ports in a very short time.

6. Task 3: Windows events

I generated the events on my real Windows laptop, using Windows PowerShell as Administrator. I created a dummy user named labtest1 for the tests, so my own account was never touched. I found each event in Event Viewer, in the Security log, with the Filter Current Log option. The 7045 event is in the System log.

6.1 Events and how I created them

Event ID	What I did	Logged	Key details
4720	Created the dummy user with New-LocalUser.	27-10-2026 18:26:25	New Account: labtest1.
4732	Added the user to the Administrators group with Add-LocalGroupMember.	27-10-2026 18:45:16	Member: labtest1. Group: Administrators.
4625	Tried a network logon with a wrong password.	27-10-2026 18:54:06	Account labtest1, Logon Type 3. Failure reason: Unknown user name or bad password. Status 0xC000006D, Sub Status 0xC000006A.
4624	Logged on again with the correct password.	27-10-2026 19:09:38	Logon Type 3 (network logon), account labtest1.
7045	Created a dummy service with sc.exe create, then removed it with sc.exe delete.	27-10-2026 19:15:37	Service LabDummySvc, file C:\Windows\System32\notepad.exe, start type demand start.
1102	Cleared the Security log with wevtutil, after saving a backup copy.	27-10-2026 19:22:31	The audit log was cleared.

For the failed and the successful logon, I used the command `net use \\localhost\IPC$ /user:labtest1`. The first time with a wrong password, and the second time with the correct one. Both events show Logon Type 3, because net use makes a network connection. At the end, I removed the user with Remove-LocalUser and checked with Get-LocalUser that it no longer exists.

6.2 Evidence




Figure 15. Event 4720: a new user account, labtest1, was created.




Figure 16. Event 4732: labtest1 was added to the Administrators group.




Figure 17. Event 4625: failed logon of labtest1, Logon Type 3.




Figure 18. Event 4624: successful logon, Logon Type 3.




Figure 19. Event 7045: the dummy service LabDummySvc was installed.




Figure 20. Event 1102: the audit log was cleared.

6.3 Why I saved the log before clearing it

Clearing the Security log erases every event in it, including the ones I needed for the report and for Task 4. So before clearing, I saved a copy with `wevtutil.exe epl Security E:\Security-backup-week2.evtx`. The copy is about 20 MB. I cleared the log only after checking that the file exists, and I used the copy for Task 4. This also shows why 1102 is a serious event: anyone who clears a log removes their traces.

7. Task 4: PowerShell hunting

In this task I used Get-WinEvent with -FilterHashtable to find all 4625 events, exported them to a CSV file, and counted the failures per account with Group-Object. Because I had cleared the live Security log in Task 3, I read the events from the backup file instead. The first command counts the events.

```
Get-WinEvent -FilterHashtable @{Path='E:\Security-backup-week2.evtx'; Id=4625} | Measure-Object
```

The second command exports them to CSV. It reads the account name, the logon type and the source address from each event.

```
Get-WinEvent -FilterHashtable @{Path='E:\Security-backup-week2.evtx'; Id=4625} | Select-Object
TimeCreated, Id, @{n='Account';e={$_.Properties[5].Value}},
@{n='LogonType';e={$_.Properties[10].Value}}, @{n='SourceIP';e={$_.Properties[19].Value}} |
Export-Csv E:\failed-logons-4625.csv -NoTypeInformation
```

The third command counts the failures per account.

```
Import-Csv E:\failed-logons-4625.csv | Group-Object Account | Sort-Object Count -Descending |
Select-Object Count, Name
```

The backup file holds 13 events with ID 4625. Twelve belong to my own local Windows account, and one belongs to labtest1.

Account	Failures	Logon Type	Note
Local Windows account (name masked as local-user)	12	2 (interactive)	Sign-in attempts at the laptop between 25 and 27 October. I did not investigate them further.
labtest1	1	3 (network)	The wrong-password test from Task 3.




Figure 21. Export of the 4625 events and the count per account in PowerShell.

The CSV file in the submission is a safe copy, where the name of my own Windows account is replaced by local-user. I kept the original on my own drive and did not upload it.

8. Task 5: Cheat sheets

I prepared two cheat sheets as PDF files. Each entry explains the item in plain words and gives a real situation where it helps.

- **Wireshark Filter, Meaning, When to Use It:** 20 display filters in six groups (host and port, TCP flags, web and DNS, ICMP and ARP, encrypted traffic and file sharing, searching and analysing).
- **Windows Event ID, What It Means, When to Use It:** the 15 Security events from the task, in five groups (logon activity, process and service activity, account and group changes, Kerberos and NTLM, log tampering). Five of them are marked with a note from my own lab.

9. TryHackMe rooms

I completed all six rooms, and every room page shows 100% completion. I wrote a separate writeup for each room, with what I learned, the practical task, why it matters for a SOC analyst and the completion proof.

No.	Room	Main topics	Link
1	Nmap	Port scanning, scan types and switches, NSE scripts, firewall evasion.	tryhackme.com/room/furthernmap
2	Nmap Live Host Discovery	Finding live hosts with ARP, ICMP, TCP and UDP ping scans.	tryhackme.com/room/nmap01
3	Nmap Basic Port Scans	Connect, SYN and UDP scans, port states, timing and speed.	tryhackme.com/room/nmap02
4	Windows Basics	Windows accounts, Task Manager, Windows Security and the firewall.	tryhackme.com/room/windowsbasics
5	Windows Fundamentals 1	The desktop, NTFS, user accounts, UAC and the Control Panel.	tryhackme.com/room/windowsfundamentals1xbx
6	Windows Fundamentals 2	System Configuration, Computer Management, Resource Monitor and the registry.	tryhackme.com/room/windowsfundamentals2x0x

10. Wireshark sample capture analyses

The task asked me to pick three official Wireshark sample captures and answer three questions for each: which protocols appear, what happened, and whether anything is suspicious. I chose three captures that cover different protocols. For each one I wrote a writeup with my own screenshots.

Capture	Protocols	What happened	Suspicious?
http_with_jpegs.cap.gz (483 packets)	Ethernet, IPv4, TCP, HTTP	A browser opened a small website, followed a link and downloaded pictures. It also sent a request to an advertising server. I rebuilt a picture from the packets with Export Objects.	No sign of an attack. The traffic is not encrypted, and 19 IP fragments appear, which are normal here.
telnet-cooked.pcap (92 packets)	Ethernet, IPv4, TCP, Telnet	A user logged in over Telnet, ran a ping and two file listings, and logged out.	No sign of an attack. The login name and the password are readable as plain text. One malformed packet is probably a recording artefact.
dns.cap (38 packets)	Ethernet, IPv4, UDP, DNS	One computer asked a DNS server for many record types. A second computer sent private network names to an outside server and got No such name.	No sign of an attack. The private names that went outside the network are worth checking.

11. Theory notes

I wrote the eight theory notes in my own words, each in a separate file, with bullet points and tables. The topics are:

- The TCP three-way handshake and teardown, with a table of TCP flags.
- What an analyst should look for in DNS, HTTP, HTTPS/TLS, ARP, ICMP and SMB traffic.

- Capture filters and display filters in Wireshark, with 10 examples.
- Nmap scan types (-sn, -sS, -sT, -sU, -sV, -O, -A) and what each leaves in packets and logs.
- Windows basics: processes, services, registry, users and groups, UAC and the three main Event Viewer logs.
- Fifteen key Windows Security Event IDs, with their meaning and use.
- Windows logon types 2, 3, 4, 5, 7, 10 and 11, with a normal and a suspicious example.
- What a baseline is, and why it matters for a SOC analyst.

12. Problems I faced and how I solved them

Problem	What happened	How I solved it
Wireshark on Windows could not see VM to VM traffic	Wireshark on my laptop showed nothing from the traffic between Kali and Ubuntu.	I recorded on the Ubuntu VM with tcpdump (interface enp0s8, filter host 192.168.56.101) and copied the file with scp. I state this clearly in the report.
Host-only addresses disappeared	I had set the addresses by hand, so they were lost after a reboot or reset.	I added them again with ip addr add on Kali (192.168.56.101/24, eth1) and on Ubuntu (192.168.56.102/24, enp0s8).
No Windows virtual machine	The task asked for a Windows VM, but I only had my real laptop.	I used the laptop as the Windows target, created only a temporary dummy user, and deleted it at the end. My own account was never changed.
Windows firewall blocked all scans	Every port showed as filtered and the OS scan gave no clear result.	I reported the result as it is and explained that filtered means no reply, so the firewall was working.
DNS query had no answer	The Ubuntu VM is not a DNS server, so it answered with ICMP Port unreachable.	I kept the result as evidence and explained why the port is closed.
Clearing the Security log destroys evidence	Event 1102 needs a cleared log, but my earlier events would be lost.	I saved a backup copy with wevtutil first and used it for the PowerShell task.
Personal details in screenshots and files	Screenshots showed my Windows username and computer name. The Nmap files and PCAP files contain MAC addresses.	I covered the details with solid black boxes, replaced the MAC addresses in the Nmap files with XX:XX:XX:XX:XX:XX, made a safe CSV, and checked the files with Select-String. The originals stay on my own drive.
Sample capture was hard to find	The file I wanted was not on the main Wireshark wiki page.	I used the GitLab copy of the same Wireshark sample captures page.
Wireshark could not save to Google Drive	Saving a capture straight to the Drive folder failed.	I saved to drive E first and then copied the file, or used scp from the VM.

13. Safety and privacy

- All scans and tests ran only on my own virtual machines and my own laptop.
- The dummy user, the dummy service and the cleared log were part of a controlled test. I deleted the user and the service afterwards.
- Only free tools were used.
- Personal details such as the Windows username, the computer name and MAC addresses are hidden in the screenshots and the files in the submission.

- Sample captures come from the official Wireshark wiki, and I analysed them with my own screenshots and words.

14. What I learned

- A TCP scan has a clear pattern: many SYN packets to many ports in a short time, answered by RST from closed ports and SYN-ACK from open ones.
- A firewall can hide a whole machine from Nmap, and the right result to report is what the scan really shows.
- The Logon Type in events 4624 and 4625 tells how a logon happened. Type 3 is a network logon and type 2 is a logon at the keyboard.
- Events 4720, 4732, 7045 and 1102 show common attacker steps: creating an account, gaining admin rights, installing a service and clearing logs.
- PowerShell can search and count events much faster than clicking through Event Viewer.
- Plain-text protocols such as HTTP, Telnet and DNS expose information, so encrypted choices such as HTTPS and SSH are safer.
- Saving evidence before a risky step, and hiding personal details before sharing it, are part of careful security work.

15. Conclusion

In Week 2, I completed all the tasks: the theory notes, six TryHackMe rooms, the traffic capture, the Nmap scans, the Windows event tasks, the PowerShell hunting, two cheat sheets and three sample capture analyses. I now understand better how network scans look in packets, and how important Windows events are when I investigate a computer. I also learned to keep my evidence safe and to explain results honestly, including the ones that did not go as expected. This work prepares me for the endpoint and IDS tasks of Week 3.

Appendix: Submission contents

Folder or file	Contents
Notes	Eight theory notes, one file for each question.
Writeups	Six TryHackMe writeups (01 to 06) and three Wireshark sample capture writeups (07 to 09), all as PDF files.
Findings	Screenshots in four groups: Wireshark, Nmap, Windows Events and PowerShell Hunting.
Captures	kali-capture.pcap, syn-scan.pcap, the nine Nmap text files (-oN) and the nine Nmap XML files (-oX).
Cheat Sheets	Wireshark Filter, Meaning, When to Use It. Windows Event ID, What It Means, When to Use It.
Report, presentation and README	This report, the presentation and the README file.