Practice 2

K.Harini
2520030399

Create a database & use:

```
1    CREATE DATABASE IF NOT EXISTS bookflow2_db;
2 •  USE bookflow_db;
```

Output

Action Output

#	Time	Action
1	09:08:46	SHOW DATABASES
2	09:09:23	CREATE DATABASE IF NOT EXISTS bookflow2_db
3	09:09:40	USE bookflow_db

Create a table:

```
3 •  CREATE TABLE orders (
4        ord_no INT PRIMARY KEY,
5        purch_amt DECIMAL(10,2),
6        ord_date DATE,
7        customer_id INT,
8        salesman_id INT
9    );
10
```

Output

Action Output

#	Time	Action
1	19:43:25	CREATE DATABASE IF NOT EXISTS bookflow7_db
2	19:43:36	USE bookflow7_db
3	19:44:15	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DE..

Insert data into table:

```
10 •  INSERT INTO orders VALUES
11    (70001,150.50,'2012-10-05',3005,5002),
12    (70009,399.65,'2012-09-10',3001,5005),
13    (70002,65.26,'2012-10-05',3002,5001),
14    (70004,110.50,'2012-08-17',3009,5003),
15    (70007,7657.50,'2012-09-10',3005,5002),
16    (70005,2400.60,'2012-07-27',3007,5001),
17    (70008,986.00,'2012-09-10',3002,5001),
18    (70010,1983.43,'2012-10-10',3004,5006),
19    (70003,2480.40,'2012-10-10',3009,5003),
20    (70012,250.45,'2012-06-27',3008,5002),
21    (70011,75.29,'2012-08-17',3003,5007),
22    (70013,46.60,'2012-04-25',3002,5001);
23 •  SELECT * FROM orders;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70004	110.50	2012-08-17	3009	5003
70005	2400.60	2012-07-27	3007	5001
70007	7657.50	2012-09-10	3005	5002
70008	986.00	2012-09-10	3002	5001
70009	399.65	2012-09-10	3001	5005
70010	1983.43	2012-10-10	3004	5006
70011	75.29	2012-08-17	3003	5007
70012	250.45	2012-06-27	3008	5002
70013	46.60	2012-04-25	3002	5001
NULL	NULL	NULL	NULL	NULL

Where clause:

```
24 •  SELECT *
25    FROM orders
26    WHERE purch_amt > 2000;
27
```

Result Grid | Filter Rows: | Edit:

ord_no	purch_amt	ord_date	customer_id	salesman_id
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70007	7657.50	2012-09-10	3005	5002
NULL	NULL	NULL	NULL	NULL

3005

```
27 •  SELECT *
28    FROM orders
29    WHERE salesman_id=5001;
30
```

Result Grid | Filter Rows: | Edit:

ord_no	purch_amt	ord_date	customer_id	salesman_id
70002	65.26	2012-10-05	3002	5001
70005	2400.60	2012-07-27	3007	5001
70008	986.00	2012-09-10	3002	5001
70013	46.60	2012-04-25	3002	5001
NULL	NULL	NULL	NULL	NULL

Order by:

```
30 •  SELECT *
31    FROM orders
32    ORDER BY purch_amt DESC;
33
```

Result Grid | Filter Rows: | Edit:

ord_no	purch_amt	ord_date	customer_id	salesman_
70007	7657.50	2012-09-10	3005	5002
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70010	1983.43	2012-10-10	3004	5006
70008	986.00	2012-09-10	3002	5001
70009	399.65	2012-09-10	3001	5005
70012	250.45	2012-06-27	3008	5002
70001	150.50	2012-10-05	3005	5002
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70002	65.26	2012-10-05	3002	5001
70013	46.60	2012-04-25	3002	5001
NULL	NULL	NULL	NULL	NULL

```
33 •  SELECT *
34    FROM orders
35    ORDER BY ord_date;
36
```

Result Grid | Filter Rows: | Edit:

ord_no	purch_amt	ord_date	customer_id	salesman_id
70013	46.60	2012-04-25	3002	5001
70012	250.45	2012-06-27	3008	5002
70005	2400.60	2012-07-27	3007	5001
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70007	7657.50	2012-09-10	3005	5002
70008	986.00	2012-09-10	3002	5001
70009	399.65	2012-09-10	3001	5005
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70010	1983.43	2012-10-10	3004	5006
NULL	NULL	NULL	NULL	NULL

Sum():

```
36 •  SELECT SUM(purch_amt) AS total_revenue
37    FROM orders;
38
```

Result Grid | Filter Rows: | Export:

total_revenue
16606.18

Avg ():

```
38 •  SELECT AVG(purch_amt) AS average_order
39    FROM orders;
40
```

Result Grid | Filter Rows: | Export:

average_order
1383.848333

Max():

```
40 •  SELECT MAX(purch_amt) AS highest_order
41    FROM orders;
42
```

Result Grid | Filter Rows: | Export:

highest_order
7657.50

Count():

```
42 •  SELECT COUNT(*) AS total_orders
43    FROM orders;
44
```

Result Grid | Filter Rows:

total_orders
12

Group by():

```
44 •  SELECT salesman_id,
45           SUM(purch_amt) AS total_sales
46    FROM orders
47    GROUP BY salesman_id
48
```

Result Grid | Filter Rows: | Export:

salesman_id	total_sales
5002	8058.45
5001	3498.46
5003	2590.90
5005	399.65
5006	1983.43
5007	75.29

```
48 •  SELECT customer_id,
49            SUM(purch_amt) AS total_purchase
50    FROM orders
51    GROUP BY customer_id;
52
```

Result Grid | Filter Rows: | Export:

customer_id	total_purchase
3005	7808.00
3002	1097.86
3009	2590.90
3007	2400.60
3001	399.65
3004	1983.43
3003	75.29
3008	250.45

Group by + having + order by:

```
52 •  SELECT customer_id,
53            SUM(purch_amt) AS total_purchase
54    FROM orders
55    GROUP BY customer_id
56    HAVING SUM(purch_amt) > 1000
57    ORDER BY total_purchase DESC;
58
```

Result Grid | Filter Rows: | Export:

customer_id	total_purchase
3005	7808.00
3009	2590.90
3007	2400.60
3004	1983.43
3002	1097.86

Between + having

```
58 •  SELECT customer_id,
59            MAX(purch_amt) AS max_purchase
60    FROM orders
61    GROUP BY customer_id
62    HAVING MAX(purch_amt) BETWEEN 2000 AND 6000;
63
```

Result Grid | Filter Rows: | Export: | Wr

customer_id	max_purchase
3009	2480.40
3007	2400.60

Count + having:

```
63 •    SELECT salesman_id,
64             COUNT(*) AS total_orders
65      FROM orders
66      GROUP BY salesman_id
67      HAVING COUNT(*) >= 2;
68
```

Result Grid | Filter Rows:

salesman_id	total_orders
5002	3
5001	4
5003	2

Max + group by + having

```
63 •    SELECT salesman_id,
64             COUNT(*) AS total_orders
65      FROM orders
66      GROUP BY salesman_id
67      HAVING COUNT(*) >= 2;
68
```

Result Grid | Filter Rows:

salesman_id	total_orders
5002	3
5001	4
5003	2