


# Imperative Programming:


```
List<Item> items = itemRepository.getAllItems();
```



- Synchronous and blocking communication Model.


## Data flow as an Event Driven stream

```
List<Item> items = itemRepository.getAllItems();
```




# Data flow as an Event Driven stream

- Error Flow




## Data flow as an Event Driven stream


- No Data



## Publisher/Subscriber Event Flow



## Publisher/Subscriber Event Flow



Project Reactor : REcommended Library for Spring Boot

Modules :

reactor-core : contain implementations of Reactive Stream Specifications ( interface)

reactor-test : api to create unit tests for REactive Streams

reactor-netty : non-blocking http server

---

Reactor-core provides implementation of interface in form of :

Reactive types/Streams

Flux : 0-N

Mono : 0-1

Publisher Stream ( implementation of publisher)

## Traditional (Imperative)

## DAO implementation

```
List<User> users = userDao getUsers();  
List<String> names = new ArrayList<String>();  
for(int i = 0; i<user.size(); i++)  
    names.add(users.get(i).getName());
```

## Functional (Java Stream: declarative)

```
List<String> names = userDao.getUsers().stream()  
    .map(user -> user.getName())  
    .collect(Collectors.toList());
```

if db is busy (lot of data)  
take some time:  
our thread will be blocked

## Reactive Stream


## Reactive DAO implementation

```
Flux<String> names = reactiveUserDao.getUsers()  
    .map(user->user.getName());
```

Non-blocking approach



To take complete advantage of Reactive Programming, a end-to-end Reactive system must be setup



Webflux web framework for Spring Boot (uses the project reactor)

reactor-core api : unit test cases

---

Creating a Flux Stream/ Reactive Stream/ Reactive Publisher

Flux.just(<data>)

Mono.just(<single data>)

# java 8 Stream are not - reusable

# Reactive Streams (Flux) is reusable

# By default when we subscribe to Publisher (Flux/Mono),

other activities :

returning subscription, sending request(unbounded) : behind the scene

publisher will start streaming data using onNext(data) event, for each data (auto)

==> Directly access the data as a stream

Factory Methods : for creating Flux and Mono

Just like Java 8 Stream a series of activities can be associated with Reactive Stream

Filter

Map/flatMap

Combine Reactive Streams...

Restart/Retry generating reactive stream after error : multiple retry...

BackOff Retry if still `OnError()` is propagated : `IllegalStateException`

## BackPressure

TO have an absolute control over backpressure, we need to provide an implementation of abstract class: BaseSubscriber

Traditional Client-server : Push based model ( Server push data to client)


Push/Pull model : Client-Server both are having equal control over data flow

Flux (publisher)variant :

- cold (default)


- hot

## Default Data Flow – Project Reactor



## What is Backpressure?

- Subscriber controls the data flow from the Publisher.



## Spring Boot

Develop Reactive REST APIs

- # Traditional Spring MVC does not have reactive support

- # Webflux : Web MVC Reactive framework

Webflux : Two approaches of reactive development

- # Similar approach of traditional MVC style ( Annotation based controller)

- # Functional Web

---

Traditional style built on top of new tech

Traditional request is converted into reactive request by netty server

### Unit Testing RestAPI

Traditional MVC : Test RestTemplate

WebFlux : WebClient


1. WebClient : Reactive Client
2. WebTestClient : Unit Test for Reactive Rest Endpoints



## WebFlux - Functional Web

# Using Functions to route request and response

1. Router Function
2. Handler Functions



Handler have access over 2 objects

1. `ServerRequest : HttpRequest`
2. `ServerResponse : HttpResponse`

=> Handle the request and generate the response

=> body of service method of controller


2 classes

1. Container for handler function
2. Container for router function

ServerResponse provides factory method/status (BodyBuilders : used to create body of response)

Routers

- Approach 1 : Individual method for each route
- Approach 2 : Single method for all route



Netty :

An asynchronous event-driven network application framework used for development of high performance servers

Netty is build on top of JAVA


# Major clients uses netty

# Protocols

FTP/HTTP/SMTP/WebSocket

---

Asynchronous



### Events (Netty)

client request for new connection

client request for data is event


client posting data is event

error are treated as event

---


Netty -Channel : represents connection between client and server






## Netty - Event Loop

- Loop the looks for events.
- EventLoop is registered with a **single** dedicated thread.




# Channel LifeCycle






## EventLoop + Channel



## EventLoop + Multiple Channel



Netty might run multiple event loops

no of event loops :  $2 \times$  no of processor (4)

eg : 8

EventLoopGroups: multiple event loops can be clubbed

2 groups of 4 event loops:

1 : handle web request (4 event loops)


2 : IoT : (4 event loops)


By default :

Provides 2 event-loop groups of 1 event-loop each

# EventLoopGroup

- How many EventLoopGroup are there in Netty?
- 2 EventLoop Groups.





Entity class :

Document class

Repository : JPA interface

mongodb-reactive-adapter reactive-repository interface (same as JPA)

unit test case for testing repository

For any reactive stream to work or activate :

1. we need to subscribe
2. we need to block // for testing

---

Reactive Rest API

# Bootstrap class : Initializer of dummy records for embedded db

---

Handling Exception

Controller (Traditional MVC) :

@ExceptionHandler

@ControllerAdvice/@RestControllerAdvice

Reactive Client Application : WebClient class

Non-Reactive : RestTemplate

---

#### MVC Application with View Templates

Webflux framework: need to use a reactive compatible view template

Thymeleaf : pre-configured to work on reactive stream

Similar to jsp + jstl

pre-configured to work boot (folder under resources : template )

files will be html files

Thymeleaf : forms by default CSRF safe