RAJALAKSHMI ENGINEERING COLLEGE

S Harini 251701014-2025-CSD

S2

Started on	Monday, 28 September 2026, 3:45 PM
State	Finished
Completed on	Monday, 28 September 2026, 4:13 PM
Time taken	27 mins 51 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int majorityelement(int nums[],int n)
{
    int candidate=0;
    int count=0;
    for(int i=0;i<n;i++) {
        if (count==0)
        candidate =nums[i];
        if(nums[i]==candidate)
        count++;
        else
        count--;
    }
    return candidate;

}
int main() {
    int n;
    scanf("%d",&n);
    int nums[n];
    for(int i=0;i<n;i++) {
        scanf("%d",&nums[i]);

    }
    printf("%d\n",majorityelement(nums,n));
    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course