TCS Corporate Website - Author Guide

Date: October 11, 2026

Adobe

Table of Contents

TCS Corporate Website - Author Guide 3
- Quick Reference 3
- Getting Started 4
- Pages to Create 5
- Content Organization 9
- Block Library (Component Picker) 12
- Available Blocks 12
- Site Global Templates (Page Types) 16
- Header and Footer 17
- Error Pages 18
- Configuration Sheets 19
- Publishing Workflow 25
- Common Tasks 25
- Sections and Section Properties 26
- Page Metadata 27
- Images and Media 28
- Troubleshooting 29
- Resources 30
- Support Contacts 31

TCS Corporate Website - Author Guide

This guide is for content authors and content managers working on the TCS Corporate website. The site is built with AEM Edge Delivery Services and authored in **AEM Sites as a Cloud Service with the Universal Editor**. You edit pages visually in the Universal Editor. When you publish, your changes go to the fast Edge Delivery Services website.

What changed in this edition:

- **New "404 Page" page property.** Page Properties now has **Title**, **Description**, **Keywords**, **Page Type**, **Navigation**, **Footer** and the new **404 Page**. 404 Page sets the "page not found" page for missing pages below that page (see *Error Pages*).
- **Navigation, Footer and 404 Page are inherited by child pages**, like AEM inherited page properties. Set them once on a section's top page (for example `/en/careers`) and every page below uses them, unless a page sets its own value (see *Header and Footer*).
- **New lookup order for the header and footer:** the page's own value, then the nearest parent page's value up to the locale's Home page, then the locale's `references/nav` / `references/footer`.
- **New lookup order for the 404 page:** the 404 Page of the nearest existing parent page, then the locale's `error-pages/404`, then the English `/en/error-pages/404`, then the built-in text. Only 404 is handled by the site. The `403` and `500` pages are kept for the CDN team and the site does not use them on its own.
- **New optional metadata sheet column** `error-page` (next to `nav` and `footer`).
- **Unchanged since the last edition:** the 13 locale sites, language-only URLs (`/en/`, `/de-de/`, ...), Home as the `index` page of each locale, the *Pages to Create* checklist and exact page names, per-locale sheets, metadata that applies only after the administrator lists all 13 sheets, per-locale redirects that need an administrator or CDN mechanism, and all blocks.

Quick Reference

Resource	URL / Location
AEM Author (Sites console)	https://author-p220207-e2271469.adobeaemcloud.com/ui#/aem/sites.html/content/tcs-corp
Content root in AEM	`/content/tcs-corp/` (13 locale sites and the Site Global Templates. The root has no page of its own)
Locale sites	`/content/tcs-corp/{country}/{language}/`, published at `/{language}/`. Example: `/content/tcs-corp/us/en/` is published at `/en/`, and `/content/tcs-corp/de/de-de/` at `/de-de/` (see *Languages and Locales*)
Home pages	`/en/`, `/de-de/`, `/fr-fr/`, `/fr-ca/`, `/es-es/`, `/pt-pt/`, `/nl-nl/`, `/sv-se/`, `/da-dk/`, `/no-no/`, `/zh-cn/`, `/ja-jp/`, `/ko-kr/`. The bare `/` has no page of its own and needs a redirect to `/en/` set up by your administrator or developer (for example a CDN rule)
Universal Editor	Open any page from the Sites console with **Edit**
Preview	https://main--tcs-corp--sradha-tcs.aem.page/en/ (and `/de-de/`, ...)
Live	https://main--tcs-corp--sradha-tcs.aem.live/en/ (and `/de-de/`, ...)
Site Global Templates	`/content/tcs-corp/site-global-templates/` (site root, shared by all locales, author only, not published)

Resource	URL / Location
Block library	Per locale: `/content/tcs-corp/{country}/{language}/block-library/`, e.g. `us/en/block-library/`, `de/de-de/block-library/` (author only, not published)
Component (block) picker	The **Add (+)** button in the Universal Editor content tree
Images and assets	AEM Assets, `/content/dam/tcs-corp/`
Bulk metadata sheet	Per locale, at its own path: `us/en/metadata` is published as `/en/metadata.json`, `de/de-de/metadata` as `/de-de/metadata.json`, … All 13 apply only after administrator configuration
Placeholders sheet	Per locale: `{locale}/placeholders`, published as `/en/placeholders.json`, `/de-de/placeholders.json`, …
Taxonomy	Per locale: `{locale}/taxonomy`, published as `/en/taxonomy.json`, `/de-de/taxonomy.json`, …
Redirects sheet	Per locale: `{locale}/redirects`, published as `/en/redirects.json`, `/de-de/redirects.json`, … Not applied by Edge Delivery on its own (the platform only applies a root `/redirects.json`); another mechanism, such as CDN rules, must apply it
Data sheets	Per locale: `{locale}/data/`, published as `/en/data/{sheet}.json`, `/de-de/data/{sheet}.json`, …

Sites

Site	Content Source	Preview	Live
tcs-corp	AEM Author: `/content/tcs-corp/` (Universal Editor)	https://main--tcs-corp--sradha-tcs.aem.page/	https://main--tcs-corp--sradha-tcs.aem.live/

> **Note on site configuration:** The Config Service organization is `sradha-tcs`. The Config Service site list (`admin.hlx.page/config/sradha-tcs/sites.json`) needs an authenticated admin token and returned HTTP 401 when this guide was generated. The site row above therefore comes from the project's preview and live URLs and its AEM content mount. This one site serves all 13 locales under their language paths (`/en/`, `/de-de/`, …). Ask your administrator to confirm whether more sites exist (a "repoless" multi-site setup). This project is authored in AEM with the Universal Editor, so there is no Document Authoring (da.live) path or `.da/library`. The component picker and the AEM block library pages take their place.

Getting Started

Access Requirements

- ☐ An Adobe ID with access to the AEM as a Cloud Service author environment (request it from your AEM administrator)
- ☐ Permissions to edit pages under `/content/tcs-corp/` (at least your locale folder, e.g. `us/en` or `de/de-de`)
- ☐ Permissions to publish, or to start a publish/approval workflow, depending on your role
- ☐ Access to the AEM Assets folder `/content/dam/tcs-corp/` for uploading images
- ☐ For content managers: permission to edit your locale's sheets (`metadata`, `placeholders`, `taxonomy`, `redirects`, `data/*`), the `references/` pages and AEM tags

Your First Page

1. Sign in to AEM Author, open **Sites** and go to your locale folder. For example, use `TCS Corp > us > en` (`/content/tcs-corp/us/en/`) for English or `TCS Corp > de > de-de` for German.
2. For a press release, blog post, article or home page, **copy the matching template page** from **Site Global Templates** (see *Site Global Templates*) and paste it into the target folder. For other pages, use **Create > Page**.
3. Give the page a title and a name. The name becomes the URL under the locale's language path. For example, `newsroom/q3-results` in `us/en` is published as `/en/newsroom/q3-results`, and in `de/de-de` as `/de-de/newsroom/q3-results`.
4. Select the page and click **Edit**. The page opens in the Universal Editor.
5. In the content tree, select a section and click **Add (+)** to insert components such as Text, Title, Image, Button, Hero or Teaser.
6. Select each component and fill in its fields in the **Properties** panel on the right.
7. Open **Page Properties** and fill in **Title**, **Description** and **Keywords**. Check the **Page Type** (a copied template page already has it). Leave **Navigation**, **Footer** and **404 Page** empty: the page then inherits them from its parent pages. Set them only if this page (and the pages below it) needs a different header, footer or "page not found" page.
8. Make sure a row of the bulk metadata sheet covers the page's URL if it needs author-id, publish-date, reading-time, region, SEO or social values (see *Page Metadata*).
9. Click **Publish** in the Universal Editor toolbar. Publish to Preview first to check the page, then publish to Live.

Pages to Create

Use this checklist to set up a locale. **Every one of the 13 locales needs the same pages and sheets.** The examples use `/content/tcs-corp/us/en` (published at `/en/`). For another locale, replace the AEM folder and the published path:

AEM folder	Published	AEM folder	Published	AEM folder	Published
us/en	/en/	pt/pt-pt	/pt-pt/	no/no-no	/no-no/
de/de-de	/de-de/	nl/nl-nl	/nl-nl/	cn/zh-cn	/zh-cn/
fr/fr-fr	/fr-fr/	se/sv-se	/sv-se/	jp/ja-jp	/ja-jp/
ca/fr-ca	/fr-ca/	dk/da-dk	/da-dk/	kr/ko-kr	/ko-kr/
es/es-es	/es-es/				

Page names matter. The site finds pages and sheets by their exact name. Use the names below exactly as written: lowercase letters, digits and hyphens only, with no spaces or capitals. The page **Title** can be anything; only the **Name** counts. For example, the URL of `/content/tcs-corp/de/de-de/data/social-links` is `/de-de/data/social-links.json`.

1. Locale Folder, Home and Content Pages

- ☐ **Country page** `/content/tcs-corp/us` (`de`, `fr`, `ca`, ...). This is only a container for the locale and is not published.
- ☐ **Locale folder page** `/content/tcs-corp/us/en` ("English"): holds all pages and sheets of the locale.
- ☐ **Home page** `/content/tcs-corp/us/en/index` (title "Home", page name `index`), published at `/en/`. Set its Page Type to **Home** and build it like `site-global-templates/home` (or create it as a copy of that page, renamed to `index`).

- ☐ **Content pages** below the locale root, named in lowercase with hyphens. Examples: `newsroom/`, `insights/`, `careers/`, `about/leadership`. A page at `us/en/about/leadership` is published at `/en/about/leadership`. For press releases, articles and blogs, copy the matching Site Global Template page.

2. References (`us/en/references/`)

Page	AEM path	Required	Purpose
`references`	`/content/tcs-corp/us/en/references`	Yes	Folder page for the pages below. Leave it empty
`nav`	`/content/tcs-corp/us/en/references/nav`	Yes	Default header navigation of the locale
`footer`	`/content/tcs-corp/us/en/references/footer`	Yes	Default footer of the locale (the social icons come from `data/social-links`)
`nav-{name}`, `footer-{name}`	e.g. `references/nav-careers`, `references/footer-campaign`	Optional	Alternative headers and footers. Choose them in the page properties of a section's top page (inherited by the pages below) or in the metadata sheet
`modals/{name}`	e.g. `references/modals/contact-us`	Optional	Pop-up content. Any link to a page with `/modals/` in its path opens as a modal
Fragments	e.g. `references/cta-banner`	Optional	Shared content for the Fragment block

3. Error Pages (`us/en/error-pages/`)

- ☐ `error-pages`: folder page, left empty (`/content/tcs-corp/us/en/error-pages`)
- ☐ `404`: "page not found" content, shown for any missing `/en/...` page (unless a parent page sets a different **404 Page**)
- ☐ `403`: access denied. Kept for the CDN team. The site does not use it on its own
- ☐ `500`: server error. Kept for the CDN team. The site does not use it on its own
- ☐ Optional: other "page not found" pages for a section, for example `error-pages/404-careers`. Pick them in the **404 Page** property of the section's top page (see *Error Pages*)

The English `/content/tcs-corp/us/en/error-pages/404` is also the fallback for every locale that has not published its own 404, so publish it first.

4. Block Library (`us/en/block-library/`, author only)

Create one page per block, each showing every variation of the block in the locale's language. These pages are **not published**. They are for checking blocks on author.

Page name	Page name	Page name
`accordion`	`form-variations`	`page-header`
`anchor-list`	`fragment`	`quote`
`cards`	`gen-carousel` (a Gen Carousel section with Hero and Teaser slides)	`table`
`columns`	`hero`	`table-list`
`conversation-canvas`	`interactive-dashboard`	`tabs`

Page name	Page name	Page name
embed	list	teaser
filter-list	modal	testimonial
		video

- ☐ `block-library` folder page (`/content/tcs-corp/us/en/block-library`)
- ☐ All 22 block pages above. Header and Footer have no block library page: they are edited through `references/nav` and `references/footer`.

5. Sheets at the Locale Root

Create each sheet with **Create** > **Page**, using the AEM template shown. Add the column headers exactly as listed.

Page name	AEM template	Columns	Published URL (example `us/en`)
placeholders	**Placeholders**	Key, Text, Description, Category	/en/placeholders.json
metadata	**Metadata**	`url` and the metadata columns (see *Bulk Metadata Sheet*)	/en/metadata.json
taxonomy	**Taxonomy**, with the **TCS Corp** tag namespace selected	Generated from the tags (tag ID, title)	/en/taxonomy.json
redirects	**Redirects**	Source, Destination	/en/redirects.json

6. Data Sheets (`us/en/data/`)

- ☐ `data`: folder page, left empty (`/content/tcs-corp/us/en/data`)

Page name	AEM template	Columns (exact headers)	Published URL (example `us/en`)
authors	**Spreadsheet**	author-id, name, designation, bio, image, linkedin, region	/en/data/authors.json
locations	**Spreadsheet**	location-id, location-name, country, region, latitude, longitude	/en/data/locations.json
partners	**Spreadsheet**	partner-id, partner-name, logo, website, tier, description	/en/data/partners.json
social-links	**Spreadsheet**	platform, url, icon, sort-order	/en/data/social-links.json
media-contacts	**Spreadsheet**	id, name, designation, email, phone, region	/en/data/media-contacts.json

In other locales the URLs follow the same pattern: `/de-de/placeholders.json`, `/de-de/metadata.json`, `/de-de/taxonomy.json`, `/de-de/redirects.json`, `/de-de/data/authors.json`, and so on.

7. Metadata Rows Every Locale Needs

- ☐ Start every `url` pattern with the locale's published path (`/en/...` in `us/en/metadata`, `/de-de/...` in `de/de-de/metadata`). Rows for other locales have no effect.
- ☐ Add `robots` = `noindex, nofollow` rows so fragments, error pages (`/{locale}/error-pages/**`) and data are never indexed:

url	robots
/en/references/**	noindex, nofollow
/en/error-pages/**	noindex, nofollow
/en/data/**	noindex, nofollow

- ☐ Add rows for the content folders as needed (for example `/en/newsroom/**` with `page-type press-release`).
- ☐ Optional: set **Navigation**, **Footer** or **404 Page** on a section's top page (for example `/en/careers`) instead of a sheet row. All pages below inherit them.

8. Site Global Templates (once, at the site root)

These pages are shared by all 13 locales and are not published. **The page name is the Page Type.**

Page name	AEM path	Page Type
site-global-templates	/content/tcs-corp/site-global-templates	Folder page, left empty
home	/content/tcs-corp/site-global-templates/home	home
article	/content/tcs-corp/site-global-templates/article	article
blog	/content/tcs-corp/site-global-templates/blog	blog
press-release	/content/tcs-corp/site-global-templates/press-release	press-release

9. Ask Your Administrator (once, for the whole site)

- ☐ **Bulk metadata:** list all 13 metadata sheets (`/en/metadata.json`, `/de-de/metadata.json`, ... `/ko-kr/metadata.json`) in the site configuration's metadata sources. **No bulk metadata applies until this is done**, English included.
- ☐ **Redirects:** set up a mechanism, such as CDN rules, that applies the 13 per-locale redirects sheets. The platform only applies a root `/redirects.json` automatically, so the locale sheets do nothing on their own. This mechanism must include the redirect from `/` to `/en/`, because the site root has no page of its own.
- ☐ **CDN error pages (optional):** the site itself handles only "page not found" (404). If access-denied (403) or server-error (500) pages are wanted, the CDN team must configure the CDN to serve `error-pages/403` and `error-pages/500`.

10. Publish

- ☐ Publish (Preview, then Live) the Home page (`index`), the content pages, `references/nav`, `references/footer`, other references, the error pages, every sheet and every data sheet. If `references/nav` (or the nav

page that a page uses) is not published, the header stays empty. Do **not** publish `block-library/` or `site-global-templates/`; they are excluded from publishing anyway.

Content Organization

Site Structure

```
/content/tcs-corp/
├── us/en/                    a locale site (country/language); this page is the
│   │                         Home page, published at /en/
│   ├── ...                   content pages (e.g. newsroom/, insights/)
│   ├── references/           nav (header), footer, other fragments and reference pages
│   ├── error-pages/          404 (used by the site); 403, 500 (kept for the CDN team)
│   ├── block-library/        every block variation, in the locale's language (not
published)
│   ├── placeholders          sheet: Key, Text, Description, Category
│   ├── metadata              sheet: bulk metadata
│   ├── taxonomy              taxonomy page (tag, title)
│   ├── redirects             sheet: Source, Destination
│   └── data/                 sheets: authors, locations, partners,
│                             social-links, media-contacts
├── de/de-de/                 published at /de-de/, same layout as us/en
├── ...                       11 more locale sites, same layout (see Languages and Locales)
└── site-global-templates/    template pages to copy, shared by all locales (not published)
```

Public URLs drop `/content/tcs-corp/{country}` and publish each locale's pages under its language code. For example, `/content/tcs-corp/us/en/about/leadership` becomes `/en/about/leadership`, and `/content/tcs-corp/de/de-de/about/leadership` becomes `/de-de/about/leadership`.

Path in AEM (example: `us/en`)	Published URL	Purpose
`/content/tcs-corp/us/en/index` (Home)	`/en/`	Home page of the English site (`/de-de/` for German, and so on)
`/content/tcs-corp/us/en/references/nav`	`/en/references/nav`	Default header navigation of the locale
`/content/tcs-corp/us/en/references/footer`	`/en/references/footer`	Default footer of the locale
`/content/tcs-corp/us/en/references/...`	`/en/references/...`	Other fragments: alternative navs and footers (e.g. `nav-careers`), shared content for the Fragment block
`/content/tcs-corp/us/en/error-pages/404`	shown on any missing `/en/...` page	Authored "page not found" content, unless a parent page sets a different 404 Page. `403` and `500` are kept for the CDN

Path in AEM (example: `us/en`)	Published URL	Purpose
		team and not used by the site
`/content/tcs-corp/us/en/.../modals/...`	`/en/.../modals/...`	Pages whose content opens in a pop-up (modal) when linked
`/content/tcs-corp/us/en/block-library/*`	(not published)	Pages with all block variations, for checking blocks in the locale's language on author
`/content/tcs-corp/us/en/metadata`	`/en/metadata.json`	Bulk metadata of the locale (`/de-de/metadata.json`, and so on)
`/content/tcs-corp/us/en/placeholders`	`/en/placeholders.json`	All interface text (labels, messages) of the locale
`/content/tcs-corp/us/en/taxonomy`	`/en/taxonomy.json`	Tag labels of the locale
`/content/tcs-corp/us/en/redirects`	`/en/redirects.json`	URL redirects of the locale (`/de-de/redirects.json`, and so on). Not applied by Edge Delivery on its own (see *Redirects Sheet*)
`/content/tcs-corp/us/en/data/*`	`/en/data/*.json`	Authors, locations, partners, social links, media contacts of the locale
`/content/tcs-corp/site-global-templates/*`	(not published)	Template pages `home`, `article`, `blog`, `press-release` (page name = Page Type)
`/content/dam/tcs-corp/`	(images)	Images and media in AEM Assets

Everything in the 13 locale folders is published except each locale's `block-library/`. `site-global-templates` is not published. Nothing at the content root (`/content/tcs-corp`) is published. The bare domain `/` therefore has no page of its own and needs a redirect from `/` to `/en/`. Because the per-locale redirects sheets are not applied by Edge Delivery on their own, your administrator or developer must set this redirect up with another mechanism (for example a CDN rule).

References, error pages, data sheets, nav and footer are **not** included in the site search index. They are not content pages.

Languages and Locales

The site has **13 locale sites**. Each lives in AEM under `/content/tcs-corp/{country}/{language}/` and is published at a language-only path:

Locale	AEM folder	Published at	Page language (`<html lang>`)
English (United States)	`us/en`	`/en/`	`en-US`
German (Germany)	`de/de-de`	`/de-de/`	`de-DE`
French (France)	`fr/fr-fr`	`/fr-fr/`	`fr-FR`
French (Canada)	`ca/fr-ca`	`/fr-ca/`	`fr-CA`
Spanish (Spain)	`es/es-es`	`/es-es/`	`es-ES`
Portuguese (Portugal)	`pt/pt-pt`	`/pt-pt/`	`pt-PT`
Dutch (Netherlands)	`nl/nl-nl`	`/nl-nl/`	`nl-NL`
Swedish (Sweden)	`se/sv-se`	`/sv-se/`	`sv-SE`
Danish (Denmark)	`dk/da-dk`	`/da-dk/`	`da-DK`
Norwegian (Norway)	`no/no-no`	`/no-no/`	`no-NO`
Chinese (China)	`cn/zh-cn`	`/zh-cn/`	`zh-CN`
Japanese (Japan)	`jp/ja-jp`	`/ja-jp/`	`ja-JP`
Korean (Korea)	`kr/ko-kr`	`/ko-kr/`	`ko-KR`

The site reads the locale from the page path. In the Universal Editor it uses the AEM folder (`/content/tcs-corp/de/de-de/...`). On the published site it uses the language path (`/de-de/...`). Pages outside a locale, such as the Site Global Templates, use English (`en`).

Per locale: every locale has its **own** pages, navigation and footer (`references/`), error pages, block library, placeholders (interface text), taxonomy (tag labels, from the locale's language sheet when titles are translated), data sheets (authors, social links, media contacts, …), bulk metadata and redirects. The page language is set from the locale (for example `de-DE`), unless a page's `language` metadata sets a different one. Locales share no content: create and translate each locale's pages, sheets and data in that locale's folder.

Set up once, at site level:

- **Bulk metadata:** every locale's sheet, English included, is published at its own path (`/en/metadata.json`, `/de-de/metadata.json`, …). There is no root `/metadata.json`. The platform applies the sheets only once your administrator lists all 13 in the site configuration (metadata sources); until then no bulk metadata applies. Each sheet's URL patterns must start with its own locale (`/en/**` in `us/en/metadata`, `/de-de/**` in `de/de-de/metadata`). Check with the administrator before you rely on the sheets.
- **Redirects:** each locale has its own redirects sheet, published at its own path (`/en/redirects.json`, `/de-de/redirects.json`, …). There is no site-root redirects sheet. The platform only applies a root `/redirects.json` automatically, so the per-locale sheets are **not** applied by Edge Delivery on their own. Your administrator or developer must set up another mechanism (for example CDN rules) that applies them, including the redirect from `/` to `/en/`. Keep each locale's redirects in its own sheet (for example `/de-de/alte-seite` to `/de-de/neue-seite` in `de/de-de/redirects`), and check with the administrator before you rely on them.

Adding a new locale takes development and administrator work (code and publishing configuration). Ask the development team.

Block Library (Component Picker)

In this Universal Editor project, blocks are called **components**. You add them through the component picker in the editor. You do not type block names or build tables.

What	Details
Open it	Select a section (or a container block such as Cards, Tabs or Accordion) in the content tree, then click **Add (+)**
What's in it	Only the components allowed in the selected container are shown. A section allows default content (Text, Title, Image, Button) and all blocks listed below. Container blocks allow only their own items. For example, Cards allows Card, and Tabs allows Tab
How to use	Click a component to insert it. Then fill in its fields in the Properties panel
Page level	At the top (page) level you can add a **Section** or a **Gen Carousel** (a carousel section)
Block library pages	Each locale has a `block-library/` folder (e.g. `/content/tcs-corp/us/en/block-library/`, `/content/tcs-corp/de/de-de/block-library/`) with pages showing every block variation in that language. Use them on author to see what each option looks like and to check blocks with the locale's text (text length, characters, translated labels). They are not published

Default Content Components

Component	Fields	Notes
Text	Rich text	Paragraphs, lists, inline links, bold and italic
Title	Title, Title Type (h1-h6)	Use one h1 per page and keep the heading levels in order
Image	Image, Alt Text	Always fill in Alt Text unless the image is purely decorative
Button	Link, Text, Title, Views (Button / Icon / Link), Type (Primary / Secondary / Tertiary), Icon (Arrow right, Chevron right, Chevron down, Search), Alignment (Left / Center / Right)	All buttons on the site share these styles

Available Blocks

Block	Purpose	Variants / Options	When to Use
Page Header	Header for secondary pages. Title, description, tags, publish date, reading time and author come from the **page metadata** and the **Authors** sheet. CTAs and actions are block fields	Style: *Auto (by Template)*, *Landing*, *Article*. See *Page Header in Detail*	First block on article, blog, press release, listing and landing pages. Added automatically by the article, blog and press-release templates
Hero	Large page-opening banner with image or animation, icon, eye-	Image type: Default image or *Lotto* (a Lottie animation, `.json` file); Alignment: Top / Middle / Bottom; BG Color: Default, Dark blue, Dark blue (subtle),	Top of landing and home pages. Can also be a slide in a Gen Carousel

Block	Purpose	Variants / Options	When to Use
	brow, title, description and CTAs	Black; Title heading level H1 / H2; CTA List (title, link, link type, CTA view)	
Teaser	Text and image side by side, or a text section with links	Style: Default (image left or right) or *No Image, Right Desc* & *Links*; BG Color: Default, Grey, Dark, Dark green; show/hide eyebrow, title, description and image; optional date (DD-MM-YYYY, MM-DD-YYYY, MMM d, yyyy) and tags (labels from the taxonomy); View All link; Short Description; primary + secondary CTA, or MultiLinks (List / Primary / Secondary style); Personalization flag	Feature callouts, "Text & Image" content, intro text with links. Can be a Gen Carousel slide
Gen Carousel	A carousel *section* whose slides are Hero or Teaser components	Navigation: Manual (previous/next, dots, swipe), Auto (with pause button), Manual and Auto; Autoplay interval in seconds (default 5, hidden for Manual)	Rotating hero or teaser content. See *Gen Carousel (Section Component)*
Cards	Grid of cards, each with an image and rich text	Standard	Lists of offerings, articles or features with images
Columns	Side-by-side columns of Text, Image, Button or Title	Number of columns and rows set in the block	Two- or three-column layouts
Quote	Eyebrow and title above a quote card with large quote marks, overlapping a portrait	BG Color: Default, Grey; Title Type h1-h6; Quote Author (name on the first line, then designation and organisation); image + alt text	Executive quotes and pull quotes
Testimonial	Centered testimonial with author image, designation and statistics	BG Color: Default, Grey; Hide Eyebrow, Hide Title, Show Description; Stats list (Stats Title + Stats Value)	Client testimonials with key figures
Table List	Heading with a "View all" link and numbered cards (number, title, description, arrow link, tags)	Variations: Compact, No Description, Black Theme, Featured Industry, No Number, Description First, Title Right; View: List / Table; Card Color: White, Blue, Black, Grey; Display: Title and Description / Title only / Description only; Motion: None, Fade, Slide, Reveal; Maximum Cards (1-4); Show Tags; View All Title + Link; List Title. Items: Table List Header, Table List Card	Solution lists, numbered highlights, featured industries
List	Header row with a title and a CTA on the right	Title Type h1-h6; CTA Style: Default (text link), Primary Button, Secondary Button	Section headings that need a "See all" style link
Anchor List	Chapter navigation. Each link jumps to a section, and the current chapter is highlighted	Sticky on/off; Links = Link Title + Anchor Name	Long pages. Give target sections an **Anchor name** in Section properties
Accordion	Collapsible items	Items: Summary + Text	FAQs and long content split into topics
Tabs	Tabbed panels	Each tab: Tab Title, Heading, Heading Type (H3-H6), Image, Content	Grouping related content on one panel
Table	Data table with 1-5 columns	Columns: 1-5; Options: Striped, Bordered, No Header	Tabular data such as specifications and comparisons
Conversation Canvas	Interactive canvas with eyebrow, title, text, buttons, a menu	Canvas Style: Default, Primary (sticky), Secondary; Title Type: Default, Bigger, Medium; background image; icon + alt text; Menu (root path + depth); Search	AI / conversational entry points on landing pages

Block	Purpose	Variants / Options	When to Use
	built from site pages and a search bar	bar (placeholder text, audio icon + alt text, button style, button hover text). Suggestion pills on pages without sub-pages come from the page's tags (labels from the taxonomy)	
Form Variations	Contact-style form built from field items	Theme: Default / Dark; Form Title and Description; items: Text Input (Text / Email / Tel), Dropdown (comma-separated options), Textarea (character limit, default 1500), Consent Checkbox, Contact Card (shown for a dropdown value), Submit Button; any field can be shown only for a given dropdown value	Contact and enquiry forms. **Note:** form submissions are not yet connected to a backend. Check with your development team before going live
Embed	Embeds videos and social posts from a URL, with an optional placeholder image	URI; Placeholder Image + alt text	YouTube, Vimeo and other embeddable content
Video	Plays a video from YouTube, Vimeo or a video file	Options: AutoPlay; Placeholder Image + alt text	Stand-alone video content
Modal	Button that opens another page's content in a pop-up	Modal Content (page), Button Text	Pop-up details, forms or disclaimers. Any link to a `/modals/` page also opens as a modal
Fragment	Reuses the content of another page	Reference (page path)	Shared content repeated on many pages. Keep fragment pages in the locale's `references/` folder
Filter List	*Placeholder.* It shows a label in the editor and nothing on the site	None yet	Do not use on live pages until the development team finishes it
Interactive Dashboard	*Placeholder.* It shows a label in the editor and nothing on the site	None yet	Do not use on live pages until the development team finishes it
Header	Site header and navigation, loaded automatically (see *Header and Footer*)	n/a	Edited through the nav page (`references/nav` by default, or the Navigation inherited from a parent page), not added to pages
Footer	Site footer, loaded automatically (see *Header and Footer*). It also shows the **Social Links** sheet	n/a	Edited through the footer page (`references/footer` by default, or the Footer inherited from a parent page), not added to pages

Page Header in Detail

The Page Header builds its text from the **page metadata** and the **Authors** data sheet, and adds the block fields listed below. You do not type the title or description into the block.

Comes from	Field	Shown as
Page properties	Title	The page heading (h1)
Page properties	Description	Description text

Comes from	Field	Shown as
Page properties or metadata sheet	Page Type (`page-type`)	Picks the layout when the block Style is *Auto*: `landing` or `listing` gives the Landing layout. Anything else (including article, blog, press-release) gives the Article layout
Metadata sheet	`publish-date`	"Published DD/MM/YY" in the Article meta row. Use `YYYY-MM-DD`
Metadata sheet	`reading-time`	A number (e.g. `14`) is shown as "14 min read". The block's Time to Read overrides it
Metadata sheet	`author-id`	Looks up the author in the **Authors** sheet: name (linked to LinkedIn), image, designation and region
Page tags	Tags	Tag labels (from the taxonomy): the eyebrow in Landing, the meta row in Article

Block tab	Field	Notes
Style	Style	*Auto (by Template)* (default), *Landing* or *Article*. A chosen style overrides the Page Type
CTAs	Primary CTA Title / Link / Link Type / Link Style	Link Type: Default or Open in New Window. Link Style: Default (text link), Primary Button (default), Secondary Button
CTAs	Second CTA Title / Link / Link Type / Link Style	Same options. Link Style defaults to text link
Author & Meta	Author Name	Overrides the name from the Authors sheet
Author & Meta	Author Image + Alt Text	Overrides the Authors sheet image. Leave the alt text empty when the name is shown next to the image
Author & Meta	Designation & Location	Overrides the Authors sheet designation and region
Author & Meta	Time to Read	Overrides `reading-time`. A number is shown as "{n} min read" (placeholder `minRead`). Any other text is shown as typed
Author & Meta	Collection Label	Shown after the tags, e.g. "Collection"
Author & Meta	Listen Link	Link to an audio version. Shows a headphones icon
Author & Meta	Social Share	Shows a share button (native share, or "Link copied to clipboard")
Author & Meta	Download	Shows a download button that prints or saves the page as a PDF
Image Collage	Image 1 (large, top left), Image 2 (bottom left), Image 3 (right), each with alt text	Shown in the **Landing** layout only. With a collage, all text sits on the left and the images on the right

Layouts: *Landing* shows the tags as an eyebrow, a large title, then the description and CTAs (or the image collage). *Article* shows a meta row (tags, collection label, publish date, reading time, listen / download / share), then the title and author on one side and the description and CTAs on the other.

Gen Carousel (Section Component)

Gen Carousel is not added inside a section. It **is** a section.

1. In the content tree, select the page (top) level and click **Add (+)** > **Gen Carousel**.
2. In its properties, choose **Navigation** (Manual, Auto, or Manual and Auto). For Auto modes, set the **Autoplay interval (seconds)** (default 5).
3. Select the Gen Carousel and click **Add (+)** to add slides. Only **Hero** and **Teaser** components are allowed. Each component is one slide.
4. Reorder slides by dragging them in the content tree.

Slide controls (previous / next, dots, pause / play) use labels from the placeholders sheet. Animation respects visitors' "reduced motion" setting.

Tips for Blocks

- **Alt text:** Most image fields have an alt-text field next to them. Describe the image, or leave it empty only when the image is decorative.
- **Heading levels:** Many blocks let you choose a Title Type (h1-h6). Use a single h1 per page, which is usually the Hero or Page Header. Then use h2, h3 and so on in order.
- **Links that open in a new window:** Choose *Open in New Window* as the link type.
- **Lotto image type (Hero):** Choose *Lotto* and point the image path to a Lottie animation `.json` file instead of an image.
- **Interface text:** Labels such as "Next slide", "Published", "About the author" or "Send" are not typed into blocks. Change them in the placeholders sheet.

Site Global Templates (Page Types)

Site Global Templates (`/content/tcs-corp/site-global-templates/`) are ready-made template pages for the main kinds of pages. They sit at the site root and are shared by all 13 locales. To create a page of a kind, **copy** its template page into your locale folder and edit (and translate) the copy. The template pages themselves are **not published**. Each template page is named after its Page Type (`home`, `article`, `blog`, `press-release`).

A page's **Page Type** selects its template code: the **Page Type** page property, or else the `page-type` column of the locale's bulk metadata sheet (for example `/en/newsroom/**` or `/de-de/newsroom/**` gives `press-release`). The Page Type is also added to the page as a CSS class, for template-specific styling.

Template page (page name)	Page Type	What the site adds automatically	What you author	Metadata to set
Home (`site-global-templates/home`)	`home`	Layout only (the first section meets the header)	All blocks (Hero, Gen Carousel, Teasers, …)	Title, Description, SEO / social columns
Article (`site-global-templates/article`)	`article`	A **Page Header** at the top if the page has none. An **"About the author"** card at the end, from the Authors sheet entry of `author-id` (image, name, designation and region, bio, LinkedIn link)	Body content. Optionally your own Page Header (for CTAs, share, download, collage)	`author-id`, `publish-date`, `reading-time`, tags

Template page (page name)	Page Type	What the site adds automatically	What you author	Metadata to set
Blog (`site-global-templates/blog`)	`blog`	Same as Article (Page Header, "About the author"), with blog styling	Body content	`author-id`, `publish-date`, `reading-time`, tags
Press Release (`site-global-templates/press-release`)	`press-release`	A **Page Header** at the top if the page has none. A **"Media contacts"** list at the end, from the Media Contacts sheet: the contacts of the page's `region`, else all contacts	Body content	`publish-date`, `region`, tags
(Default)	(empty)	Nothing	Everything, usually a Page Header or Hero first	As needed

How to apply:

1. Copy the template page from Site Global Templates into the target folder of your locale (for example `/content/tcs-corp/us/en/newsroom/` or `/content/tcs-corp/de/de-de/newsroom/`). The copy already has the right Page Type and starter content.
2. Or set **Page Properties** > **Page Type** (Default, Home, Article, Blog, Press Release) on any page.
3. Or set the Page Type for a whole folder with a `page-type` row in the locale's metadata sheet. The page property overrides the sheet.

Notes:

- The automatic "About the author" and "Media contacts" sections are removed when there is no matching data. Examples: no `author-id`, an unknown author, or no media contacts.
- An authored Page Header always wins. The template only adds one if the page has none.
- The values `landing` and `listing` can be set in the `page-type` column to give the Page Header its Landing layout. They have no template code.
- New Page Types (for example a case study) need a new template page and development work. Ask the development team.

Header and Footer

Every page loads a header (navigation) page and a footer page. They are **configurable** and **inherited**: like AEM inherited page properties, a page without its own Navigation or Footer uses the value of its nearest parent page. The first match wins:

Order	Where	Example
1	The page's **own** value: **Page Properties** > **Navigation / Footer** (content picker), or the `nav` / `footer` columns of the locale's **metadata sheet** for pages matching the row's URL pattern	`/content/tcs-corp/de/de-de/references/nav-careers`, or sheet row url `/de-de/careers/**`, nav `references/nav-careers`
2	The **nearest parent page** that has a value (its page property or sheet value), going up to the locale's Home page (`index`)	`/en/insights/blogs/post` checks `/en/insights/blogs`, then `/en/insights`, then `/en/`
3	The locale's default pages	`/de-de/references/nav` and `/de-de/references/footer` (`/en/references/nav` and `/en/references/footer` for English)

Tip: set **Navigation** (or Footer) once on a section's top page, for example `/en/careers`, and all pages below it inherit it. A page further down can still set its own value, which then also applies to the pages below it.

Values may be an AEM path (`/content/tcs-corp/de/de-de/references/nav-careers`), a published path (`/de-de/references/nav-careers`) or a path relative to the locale root (`references/nav-careers`). The relative form is recommended: it always points to the page's own locale, so the same value works in every locale's sheet.

Good to know:

- Inherited values are read from the **published** parent pages. Publish the parent page after you change its Navigation or Footer.
- Visitors' browsers remember inherited values for the browser session. A change on a parent page shows for visitors in a **new browser session** (or a new private window when you check it yourself). A value set on the page itself shows right after publishing.
- If the header's nav page is not published, the header **stays empty**. It does not fall back to another nav page. Publish the nav page that the page uses.

The **footer** also shows the locale's **Social Links** sheet as an icon list, in `sort-order`. Each link is labelled "Follow us on {platform}" (placeholder `followUsOn`).

Each locale has its own nav and footer, in its own language. Keep all navs, footers and other fragments in the locale's `references/` folder, and publish them like any other page.

Error Pages

The site handles **"page not found" (404)** only. When a visitor opens a page that does not exist, the site shows authored "page not found" content. It picks the content in this order, and the first page that loads wins:

Order	Where	Example
1	The **404 Page** set on the missing page's **nearest existing parent page**, going up to the locale's Home page (its page property, or the metadata sheet's `error-page` column). The 404 Page is inherited like Navigation and Footer	A missing `/en/careers/old-job` uses the 404 Page of `/en/careers` (for example `error-pages/404-careers`), else of `/en/`
2	The locale's `error-pages/404`	`/de-de/error-pages/404`
3	The English `/en/error-pages/404`. Its content is marked as English for screen readers and search engines	Used by a locale that has not published its own 404 yet
4	The built-in "page not found" text of the site	Shown when none of the above is published

If a configured 404 Page is not published or fails to load, the site moves on to the next step. The built-in **Go home** button leads to the locale's home page (e.g. `/de-de/`).

Page (in each locale, e.g. `us/en`, `de/de-de`)	Used for
`{locale}/error-pages/404`	Default "page not found" content of the locale. Its content replaces the built-in text
`{locale}/error-pages/404-{name}` (optional)	Section-specific "page not found" pages, picked in the 404 Page property of a section's top page
`{locale}/error-pages/403`	Access denied page. Kept for the CDN team. The site does not use it on its own
`{locale}/error-pages/500`	Server error page. Kept for the CDN team. The site does not use it on its own

Author error pages like normal pages (text, images, buttons) and publish them. Create and translate them in every locale. Add a `robots` = `noindex, nofollow` row for `/{locale}/error-pages/**` in each locale's metadata sheet (for example `/en/error-pages/**`, `/de-de/error-pages/**`, see *SEO and Social Sharing*).

Configuration Sheets

Sheet	Location in AEM	Published As	Purpose	When to Update
Bulk Metadata	`{locale}/metadata`	`/en/metadata.json`, `/de-de/metadata.json`, … (apply once the administrator lists all 13)	Page Type, SEO, social, author-id, dates, nav / footer / error-page and other metadata for pages matched by URL pattern	New sections, new articles, SEO and social changes
Placeholders	`{locale}/placeholders`	`/en/placeholders.json`, `/de-de/placeholders.json`, …	All interface text used by the site (Key, Text, Description, Category)	Changing labels, button text, messages, translations
Taxonomy	`{locale}/taxonomy`	`/en/taxonomy.json`, `/de-de/taxonomy.json`, …	Display labels for AEM tags (a sheet per language for translations)	Adding or renaming tags
Redirects	`{locale}/redirects`	`/en/redirects.json`, `/de-de/redirects.json`, … (not applied by Edge Delivery on its own, see *Redirects Sheet*)	Forward old URLs of the locale to new URLs (Source, Destination)	After deleting, moving or renaming pages in the locale
Authors	`{locale}/data/authors`	`/en/data/authors.json`, …	Author profiles for the Page Header and "About the author"	New or changed authors
Locations	`{locale}/data/locations`	`/en/data/locations.json`, …	Office locations	New or changed offices
Partners	`{locale}/data/partners`	`/en/data/partners.json`, …	Partner list	New or changed partners
Social Links	`{locale}/data/social-links`	`/en/data/social-links.json`, …	Social profile icons in the footer	New or changed social profiles
Media Contacts	`{locale}/data/media-contacts`	`/en/data/media-contacts.json`, …	"Media contacts" on press releases	Changes to press contacts

All locations are under `/content/tcs-corp/`. `{locale}` is the locale folder, for example `us/en` or `de/de-de`, published under its language path (`/en/`, `/de-de/`). Every locale has its own copy of each sheet, Redirects included.

> **Status:** When this guide was generated, none of the locale pages or sheets had been previewed yet. `/`, `/en/`, `/de-de/`, `/en/metadata.json`, `/en/redirects.json`, `/en/placeholders.json`, `/en/taxonomy.json` and `/en/`

> `references/nav` all returned "not found" on preview. Until they are published, the site uses built-in English labels, tag names derived from the tag IDs, the Article layout for Page Headers, no social links and no author or media contact data. Create each sheet in each locale as described below and publish it. Ask your administrator or developer to set up the `/` to `/en/` redirect (see *Redirects Sheet*).

Creating a Sheet in AEM

1. In the Sites console, open the locale (for example `TCS Corp > us > en` or `TCS Corp > de > de-de`, or its `data` folder for data sheets).
2. Click **Create > Page** and choose the matching spreadsheet template (**Metadata**, **Placeholders**, **Taxonomy**, **Redirects** or a general **Spreadsheet** for the data sheets). For the taxonomy, select the **TCS Corp** tag namespace.
3. Repeat for every locale that needs the sheet. Use exactly the page name shown in the table above (`metadata`, `placeholders`, `taxonomy`, `redirects`, `authors`, `locations`, `partners`, `social-links`, `media-contacts`).
4. Add the column headers exactly as listed below, add the rows, then **Publish** the sheet (Preview first, then Live).

Bulk Metadata Sheet (`{locale}/metadata`)

Each locale has its own sheet, published at its own path (`/en/metadata.json`, `/de-de/metadata.json`, ...). Its URL patterns must start with that locale's published path (`/en/...` in `us/en/metadata`, `/de-de/...` in `de/de-de/metadata`). No sheet is special: all 13 apply only after your administrator lists them in the site configuration; until then no bulk metadata applies (see *Languages and Locales*).

Each row applies metadata to every page whose URL matches the `url` column. Use `/**` for "this folder and everything below". Later rows add to and can override earlier rows. Values set on the page itself (page properties) take priority. Each column is published on the page as a `<meta name="{column}">` tag.

Column	Purpose	Example
`url`	Page path or pattern (published path, without `/content/tcs-corp/{country}`)	`/en/newsroom/**`, `/de-de/newsroom/**`
`page-type`	Page Type / template (see *Site Global Templates*)	`press-release`
`meta-title`	SEO title (browser tab), if different from the page Title	TCS Q3 Results
`meta-description`	SEO description, if different from the page Description	...
`meta-keywords`	SEO keywords	cloud, AI
`author-id`	Author ID from the Authors sheet	`jdoe`
`publish-date`	Publish date, `YYYY-MM-DD`	2026-10-01
`modified-date`	Last updated date, `YYYY-MM-DD`	2026-10-05
`reading-time`	Reading time in minutes	8
`og-title`, `og-description`, `og-image`, `og-type`	Social sharing (Open Graph). Title and description fall back to `meta-title` / `meta-description`	`article`
`twitter-card`, `twitter-title`, `twitter-description`, `twitter-image`	X (Twitter) cards. These fall back to the `og-*` values	`summary_large_image`

Column	Purpose	Example
`canonical-url`	Canonical URL of the page	`https://www.tcs.com/en/...`
`robots`	Search engine directives (standard, works without JavaScript)	`noindex, nofollow`
`region`, `country`, `language`	Targeting. `region` filters Media Contacts on press releases. `language` overrides the page language of the locale (e.g. `en-GB`). Leave it empty to use the locale's language (`en-US`, `de-DE`, ...)	`americas`, `us`, `en-US`
`persona`	Audience	`cio`
`thumbnail-image`, `featured-image`	Images for listings and cards	`/content/dam/tcs-corp/...`
`campaign-id`	Campaign tracking ID	`fy27-cloud`
`content-type`	Kind of content, for listings	`press-release`
`featured`	Featured in listings (`yes` / `no`)	yes
`priority`	Sort priority in listings (number)	1
`nav`, `footer`	Optional. Header / footer page for the matching pages and, unless they set their own, the pages below them (see *Header and Footer*)	`references/nav-careers`
`error-page`	Optional. "Page not found" page for missing pages below the matching pages (see *Error Pages*)	`error-pages/404-careers`

These columns are also stored in the search index, for listings: `page-type`, `meta-title`, `meta-description`, `content-type`, `author-id`, `publish-date`, `modified-date`, `reading-time`, `thumbnail-image`, `featured-image`, `region`, `country`, `language`, `persona`, `campaign-id`, `featured`, `priority` and `robots` (plus the page title, description, image and tags).

Example rows (English sheet `us/en/metadata`):

url	page-type	author-id	publish-date	region	nav	robots
`/en/newsroom/**`	press-release			americas		
`/en/insights/**`	article					
`/en/insights/headless-is-here`		jdoe	2026-10-01			
`/en/careers/**`					references/nav-careers	
`/en/error-pages/**`						noindex, nofollow
`/en/references/**`						noindex, nofollow
`/en/data/**`						noindex, nofollow

In the German sheet (`de/de-de/metadata`) the same rows start with `/de-de/`, for example `/de-de/careers/**` with nav `references/nav-careers`. The relative nav value then points to `/de-de/references/nav-careers`.

Instead of the `/en/careers/**` sheet row you can set **Navigation** in the page properties of `/en/careers`; the pages below inherit it. Use whichever is easier to maintain, but avoid setting different values in both places.

SEO and Social Sharing

The site turns the `meta-title`, `meta-description`, `meta-keywords`, `og-*`, `twitter-*`, `canonical-url` and `language` columns into the standard head tags **in the browser**. Search engines that run JavaScript (such as Google) see them. **Social crawlers (LinkedIn, Facebook, X, Teams, Slack) do not run JavaScript**, so they do not see these values.

For reliable social previews, also add the **standard** metadata columns. The platform writes these into the page directly:

Standard column	Effect without JavaScript
`og:title`	Title of the social preview
`og:description`	Description of the social preview
`og:image`	Image of the social preview (absolute URL or asset path)
`twitter:card`	Card type, e.g. `summary_large_image`
`canonical`	Canonical URL
`robots`	`noindex, nofollow` for pages that must not appear in search

Recommendation: set `og:title`, `og:description`, `og:image`, `twitter:card` and `canonical` for important pages (home, press releases, articles). Add `robots: noindex, nofollow` rows for `error-pages/**`, `references/**` and `data/**` in each locale's sheet so that fragments, error pages and data are never indexed. Page Title and Description from the page properties are always rendered without JavaScript.

Placeholders Sheet (`{locale}/placeholders`)

Each locale has its own placeholders sheet (`/en/placeholders.json`, `/de-de/placeholders.json`, ...) with the same keys. Translate the Text column in each locale. The sheet has four columns: **Key**, **Text**, **Description** and **Category**. The site uses Key and Text. Description (what the text is for) and Category (e.g. Carousel, Page Header, Forms) help authors and translators. Keys may use any casing or separators. For example, `Pause Slides`, `pause-slides` and `pauseSlides` all match. Text in `{curly braces}` is filled in by the site, so keep those variables in your text. If a key is missing, the English default below is used.

Key	Default text	Used in
`carousel`	Carousel	Gen Carousel (region label)
`previousSlide` / `nextSlide`	Previous slide / Next slide	Gen Carousel buttons
`pauseSlides` / `playSlides`	Pause slides / Play slides	Gen Carousel autoplay button
`showSlide`	Show slide {n} of {total}	Gen Carousel dots
`slideOf`	{n} of {total}	Gen Carousel slide label
`published`	Published	Page Header date
`minRead`	{n} min read	Page Header reading time
`listenToThisPage`	Listen to this page	Page Header listen link
`downloadThisPage`	Download this page	Page Header download button
`shareThisPage`	Share this page	Page Header share button
`linkCopied`	Link copied to clipboard	Page Header share message

Key	Default text	Used in
`aboutTheAuthor`	About the author	Article / blog template
`viewLinkedinProfile`	View LinkedIn profile	Article / blog “About the author” link
`mediaContacts`	Media contacts	Press release template
`followUsOn`	Follow us on {platform}	Footer social links
`onThisPage`	On this page	Anchor List label
`close`	Close	Modal close button
`openNavigation` / `closeNavigation`	Open navigation / Close navigation	Header mobile menu button
`play`	Play	Embed placeholder button
`playVideo`	Play video	Video placeholder button
`card`	card	Table List (link label for cards without a title)
`exploreItem`	Explore {title}	Table List card links
`selectAnOption`	Select an option	Form dropdowns
`send`	Send	Form submit button (when no label is set)
`formSuccess`	Thank you, your details were sent.	Form success message
`shownWhenValue`	Shown when a dropdown value is “{value}”	Form (editor hint)
`menu` / `back`	Menu / Back	Conversation Canvas menu
`noPagesFound`	No pages found	Conversation Canvas menu
`siteNavigation`	Site	Conversation Canvas navigation label
`suggestions`	Suggestions	Conversation Canvas suggestion pills
`searchPlaceholder`	Ask us a question	Conversation Canvas search (when the block has none)
`searchByVoice`	Search by voice	Conversation Canvas audio button (when the block has no alt text)
`submit`	Submit	Conversation Canvas search button (when the block has no hover text)

Taxonomy (`{locale}/taxonomy`)

Each locale’s taxonomy page publishes your AEM tags as `/{language}/taxonomy.json` (`/en/taxonomy.json`, `/de-de/taxonomy.json`, …) with the tag ID and its title. For translated titles, it has one sheet per language, and the site uses the sheet of the locale’s language (for example `de` on `/de-de/` pages), else the default sheet. The site uses it to show readable tag labels in the **Teaser** (Display Tags), the **Page Header** and the **Conversation Canvas** suggestion pills. If a tag is missing from the taxonomy, the site shows a label derived from the tag ID (for example `tcs:topics/cloud-services` shows as “Cloud services”). Manage the tags themselves in AEM **Tagging** (in the **TCS Corp** namespace). Create the page from the **Taxonomy** template with the name `taxonomy`, select the **TCS Corp** namespace in it, and publish it.

Redirects Sheet (`{locale}/redirects`)

Each locale has its own redirects sheet, published at its own path (`us/en/redirects` as `/en/redirects.json`, `de/de-de/redirects` as `/de-de/redirects.json`, ...). There is no site-root redirects sheet. Example rows (English sheet `us/en/redirects`):

Source	Destination
`/en/old-page`	`/en/new-page`
`/en/insights/2025/report`	`/en/insights/annual-report`

In the German sheet (`de/de-de/redirects`) the rows use `/de-de/` paths, for example `/de-de/alte-seite` to `/de-de/neue-seite`.

> **Important:** the platform only applies a root `/redirects.json` automatically. The per-locale redirects sheets are therefore **not** applied by Edge Delivery on their own. Redirects, including the `/` to `/en/` redirect (the site root has no page of its own), need another mechanism that your administrator or developer sets up, for example CDN rules that read the locale sheets. Ask them whether that mechanism is in place before you rely on a redirect.

Use published paths (`/en/...`, `/de-de/...`), not AEM paths. Keep only the locale's own URLs in its sheet. Add a redirect **before** you delete, move or rename a published page, and publish the sheet so that the redirect mechanism can pick it up.

Data Sheets (`{locale}/data/`)

Each locale has its own data sheets (`/en/data/authors.json`, `/de-de/data/authors.json`, ...). Fill them in the locale's language. Use exactly these column headers. Rows without the key column are ignored.

Sheet	Columns	Used by
`authors`	`author-id`, `name`, `designation`, `bio`, `image`, `linkedin`, `region`	Page Header author (via the page's `author-id`), "About the author" on articles and blogs
`locations`	`location-id`, `location-name`, `country`, `region`, `latitude`, `longitude`	Office location data (for location features)
`partners`	`partner-id`, `partner-name`, `logo`, `website`, `tier`, `description`	Partner data (for partner features)
`social-links`	`platform`, `url`, `icon`, `sort-order`	Footer social icons, in `sort-order` (rows without one come last)
`media-contacts`	`id`, `name`, `designation`, `email`, `phone`, `region`	"Media contacts" on press releases (contacts of the page's `region`, else all)

Tips:

- `author-id` and `region` are matched without regard to case. Use short, stable IDs (for example `jdoe`).
- `image` and `logo` are image URLs or asset paths.
- `icon` in Social Links is an icon name (`linkedin`, `x`, `facebook`, `instagram`, `youtube`) or an image URL. If it is empty, the platform name is used as the icon name when one exists (`twitter` shows the `x` icon). Otherwise the platform name is shown as text.
- `email` and `phone` become clickable mail and phone links.

Publishing Workflow

Environment	Domain	Purpose
Author	`author-p220207-e2271469.adobeaemcloud.com`	Edit content in the Universal Editor (not public)
Preview	`main--tcs-corp--sradha-tcs.aem.page`	Check changes before going live
Live	`main--tcs-corp--sradha-tcs.aem.live`	Production site

Workflow: Edit in the Universal Editor, then **Publish > Preview** and check the page on `.aem.page`. Then **Publish > Live**, and the page is updated on `.aem.live` within a minute or two.

Not published: Pages under `site-global-templates/` and each locale's `block-library/` are excluded from publishing. They are only for copying and testing on author.

Sheets and references: Changes to sheets, data sheets, navs, footers, fragments and error pages take effect only after that page or sheet itself is published. Metadata changes appear on a page after the sheet is published. Changes to an inherited Navigation, Footer or 404 Page on a parent page show for visitors in a new browser session. Re-publish the affected pages if the search index (listings) must pick up new values.

Bulk publishing: In the AEM Sites console, select multiple pages and use **Manage Publication** (or Quick Publish) to publish them together, including referenced assets.

Common Tasks

Task	Steps
Create a page	Sites console > your locale folder (e.g. `us/en`, `de/de-de`) > Create > Page > set title and name > Edit > add components > set Title, Description, Keywords in Page Properties > check the locale's metadata sheet covers the page > Publish
Create a press release	Copy *Site Global Templates* > *press-release* into `{locale}/newsroom/` > rename > Edit body content > set `publish-date` and `region` (row in the locale's metadata sheet) > check the locale's Media Contacts sheet > Publish
Create an article or blog post	Copy the *article* or *blog* template page from Site Global Templates into your locale > rename > Edit > set `author-id`, `publish-date`, `reading-time` in the locale's metadata sheet (and add the author to the locale's Authors sheet) > optionally add your own Page Header for CTAs, share and download > Publish the sheet and the page
Edit a page	Sites console > select page > Edit > change content in the Universal Editor > Publish
Work in another locale	Open its folder (e.g. `de/de-de`) and use its own references, sheets and data. Its URLs and metadata patterns start with its language path (`/de-de/...`)
Change a label or button text	Edit `{locale}/placeholders` (each locale separately) > change the Text for the key (add the row if missing) > Publish the sheet
Add an author	Edit `{locale}/data/authors` > add a row with a new `author-id` > Publish > use the ID in the `author-id` column
Update social links	Edit `{locale}/data/social-links` > set platform, url, icon, sort-order > Publish

Task	Steps
Update media contacts	Edit `{locale}/data/media-contacts` > set region per contact > Publish
Add or rename a tag	Edit the tag in AEM Tagging > update and publish the taxonomy of each locale
Delete a page	Add a redirect for the old published URL (e.g. `/de-de/old-page`) in the locale's redirects sheet (e.g. `de/de-de/redirects`) and publish it > Unpublish the page > Delete it
Move or rename a page	Use Move in the Sites console > add a redirect from the old URL in the locale's redirects sheet > update the locale's metadata sheet patterns if needed > publish
Update navigation	Edit `{locale}/references/nav` (or the nav page the pages use, set on the page or a parent page) > Publish
Update the footer	Edit `{locale}/references/footer` (or the footer the pages use) > Publish
Use a different nav or footer for a section	Create it in `{locale}/references/` (e.g. `nav-careers`) > Publish > open the section's top page (e.g. `/en/careers`) > Page Properties > Navigation / Footer > Publish that page. All pages below inherit it. Or add `references/nav-careers` as the `nav` / `footer` value on a metadata sheet row
Edit the 404 page	Edit `{locale}/error-pages/404` (or the 404 Page set on a parent page) > Publish
Use a different 404 page for a section	Create it in `{locale}/error-pages/` (e.g. `404-careers`) > Publish > set it as **404 Page** in the page properties of the section's top page (e.g. `/en/careers`) > Publish that page. Or use the sheet's `error-page` column
Test a block variation	Open the matching page in the locale's `block-library/` (e.g. `de/de-de/block-library/`) on author (not published)
Add a carousel	At page level click Add > Gen Carousel > set Navigation and interval > add Hero or Teaser slides inside
Add chapter navigation	Give each target section an *Anchor name* (e.g. `overview`) > add an Anchor List with matching Anchor Names
Reuse content	Create the shared content as a page in `{locale}/references/` > add a Fragment block referencing it
Open content in a pop-up	Create a page under a `modals` folder > link to it, or add a Modal block

Sections and Section Properties

Sections group content on the page. In the Universal Editor, add a section with **Add > Section** at page level. Then select it to edit its properties.

Property	Options	Effect
Section Name	text	Label shown in the content tree (not on the site)
Style	Highlight	Light secondary background with extra vertical padding

Property	Options	Effect
Width Type	Full Width (default), Fixed Width	Full Width spans the page. Fixed Width limits the section to the content width
Rounded edge	on / off	Rounds the corners of the section
Background Image	image	Image behind the section content, scaled to cover it
Image alt text	text	Describes the background image for screen readers. Leave empty if decorative
Anchor name	text (lowercase, no spaces)	Gives the section an ID so Anchor List links (and `#links`) can jump to it, e.g. `overview`

Available Section Styles:

Style	Effect
Highlight	Secondary (light) background color with padding
Fixed Width	Section content and background limited to the content width, centered
Rounded edge	Rounded corners (combine with Highlight or a background image)
Background image	Full-cover image behind the section

Page Metadata

Page metadata comes from standard places. There is no custom properties tab.

1. Page Properties (per page):

Property	Required	Purpose	Example
Title	Yes	Page title for the browser tab, SEO, social sharing and the Page Header heading	"Cloud Transformation Services"
Description	Yes	SEO description, also shown in the Page Header	"Learn how TCS helps…"
Keywords	No	SEO keywords (multiple values)	cloud, AI
Page Type	No	Site Global Template: Default, Home, Article, Blog, Press Release. Overrides the sheet's `page-type`	Press Release
Navigation	No	Header (nav) page of this page **and of its child pages** (inherited, content picker). Empty: the sheet's `nav`, else the nearest parent page's Navigation up to Home, else the locale's `references/nav`	`/content/tcs-corp/de/de-de/references/nav-careers`

Property	Required	Purpose	Example
Footer	No	Footer page of this page **and of its child pages** (inherited, content picker). Empty: the sheet's `footer`, else the nearest parent page's Footer up to Home, else the locale's `references/footer`	`/content/tcs-corp/us/en/references/footer-campaign`
404 Page	No	"Page not found" page for missing pages **below** this page (inherited, content picker). Empty: the sheet's `error-page`, else the nearest parent page's 404 Page up to Home, else the locale's `error-pages/404` (see *Error Pages*)	`/content/tcs-corp/us/en/error-pages/404-careers`

Navigation, Footer and 404 Page are **inherited** like AEM inherited page properties: a child page that leaves them empty uses its nearest parent page's value. Set them on a section's top page, not on every page.

2. The locale's bulk metadata sheet (`{locale}/metadata`, by URL pattern): everything else page-level. This covers page-type, SEO and social columns, author-id, publish-date, modified-date, reading-time, region, country, language, persona, images, campaign-id, content-type, featured, priority and the optional nav, footer and error-page (see *Bulk Metadata Sheet*). For reliable social previews, also add the standard `og:title`, `og:description`, `og:image`, `twitter:card` and `canonical` columns (see *SEO and Social Sharing*).

3. Page Header block fields (per page, not metadata): CTAs, Time to Read override, Author Name / Image / Designation & Location overrides, Collection Label, Listen Link, Social Share, Download and the Image Collage (see *Page Header in Detail*).

Images and Media

Method	How
AEM Assets	Upload to `/content/dam/tcs-corp/`, then pick the asset in the image field
Drag and drop	Drag an asset from the Assets panel onto an image field in the Universal Editor
Videos	Use the Video or Embed block with a YouTube, Vimeo or video file link
Animations	Use the Hero *Lotto* image type with a Lottie `.json` file
Sheet images	Author photos, partner logos, social icons and `og-image` / `thumbnail-image` / `featured-image`: use the asset URL or path

Best practices: Use descriptive file names and always add alt text. Upload high-quality originals, because images are optimized automatically for each device when published. Do not upload images with text baked into them. For social previews, use images of at least 1200 x 630 pixels.

Troubleshooting

Issue	Solution
Page not updating after publish	Wait 1-2 minutes for the cache, then hard refresh (Cmd+Shift+R / Ctrl+Shift+R). Check that you published to Live and not only to Preview
Block not displaying correctly	Check that the required fields are filled in and the options are valid. Compare with the block library page. Re-select the component in the editor
Images not showing	Check that the asset is published (Manage Publication includes references) and that the image field points to it
Template content missing (no automatic Page Header, author or media contacts)	Check the **Page Type** (page property, or the sheet's `page-type` for the page's URL). Check the spelling (`press-release`)
"About the author" missing	Set `author-id` for the page and make sure the Authors sheet has that ID with a `name`. Publish both sheets
"Media contacts" missing or wrong	Publish the Media Contacts sheet. Check the page's `region` and the contacts' `region` values (all contacts are shown when none match)
Page Header has no date, reading time or author	Add `publish-date`, `reading-time` and `author-id` for the page's URL in the metadata sheet and publish it. Check the URL pattern (`/en/folder/**`, `/de-de/folder/**`). For locales other than English, check that the administrator has added the locale's metadata sheet to the site configuration
Page Header shows the wrong layout	Check the Page Type (`landing` / `listing` give Landing; everything else gives Article), or set the block Style to Landing or Article
Image collage not visible	The collage is shown only in the Landing layout
Wrong header or footer	Check Page Properties > Navigation / Footer of the page, then the sheet's `nav` / `footer` rows, then the same on each parent page up to Home (the nearest parent with a value wins). Publish the referenced page in `references/`
Header is empty	The nav page the page uses (its own, inherited from a parent, or `references/nav`) is not published. Publish it. The header does not fall back to another nav page
A changed Navigation, Footer or 404 Page on a parent page does not show	Publish the parent page. Inherited values are remembered for the browser session, so check in a new private window or a new browser session
No social icons in the footer	Publish the locale's `data/social-links` (e.g. `de/de-de/data/social-links`). Each row needs a `url`
Social preview (LinkedIn, Facebook) shows the wrong title or image	Add the standard `og:title`, `og:description`, `og:image` and `twitter:card` columns. Social crawlers ignore `og-title` etc. because those need JavaScript
Fragments or error pages appear in search	Add `robots: noindex, nofollow` rows for `/en/references/**`, `/en/error-pages/**` and `/en/data/**` (and the same with `/de-de/`, … in each locale's sheet)
Tags show odd labels	Add the tag to the taxonomy and publish it. Without it, labels are derived from the tag ID
A label or button text is wrong	Change it in the locale's placeholders sheet (check the Key spelling) and publish the sheet
English labels on a translated page	Add the key to that locale's placeholders sheet (e.g. `de/de-de/placeholders`) and publish it. Missing keys fall back to built-in English
Old URL shows "page not found"	Add a row to the locale's redirects sheet (e.g. `us/en/redirects`) and publish it. If it still has no effect, see the next rows

Issue	Solution
Old `/us/en/...` link shows "page not found"	Pages are now published at `/en/...`. Update the link, or add a redirect in the `us/en/redirects` sheet
The site root `/` shows "page not found"	The site root has no page of its own. Ask your administrator or developer to set up the `/` to `/en/` redirect (for example a CDN rule)
A locale's redirects sheet has no effect	Expected without extra setup. The platform only applies a root `/redirects.json` automatically, so the per-locale sheets (`/en/redirects.json`, ...) need another mechanism, such as CDN rules, set up by your administrator or developer. Keep the rows in the locale's sheet
404 page shows built-in text	Publish the locale's `error-pages/404` (e.g. `de/de-de/error-pages/404`), or the English `/en/error-pages/404` as the fallback for all locales
404 page shows English content in another locale	The locale has no published `error-pages/404`, so the English one is used. Publish the locale's own 404
Wrong 404 page for a section	Check the **404 Page** of the missing page's nearest existing parent page (and the sheet's `error-page` rows). An unpublished 404 Page is skipped, so publish it
403 or 500 page never shows	Expected. The site only handles 404. The 403 and 500 pages are kept for the CDN team, who must configure the CDN to serve them
Template or block library page not reachable on preview	Expected. These pages are not published
Anchor List link does not jump	The section's *Anchor name* must exactly match the link's Anchor Name (lowercase, no spaces)
Filter List / Interactive Dashboard shows nothing	These are placeholders under development and render nothing on the site
Form submit does nothing	Form submissions are not yet connected to a backend. Contact the development team

Resources

Resource	URL
Universal Editor documentation	https://experienceleague.adobe.com/en/docs/experience-manager-cloud-service/content/implementing/developing/universal-editor/introduction
Authoring with AEM (Universal Editor) for Edge Delivery Services	https://www.aem.live/developer/ue-tutorial
Authoring Guide	https://www.aem.live/docs/authoring
Bulk Metadata Docs	https://www.aem.live/docs/bulk-metadata
Special Metadata Properties	https://www.aem.live/docs/special-metadata-properties
Placeholders Docs	https://www.aem.live/docs/placeholders
Taxonomy Docs	https://www.aem.live/docs/authoring-taxonomy
Redirects Docs	https://www.aem.live/docs/redirects
Spreadsheets and JSON	https://www.aem.live/developer/spreadsheets

Support Contacts

Role	Contact
AEM administrator (access, permissions, sites, locales, sheets)	*To be added by the project team*
Development team (templates, blocks, forms, placeholder keys)	*To be added by the project team*
Content lead	*To be added by the project team*