FINAL RESEARCH PROJECT DEFENSE • PREPRINT WORKING PAPER

Autonomic Cloud Resilience Through Brownout-Based Graceful Degradation

A Simulation-Based Evaluation of Brownout-Aware Load Balancing (BALB)

Hari Prasad L
Lead Author & System Architect
Core Balancer Architecture, DEC-010 Formulation & Paper Writing

Yeruva Mahesh Reddy
Evaluation & Statistical Analysis
360-Run Factorial Benchmark, Paired Tests & Sensitivity Sweep

K. Ram Charan
Controller Design & Implementation
Velocity-Form PI Controller, Multi-Stream PRNG & Telemetry Engine

Department of Computer Science and Engineering
Indian Institute of Information Technology Dharwad (IIIT Dharwad), Karnataka, India

Preprint Working Paper • Target Venues: IEEE Transactions on Cloud Computing / ACM TAAS • November 2026

CONTEXT & PROBLEM

The Cloud Resilience Challenge: Unpredictable Shocks

Stochastic traffic surges and compute instance crash-stops induce non-linear queuing collapse

Demand-Side Shocks (Flash Crowds)

- Sudden traffic surges where arrival rate λ doubles from nominal 70 to 140 req/s (140% cluster capacity).
- Driven by breaking news events, viral spikes, flash sales, or coordinated client retries.
- Arriving request rate exceeds aggregate processing capacity of operational worker instances.

Capacity-Side Shocks (Server Crashes)

- Abrupt hardware faults, hypervisor evictions, memory exhaustion, or unhandled software crashes.
- Half the cluster compute capacity vanishes simultaneously (Workers 1 & 2 drop offline at t = 300s).
- Available processing capacity instantly drops from 100 req/s to 50 req/s while traffic persists.

The Non-Linear Queuing Tipping Point

- In multi-server queueing systems, waiting delay W_i scales non-linearly with traffic intensity ρ.
- Finite FIFO buffers ($Q_{max} = 50$) rapidly saturate, causing severe Head-of-Line (HOL) blocking.
- Client timeout deadline (200 ms) breached, causing widespread queue dropouts and SLA breakdown.

CRITICAL IMPLICATION: CATASTROPHIC UNMANAGED FAILURE

Under unmanaged operation (CFG-A), SLA failure rate escalates from 26.54% (nominal) to 44.04% (flash crowd) and 47.70% (compound stress). Dropped requests consume network bandwidth, waste upstream compute resources, and deliver zero value to end users.

Breakdown of Conventional Cloud Resilience Defenses

Hardware over-provisioning is economically wasteful; reactive auto-scaling is dangerously slow

Static Hardware Over-Provisioning

- Mechanism: Maintain redundant pools of hot-standby instances provisioned for theoretical peak load.
- Economic Inefficiency: Massive capital and operational expenditures; servers sit idle under nominal load (Welsh & Benkhelifa [1]).
- Fragility to Compound Shocks: Completely defeated when correlated compound shocks exceed provisioned ceilings.

Reactive Horizontal Auto-Scaling

- Mechanism: Monitor threshold breaches (e.g. CPU > 80%) to dynamically spawn new VM/container instances.
- The Critical Provisioning Gap: Virtual machine allocation, container pull, OS boot, and runtime warmup require 60 to 300+ seconds (Cartlidge & Sriram [5]).
- Cascading Failure: Ingress queues saturate in 5–10s, triggering client timeouts before new instances become operational.

The Paradigm Shift: Graceful Degradation

- Software-Level Autonomic Adaptation: Real-time capacity expansion within existing physical infrastructure.
- Brownout Paradigm: Temporarily sheds optional microservice features (recommendations, analytics) to preserve core business transactions.
- Sub-Second Response: Adapts instantly (< 1.0s) without incurring hardware allocation latency.

CORE RESEARCH MOTIVATION

Modern cloud systems cannot rely solely on physical scaling to survive sudden shocks. An effective resilience mechanism must act instantaneously at the application layer to guarantee bounded response latency and high availability during extreme stress.

PROBLEM FORMULATION

The Join-Shortest-Queue (JSQ) Pathology Under Brownout

Uncoordinated brownout controllers and agnostic load balancers create destructive load skew

THE DESTRUCTIVE JSQ FEEDBACK LOOP

1. Local Congestion

A worker experiences elevated response latency; its local PI controller reduces dimmer $\theta \to 0$.

2. Rapid Queue Clearing

Degraded worker executes only mandatory code (10 ms vs 40 ms), clearing its queue 4× faster.

3. Misguided Agnostic Dispatching

Agnostic JSQ proxy sees the short queue and dumps MORE traffic onto the already degraded worker!

4. Severe Starvation & Load Skew

Healthy workers at full fidelity (40 ms) retain longer queues and are starved of incoming requests.

EMPIRICAL PATHOLOGY & RESEARCH GAP

- Severe Load Skew: In CFG-B (Brownout + JSQ), Jain's fairness index collapses to $J = 0.607$ (Nominal) and 0.646 (Crash), violating workload equity.
- Delayed Recovery: Repaired workers take up to 323s to recover or suffer permanent right-censoring because incoming load is unfairly steered.
- Prior Literature Gap: Foundational works (Klein et al. [2, 3], Tomas & Tordsson [8]) deployed brownout controllers in isolation or with naive heuristics.
- Research Opportunity: Co-designing an ingress load balancer that coordinates with local brownout elasticity states to restore fairness and accelerate recovery.

PROPOSED ARCHITECTURE

CloudRescue: Co-Designed Autonomic Resilience

Decentralized local PI controllers combined with centralized Brownout-Aware Load Balancing

Pillar 1: Velocity-Form PI Controller

- Deployed locally on every worker node.
- Monitors empirical 95th-percentile response latency $r_{95,w}(t)$ at 1.0s epochs.
- Setpoint r_{target} = 80 ms provides a 20 ms safety margin below the 100 ms SLA threshold.
- Intrinsic anti-windup clamping [0.0, 1.0] eliminates integrator windup without reset heuristics.

Pillar 2: Brownout-Aware Balancing (BALB)

- Deployed at cluster ingress reverse proxy.
- Computes multi-attribute dispatch score: $Score = \alpha*\theta - \beta*(q/Q_{max}) - \gamma*U$.
- Decouples buffer backlog risk from historical CPU utilization.
- Anti-overloading penalty with soft-overload fallback ($\alpha = 0$ when $q_w \geq Q_{soft}$).

Pillar 3: Graceful Degradation Model

- Admitted requests execute mandatory core logic (10 ms) unconditionally.
- Optional computation (30 ms) dynamically modulated by worker dimmer $\theta_w \in [0, 1]$.
- Throughput expands up to 4× (100 → 400 req/s) under full degradation.
- Eliminates client drops while preserving critical transaction integrity.

ARCHITECTURAL SYNERGY: THE POWER OF CO-DESIGN

By pairing local velocity-form PI feedback with global elasticity-aware routing, CloudRescue guarantees that degraded workers are not unfairly overloaded, healthy workers are utilized effectively, and tail latency remains strictly bounded under extreme stress.

SYSTEM DESIGN

Cluster Topology & Dual-Stage Execution Pipeline

Multi-worker microservice cluster with closed-loop telemetry and dynamic capacity expansion

LOGICAL ARCHITECTURE TOPOLOGY

- **Ingress Proxy Layer:**
  Accepts stochastic client requests. Routes via CFG-A (JSQ), CFG-B (JSQ), or CFG-C (BALB scoring).
- **M = 4 Independent Workers:**
  Each maintains an independent FIFO queue (capacity $Q_{max} = 50$). HOL timeout threshold $W_i > 200$ ms.
- **Local Control Loop:**
  Worker controllers sample completed request latencies every $\Delta t_{ctrl} = 1.0$s and broadcast $[\theta_w, q_w, U_w]$ telemetry.
- **Failure Injection Module:**
  Deterministically triggers crash-stop and restoration events (e.g. Workers 1 & 2 down at t=300s, restored at t=450s).

DUAL-STAGE EXECUTION & CAPACITY EXPANSION

- **Stage 1: Mandatory Service (S_{mand}):**
  Exponentially distributed, mean $\mu_{mand} = 10$ ms. Core financial transaction, order persistence, authentication.
- **Stage 2: Optional Service (S_{opt}):**
  Exponentially distributed, mean $\mu_{opt} = 30$ ms. Executed iff $U_{opt} \le \theta_w(t)$. Recommendations, analytics, rich styling.
- **Full Fidelity Execution ($\theta = 1.0$):**
  Expected service duration $E[S] = 40$ ms. Individual worker throughput: 25 req/s. Aggregate cluster capacity: 100 req/s.
- **Degraded Execution ($\theta = 0.0$):**
  Expected service duration $E[S] = 10$ ms. Individual worker throughput: 100 req/s. Aggregate cluster capacity: 400 req/s.
- **Instantaneous 4× Expansion:**
  Shedding optional features expands compute capacity by 400% without spawning new hardware or incurring VM boot lag!

ALGORITHMIC FOUNDATION

Local Velocity-Form Discrete PI Controller

Continuous dimmer modulation, intrinsic anti-windup clamping, and telemetry safeguards

1. Error Formulation & Sign Convention

- Feedback Metric: Empirical 95th-percentile response latency $r_{95,w}(t)$ evaluated over completed requests in preceding 1.0s window.
- Error Definition: $e_w(t) = r_{target} - r_{95,w}(t)$
- Setpoint Selection: $r_{target} = 80.0$ ms (enforces a 20 ms safety buffer below $r_{SLA} = 100.0$ ms).
- Sign Physics: Overload ($r_{95} > 80$ms) yields negative error ($e < 0$) driving dimmer downward; underload ($e \geq 0$) restores dimmer upward.

2. Velocity-Form Incremental Update

- Mathematical Recurrence: $\Delta\theta_w(t) = K_p*(e_w(t) - e_w(t-1)) + K_i*e_w(t)*\Delta t_{ctrl}$
- Tuned Parameters: $K_p = 0.001$, $K_i = 0.0005$, control period $\Delta t_{ctrl} = 1.0$s.
- Raw Dimmer Adjustment: $\theta_{raw,w}(t) = \theta_w(t-1) + \Delta\theta_w(t)$
- Stability: Operates purely on error differences, eliminating cumulative error drift and dampening oscillation.

3. Anti-Windup Clamping & Guard

- Intrinsic Output Clamping: $\theta_w(t) = \min(1.0, \max(0.0, \theta_{raw,w}(t)))$
- Integrator Windup Prevention: Clamping the velocity output prevents the internal integrator from saturating during sustained overload.
- Data Sufficiency Guard: If completed requests $N_{ctrl} < N_{min,ctrl} = 5$, skips PI update and holds $\theta_w(t) = \theta_w(t-1)$.
- Prevents stochastic estimation noise from causing false degradation during low-traffic windows.

MATHEMATICAL CONTROL LAW SUMMARY

$$e_w(t) = 80.0\text{ ms} - r_{95,w}(t) \implies \Delta\theta_w(t) = 0.001*(e_w(t) - e_w(t-1)) + 0.0005*e_w(t)*1.0 \implies \theta_w(t) = \text{clamp}(\theta_w(t-1) + \Delta\theta_w(t), 0.0, 1.0)$$

ALGORITHMIC FOUNDATION

Brownout-Aware Load Balancing (BALB)

Composite elasticity scoring, anti-overload bounds, and soft-overload fallback

MULTI-ATTRIBUTE ROUTING SCORE

$$Score_w(t) = \alpha * \theta_w(t) - \beta * (q_w(t) / Q_{max}) - \gamma * U_w(t)$$

- **Term 1: Dimmer Elasticity (α = 1.0):**
  Provides positive preference for workers operating at higher service fidelity. Encourages optional feature execution when capacity allows.
- **Term 2: Normalized Backlog (β = 2.0):**
  Penalizes queue occupancy (q_w / Q_{max}). Prevents buffer overflow and protects queuing delay headroom.
- **Term 3: Historical CPU Utilization (γ = 0.5):**
  Penalizes cumulative CPU busy time U_w. Prevents dispatching ping-pong thrashing between workers.
- **Routing Decision:**
  Request dispatched to: $w^* = \text{argmax}_w Score_w(t)$. Ties broken via uniform random selection.

ANTI-OVERLOAD PENALTY & FALLBACK

- **Soft-Overload Threshold (Q_soft = 40):**
  Defined at 80% of buffer capacity ($Q_{soft} = 0.8 * Q_{max} = 40$ requests). Acts as an early congestion circuit-breaker.
- **Elasticity Clamping (α = 0 when $q_w \geq Q_{soft}$):**
  When a worker's queue reaches Q_{soft}, its dimmer elasticity bonus is instantly zeroed ($\alpha \leftarrow 0$).
- **Preventing High-Dimmer Trap:**
  Guarantees that a worker retaining a high dimmer cannot attract requests when its queue buffer is dangerously saturated.
- **Soft-Overload Fallback:**
  If all operational workers have saturated queues ($q_w \geq Q_{soft}$) or negative scores, BALB reverts to pure queue minimization: $w^* = \text{argmin}_w q_w$.
- **Headroom Guarantee:**
  Ensures the cluster never drops requests due to score distortion under extreme compound stress.

EXPERIMENTAL METHODOLOGY

Multi-Stream PRNG Isolation & Factorial Design

Deterministic Common Random Numbers (CRN) stream isolation across 360 primary simulation runs

Multi-Stream PRNG Architecture

• The Confounding Problem: In stochastic simulation, shedding optional tasks draws fewer random numbers, desynchronizing baseline vs treatment arrival streams.

• CloudRescue PRNG Solution: 3 independent PCG64 bit-generator streams derived deterministically from master seed S:

• - Stream 1: Request Arrival Schedules (Poisson timestamps).

• - Stream 2: Mandatory Processing Times (Exp, 10 ms).

• - Stream 3: Optional Processing Times (Exp, 30 ms).

• Confounding Eliminated: All configurations process identical arrival timestamps and service demands!

Three-Way Factorial Matrix

• Ablation Matrix evaluates 3 core configurations:

• - CFG-A (Baseline): Unmanaged Baseline (No Brownout + JSQ). Industry default.

• - CFG-B (Ablation): Local Brownout Adaptation (Brownout + JSQ). State-of-the-art literature.

• - CFG-C (Proposed): Full CloudRescue (Brownout + BALB). Co-designed architecture.

• 4 Operational Scenarios: Nominal, Flash Crowd, Server Crash, and Compound Stress.

• Sample Scale: 4 Scenarios × 3 Configurations × 30 Matched Seeds = 360 Primary Runs.

Statistical Battery Rigor

• Normality Pre-Testing: Shapiro-Wilk test on paired differences (D_k) at $\alpha = 0.05$.

• Paired Testing Battery: Paired Student's t-test for normal distributions; Wilcoxon signed-rank test for non-normal distributions.

• Effect Sizes: Standardized Cohen's d_z effect sizes across all matched pairs.

• Multiple Testing Corrections: Bonferroni adjustment ($m = 114$ family tests) and Benjamini-Hochberg False Discovery Rate (FDR q-values).

• Full Reproducibility: Pre-registered scripts, deterministic seeds (1001-1030).

METHODOLOGICAL DISTINCTION: CONTROLLED COMPARABILITY

Through deterministic multi-stream PRNG isolation and paired seed matching, every observed difference between CFG-A, CFG-B, and CFG-C is strictly attributable to architectural and algorithmic treatments—not stochastic simulation noise.

EXPERIMENTAL METHODOLOGY

Four Standardized Stress Scenarios

Standardized operating profiles isolating stationary load, traffic surges, and crash outages

1. Nominal Scenario

Stationary Load Baseline

- Arrival rate λ = 70.0 req/s constant (70% cluster capacity).
- All 4 worker nodes active (M = 4) across entire 600s horizon.
- Cluster traffic intensity: ρ = 0.70.
- Evaluates steady-state stability, nominal latency, and unperturbed dimmer equilibrium.

2. Flash Crowd Scenario

Demand-Side Surge Shock

- Phase 1 (0–200s): Nominal load λ = 70 req/s.
- Phase 2 (200–400s): Instantaneous surge to λ = 140 req/s (140% cluster capacity, ρ = 1.40).
- Phase 3 (400–600s): Returns to nominal λ = 70 req/s.
- Evaluates speed of dimmer degradation and queue overflow prevention.

3. Server Crash Scenario

Capacity-Side Crash Shock

- Arrival rate λ = 70.0 req/s constant throughout 600s horizon.
- Outage Event: Workers 1 & 2 crash at t = 300s (capacity drops 50%, ρ jumps from 0.70 to 1.40).
- Restoration Event: Workers 1 & 2 repaired and rejoin cluster at t = 450s.
- Evaluates capacity loss tolerance and post-restoration recovery speed (DEC-010).


4. Compound Stress

Correlated Simultaneous Crisis

- Demand Shock: Flash crowd (λ = 140 req/s) active from t = 200s to 400s.
- Capacity Shock: Workers 1 & 2 offline from t = 300s to 450s.
- Crisis Overlap (300–400s): λ = 140 req/s on 2 workers ==> ρ = 2.80 (280% overload!).
- The ultimate resilience test: Evaluates graceful survival under extreme correlated failure.

SLA Compliance & Latency Bounds Across Scenarios

Brownout decisively bounds tail latency and reduces overall SLA failures by up to 41.10 percentage points



Overall SLA Failure Rates (V_overall) and Latency Violation Rates (V_lat) across 360 runs. CFG-C drastically suppresses failures across all stress regimes.

CERTIFIED EXPERIMENTAL BENCHMARKS

Flash Crowd SLA Failure (V_overall):

- CFG-A (Baseline): 44.04% ± 0.16%
- CFG-B (Brownout+JSQ): 5.69% ± 0.17%
- CFG-C (CloudRescue): 2.94% ± 0.17%
- Reduction: -41.10 percentage points (p = 3.01 × 10^-62, Cohen's d_z = -121.71)

Compound Stress SLA Failure (V_overall):


- CFG-A (Baseline): 47.70% ± 0.24% (Catastrophic collapse)
- CFG-B (Brownout+JSQ): 33.38% ± 0.24%
- CFG-C (CloudRescue): 35.33% ± 0.34%
- Reduction vs Baseline: -12.37 percentage points (p = 1.05 × 10^-42)

Latency Tail Reduction (P_95) & Compliance:

- Latency Violations (V_lat): Drops from 32.83% (CFG-A) to 2.89% (CFG-C) under Flash Crowd (-29.94 pp, p < 10^-45).
- 95th-Percentile Latency (P_95): CFG-A 184.34 ms ==> CFG-C 82.87 ms (reduction of -101.47 ms, strictly inside SLA setpoint!).

Recovery Dynamics & DEC-010 Methodology

Accelerating adaptation up to 28.4× and resolving right-censoring via empirical nominal baselines



Detailed time-series telemetry (seed 1001) under Compound Stress, depicting dimmer shedding, queue buffer stability, and rapid post-restoration recovery.

DYNAMIC ADAPTATION & RECOVERY BENCHMARKS

Real-Time Adaptation Speed (T_adapt):


- Flash Crowd: CFG-B requires 56.73s to stabilize; BALB accelerates stabilization to 2.50s (22.7× faster, p = 2.85 × 10^-24).
- Server Crash: CFG-B takes 56.80s; BALB stabilizes in 2.00s (28.4× faster, p = 1.81 × 10^-5).
- Mechanism: BALB incorporates dimmer state in routing, pre-emptively directing load without waiting for local queues to saturate.


DEC-010 Post-Restoration Recovery:

- The Right-Censoring Trap: Demanding static recovery (θ ≥ 0.8) fails because unperturbed nominal equilibrium naturally stabilizes at θ ≈ 0.70.
- DEC-010 Solution: Establishes seed- and worker-specific nominal baselines (θ_nom,w,s ± 0.05) to eliminate artificial right-censoring.
- Recovery Time (T_restore): CFG-B 323.47s ==> CFG-C 151.63s (2.13× speedup, p = 2.03 × 10^-5).
- 30-Seed Full Restoration Rate: Jumps from 46.7% in CFG-B to 100.0% in CFG-C (zero censored seeds!).

Workload Equity Proven, Fidelity Superiority Rejected

Empirical demonstration of a fundamental architectural trade-off in autonomic systems





DIMENSION 1: LOAD FAIRNESS (H1,3 — DECISIVELY SUPPORTED)

- Under JSQ (CFG-B), load skew is pathological: Jain's Index collapses to J = 0.607 (Nominal), 0.730 (Flash), 0.646 (Crash), and 0.764 (Compound).
- BALB (CFG-C) completely restores workload equity: J ≥ 0.981 to 0.996 across all scenarios (ΔJ = +0.232 to +0.374, p < 10^-8 across all tests).
- Eliminates degraded worker starvation and balances processor utilization.

DIMENSION 2: SERVICE FIDELITY (H1,3 — DECISIVELY REJECTED)

- Pre-registered hypothesis H1,3 expected BALB to increase fidelity F by routing requests toward high-dimmer workers.
- Empirical data decisively rejected the hypothesis (p < 10^-38): Service fidelity dropped by 11.4 to 17.9 percentage points in CFG-C vs CFG-B.
- Architectural Insight: High fidelity in CFG-B was an illusion maintained by starving healthy workers. True equity demands distributing degradation across the cluster.

CRITICAL DISCUSSION

Honest Academic Scope & Research Roadmap

Documented threats to validity and the scientific pathway toward physical testbeds

DOCUMENTED RESEARCH LIMITATIONS

- **Synthetic Queuing Model:**
  M/M/1-FIFO queues; production systems feature microservice DAGs, database lock contention, and heavy-tailed service distributions.
- **Static BALB Dispatch Weights:**
  Default weights (α=1.0, β=2.0, γ=0.5) proved robust in 144-run sweep, but remain fixed rather than dynamically self-tuning.
- **Single-Tier Ingress Proxy:**
  Production cloud infrastructures utilize distributed reverse proxies (Envoy/NGINX) with asynchronous gossip telemetry.
- **Discrete-Event Timing Abstraction:**
  SimPy models idealized clock ticks; real-world Linux deployments incur kernel socket buffer delay and scheduler context switching.

FUTURE RESEARCH DIRECTIONS

- **Autonomous Online Weight Adaptation:**
  Deploying reinforcement learning (contextual bandits / Q-learning) or Bayesian optimization to dynamically adjust (α, β, γ) based on traffic regimes.
- **Physical Kubernetes & Mesh Testbed:**
  Implementing CloudRescue as an Envoy WASM filter and Istio service mesh extension deployed on a multi-node Kubernetes bare-metal cluster.
- **Multi-Tier Microservice Benchmarks:**
  Evaluating resilience on industry microservice suites (TeaStore, DeathStarBench) with nested RPC dependencies and distributed databases.
- **Multi-Dimensional Feature Shedding:**
  Extending beyond binary optional logic to support multi-tier discrete quality tiers (e.g. video resolution downsampling, caching depth).

CloudRescue: Summary of Scientific Contributions

Three actionable architectural tenets for autonomic cloud microservice resilience

1. Brownout is an Essential Resilience Pillar

- Eliminates catastrophic queuing dropouts without expensive hardware over-provisioning.
- Reduces overall SLA failures by up to 41.10 percentage points ($p < 10^{-60}$).
- Bounds 95th-percentile response latency within strict SLA limits under severe traffic surges.

2. Ingress Co-Design is Mandatory

- Conventional JSQ load balancing breaks down under brownout, causing pathological load skew ($J \approx 0.607$).
- BALB restores near-perfect equity ($J \geq 0.985$) across all scenarios.
- Accelerates adaptation stabilization by up to 28.4× and doubles post-restoration recovery speed.

3. Fundamental Architectural Trade-off

- Workload fairness and service fidelity cannot be simultaneously maximized under overload.
- True cluster equity demands distributing degradation across all operational workers.
- Provides actionable engineering trade-off envelopes for production microservice tuning.

OPEN RESEARCH ARTIFACTS & QUESTIONS / DISCUSSION

Open Source Repository: https://github.com/hariprasadkishan/CloudRescue-Research

Thank you! We welcome questions, feedback, and discussion from the examination committee.