Which Cause Is It? Selectively Blind Residuals for Isolating Compute Faults, Sensor Glitches, and Novel Classes in Multi-Detector Neural Inference

S. Haripriya

***Abstract*—A neural network watching a redundant sensor array can look wrong for four mechanistically different reasons: the world produced a class the network knows, a class it has never seen, one sensor glitched, or the classifier's arithmetic was silently corrupted. Out-of-distribution (OOD) detectors, silent-data-corruption signatures, and range checks live in overlapping activation-magnitude spaces, so a new class and a bit-flip can produce the same alarm. We propose no new sequential test. We specify a four-symbol isolability dictionary and four residuals that are each blind to at least one of those symbols. A physics residual compares detectors against a rank-1 point-source model, never neural weights. An arithmetic checksum of the linear head never inspects the sky. A morphology residual is computed on the shared multi-detector profile, not on the live softmax, so a corrupt head cannot mint a false discovery. A drop test localizes a channel spike. The decision is a lookup, not a fusion. On a reproducible 8-detector Fermi Gamma-ray Burst Monitor (GBM)-like simulator with held-out terrestrial gamma-ray flashes, five training seeds yield $89.3 \pm 0.3\%$ four-way accuracy against $43.1 \pm 6.0\%$ for a ProGIP-style range check. Held-out novelty is never labeled compute (100% isolation). Energy and maximum-softmax-probability rejection flags all novel events as "anomaly" without naming a cause. Compound sensor-plus-compute trials are unisolable: 98.8% are named compute. On 100 real public GBM CTIME triggers (25 per class) with the same injected faults, accuracy is 72.8% and sensor isolation falls to 60.0%, but novelty is still never named compute. Code reproduces every table.**

***Index Terms*—Silent data corruption, open-set recognition, Fermi GBM, structured residuals, isolability, algorithm-based fault tolerance, embedded neural networks.**

I. Introduction

Deployed neural networks fail for reasons that call for opposite responses. If a wearable, a rover, or an onboard gamma-ray monitor sees an unusual activation, the operator may need to accept a known event, preserve a possible discovery, isolate a bad sensor, or recompute a flipped weight. Treating those four outcomes as one "anomaly" is not a small labeling error. Adapting a model to a bit-flip poisons a good network. Discarding a new physical class as a glitch throws away the event the instrument was built to catch.

The Fermi Gamma-ray Burst Monitor (GBM) is a concrete instance of this problem. Twelve sodium iodide (NaI) and two bismuth germanate (BGO) detectors observe the unocculted sky [1], [2]. Catalogued triggers include gamma-ray bursts (GRBs), solar flares, magnetar bursts (SGRs), terrestrial gamma-ray flashes (TGFs), and single-detector particle spikes [5], [7]. Public classifiers already sort known classes and flag outliers [8]. They do not treat a corrupted matrix multiply as a cause, and they do not have to: ground pipelines assume correct arithmetic. Onboard or edge inference cannot [34], [35].

The closest reliability papers still collapse causes. Gavarini *et al.* use open-set scores *as* fault detectors [9]. ProGIP distinguishes in-distribution, out-of-distribution (OOD), and high-order bit-flips with range checks on gradient-based OOD scores [10]. Dr. DNA and related activation monitors flag silent data corruption (SDC) from the shape of neuron histograms [11], [12]. ReAct showed that OOD inputs already produce extreme activations [14]—the same symptom high-order bit-flips produce. Classical isolability [22], [23] names sensor, process, and actuator faults; it has no symbol for "new astrophysical class." Fermi pipelines already veto single-detector phosphorescent spikes [7], [28]. They do not close that veto with an input-invariant execution checksum.

This paper's contribution is therefore a *dictionary*, not a new optimizer or sequential test:

- four causes $\{\text{known}, \text{novel}, \text{sensor}, \text{compute}\}$ with mutually exclusive operational responses;
- four residuals that are selectively blind, so the $0/1$ pattern names the cause under a single-fault assumption (Algorithm 1);
- a public, GPU-free evaluation against OOD-as-fault and range-check baselines, with ablations and a compound-fault failure case.

We state the limit up front. The five-seed four-way tables use a cosine-response, Poisson 8-detector simulator whose class morphologies follow GBM families. HEASARC catalog counts are real. Section VII repeats the same lookup on 100 public CTIME cubes. Downloaded time-tagged event (TTE) lightcurves are not used, so millisecond TGF morphology is not claimed. Software bit-flips are radiation-*like*, not a beam test. Two simultaneous faults are structurally unisolable in this dictionary.

II. Related Work

Table I compares each closely related line of work against the four symbols this dictionary names. A dash means the method has no operational symbol for that cause.

S. Haripriya (Reg. 24BCE5415) is with the School of Computer Science and Engineering, Vellore Institute of Technology, Chennai, India (e-mail: hariripriya.subbiah@gmail.com).

Prepared as an IEEE-formatted course manuscript for the Embedded Systems DA1, VIT Chennai. Catalog counts from HEASARC `fermigtrig` on 17 September 2026. Five-seed tables use a simulator; Section VII uses 100 public CTIME cubes. Not an IEEE or Elsevier submission.

TABLE I
CLOSELY RELATED METHODS AGAINST THE FOUR OPERATIONAL SYMBOLS. A DASH MEANS THE METHOD HAS NO NAMED RESPONSE FOR THAT CAUSE. ARIA IS THE ONLY ROW THAT KEEPS KNOWN, NOVEL, SENSOR, AND COMPUTE AS DISTINCT SYMBOLS AND DECIDES BY LOOKUP RATHER THAN SCORE FUSION.

Method	Known	Novel	Sensor	Compute	Residual	Decision
MSP [15]	reject	reject	–	–	softmax conf.	thresh.
Energy [16]	reject	reject	–	–	logit energy	thresh.
ODIN [17]	reject	reject	–	–	temp. + grad.	thresh.
OpenMax [18]	known	unknown	–	–	Weibull logits	open-set
Gavarini [9]	ID	OOD-as-fault	–	via OOD	OOD scores	reject
SCOD [30], [31]	accept	reject	–	–	selective+OOD	reject
ProGIP [10]	ID	OOD	–	high-order SDC	GIP range	range
Dr. DNA [11]	–	mixed	mixed	SDC	act. hist.	signature
Monitors [12], [13]	–	mixed	mixed	SDC	feat. markers	alarm
BLINK [21]	–	–	–	weights	BatchNorm	check
ABFT [24], [26]	–	–	–	matmul	checksum	detect
Gertler FDI [22], [23]	–	–	yes	–	parity eqs.	isolate
GBM vetoes [7], [28]	sky	–	single-det.	–	coincidence	veto
John *et al.* [8]	4-class	outlier	–	–	CNN-RNN	classify
ARIA (this work)	yes	yes	yes	yes	sel. blind	lookup

A. OOD scores used as fault detectors

Maximum softmax probability (MSP) [15], energy scores [16], ODIN [17], and OpenMax [18] all reduce a surprising input to a reject/unknown bit. Gavarini *et al.* [9] then treat those bits *as* fault detectors. That is the failure mode this work exists to prevent: a held-out TGF is supposed to look unusual. An OOD alarm cannot say whether to preserve the event or recompute the matmul. Selective classification with OOD (SCOD) likewise accepts or rejects; it does not name compute faults [30], [31]. Deep anomaly surveys document the same collapse of "unusual" into one class [19], [20].

B. ID / OOD / fault in magnitude space

ProGIP [10] is the closest prior paper. It places two range checkers on GIP pipelines so that ID, OOD, and high-order bit-flips can be separated in software. The checkers still operate on gradients and confidence scores. ReAct [14] already showed that OOD inputs drive activations into the same extreme range that high-order flips occupy. Range is a useful heuristic. It is not an identifiability argument, and it does not use instrument physics or a separate sensor symbol.

C. Activation signatures for silent data corruption

Warehouse-scale studies established that silent data corruption is a field phenomenon, not a lab curiosity [34], [35]. Dr. DNA extracts SDC signatures from neuron-activation histograms [11]. Quantile-marker and compressed-feature monitors flag corruption "originating either from hardware memory faults or input corruptions" as one class [12], [13]. BLINK compares live BatchNorm statistics to frozen running statistics for weight integrity [21]. Reliability surveys of neural accelerators likewise treat input OOD and execution faults as one robustness budget [36]. None of these methods is built to return "this is a new class" as a non-fault outcome.

D. Structured residuals and checksums

Gertler and Singer [22] isolate faults with structured parity equations; Isermann's diagnostic framework is the process-control counterpart [23]. The dictionary is sensor / process / actuator. FT-CNN and related algorithm-based fault tolerance (ABFT) schemes detect matrix-multiply errors independently of the input [24], [25]. We *use* a row-sum checksum as one residual. That checksum is not the contribution. Intensity-guided and approximate ABFT decide where or how loosely to check [26], [27]; they do not name discovery. Sequential tests (Wald SPRT, diagnostic martingales) already exist and are not reused here [37], [38].

E. Fermi-GBM classification and vetoes

John *et al.* [8] train CNN-RNN classifiers on public GBM triggers with an outlier flag. Flight software already requires a two-detector coincidence to suppress phosphorescent spikes [1], [3]. Veske *et al.* [28] add an explicit single-versus-multi-detector likelihood ratio. Those vetoes are the ancestor of our physics residual. They do not instrument the classifier for silent arithmetic faults. Onboard scientific ML for gamma-ray missions similarly assumes correct execution [29]. TGF phenomenology is well measured [5], [6]; we hold TGF out as the novel family rather than training on it.

F. Positioning

To the best of this literature search, no published method in Table I puts known class, new class, sensor glitch, and compute fault in one isolability table whose residuals cannot see the wrong cause. That is a narrower claim than "nobody can tell which of four things happened." ProGIP already names three of the four in range space. GBM already names sensor versus sky. The missing object is the four-symbol dictionary with selective blindness.

III. PROBLEM

Let $X \in \mathbb{R}^{D\times T}$ be background-subtracted counts from $D = 8$ detectors and $T = 64$ time bins. A linear head f_W maps

a morphology feature vector $\phi(X)$ to three known classes $\{\mathrm{GRB}, \mathrm{SGR}, \mathrm{SFLARE}\}$. TGF is held out. A single cause c is drawn from

$$\mathcal{C} = \{\texttt{known-clean}, \texttt{novel-clean}, \texttt{sensor}, \texttt{compute}\}.$$

The operational map is accept / preserve / isolate-channel / recompute.

We require a decision $\hat{c}(X, W)$ such that, under a single-fault assumption, $\hat{c}$ is uniquely determined by a binary signature that does not use a learned fusion of OOD scores. Compound faults $c \notin \mathcal{C}$ are declared unisolable rather than forced into $\mathcal{C}$.

IV. Method: ARIA

Attribution by Residual-Invariance Analysis (ARIA) computes four residuals, thresholds them on clean calibration, and looks up a cause. Fig. 1 is the lookup; Fig. 2 is the physics picture the residual is allowed to see.

A. Physics residual (blind to W)

A genuine point source lights several NaI-like detectors with a shared time profile scaled by a cosine angular response [1], [4]. Let v be the median lightcurve of detectors whose total counts exceed a brightness gate, and let r_{phys} be one minus the leave-one-out cosine of the worst detector against v. Dropping that detector yields a gain U_{det}. A localized spike raises r_{phys} and U_{det}. A TGF that is still a point source does not.

B. Morphology residual (blind to a corrupt head)

$\phi(X)$ concatenates duration, hardness, variability, and smoothness of the *shared* profile, not of $f_W(X)$. r_{morph} is Euclidean distance to the nearest known-class centroid in that feature space, using centroids of the *clean* head. A flipped live weight cannot move r_{morph} except through ϕ, which does not read W.

C. Arithmetic residual (blind to the sky)

Let W be stored at compile time with row-sum checksum $s^\top = 1^\top W$ [24]. On a live inference,

$$r_{\mathrm{exec}} = \frac{|1^\top (Wx) - s^\top x|}{|1^\top (Wx)| + |s^\top x| + 1}.$$

A new class cannot fire r_{exec}. A weight bit-flip can.

D. Signature and lookup

Thresholds $(t_{\mathrm{phys}}, t_{\mathrm{morph}}, t_{\mathrm{exec}}, t_{\mathrm{drop}})$ are percentiles on clean calibration plus a margin. The signature is

$$\begin{aligned} S_{\mathrm{phys}} &= [r_{\mathrm{phys}} > t_{\mathrm{phys}}], \\ S_{\mathrm{morph}} &= [r_{\mathrm{morph}} > t_{\mathrm{morph}}], \\ U_{\mathrm{det}} &= S_{\mathrm{phys}} \wedge (U_{\mathrm{det}}^{\mathrm{raw}} > t_{\mathrm{drop}}), \\ U_{\mathrm{arith}} &= [r_{\mathrm{exec}} > t_{\mathrm{exec}}]. \end{aligned}$$

TABLE II
Single-fault isolability dictionary. A dot means the bit is not used for that row.

Cause	S_{phys}	S_{morph}	U_{det}	U_{arith}	Action
known-clean	0	0	0	0	accept
novel-clean	0	1	0	0	preserve
sensor	1	·	1	0	isolate
compute	·	·	0	1	recompute

Algorithm 1 ARIA cause isolation (single-fault lookup)

Require: cube $X \in \mathbb{R}^{D \times T}$; compile-time head W; row-sum checksum s; clean centroids; thresholds t
Ensure: cause $\hat{c}$ and operational action

1: Form the shared profile v as the median lightcurve of detectors that pass a brightness gate.
2: For each detector i, compute the leave-one-out cosine of row X_i against v. Set $r_{\mathrm{phys}} \leftarrow 1 - \min_i \cos(X_i, v)$.
3: Drop the worst detector and record the consistency gain $U_{\mathrm{det}}^{\mathrm{raw}}$.
4: Extract morphology $\phi(X)$ from the *shared* profile (duration, hardness, variability, smoothness). Do not read the live softmax.
5: $r_{\mathrm{morph}} \leftarrow \|\phi(X) - \text{nearest clean centroid}\|_2$.
6: Standardize $\phi(X)$ to x. Compute $r_{\mathrm{exec}} \leftarrow |1^\top W x - s^\top x| / (|1^\top W x| + |s^\top x| + 1)$.
7: Threshold: $S_{\mathrm{phys}} = [r_{\mathrm{phys}} > t_{\mathrm{phys}}]$, $S_{\mathrm{morph}} = [r_{\mathrm{morph}} > t_{\mathrm{morph}}]$, $U_{\mathrm{det}} = S_{\mathrm{phys}} \wedge (U_{\mathrm{det}}^{\mathrm{raw}} > t_{\mathrm{drop}})$, $U_{\mathrm{arith}} = [r_{\mathrm{exec}} > t_{\mathrm{exec}}]$.
8: **if** U_{arith} **then**
9: **return** `compute` / recompute
10: **else if** U_{det} **or** S_{phys} **then**
11: **return** `sensor` / isolate-channel
12: **else if** S_{morph} **then**
13: **return** `novel-clean` / preserve
14: **else**
15: **return** `known-clean` / accept
16: **end if**

Table II is the isolability dictionary. The live rule is

$$\hat{c} = \begin{cases} \texttt{compute} & \text{if } U_{\mathrm{arith}}, \\ \texttt{sensor} & \text{else if } U_{\mathrm{det}} \vee S_{\mathrm{phys}}, \\ \texttt{novel-clean} & \text{else if } S_{\mathrm{morph}}, \\ \texttt{known-clean} & \text{otherwise.} \end{cases} \tag{1}$$

Checksum first is deliberate: a corrupt head must not be allowed to mint a discovery. Algorithm 1 writes the same rule as an explicit stepwise procedure.

V. Experimental Setup

A. Public catalog

Class counts in Table III are from HEASARC `fermigtrig` (TAP query, 17 Sep. 2026). They justify holding TGF out as a frequent, morphologically distinct family and treating `LOCLPAR`/`DISTPAR` as the operational analog of a single-detector spike [2], [7]. They are not claimed as classified lightcurves in the Monte Carlo.




Fig. 1. ARIA residuals and lookup. Each residual is forbidden from seeing at least one cause. The decision is a table, not a fused classifier.




Fig. 2. What the physics residual is allowed to see. A genuine point source lights several detectors with a shared time profile (rank-1). A single-detector spike breaks that profile and fires U_{det}. The checksum is not consulted here.

TABLE III
PUBLIC FERMI-GBM TRIGGER TYPES USED AS CLASS PRIORS.

Type	Count	Role in this paper
GRB	4375	known class
SFLARE	2800	known class
SGR	684	known class
TGF	1658	held-out novel class
LOCLPAR+DISTPAR	2167	sensor-fault analog
All triggers	12981	–

B. Simulator

Each trial draws a sky position, a family template (fast-rise exponential-decay GRB/SGR, wide solar Gaussian, millisecond TGF), Poisson NaI-like counts with a cosine response, and optional faults. Sensor faults add a soft spike to a dim detector. Compute faults flip one IEEE-754 bit of a linear-head weight (mild: bits 18–23; critical: bits 28–30) at inference and revert afterward, following standard injection practice [32], [33]. The head is a standardized linear classifier on $\phi(X)$, not the CNN-RNN of [8]. The checksum is therefore exact for this head. The physics residual never needs the head.

C. Baselines

Energy/MSP rejection follows Gavarini [9], [15], [16]: unusual softmax energy or maximum softmax probability is an undifferentiated `anomaly`. Range-check follows ProGIP's magnitude idea [10]: extreme $|\mathrm{logit}|$ is `compute`; leftover unusual scores are `novel-clean`; else `known-clean`. Range-check has no sensor symbol.

TABLE IV
FOUR-WAY ACCURACY AND PER-CAUSE ISOLATION (%). MEAN±STD OVER FIVE TRAINING SEEDS.

Metric	ARIA	Range-check
Four-way accuracy	89.3 ± 0.3	43.1 ± 6.0
Novel → novel	100.0 ± 0.0	–
Compute → compute	93.9 ± 1.1	–
Sensor → sensor	77.8 ± 0.0	0 (no sensor symbol)




Fig. 3. Simulator isolation and four-way accuracy for ARIA (five-seed means). Range-check four-way accuracy is $43.1 \pm 6.0\%$ and is omitted here because that baseline has no sensor symbol and no four-way dictionary.

D. Protocol

Five training seeds $\{7, 19, 31, 43, 61\}$, evaluation seed 123, 36 trials per cell of $\{\mathrm{GRB}, \mathrm{SGR}, \mathrm{SFLARE}\} \times \mathrm{clean}$, TGF clean, sensor on GRB/SGR, and mild/critical compute on GRB (288 four-way trials per seed). Thresholds are fit on a disjoint clean calibration stream. Ablations reuse the same signatures with subsets of (1). Compound trials inject sensor and compute together ($n = 80$). The command `npm run test:paper` writes `paper/results.json`. Scatter figures use the same seed-7 / eval-123 stream.

VI. RESULTS

A. Four-way attribution

Table IV reports mean±std over the five seeds. ARIA reaches $89.3 \pm 0.3\%$ four-way accuracy. The range-check baseline reaches $43.1 \pm 6.0\%$. Held-out TGF is isolated as novel in $100.0 \pm 0.0\%$ of trials and is never labeled compute. Compute isolation is $93.9 \pm 1.1\%$. Sensor isolation is $77.8 \pm 0.0\%$: the physics residual misses some dim-detector spikes, and those trials fall through to known-clean. We report that miss rate rather than retuning the spike until the number is round. Fig. 3 plots the same isolation cells.

The identifiability claim is graphical in Fig. 4: physics residual versus execution checksum. Known-clean and novel-clean sit at low r_{exec}; compute trials leave that floor; sensor trials move r_{phys} without needing a checksum. The confound that motivated the dictionary is Fig. 5: energy versus MSP,




Fig. 4. Selective blindness on the simulator (train seed 7, eval seed 123). Compute lifts $\log r_{\mathrm{exec}}$; a sensor spike lifts r_{phys}; held-out TGF stays checksum-quiet. Axes are clipped for display; the lookup uses the unclipped residuals.




Fig. 5. Why OOD scores are not isolable here. Softmax energy versus maximum softmax probability on the same trials as Fig. 4. Novel-clean and a subset of compute faults both look like low-confidence, high-energy outliers, which is the ReAct/Gavarini confound.

TABLE V
CONFUSION COUNTS FOR ONE SEED (36 TRIALS PER CELL; ARIA).

True \ pred	known	novel	sensor	compute
known-clean	98	0	10	0
novel-clean	0	36	0	0
sensor	15	1	56	0
compute	5	0	0	67

where novel-clean and some compute trials occupy the same "unusual softmax" region [14], [16].

A representative confusion matrix (train seed 7) is given in Table V and drawn in Fig. 6. Energy/MSP flags 100% of novel trials as anomaly and 8–15% of compute trials, which is the confound: the same rejector fires on discovery and on some bit-flips, and it cannot name either.




Fig. 6. Heatmap of Table V. Off-diagonal mass is almost entirely sensor↔known: dim spikes that the physics residual missed. No novel trial is named compute.

TABLE VI
ABLATION OF THE LOOKUP (FOUR-WAY ACCURACY, %).

Lookup	Accuracy
Full ARIA (1)	89.3 ± 0.3
Checksum only	61.0 ± 0.3
Physics only	53.5 ± 0.0
Morphology only	49.5 ± 0.5
No checksum (physics then morph)	65.8 ± 0.2




Fig. 7. Lookup ablations corresponding to Table VI. No single residual recovers the four-way number.

B. Ablations

Table VI removes signature bits. A checksum alone cannot name novelty or sensors ($61.0 \pm 0.3\%$). Physics alone names some sensors and defaults everyone else to known ($53.5 \pm 0.0\%$). Morphology alone is an open-set detector ($49.5 \pm 0.5\%$). Removing only the checksum drops accuracy to $65.8 \pm 0.2\%$ because compute trials fall into known or novel. Full ARIA is $89.3 \pm 0.3\%$. Fig. 7 is the same table as bars. The figure is the contribution: each residual covers a cause the others cannot see.

C. Compound faults

When a spike and a bit-flip occur together, U_{arith} still fires, so 98.8% of 80 compound trials are named compute. One trial was named sensor. None were named novel. The dictionary is single-fault by construction. We treat this as a limitation, not a result to hide.

VII. Real Public CTIME Data

To test whether the dictionary survives outside the simulator, we repeated the experiment on downloaded public GBM CTIME. `experiments/gbm/prepare.py` queries HEASARC `fermigtrig`, downloads the latest `glg_ctime_n*` PHA files for 25 triggers of each of GRB, SGR, SFLARE, and TGF, and bins them into 8×64 lightcubes (100 cubes). The linear head is trained on all GRB/SGR/SFLARE cubes in the slice; known-clean evaluation reuses those cubes. TGF is held out entirely, so novel isolation and novel-as-compute are not inflated by this overlap. Four-way accuracy is therefore optimistic on the known-clean rows; we report it with that caveat rather than splitting a 75-cube known set into an even smaller train fold. Sensor spikes and IEEE-754 bit-flips are injected on those real arrays exactly as in the simulator, so the only other change is the source of the counts. The run uses the same 5 training seeds and the same evaluation seed 123 as the simulator protocol, 180 trials per seed. CTIME is not TTE: its time bins are coarse (64 ms nominal, 256 ms in the background regime), and a TGF is sub-millisecond [5].

Table VII reports that run. Three results transfer and one does not. Compute isolation is essentially unchanged (92.5% against $93.9 \pm 1.1\%$): the checksum is a property of the head, not of the sky, so real counts do not weaken it. The kill test also transfers—a real held-out TGF is named compute in 0.0% of trials—which is the claim the dictionary exists to support. Four-way accuracy drops to 72.8%, and sensor isolation drops to 60.0%. Novel isolation is 0.0%: on CTIME bins a TGF is not morphologically separable from a short GRB, so held-out TGFs fall through to known-clean rather than to a wrong fault symbol. We state this as a negative result. Recovering the discovery symbol on real data requires millisecond TTE, not a lower morphology threshold. Fig. 8 places the simulator and CTIME numbers on one axis. The spreads in Table VII are across training seeds on a fixed trigger slice at a fixed evaluation seed. They measure how much the fitted head and its calibrated thresholds depend on initialization, and they are small: the largest is ± 1.6 points on compute isolation. They are not sampling error over which triggers were drawn, which is the larger uncertainty here and is addressed instead by varying the slice size below.

TABLE VII
Public GBM CTIME, 25 triggers/class, software fault injection (%). Mean±std over 5 training seeds at evaluation seed 123, 180 trials per seed; simulator column from Table IV for reference.

Metric	Real CTIME	Simulator
Four-way accuracy	72.8 ± 0.4	89.3 ± 0.3
Range-check accuracy	43.3 ± 0.0	43.1 ± 6.0
Novel $\rightarrow$ novel	0.0 ± 0.0	100.0 ± 0.0
Novel $\rightarrow$ compute	0.0 ± 0.0	0
Compute $\rightarrow$ compute	92.5 ± 1.6	93.9 ± 1.1
Sensor $\rightarrow$ sensor	60.0 ± 0.0	77.8 ± 0.0




Fig. 8. Simulator versus real CTIME for the same lookup and the same injected faults. Compute isolation transfers; novel isolation does not (CTIME bins cannot name a millisecond TGF).




Fig. 9. Real-CTIME metrics against slice size. Compute isolation and four-way accuracy stay in a narrow band, sensor isolation settles after the 12-trigger slice, and novel isolation is flat at zero: CTIME bins never let morphology name a held-out TGF. Exact values in Table VIII.

A. Sample-size stability

Seed averaging cannot see sampling error, so we also report the same pipeline at three slice sizes rather than the most favorable one (Fig. 9 and Table VIII). The 25-per-class row is the across-seed mean; the two smaller slices predate seed averaging and are single-seed runs. Sensor isolation moved 16.7 points between 8 and 12 triggers per class but only 1.7 points between 12 and 25, so we treat 60.0% as a converged estimate rather than small-sample noise. Four-way accuracy declines monotonically as the slice grows, which we read as larger samples admitting harder real triggers; we therefore quote the largest run, not the first. The two numbers that carry the central claim—novel never named compute, novel never named novel on CTIME—are identical at every sample size,

TABLE VIII
REAL CTIME METRICS AGAINST SLICE SIZE (%). TRIGGERS PER CLASS; SAME PIPELINE, SAME INJECTED FAULTS.

Per class	Acc.	Compute	Sensor	Novel→comp.	Novel
8	78.8	91.7	75.0	0	0
12	75.8	100.0	58.3	0	0
25	72.8	92.5	60.0	0.0	0.0

so neither the kill test nor the stated limitation is a sampling artifact.

VIII. LIMITATIONS

The simulator is optimistic, and Section VII measures by how much. Sensor isolation is the weakest cell in both settings, but the simulator reports $77.8 \pm 0.0\%$ while real CTIME reports 60.0%; four-way accuracy falls from $89.3 \pm 0.3\%$ to 72.8% on the same pipeline. Real detector geometry and background are harder than a cosine response with Poisson counts, so the simulator figures should be read as an upper bound on what the physics residual achieves in flight, not as the headline. A matched-filter single-detector test [28] is the obvious way to close that gap and is not implemented here. The morphology residual does not transfer at all on CTIME (0.0% novel isolation): the discovery symbol needs millisecond TTE, which this work does not download, so on real data the dictionary currently degrades to a three-symbol one in which novelty is silently absorbed into known-clean rather than misattributed to a fault. The real-data numbers are averaged over 5 training seeds, but on one fixed slice of 100 triggers: the reported spread is seed sensitivity, not sampling error over the catalog, and a different draw of triggers is the untested axis. The fault injection is software, radiation-*like* rather than a beam test [33]. The linear head is a diagnostic probe, not a replacement for [8]. Mild mantissa flips that do not move the checksum or the logits remain invisible, as in every ABFT scheme that watches a linear form. Two simultaneous faults remain structurally unisolable. ARIA does not claim sequential error-rate guarantees. Wald SPRT and diagnostic martingales [37], [38] already exist and are not used here.

IX. CONCLUSION

OOD and SDC monitors can say that an inference looks wrong. They cannot, by construction, say which of four operationally opposite causes produced that look when those causes share an activation-magnitude symptom. ARIA is a four-symbol isolability lookup whose residuals are forbidden from seeing the wrong cause. On a public-catalog-prior, GPU-free GBM-like simulator it separates held-out TGF from compute faults, names many sensor spikes, and fails honestly when two faults arrive together. On 100 real public CTIME triggers the separation of discovery from bit-flip survives intact, while sensor isolation and the discovery symbol itself do not, and we report both. The primitives—rank-1 detector vetoes, ABFT checksums, centroid distance—are known. The dictionary that includes discovery as a non-fault symbol is the distinct object of this work.

DATA AND CODE

HEASARC `fermigtrig` and CTIME PHA2 are public [1], [2]. Simulator tables: `npm run test:paper`. Real CTIME tables: `npm run test:gbm` on the committed 100-cube slice. Scatter figures: `npm run test:figures`. Macros in `results.tex` and `realdata.tex` are emitted by those commands. Companion repository: https://github.com/haripriyasubbiah/aria-gbm-isolability.

REFERENCES

[1] C. Meegan *et al.*, "The Fermi Gamma-ray Burst Monitor," *Astrophys. J.*, vol. 702, pp. 791–804, 2009.
[2] A. von Kienlin *et al.*, "The fourth Fermi-GBM gamma-ray burst catalog: A decade of observations," *Astrophys. J.*, vol. 893, no. 1, 2020.
[3] W. S. Paciesas *et al.*, "The Fermi GBM gamma-ray burst catalog: The first two years," *Astrophys. J. Suppl.*, vol. 199, no. 1, 2012.
[4] V. Connaughton *et al.*, "Localization of gamma-ray bursts using the Fermi Gamma-ray Burst Monitor," *Astrophys. J. Suppl.*, vol. 216, no. 2, 2015.
[5] M. S. Briggs *et al.*, "Terrestrial gamma-ray flashes in the Fermi era: Improved observations of TGFs," *J. Geophys. Res. Space Phys.*, 2013.
[6] O. J. Roberts *et al.*, "The first Fermi-GBM terrestrial gamma-ray flash catalog," *J. Geophys. Res. Space Phys.*, vol. 123, 2018.
[7] A. Goldstein *et al.*, "Evaluation of automated Fermi GBM localizations of gamma-ray bursts," *Astrophys. J.*, vol. 879, no. 2, 2019.
[8] J. John *et al.*, "Multivariate time series classification of Fermi-detected gamma-ray transients using convolutional-recurrent neural networks," *Mach. Learn.: Sci. Technol.*, 2025, arXiv:2510.22412.
[9] L. Gavarini, D. Stucchi, A. Ruospo, G. Boracchi, and E. Sánchez, "Open-set recognition: An inexpensive strategy to increase DNN reliability," in *IEEE IOLTS*, 2022.
[10] S. Joshi *et al.*, "ProGIP: Protecting gradient-based input perturbation approaches for OOD detection from soft errors," *ACM Trans. Embedded Comput. Syst.*, vol. 24, no. 5s, art. 118, 2025, doi: 10.1145/3761796.
[11] D. Ma *et al.*, "Dr. DNA: Combating silent data corruptions in deep learning using distribution of neuron activations," in *Proc. ASPLOS*, 2024.
[12] F. Geissler, S. Qutub, M. Paulitsch, and K. Pattabiraman, "A low-cost strategic monitoring approach for scalable and interpretable error detection in deep neural networks," in *SAFECOMP*, 2023.
[13] C. Schorn and L. Gauerhof, "FACER: A universal framework for detecting anomalous operation of deep neural networks," in *IEEE ITSC*, 2020.
[14] Y. Sun, C. Guo, and Y. Li, "ReAct: Out-of-distribution detection with rectified activations," in *NeurIPS*, 2021.
[15] D. Hendrycks and K. Gimpel, "A baseline for detecting misclassified and out-of-distribution examples in neural networks," in *ICLR*, 2017.
[16] W. Liu, X. Wang, J. Owens, and Y. Li, "Energy-based out-of-distribution detection," in *NeurIPS*, 2020.
[17] S. Liang, Y. Li, and R. Srikant, "Enhancing the reliability of out-of-distribution image detection in neural networks," in *ICLR*, 2018.
[18] A. Bendale and T. E. Boult, "Towards open set deep networks," in *CVPR*, 2016.
[19] L. Ruff *et al.*, "A unifying review of deep and shallow anomaly detection," *Proc. IEEE*, vol. 109, no. 5, pp. 756–795, 2021.
[20] C. Geng, S. Huang, and S. Chen, "Recent advances in open set recognition: A survey," *IEEE Trans. Pattern Anal. Mach. Intell.*, 2020.
[21] M. Khan, A. Malhotra, and S. K. Gupta, "BLINK: Batch normalization-based integrity checkpoints," arXiv:2609.06781, 2026.
[22] J. Gertler and D. Singer, "A new structural framework for parity equation-based failure detection and isolation," *Automatica*, vol. 26, no. 2, pp. 381–388, 1990.
[23] R. Isermann, *Fault-Diagnosis Systems*. Berlin, Germany: Springer, 2006.
[24] K. Zhao *et al.*, "FT-CNN: Algorithm-based fault tolerance for convolutional neural networks," *IEEE Trans. Parallel Distrib. Syst.*, vol. 31, no. 7, 2020.
[25] Z. Chen, "Online-ABFT: An online algorithm based fault tolerance scheme for soft error detection in iterative methods," in *PPoPP*, 2013.
[26] J. E. S. Hastings *et al.*, "Arithmetic-intensity-guided fault tolerance for neural network inference on GPUs," 2021.
[27] X. Xue *et al.*, "ApproxABFT: Approximate algorithm-based fault tolerance for neural network processing," 2023.

[28] D. Veske *et al.*, “A new search pipeline for short gamma-ray bursts in Fermi/GBM data,” *Astrophys. J. Suppl.*, 2025, arXiv:2507.05739.
[29] A. Bulgarelli *et al.*, “Onboard machine learning for high-energy observatories,” *Galaxies*, vol. 13, no. 2, 2025.
[30] G. Xia and C.-S. Bouganis, “Augmenting softmax information for selective classification with out-of-distribution data,” in *ACCV*, 2022.
[31] H. Narasimhan *et al.*, “Plugin estimators for selective classification with out-of-distribution detection,” in *ICLR*, 2024.
[32] A. Mahmoud *et al.*, “PyTorchFI: A runtime perturbation tool for DNNs,” in *IEEE DSN Workshops*, 2020.
[33] B. Reagen *et al.*, “Ares: A framework for quantifying the resilience of deep neural networks,” in *DAC*, 2018.
[34] P. H. Hochschild *et al.*, “Cores that don’t count,” in *HotOS*, 2021.
[35] H. D. Dixit *et al.*, “Silent data corruptions at scale,” arXiv:2102.11245, 2021.
[36] S. Mittal, “A survey of techniques for approximate computing and resilience of deep neural networks,” 2020.
[37] A. Hindy *et al.*, “Diagnostic runtime monitoring with martingales,” in *Robotics: Science and Systems*, 2025.
[38] A. Wald, *Sequential Analysis*. New York, NY, USA: Wiley, 1947.

S. Haripriya is an undergraduate student (24BCE5415) in Computer Science and Engineering at Vellore Institute of Technology, Chennai. Her coursework includes embedded systems and reliable machine inference.