

Ex No: 1c

IMPLEMENTATION OF MINIMAX algorithm

Aim:

To implement MINIMAX algorithm.

Procedure:

Program:

Constants for players

PLAYER_X = 1

PLAYER_O = -1

EMPTY = 0

Evaluate the board

def evaluate(board):

 for row in range(3):

 if board[row][0] == board[row][1] == board[row][2] != EMPTY:

 return board[row][0]

 for col in range(3):

 if board[0][col] == board[1][col] == board[2][col] != EMPTY:

 return board[0][col]

 if board[0][0] == board[1][1] == board[2][2] != EMPTY:

 return board[0][0]

 if board[0][2] == board[1][1] == board[2][0] != EMPTY:

```

        return board[0][2]
    return 0

# Check if moves are left
def isMovesLeft(board):
    for row in range(3):
        for col in range(3):
            if board[row][col] == EMPTY:
                return True
    return False

# Minimax function
def minimax(board, isMax):
    score = evaluate(board)
    if score == PLAYER_X: return score
    if score == PLAYER_O: return score
    if not isMovesLeft(board): return 0

    if isMax:
        best = -float('inf')
        for row in range(3):
            for col in range(3):
                if board[row][col] == EMPTY:
                    board[row][col] = PLAYER_X
                    best = max(best, minimax(board, not isMax))
                    board[row][col] = EMPTY
        return best
    else:
        best = float('inf')
        for row in range(3):
            for col in range(3):

```

```

        if board[row][col] == EMPTY:
            board[row][col] = PLAYER_O
            best = min(best, minimax(board, not isMax))
            board[row][col] = EMPTY
    return best

# Find the best move for PLAYER_X
def findBestMove(board):
    bestVal = -float('inf')
    bestMove = (-1, -1)
    for row in range(3):
        for col in range(3):
            if board[row][col] == EMPTY:
                board[row][col] = PLAYER_X
                moveVal = minimax(board, False)
                board[row][col] = EMPTY
                if moveVal > bestVal:
                    bestMove = (row, col)
                    bestVal = moveVal
    return bestMove

# Print the board
def printBoard(board):
    for row in board:
        print(" ".join(["X" if x == PLAYER_X else "O" if x == PLAYER_O else "." for x in
row]))

# Example game
board = [
    [PLAYER_X, PLAYER_O, PLAYER_X],
    [PLAYER_O, PLAYER_X, EMPTY],

```

```
[EMPTY, PLAYER_O, PLAYER_X]
]

print("Current Board:")
printBoard(board)

move = findBestMove(board)
print(f'Best Move: {move}')
board[move[0]][move[1]] = PLAYER_X
print("\nBoard after best move:")
printBoard(board)
```

Output:

```
Current Board:
X O X
O X .
. O X

Best Move: (2, 0)

Board after best move:
X O X
O X .
X O X
```

Output

Current Board:

X O X

O X .

. O X

Best Move: (1, 2)

Board after best move:

X O X

O X X

. O X

=== Code Execution Successful ===