Rajalakshmi Engineering College

Name: Harish S

Email: 240701173@rajalakshmi.edu.in

Roll no: 240701173 Phone: 9345569745

Branch: REC

Department: I CSE AG

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
- 2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

```
240701173
Output: 10 is inserted in the queue.
    Elements in the queue are: 10
    Invalid option.
    Answer
     #include <stdio.h>
     #include <stdlib.h>
     #define max 5
    int queue[max];
    int front = -1, rear = -1;
// You are using GCC int insertq(int *data)
    if(rear==max-1){
       return 0;
    }
     else{
       rear+=1;
       queue[rear]=*data;
       if(front==-1){
         front=0;
      return 1;
    int delq()
      if(front==-1){
         printf("Queue is empty.\n");
         return 0;
      }
      else{
         printf("Deleted number is:");
printf("\n"\
                                                       240701173
        int n=queue[front];
```

```
240701173
    if(front ==rear){
      front=rear=-1;
    else{
      front=front+1;
    return 1;
 }
}
void display()
  //Type your code here
  if(front==-1){
    printf("Queue is empty \n");
  }
  else{
     printf("Elements in the queue are:");
    for(int i=front;i<=rear;i++){</pre>
       printf("%d",queue[i]);
    printf("\n");
  }
}
int main()
  int data, reply, option;
  while (1)
    if (scanf("%d", &option) != 1)
       break;
     switch (option)
       case 1:
         if (scanf("%d", &data) != 1)
            break;
         reply = insertq(&data);
         if (reply == 0)
            printf("Queue is full.\n");
          else
            printf("%d is inserted in the queue.\n", data);
```

```
240701173
             break;
          case 2:
                        Called without arguments
             delq(); //
             break;
          case 3:
             display();
             break;
          default:
             printf("Invalid option.\n");
             break;
        }
      }
      return 0;
Status : Correct
                                                                       Marks: 10/10
```

240701713

0,40707173

240701173

2407071713

240701713

2,40707173

240701173

2407071713