

# Rajalakshmi Engineering College

Name: Harish S  
Email: 240701173@rajalakshmi.edu.in  
Roll no: 240701173  
Phone: 9345569745  
Branch: REC  
Department: I CSE AG  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

##### ***Input Format***

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

### **Output Format**

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 7

8 3 10 1 6 14 23

6

Output: Value 6 is found in the tree.

### **Answer**

```
// You are using GCC
```

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
struct tree{
```

```
    int data;
```

```
    struct tree*left;
```

```
    struct tree*right;
```

```
};
```

```
struct tree*cr(int val){
```

```
    struct tree*newnode=(struct tree*)malloc(sizeof(struct tree));
```

```
    newnode->left=newnode->right=NULL;
```

```
    newnode->data=val;
```

```
    return newnode;
```

```
}
```

```
struct tree*in(struct tree*root,int val){
```

```
    if(root==NULL) return cr(val);
```

```
    else if(val<root->data){
```

```
        root->left=in(root->left,val);
```

```
    }
```

```

        else if(val>root->data){
            root->right=in(root->right,val);
        }
        return root;
    }
    int po(struct tree*root,int k){
        if(root==NULL) return 0;
        if(root->data==k) return 1;
        return po(root->left,k) || po(root->right,k);
    }

    int main(){
        int n,val,k;
        struct tree*root=NULL;
        scanf("%d",&n);
        for(int i=0;i<n;i++){
            scanf("%d",&val);
            root=in(root,val);
        }
        scanf("%d",&k);
        if(po(root,k)){
            printf("Value %d is found in the tree.",k);
        }
        else{
            printf("Value %d is not found in the tree.",k);
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10