

# Rajalakshmi Engineering College

Name: Harish S  
Email: 240701173@rajalakshmi.edu.in  
Roll no: 240701173  
Phone: 9345569745  
Branch: REC  
Department: I CSE AG  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are tasked with implementing basic operations on a queue data structure using a linked list.

You need to write a program that performs the following operations on a queue:

Enqueue Operation: Implement a function that inserts an integer element at the rear end of the queue. Print Front and Rear: Implement a function that prints the front and rear elements of the queue. Dequeue Operation: Implement a function that removes the front element from the queue.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements to be inserted into the queue.

The second line consists of N space-separated integers, representing the queue elements.

### **Output Format**

The first line prints "Front: X, Rear: Y" where X is the front and Y is the rear elements of the queue.

The second line prints the message indicating that the dequeue operation (front element removed) is performed: "Performing Dequeue Operation:".

The last line prints "Front: M, Rear: N" where M is the front and N is the rear elements after the dequeue operation.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

12 56 87 23 45

Output: Front: 12, Rear: 45

Performing Dequeue Operation:

Front: 56, Rear: 45

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
};
```

```
struct Node* front = NULL;
struct Node* rear = NULL;
```

```
// You are using GCC
```

```
void enqueue(int d) {
```

```
    //Type your code here
```

```
    struct Node*newnode=(struct Node*)malloc(sizeof(struct Node));
```

```
newnode->data=d;
newnode->next=NULL;
if(front==NULL){
    front=rear=newnode;
}
else{
    rear->next=newnode;
    rear=newnode;
}
}
```

```
void printFrontRear() {
    //Type your code here
    if(front!=NULL){
        printf("Front:%d, ",front->data);}
    if(rear!=NULL){
        printf("Rear:%d",rear->data);

    }
    printf("\n");
}
```

```
void dequeue() {
    //Type your code here
    if(front==NULL){
        return;
    }
    else{
        if(front==rear){
            front=rear=NULL;
        }
        else{
            front=front->next;
        }
    }
}
```

```
int main() {
    int n, data;
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        enqueue(data);
```

```
}  
printFrontRear();  
printf("Performing Dequeue Operation:\n");  
dequeue();  
printFrontRear();  
return 0;  
}
```

**Status :** Correct

**Marks :** 10/10