step 5:

Next push the cable right in. The not chat the cable to be just over the cable shielding. and if it isn't, that means that you stripped off too much shielding.

step 6:

After the wires are securely sitting inside the plug insert it into the crimp-ing go to go and push down.

step 4:

Lastly repeat for the other ending diagram B

To test it plug it in and ~~attempt~~ attempt to connect two device directly

23/1/26

RESULT:

Thus, different types of network cables were studied successfully, and straight Through and cross over ethernet cables were prepared and Tested successfully.

Scanned with OKEN Scanner

Exp no: 3a 23/01/2020	UNDERSTANDING THE CISCO PACKET TRACER ENVIRONMENT

AIM:

To understand the cisco Packet environment and design a simple computer network using its interface and networking components.

STEPS:

- Open the CISCO Packet Tracer
- Observe the UI including the Menu Bar, Main Toolbar, Workspace, Common Tools Bar, Network Component Box and Realtime/Simulation tabs
- From the Network Component Box, select the required network devices such as PC's, Hub & Switch
- Drag & drop the device into workspace
- Connect the devices using Copper straight-through cables
- Configure IP address
- Verify that all links are active
- Use the Add Simple PDU tool to send a packet between two PC's
- Observe packet transmission in Realtime Mode and Simulation Mode
- Save the network topology

RESULT:

The CISCO Packet Tracer environment was succesfully explored and a simple network was designed. The interface components, device connections, IP configuration & packet transmission were succesfully

Scanned with OKEN Scanner

Exp: 3 b1
23/01/2026

HUB

AIM:

To study the behaviour of a Hub by observing how it forwards data Packets using Cisco packet tracer

STEPS:

- Open Cisco Packet tracer
- Drag and place 1 Hub & 4 Generic PCs into the workspace
- Connect all PC's to the Hub using Copper straight - through cables
- Configure IP addresses for all PCs in same network.
- Add simple PDU from Common Tools bar
- Send a packet from one PC to another PC
- Switch to Simulation Mode and observe how the hub forwards the Packet

RESULT:

The hub broadcasts the Received packet to all connected devices. Every PC receives the packet, but only the destination PC accepts it, while the other discard it.

Scanned with OKEN Scanner