

Exp. No : 9

Implement clustering techniques – Hierarchical and K-Means

a) Hierarchical Clustering

```
# Load the iris dataset
data(iris)

# Use only the numeric columns for clustering (exclude the Species column)
iris_data <- iris[, -5]

# Standardize the data
iris_scaled <- scale(iris_data)

# Compute the distance matrix
distance_matrix <- dist(iris_scaled, method = "euclidean")

# Perform hierarchical clustering using the "complete" linkage method
hc_complete <- hclust(distance_matrix, method = "complete")

# Plot the dendrogram
plot(hc_complete, main = "Hierarchical Clustering Dendrogram", xlab = "", sub = "", cex = 0.6)


# Cut the tree to form 3 clusters
clusters <- cutree(hc_complete, k = 3)

# Print the cluster memberships
print(clusters)

# Add the clusters to the original dataset
iris$Cluster <- as.factor(clusters)

# Display the first few rows of the updated dataset
head(iris)
```

Hierarchical Clustering Dendrogram



b) K-Means Clustering

Load the iris dataset

```
data(iris)
```

Use only the numeric columns for clustering (exclude the Species column)

```
iris_data <- iris[, -5]
```

Standardize the data

```
iris_scaled <- scale(iris_data)
```

Set the number of clusters

```
set.seed(123) # For reproducibility
```

```
k <- 3 # Number of clusters
```

Perform K-Means clustering

```
kmeans_result <- kmeans(iris_scaled, centers = k, nstart = 25)
```

Print the K-Means result

```
print(kmeans_result)
```

Print the cluster centers

