

[Harish Kumar S 251801090-2025-AIDS](#) ▾**H2****Started on** Tuesday, 25 August 2026, 5:05 PM**State** Finished**Completed on** Tuesday, 25 August 2026, 5:06 PM**Time taken** 41 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  // Sort in ascending order
5  int compare_asc(const void *a, const void *b) {
6      long long x = *(const long long *)a;
7      long long y = *(const long long *)b;
8      if (x < y) return -1;
9      if (x > y) return 1;
10     return 0;
11 }
12
13 // Sort in descending order
14 int compare_desc(const void *a, const void *b) {
15     long long x = *(const long long *)a;
16     long long y = *(const long long *)b;
17     if (x < y) return 1;
18     if (x > y) return -1;
19     return 0;
20 }
21
22 int main() {
23     int n;
24     if (scanf("%d", &n) != 1) return 0;
25
26     long long A[n], B[n];
27
28     for (int i = 0; i < n; i++) {
29         scanf("%lld", &A[i]);
30     }
31
32     for (int i = 0; i < n; i++) {
33         scanf("%lld", &B[i]);
34     }
35
36     // Sort A in ascending order and B in descending order
37     qsort(A, n, sizeof(long long), compare_asc);
38     qsort(B, n, sizeof(long long), compare_desc);
39
40     long long min_sum = 0;
41     for (int i = 0; i < n; i++) {
42         min_sum += A[i] * B[i];
43     }
44
45     printf("%lld\n", min_sum);
46     return 0;
47 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)