INDEX

NAME Harish Rahul B SUBJECT Computer Network

STD. _____ DIV. _____ ROLL NO. 240701166 SCHOOL _____

SR. NO.	PAGE NO.	TITLE	DATE	TEACHER'S SIGN / REMARKS
1.	23.7.25	Networking Commands used in Linux & Windows	9	
2.	23.7.25	Learning and Assignment of IP Address Manally	9	
3.	30.7.25	Study of different types of Network cables	9	
4.	3.8.25	Design a simple topology and configure with one Routers, Two Switches and Pc using CISCO Packets	9	
5.	10.8.26	Setting up o/a LAN	9	
6.	14.8.25	Experiment on Packet capture tools WireShark	9	
6.	24.9.25	Hamming code	8	
7.	24.9.26	Sliding Window Protocol	8	
8.	28.9.26	NMAP on TryHackMe Platform	9	
9.	28.9.26	Internetting with routers	9	
10.	1.10.26	Simulation of RIP using CISCO Packet Tracer	9	
11.	2.10.25	Implementation of subnetting in CISCO Packet Tracer	8	
12.	2.10.25	End to End communication at transport layer	10	
13.	2.10.26	Implement your own ping Program	10	
14.	5.10.26	Row Sockets - Pocket Sniffing	10	
15.	5.10.26	Analysis of Web logs using webalizer tool	10	

Completed

Exc. No: 01

Networking commands and Uses in Linux and Windows

Aim:
Study of various Network commands used in Linux and Windows.

Basic Networking Commands - Windows :-

1. **arp -a :** (device discovery)
→ address resolution protocol, shows IP address of computer and connected devices and MAC address of router

2. **hostname:**
→ name of our own computer (host)

3. **ipconfig /all:**
→ detailed configuration information (networ setup): routers, gateways, DNS, DHCP and type of Ethernet

4. **netstat -a :** (device dicovery)
→ helps to solve problems with NetBIOS name resolution (troubleshoot naming issues older window network naming)

5. **nslookup:**
→ name server lookup - DNS lookups and display DNS details like IP address both in interactive and non-interactive.

6. **pathping:**
→ unique to windows, shows the path our data takes to reach the destination and find data loss for slow connection identification.
Eg: ping localhost / 4.2.2.2 / ibaan.

10. tracert (Windows) and traceroute (Linux)
→ shows path (hops) our data takes to reach destination.

11. telnet: tests if a specific portion on a remote device is open (reachable).

IP & Adapter Config:

12. ipconfig: shows/manages network adapter IP settings.

13. getmac: shows MAC address of network adapter.

DNS tools:

lookup:

* dig: flexible version of nslookup
* host.

14. iperf / iperf3: measures actual bandwidth/throughput between 2 devices.

15. netsh: advanced tool to view/config net settings.

Networking Commands - Linux

1. **ip** :

→ View and manages network settings (show IP, add & remove IP, enable and disable network interfaces and manage router).

a) Show IP address :
[root @ server ~] # ip address show

b) add an IP address :- assign new IP address
ip address add 192.168.1.254/24

c) delete an IP address :
ip address del 192.168.1.254/24 dev enp0s 3.

d) enables a network interface - turn on network connection : # ip link set eth0 up.

e) disable a network :
ip link set eth0 down

f) enable promiscuous mode : allow interfaces recieve all net packets # ip link set eth0 promisc on

g) Add a route : adds path to reach another network
ip route add 192.168.1.0/24 via 192.168.1.254.

h) delete a route :
ip route delete 192.168.1.0/24 via 192.168.1.254

2. **ip config** :

→ config and display network interfaces.
(IP & status of network interfaces)

3.

3. mtr:
→ checks path between computers (ping and traceroute combination). It shows packet loss delays and route along the path.
a) mtr google.com.
→ every router between computer and google.
b) mtr -g google.com
→ router IP address instead of names
c) mtr -c 10 google.com.
→ sends 10 test packets.

4. tcpdump:-
→ captures and displays network packets

Install
#dnf install -y tcpdump
show available interfaces
tcpdump -D
capture traffic: all packets on interface eth
#tcpdump -i eth0

Outgoing traffic:
#tcpdump -i eth0 dst host 8.8.8.8
DNS traffic:
#tcpdump -i eth0 port 53
HTTPS traffic:
#tcpdump -i eth0 www.google.com and port 443.

5. Ping

→ test whether another computer or website is reachable

ping google.com

ping 10 times

ping -c 10 google.com

Common messages:

* Destination host unreachable : no route exist
* Request timed out : no reply received.
* Unknown host : Incorrect host or doesn't exist

6. Configure IPV6 :

Automatic

nmcli connection modify "Wired connection 1"

*ipv6 meathod auto.

Static

manual.

7. Activate connection:

nmcli connection up Internal-LAN

IP address : ip address show

Default gateway : "route"

IPV6 gateway : ip -6 route show

DNC servers : cat /etc/resolv.conf

Test network : ping google.com

15/9/26 9/10